



Agilent 7010 Triple Quadrupole GC/MS System

Data Sheet



The Agilent 7890B Gas Chromatograph and Agilent 7010 Mass Spectrometer is the most sensitive GC/MS/MS system with the lowest, 0.5 fg Octafluoronaphthalene Instrument Detection Limit (IDL) specification. The IDL is demonstrated at installation, verifying total system performance: the ALS, GC, and MS.

The Agilent rich tradition of innovation and quality is embodied in the 7010 GC/TQ system, making it ready to join the tens of thousands of Agilent GC/MS systems delivered over the past 45 years.

Agilent 7010 Triple Quadrupole Mass Spectrometer

Mode of operation	El standard, CI optional
Ion source material	Noncoated, proprietary inert source
Ion source temperature	150 to 350 °C
Filaments	Dual filaments for EI
Electron energy	10 to 300 eV
Mass filters (2)	Proprietary monolithic hyperbolic gold-coated quadrupole
Mass axis stability	< ± 0.10 u over 24 hours (10 to 40 °C)
Quadrupole temperature	106 to 200 °C
Mass range	m/z 10 to 1,050
Resolution	Selectable, 0.7 to 2.5 Daltons, default tune Settable, 0.4 to 4.0 Daltons, custom tune
Scan rate	Up to 6,250 u/s
Tuning	Autotune or manual
Detector	Triple-Axis HED-EM with extended-life EM and dynamically ramped-iris
MRM speed	800 transitions/sec
Minimum MRM dwell	0.5 msec
Collision cell	Linear hexapole
Collision cell gas	Nitrogen with helium quench gas
Collision energy	Selectable up to 60 eV
Vacuum system	Dual stage turbomolecular pump Total gas flow up to 8 mL/min
Software	Agilent MassHunter acquisition, data handling (quant/qual) and reporting Pesticides and Environmental Pollutants MRM database with over 8,000 optimized transitions (optional)



Agilent Technologies

Gas Chromatograph: Agilent 7890B GC

For more specifications, refer to the GC Data Sheet.

Injector	Split/splitless, Multimode inlet, PTV and others
Autosampler	Agilent 7693 ALS, CombiPAL, Agilent 7697A Headspace Sampler
Oven temperature	Ambient + 4 to 450 °C
Oven ramps/plateaus	Supports 20 oven ramps and 21 plateaus Negative ramps are allowed
Ramp rate	120 °C/min (200 +V), 75 °C/min (120 V)
Capillary Flow Technology	Effluent splitting, backflushing, column switching
Retention Time Locking (RTL)	RTL-ready, constant flow or pressure

Integrated GC/MS System Features

Early Maintenance Feedback (EMF)	Monitors GC and MS resources: injection counter, operation times, and electronic logs to aid planned maintenance
Parts finder	Easy, convenient access to pertinent consumables part numbers
Quick vent	Automated, rapid venting the MS
Eco-friendly operation	User scheduled Sleep-Wake mode saves carrier gas and power
Integrated calculators	Vapor volume calculator, solvent vent calculator, method translator, and so forth

Instrument Dimensions

Agilent 7010 MS	35 cm (w) × 86 cm (d) × 47 cm (h); Weight: 60 kg Additional space for the data system and printer
Mechanical pump	18 cm (w) × 35 cm (d) × 28 cm (h); Weight: 21.5 kg
Agilent 7890B GC	58 cm (w) × 54 cm (d) × 57 cm (h); Weight: 45 kg

www.agilent.com/chem

Agilent shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Information, descriptions, and specifications in this publication are subject to change without notice.

© Agilent Technologies, Inc., 2014
Published in USA,
December 4, 2014
5991-4782EN

Installation Checkout Specifications

IDL is a more accurate indication of true sensitivity (minimum detectable quantity) than signal-to-noise (S/N), particularly when background noise levels are very low, as with MS/MS measurements when only standard is injected.

IDL verification is a more extensive (eight consecutive injections versus one, in case of S/N) and reliable test that is performed at installation to ensure proper system qualification.

EI MRM IDL	0.5 fg or less octafluoronaphthalene (OFN) Statistically derived at 99% confidence level from the area precision of eight sequential splitless injections ¹ of 1 µL, 2 fg/µL OFN standard. MS/MS transition of m/z 272 → 222, 100 msec dwell time.
PCI MRM S/N	1 µL of 5 pg/µL Benzophenone (BZP) produces > 2,500:1 RMS S/N for the MS/MS transition of m/z 183 → 105 (CH ₄)

All tests are carried out on a 30 m × 0.25 mm, 0.25 µm column

Reference Specifications²

EI MRM S/N	1 µL of 100 fg/µL of OFN produces > 10,000:1 RMS S/N for the transition of m/z 272 → 222
------------	--------------------------------------------------------------------------------------------

1. IDL specification is only demonstrated if an autosampler is part of the installed system. If an autosampler is not present, the EI MRM S/N spec is performed.
2. Reference specifications represent typical performance and are not confirmed at installation.



Agilent Technologies