

Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

### 1 Identification

· Product identifier

· Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

· Part number: 1268TK-1

· Relevant identified uses of the substance or mixture and uses advised against

Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Agilent Technologies Australia Pty Ltd

679 Springvale Road

Mulgrave

Victoria 3170, Australia

· Further information obtainable from:

Telephone: 1800 802 402

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: +(61) - 290372994

### 2 Hazard(s) Identification

· Classification of the substance or mixture



health hazard

Carc. 1B H350 May cause cancer.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

May cause cancer.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)


(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

64742-53-6 Distillates (petroleum), hydrotreated light naphthenic



99.989%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **4 First Aid Measures**

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5 Fire Fighting Measures**

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## **6 Accidental Release Measures**

- Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

AU ·



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

(Contd. of page 2)

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### · Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

#### · Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

## · Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

## Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: > 4 hours

(Contd. on page 4)



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

Information on basic physical and chen	nical properties				
General Information Appearance:					
Form:	Fluid				
Colour:	According to product specification				
Odour:	Characteristic				
Odour threshold:	Not determined.				
pH-value:	Not determined.				
Change in condition					
Melting point/freezing point:	Undetermined.				
Initial boiling point and boiling range	: Undetermined.				
Flash point:	146 °C				
Flammability (solid, gas):	Not applicable.				
Decomposition temperature:	Not determined.				
Auto-ignition temperature:	Product is not selfigniting.				
<b>Explosive properties:</b>	Product does not present an explosion hazard.				
<b>Explosion limits:</b>					
Lower:	Not determined.				
Upper:	Not determined.				
Vapour pressure at 20 °C:	0.1 hPa				
Density at 20 °C:	$0.88 \text{ g/cm}^3$				
Relative density	Not determined.				
Vapour density	Not determined.				
Evaporation rate	Not determined.				
Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				
Partition coefficient: n-octanol/water:	Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
Solvent content:					
VOC (EC)	0.00 %				

(Contd. on page 5)



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

(Contd. of page 4)

· Other information

No further relevant information available.

## 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50	values	r	eleva	ant	for	classification:

ATE (A	Acute	Toxicity	y Es	tima	tes)

Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/L (rat)

### 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/L (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc. 1B

## 12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

(Contd. of page 5)

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

•		-				- 1	•					
			Tron I	1	$\mathbf{n}$	•	7		mo	T 7	$\mathbf{T}$	$\mathbf{r}$
	_		rai	INI		,			110			
					~ ~			<u> </u>		-	~~	

14 Transport information	
· UN-Number · ADG, ADN, IMDG, IATA	not regulated
· UN proper shipping name · ADG, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· ADG, ADN, IMDG, IATA · Class	not regulated
· Packing group · ADG, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
Transport in bulk according to Annex II of Marp and the IBC Code	ol Not applicable.
· UN "Model Regulation":	not regulated

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Australian Inventory of Chemical Substances

64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)



Printing date 27.03.2019 Version number 3 Revision: 22.03.2019

Trade name: Aroclor 1268, 100 ug/mL in PCB free transformer oil (1X2 mL)

(Contd. of page 6)

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

#### · Relevant phrases

H350 May cause cancer.

- Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Carc. 1B: Carcinogenicity – Category 1B

AU