# SAFETY DATA SHEET



### Sample Test, High Concentration Evaluation Standard

### **Section 1. Identification**

1.1 Product identifier

Product name : Sample Test, High Concentration Evaluation Standard

**Part no.** : 393110101 **Validation date** : 12/26/2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemistry Laboratory Use

5 x 1 ml

1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer**: Agilent Technologies, Inc.

5301 Stevens Creek Blvd Santa Clara, CA 95051, USA

800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

### Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

F225 FLAMMABLE LIQUIDS - Category 2
H315 SKIN IRRITATION - Category 2

H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

H304 ASPIRATION HAZARD - Category 1 H400 AQUATIC HAZARD (ACUTE) - Category 1 H410 AQUATIC HAZARD (LONG-TERM) - Category 1

2.2 GHS label elements

Hazard pictograms :









Signal word : Danger

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H410 - Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Date of issue**: 12/26/2024 1/12

### Section 2. Hazards identification

Prevention

: P280 - Wear protective gloves.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapor.

P264 - Wash thoroughly after handling.

Response

: P391 - Collect spillage.

P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed. P403 + P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

2.3 Other hazards

**Hazards not otherwise** 

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	Identifiers
2,2,4-trimethylpentane	≥90	CAS: 540-84-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### 4.1 Description of necessary first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Date of issue**: 12/26/2024 **2/12** 

### Section 4. First aid measures

#### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### 4.2 Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact**: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

**Date of issue**: 12/26/2024 3/12

### Section 5. Fire-fighting measures

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **6.2 Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

# Section 7. Handling and storage

### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Date of issue**: 12/26/2024 **4/12** 

### Section 7. Handling and storage

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations

: Industrial applications, Professional applications.

Industrial sector specific

solutions

: Not available.

# Section 8. Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2,2,4-trimethylpentane	ACGIH TLV (United States, 1/2024) [Octane
	TWA 8 hours: 300 ppm.

#### **Biological exposure indices**

No exposure indices known.

#### **8.2 Exposure controls**

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Date of issue**: 12/26/2024 5/12

# Section 8. Exposure controls/personal protection

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.

Color : Clear. Colorless.

Odor : Gasoline
Odor threshold : Not available.

pH : Not available.

Melting point/freezing point : -107°C (-160.6°F)

Boiling point or initial : 99°C (210.2°F)

boiling point and boiling

range

Flash point : Closed cup: -12°C (10.4°F)
Evaporation rate : <1 (ether (anhydrous) = 1)

Flammability
Lower and upper explosion limit/flammability limit

: Lower: 1.1% Upper: 6%

: Not applicable.

Vapor pressure :

	Vapor Pressure at 20°C		Vapor pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
2,2,4-trimethylpentane	21.00171	2.8	-	150.01	20	-

Relative vapor density : 3.9 [Air = 1]

Relative density : 0.69

Density : 0.69 g/cm<sup>3</sup>

Solubility(ies) : Media

:	Media	Result
	<b>w</b> ater	Insoluble

Miscible with water : No.

Partition coefficient: n-

octanol/water

: Not applicable.

**Date of issue**: 12/26/2024 6/12

# Section 9. Physical and chemical properties and safety characteristics

**Auto-ignition temperature** 

Ingredient name °C °F **Method** 418 784.4 2,2,4-trimethylpentane

**Decomposition temperature** 

**Viscosity** 

: Not available.

Dynamic (room temperature): Not available. Kinematic (room temperature): Not available.

Kinematic (40°C (104°F)): Not available.

**Particle characteristics** 

Median particle size : Not applicable.

### Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

: The product is stable. 10.2 Chemical stability

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

Reactive or incompatible with the following materials: reducing materials.

10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### 11.1 Information on toxicological effects

**Acute toxicity** 

Product/ingredient name Result

2,2,4-trimethylpentane Rat - Male, Female - Oral - LD50 >5000 mg/kg

> Rat - Male, Female - Inhalation - LC50 Vapor >33.52 mg/l [4 hours]

**Conclusion/Summary** 

[Product]

: Not available.

Skin corrosion/irritation

**Conclusion/Summary** 

: Repeated exposure may cause skin dryness or cracking.

[Product]

Serious eye damage/eye irritation

**Conclusion/Summary** 

: Not available.

[Product]

Respiratory corrosion/irritation

**Conclusion/Summary** : Not available.

[Product]

Respiratory or skin sensitization

Skin

Date of issue: 12/26/2024 7/12

# **Section 11. Toxicological information**

**Conclusion/Summary** 

[Product]

: Not available.

Respiratory

**Conclusion/Summary** 

: Not available.

[Product]

Germ cell mutagenicity

**Conclusion/Summary** 

: Not available.

[Product]

Carcinogenicity

Not available.

**Conclusion/Summary** 

[Product]

: Not available.

**Reproductive toxicity** 

**Conclusion/Summary** 

: Not available.

[Product]

Specific target organ toxicity (single exposure)

Product/ingredient name Result

2,2,4-trimethylpentane SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic

effects) - Category 3

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Product/ingredient name Result

Sample Test, High Concentration

ASPIRATION HAZARD - Category 1

Evaluation Standard 2,2,4-trimethylpentane

ASPIRATION HAZARD - Category 1

Information on the likely

: Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

routes of exposure

Potential acute health effects

**Eye contact**: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact : Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Date of issue**: 12/26/2024 **8/12** 

### **Section 11. Toxicological information**

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

#### Potential chronic health effects

**Conclusion/Summary** 

[Product]

: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

**Acute toxicity estimates** 

N/A

# Section 12. Ecological information

#### 12.1 Toxicity

Conclusion/Summary

: Not available.

[Product]

#### 12.2 Persistence and degradability

Conclusion/Summary

: Not available.

[Product]

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2,4-trimethylpentane	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2,4-trimethylpentane	4.08	231	Low

#### 12.4 Mobility in soil

Soil/Water partition

: Not available.

coefficient

**Date of issue**: 12/26/2024 9/12

### Section 12. Ecological information

12.5 Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

# Section 14. Transport information

DOT / TDG / Mexico / IMDG / : Not regulated.

**IATA** 

**Additional information** 

**Remarks**: De minimis quantities

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

### Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**U.S. Federal regulations** 

TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112

(b) Hazardous Air

Listed

**Pollutants (HAPs)** 

Clean Air Act Section 602

**Class I Substances** 

: Not listed

Date of issue: 12/26/2024 10/12

### Section 15. Regulatory information

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : FLAMMABLE LIQUIDS - Category 2

SKIN IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

ASPIRATION HAZARD - Category 1

#### Composition/information on ingredients

Name	%	Classification
2,2,4-trimethylpentane		FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid

#### State regulations

**Massachusetts** : The following components are listed: ISOOCTANE

**New York** : The following components are listed: 2,2,4-Trimethylpentane

: The following components are listed: ISOOCTANE **New Jersey** 

**Pennsylvania** : The following components are listed: PENTANE, 2,2,4-TRIMETHYL-

California Prop. 65



MARNING: This product can expose you to Benzophenone, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name		Maximum acceptable dosage level
Benzophenone	-	-

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Date of issue: 12/26/2024 11/12

### **Section 15. Regulatory information**

Not listed.

#### **Inventory list**

Australia : Not determined.
Canada : Not determined.
China : Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : All components are listed or exempted.

### Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
LAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
ASPIRATION HAZARD - Category 1	Expert judgment
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

#### **History**

Date of issue/Date of :

revision

: 12/26/2024

Date of previous issue : 12/23/2021

Version : 6

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

Indicates information that has changed from previously issued version.

#### **Notice to reader**

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

**Date of issue**: 12/26/2024 12/12