

# SAFETY DATA SHEET

Boiling Point Calibration Sample #3 Kit, Part Number 5080-8769

## Section 1. Identification

### 1.1 Product identifier

**Product name** : Boiling Point Calibration Sample #3 Kit, Part Number 5080-8769  
**Part No.** : 5080-8769  
**Validation date** : 7/21/2017

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Analytical reagent.  
 5080-8769-1 Boiling Point Calibration Sample #3 Kit 6 x 1 ml ampoule

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer** : Agilent Technologies, Inc.  
 5301 Stevens Creek Blvd  
 Santa Clara, CA 95051, USA  
 800-227-9770

### 1.4 Emergency telephone number

**In case of emergency** : CHEMTREC®: 1-800-424-9300

## Section 2. Hazards identification

### 2.1 Classification of the substance or mixture

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2  
 H315 SKIN IRRITATION - Category 2  
 H319 EYE IRRITATION - Category 2A  
 H361 TOXIC TO REPRODUCTION (Fertility) - Category 2  
 H361 TOXIC TO REPRODUCTION (Unborn child) - Category 2  
 H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
 H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), kidneys, liver, nervous system) - Category 2  
 H304 ASPIRATION HAZARD - Category 1

**Ingredients of unknown toxicity** : Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 30 - 60%  
 Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: > 60%  
 Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 10 - 30%

### 2.2 GHS label elements

**Hazard pictograms** :



**Signal word** : Danger

## Section 2. Hazards identification

**Hazard statements** : P225 - Highly flammable liquid and vapor.  
H319 - Causes serious eye irritation.  
H315 - Causes skin irritation.  
H361 - Suspected of damaging fertility or the unborn child.  
H304 - May be fatal if swallowed and enters airways.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS), kidneys, liver, nervous system)

### Precautionary statements

**Prevention** : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P233 - Keep container tightly closed.  
P271 - Use only outdoors or in a well-ventilated area.  
P260 - Do not breathe vapor.  
P264 - Wash hands thoroughly after handling.

**Response** : P314 - Get medical attention if you feel unwell.  
P308 + P313 - IF exposed or concerned: Get medical attention.  
P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.  
P332 + P313 - If skin irritation occurs: Get medical attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical attention.

**Storage** : P405 - Store locked up.  
P403 - Store in a well-ventilated place.  
P235 - Keep cool.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 Other hazards

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

## Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Undecane	≥10 - ≤25	112-40-3
Hexadecane	≤10	544-76-3
Tetradecane	≤10	629-59-4
Decane	≤10	124-18-5
pentane	≤10	109-66-0
Propylbenzene	≤5	103-65-1
p-Xylene	≤5	106-42-3
Toluene	≤5	108-88-3
2-Methylpentane	≤5	107-83-5
Butylbenzene	≤5	104-51-8
n-Heptadecane	≤5	629-78-7
Tridecane	≤5	629-50-5
Pentadecane	≤5	629-62-9
Octane	≤5	111-65-9
Heptane	≤5	142-82-5
2,4-Dimethylpentane	≤5	108-08-7
n-Hexane	<5	110-54-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### 4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 4.2 Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.

## Section 4. First aid measures

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

## Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Section 7. Handling and storage

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- 7.3 Specific end use(s)**
- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not applicable.

## Section 8. Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
dodecane Hexadecane Tetradecane Decane pentane	None. None. None. None. <b>ACGIH TLV (United States, 3/2016).</b> TWA: 1000 ppm 8 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 600 ppm 8 hours. TWA: 1800 mg/m <sup>3</sup> 8 hours. STEL: 750 ppm 15 minutes. STEL: 2250 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2013).</b> TWA: 120 ppm 10 hours. TWA: 350 mg/m <sup>3</sup> 10 hours. CEIL: 610 ppm 15 minutes. CEIL: 1800 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL (United States, 6/2016).</b> TWA: 1000 ppm 8 hours. TWA: 2950 mg/m <sup>3</sup> 8 hours.
Propylbenzene p-Xylene	None. <b>ACGIH TLV (United States, 3/2016).</b> TWA: 100 ppm 8 hours. TWA: 434 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2013).</b>

## Section 8. Exposure controls/personal protection

<p>Toluene</p>	<p>TWA: 100 ppm 10 hours.                      TWA: 435 mg/m<sup>3</sup> 10 hours.                      STEL: 150 ppm 15 minutes.                      STEL: 655 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL (United States, 6/2016).</b>                      TWA: 100 ppm 8 hours.                      TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b>                      TWA: 100 ppm 8 hours.                      TWA: 375 mg/m<sup>3</sup> 8 hours.                      STEL: 150 ppm 15 minutes.                      STEL: 560 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL Z2 (United States, 2/2013).</b>                      TWA: 200 ppm 8 hours.                      CEIL: 300 ppm                      AMP: 500 ppm 10 minutes.  <b>NIOSH REL (United States, 10/2013).</b>                      TWA: 100 ppm 10 hours.                      TWA: 375 mg/m<sup>3</sup> 10 hours.                      STEL: 150 ppm 15 minutes.                      STEL: 560 mg/m<sup>3</sup> 15 minutes.  <b>ACGIH TLV (United States, 3/2016).</b>                      TWA: 20 ppm 8 hours.</p>
<p>2-Methylpentane</p>	<p><b>ACGIH TLV (United States, 3/2016).</b>                      TWA: 500 ppm 8 hours.                      TWA: 1760 mg/m<sup>3</sup> 8 hours.                      STEL: 1000 ppm 15 minutes.                      STEL: 3500 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL 1989 (United States, 3/1989).</b>                      TWA: 500 ppm 8 hours.                      TWA: 1800 mg/m<sup>3</sup> 8 hours.                      STEL: 1000 ppm 15 minutes.                      STEL: 3600 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2013).</b>                      TWA: 100 ppm 10 hours.                      TWA: 350 mg/m<sup>3</sup> 10 hours.                      CEIL: 510 ppm 15 minutes.                      CEIL: 1800 mg/m<sup>3</sup> 15 minutes.</p>
<p>Butylbenzene                      n-Heptadecane                      Tridecane                      Pentadecane                      Octane</p>	<p>None.                      None.                      None.                      None.  <b>OSHA PEL 1989 (United States, 3/1989).</b>                      TWA: 300 ppm 8 hours.                      TWA: 1450 mg/m<sup>3</sup> 8 hours.                      STEL: 375 ppm 15 minutes.                      STEL: 1800 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2013).</b>                      TWA: 75 ppm 10 hours.                      TWA: 350 mg/m<sup>3</sup> 10 hours.                      CEIL: 385 ppm 15 minutes.                      CEIL: 1800 mg/m<sup>3</sup> 15 minutes.  <b>ACGIH TLV (United States, 3/2016).</b>                      TWA: 300 ppm 8 hours.  <b>OSHA PEL (United States, 6/2016).</b>                      TWA: 500 ppm 8 hours.</p>



## Section 8. Exposure controls/personal protection

Heptane	<p>TWA: 2350 mg/m<sup>3</sup> 8 hours.  <b>ACGIH TLV (United States, 3/2016).</b>            TWA: 400 ppm 8 hours.            TWA: 1640 mg/m<sup>3</sup> 8 hours.            STEL: 500 ppm 15 minutes.            STEL: 2050 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 400 ppm 8 hours.            TWA: 1600 mg/m<sup>3</sup> 8 hours.            STEL: 500 ppm 15 minutes.            STEL: 2000 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2013).</b>            TWA: 85 ppm 10 hours.            TWA: 350 mg/m<sup>3</sup> 10 hours.            CEIL: 440 ppm 15 minutes.            CEIL: 1800 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL (United States, 6/2016).</b>            TWA: 500 ppm 8 hours.            TWA: 2000 mg/m<sup>3</sup> 8 hours.</p>
2,4-Dimethylpentane	<p><b>ACGIH TLV (United States, 3/2016).</b>            TWA: 400 ppm 8 hours.            TWA: 1640 mg/m<sup>3</sup> 8 hours.            STEL: 500 ppm 15 minutes.            STEL: 2050 mg/m<sup>3</sup> 15 minutes.</p>
n-Hexane	<p><b>ACGIH TLV (United States, 3/2016).</b>  <b>Absorbed through skin.</b>            TWA: 50 ppm 8 hours.  <b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 50 ppm 8 hours.            TWA: 180 mg/m<sup>3</sup> 8 hours.  <b>NIOSH REL (United States, 10/2013).</b>            TWA: 50 ppm 10 hours.            TWA: 180 mg/m<sup>3</sup> 10 hours.  <b>OSHA PEL (United States, 6/2016).</b>            TWA: 500 ppm 8 hours.            TWA: 1800 mg/m<sup>3</sup> 8 hours.</p>

### 8.2 Exposure controls

#### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



## Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : >35°C (>95°F)
- Flash point** : Closed cup: -57°C (-70.6°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Lower and upper explosive (flammable) limits** : Lower: 1.5%  
Upper: 7.6%
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : Not available.
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

## Section 10. Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dodecane	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Hexadecane	LC50 Inhalation Dusts and mists	Rat	>5266 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Tetradecane	LC50 Inhalation Vapor	Rat	9.3 mg/l	4 hours
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Decane	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
pentane	LC50 Inhalation Vapor	Rat	364 g/m <sup>3</sup>	4 hours
Propylbenzene	LD50 Oral	Rat	6040 mg/kg	-
p-Xylene	LC50 Inhalation Vapor	Rat	4550 ppm	4 hours
	LD50 Oral	Rat	3910 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Tridecane	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Pentadecane	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Octane	LC50 Inhalation Vapor	Rat	118 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	25260 ppm	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Heptane	LC50 Inhalation Vapor	Rat	103 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
n-Hexane	LC50 Inhalation Vapor	Rat - Male, Female	>31.86 mg/l	4 hours

**Section 11. Toxicological information**

	LC50 Inhalation Vapor LD50 Oral	Rat Rat	48000 ppm 15840 mg/kg	4 hours -
--	------------------------------------	------------	--------------------------	--------------

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Decane	Skin - Moderate irritant	Rat	-	96 hours 300 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 0.05 Milliliters	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
Tridecane	Skin - Severe irritant	Rabbit	-	24 hours 0.05 Milliliters	-
n-Hexane	Eyes - Mild irritant	Rabbit	-	10 milligrams	-

**Conclusion/Summary****Skin**

: Repeated exposure may cause skin dryness or cracking.

**Sensitization**

Not available.

**Mutagenicity**

Not available.

**Carcinogenicity**

Not available.

**Classification**

Product/ingredient name	OSHA	IARC	NTP
p-Xylene	-	3	-
Toluene	-	3	-

**Reproductive toxicity**

Not available.

**Teratogenicity**

Not available.

**Specific target organ toxicity (single exposure)**

Name	Category	Route of exposure	Target organs
pentane	Category 3	Not applicable.	Narcotic effects
Propylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
p-Xylene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Toluene	Category 3	Not applicable.	Respiratory tract

**Section 11. Toxicological information**

2-Methylpentane	Category 3	Not applicable.	irritation and Narcotic effects Respiratory tract irritation and Narcotic effects
Butylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Tridecane	Category 3	Not applicable.	Respiratory tract irritation
Octane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Heptane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2,4-Dimethylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
n-Hexane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

**Specific target organ toxicity (repeated exposure)**

<b>Name</b>	<b>Category</b>	<b>Route of exposure</b>	<b>Target organs</b>
p-Xylene	Category 2	Not determined	kidneys, liver and nervous system
Toluene	Category 2	Oral	central nervous system (CNS) and kidneys
n-Hexane	Category 2	Not determined	nervous system and peripheral nervous system

**Aspiration hazard**

<b>Name</b>	<b>Result</b>
Boiling Point Calibration Sample #3 Kit, Part Number 5080-8769	ASPIRATION HAZARD - Category 1
dodecane	ASPIRATION HAZARD - Category 1
Hexadecane	ASPIRATION HAZARD - Category 1
Decane	ASPIRATION HAZARD - Category 1
pentane	ASPIRATION HAZARD - Category 1
Propylbenzene	ASPIRATION HAZARD - Category 1
p-Xylene	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
2-Methylpentane	ASPIRATION HAZARD - Category 1
n-Heptadecane	ASPIRATION HAZARD - Category 1
Tridecane	ASPIRATION HAZARD - Category 1
Pentadecane	ASPIRATION HAZARD - Category 1
Octane	ASPIRATION HAZARD - Category 1
Heptane	ASPIRATION HAZARD - Category 1
2,4-Dimethylpentane	ASPIRATION HAZARD - Category 1
n-Hexane	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

**Potential acute health effects**

## Section 11. Toxicological information

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

## Section 11. Toxicological information

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	8615.6 mg/kg
Dermal	13177.1 mg/kg
Inhalation (vapors)	44.18 mg/l

## Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Decane	Acute EC50 89 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute LC50 18000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 >500 ppm Marine water	Fish - Cyprinodon variegatus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
Propylbenzene	Acute EC50 1800 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
p-Xylene	Acute LC50 1550 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 3200 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Toluene	Acute EC50 4730 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2 µl/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Butylbenzene	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
Heptane	Chronic NOEC 0.74 mg/l	Daphnia - Ceriodaphnia dubia	7 days
	Acute EC50 340 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
n-Hexane	Acute LC50 375000 µg/l Fresh water	Fish - Oreochromis mossambicus	96 hours
	Acute LC50 2500 µg/l Fresh water	Fish - Pimephales promelas	96 hours

### 12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hexadecane	-	-	Readily
Tetradecane	-	-	Readily
pentane	-	-	Readily
Toluene	-	-	Readily
Pentadecane	-	-	Readily
Octane	-	-	Readily

### 12.3 Bioaccumulative potential

## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
dodecane	6.98	239.88	low
Hexadecane	8.25	5011.87	high
Tetradecane	8.11	-	high
Decane	5.86	-	high
pentane	3.45	171	low
Propylbenzene	3.69	-	low
p-Xylene	3.15	8.1 to 25.9	low
Toluene	2.73	90	low
2-Methylpentane	3.21	-	low
Butylbenzene	4.38	-	high
Tridecane	7.54	-	high
Pentadecane	7.71	-	high
Octane	5.18	198.7	low
Heptane	4.66	552	high
2,4-Dimethylpentane	3.9	-	low
n-Hexane	4	501.187	high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**12.5 Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Xylene Toluene; Benzene, methyl-	106-42-3 108-88-3	Listed Listed	U239 U220

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.



## Section 13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

**DOT / TDG / Mexico / IMDG / IATA** : Not regulated.

### Additional information

**Remarks:** De minimis quantities

**DOT Classification** : **Reportable quantity** 2083.3 lbs / 945.83 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**U.S. Federal regulations** : **TSCA 8(a) PAIR:** pentane; p-Xylene; Heptane  
**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**Clean Water Act (CWA) 307:** Toluene  
**Clean Water Act (CWA) 311:** p-Xylene; Toluene  
**Clean Air Act (CAA) 112 regulated flammable substances:** pentane

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard  
Immediate (acute) health hazard  
Delayed (chronic) health hazard

#### Composition/information on ingredients

## Section 15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
<input checked="" type="checkbox"/> Dodecane	≥10 - ≤25	Yes.	No.	No.	Yes.	No.
Hexadecane	≤10	Yes.	No.	No.	Yes.	No.
Tetradecane	≤10	No.	No.	No.	Yes.	No.
Decane	≤10	Yes.	No.	No.	Yes.	No.
pentane	≤10	Yes.	No.	No.	Yes.	No.
Propylbenzene	≤5	Yes.	No.	No.	Yes.	No.
p-Xylene	≤5	Yes.	No.	No.	Yes.	Yes.
Toluene	≤5	Yes.	No.	No.	Yes.	Yes.
2-Methylpentane	≤5	Yes.	No.	No.	Yes.	No.
Butylbenzene	≤5	Yes.	No.	No.	Yes.	No.
Tridecane	≤5	Yes.	No.	No.	Yes.	No.
Pentadecane	≤5	No.	No.	No.	Yes.	No.
Octane	≤5	Yes.	No.	No.	Yes.	No.
Heptane	≤5	Yes.	No.	No.	Yes.	No.
2,4-Dimethylpentane	≤5	Yes.	No.	No.	Yes.	No.
n-Hexane	<5	Yes.	No.	No.	Yes.	Yes.

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	<input checked="" type="checkbox"/> p-Xylene	106-42-3	≤5
	Toluene	108-88-3	≤5
	n-Hexane	110-54-3	<5
<b>Supplier notification</b>	<input checked="" type="checkbox"/> p-Xylene	106-42-3	≤5
	Toluene	108-88-3	≤5
	n-Hexane	110-54-3	<5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

#### Massachusetts

The following components are listed: PENTANE; PROPYL BENZENE; N-PROPYLBENZENE; P-XYLENE; P-DIMETHYLBENZENE; TOLUENE; METHYLBENZENE; ISOHEXANE; BUTYLBENZENE; N-BUTYLBENZENE; OCTANE; HEPTANE; N-HEPTANE; 2,4-DIMETHYLPENTANE; HEXANE; N-HEXANE

#### New York

The following components are listed: p-Xylene; Toluene; Hexane

#### New Jersey

The following components are listed: DECANE; PENTANE; PROPYL BENZENE; BENZENE, PROPYL-; p-XYLENE; BENZENE, 1,4-DIMETHYL-; TOLUENE; BENZENE, METHYL-; 2-METHYLPENTANE; ISOHEXANE; BUTYL BENZENE; BENZENE, BUTYL-; OCTANE; n-HEPTANE; HEPTANE; 2,4-DIMETHYLPENTANE; PENTANE, 2, 4-DIMETHYL-; n-HEXANE; HEXANE

#### Pennsylvania

The following components are listed: DECANE; PENTANE; BENZENE, PROPYL-; BENZENE, 1,4-DIMETHYL-; BENZENE, METHYL-; PENTANE, 2-METHYL-; BENZENE, BUTYL-; OCTANE; HEPTANE; PENTANE, 2,4-DIMETHYL-; HEXANE

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
<input checked="" type="checkbox"/> Toluene	No.	Yes.	-	Yes.

### International regulations

## Section 15. Regulatory information

### [Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

### [Montreal Protocol \(Annexes A, B, C, E\)](#)

Not listed.

### [Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

### [Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

### [Inventory list](#)

<a href="#">Australia</a>	: Not determined.
<a href="#">Canada</a>	: At least one component is not listed in DSL but all such components are listed in NDSL.
<a href="#">China</a>	: All components are listed or exempted.
<a href="#">Europe</a>	: All components are listed or exempted.
<a href="#">Japan</a>	: <input checked="" type="checkbox"/> <b>Japan inventory (ENCS)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : Not determined.
<a href="#">Malaysia</a>	: Not determined.
<a href="#">New Zealand</a>	: All components are listed or exempted.
<a href="#">Philippines</a>	: All components are listed or exempted.
<a href="#">Republic of Korea</a>	: Not determined.
<a href="#">Taiwan</a>	: All components are listed or exempted.
<a href="#">Thailand</a>	: <input checked="" type="checkbox"/> Not determined.
<a href="#">Turkey</a>	: Not determined.
<a href="#">United States</a>	: All components are listed or exempted.
<a href="#">Viet Nam</a>	: <input checked="" type="checkbox"/> Not determined.

## Section 16. Other information

### [History](#)

<a href="#">Date of issue</a>	: 07/21/2017
<a href="#">Date of previous issue</a>	: 05/02/2016.
<a href="#">Version</a>	: 5

Indicates information that has changed from previously issued version.

### [Notice to reader](#)

**Disclaimer:** The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.