

SAFETY DATA SHEET

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 2X Hi-RPM Hybridization Buffer, 25 ml
Part no. : 5190-0403

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Analytical reagent.
 25 ml 2X Hi-RPM Hybridization Buffer 5188-6420
Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Agilent Technologies Deutschland GmbH
 Hewlett-Packard-Str. 8
 76337 Waldbronn
 Germany
 0800 603 1000
e-mail address of person responsible for this SDS : pdl-msds_author@agilent.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation) : CHEMTREC®: +353 1 901 4670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

H315	SKIN CORROSION/IRRITATION	Category 2
H318	SERIOUS EYE DAMAGE/EYE IRRITATION	Category 1
H412	LONG-TERM (CHRONIC) AQUATIC HAZARD	Category 3
EUH430	ENDOCRINE DISRUPTOR FOR THE ENVIRONMENT	Category 1

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 10 - 30%
 Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 1 - 10%
 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 1 - 10%

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hi-RPM Hybridization Buffer, 25 ml

SECTION 2: Hazards identification

Hazard statements : H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H412 - Harmful to aquatic life with long lasting effects.
EUH430 - May cause endocrine disruption in the environment.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
P280 - Wear protective gloves. Wear eye or face protection.
P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Polyoxyethylene octyl phenyl ether and lithium hydroxide

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. : Contains Polyoxyethylene octyl phenyl ether. May cause endocrine disruption.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
<input checked="" type="checkbox"/> morpholinoethanesulphonic acid	EC: 224-632-3 CAS: 145224-94-8	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	-	[1]
lithium chloride	EC: 231-212-3 CAS: 7447-41-8	≤10	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 526 mg/kg	[1]
lithium dodecyl sulphate	EC: 218-058-2 CAS: 2044-56-6	≤5	Flam. Sol. 1, H228 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)]	[1]

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 3: Composition/information on ingredients

Polyoxyethylene octyl phenyl ether	CAS: 9002-93-1	<2.5	Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412	= 1.5 mg/l Eye Dam. 1, H318: C ≥ 20% Eye Irrit. 2, H319: 10% ≤ C < 20%	
Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-(trimethylsilyloxy)-1-disiloxanyl]propyl] ether	CAS: 134180-76-0	≤3	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 ED ENV 1, EUH430	ATE [Oral] = 1800 mg/kg M [Acute] = 10 M [Chronic] = 1	[1] [2]
lithium hydroxide	EC: 215-183-4 CAS: 1310-66-3	≤2.6	Acute Tox. 4, H302 Skin Corr. 1B, H314 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance of equivalent concern - Endocrine disrupting properties

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 4: First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 pain
 watering
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
- Ingestion** : Adverse symptoms may include the following:
 stomach pains

4.3 Indication of any immediate medical attention and special treatment needed


- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** :  In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. This material may cause endocrine disruption in the environment. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
 carbon dioxide
 carbon monoxide
 nitrogen oxides
 sulfur oxides
 halogenated compounds
 metal oxide/oxides

5.3 Advice for firefighters

X Hi-RPM Hybridization Buffer, 25 ml

SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : **A**void dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. May be harmful to the environment if released. Dispose of spillages under controlled conditions.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : **P**ut on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Avoid breathing vapour or mist. Avoid release to the environment. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Do not breathe vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 7: Handling and storage

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Result

lithium chloride	DNEL - General population - Long term - Oral	0.38 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	0.56 mg/m ³
	DNEL - General population - Short term - Oral	1.14 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	3.5 mg/m ³
	DNEL - General population - Long term - Dermal	3.75 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	9.9 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	30 mg/m ³
	DNEL - Workers - Short term - Inhalation	30 mg/m ³
	DNEL - General population - Short term - Dermal	50 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	100 mg/kg bw/day
lithium dodecyl sulphate	DNEL - General population - Long term - Inhalation	2.26 mg/m ³
	DNEL - General population - Long term - Oral	2.6 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	7.6 mg/m ³
	DNEL - General population - Long term - Dermal	260 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	433.3 mg/kg bw/day

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Yellow. [Light]
- Odour** : Not available.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : Not available.
- Flammability** : Not applicable.
- Lower and upper explosion limit/flammability limit** : Not available.
- Flash point** :

Ingredient name	Closed cup		Open cup	
	°C	Method	°C	Method
Polyoxyethylene octyl phenyl ether	>109.85	-	-	-

- Auto-ignition temperature** :

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 9: Physical and chemical properties

Ingredient name	°C	Method
Lithium dodecyl sulphate	366	-

Decomposition temperature : Not available.

pH : 6.1

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Solubility	Media	Result
	water	Soluble

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure	Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
		mm Hg	kPa	Method	mm Hg	kPa	Method
	Water	17.5	2.3	-	92.258	12.3	-
	Polyoxyethylene octyl phenyl ether	0.997581	0.13	-	-	-	-

Relative density : Not available.

Relative vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Miscible with water : Yes.

Evaporation rate : Not available.

Physical/chemical properties comments : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : May react or be incompatible with oxidising materials.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	
lithium chloride	Rat - Oral - LD50	526 mg/kg
	Rat - Male, Female - Inhalation - LC50 Dusts and mists	>5.57 mg/l [4 hours]
lithium dodecyl sulphate	Rat - Oral - LD50	>5000 mg/kg
Polyoxyethylene octyl phenyl ether	Rat - Oral - LD50	1800 mg/kg

Conclusion/Summary : Not available.

[Product]

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2X Hi-RPM Hybridization Buffer, 25 ml	5264.0	N/A	N/A	733.3	50
lithium chloride	526	N/A	N/A	N/A	N/A
lithium dodecyl sulphate	500	N/A	N/A	N/A	1.5
Polyoxyethylene octyl phenyl ether	1800	N/A	N/A	N/A	N/A
Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyloxy)-1-disiloxanyl]propyl] ether	N/A	N/A	N/A	11	N/A
lithium hydroxide	500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name	Result	
lithium chloride	Rabbit - Skin - Severe irritant	Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg
Polyoxyethylene octyl phenyl ether	Rabbit - Skin - Mild irritant	Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 uL

Conclusion/Summary : Not available.

[Product]

Serious eye damage/eye irritation

Product/ingredient name	Result	
lithium chloride	Rabbit - Eyes - Moderate irritant	Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Conclusion/Summary : Not available.

[Product]

Respiratory corrosion/irritation

Conclusion/Summary : Not available.

[Product]

Respiratory or skin sensitization

Skin

Conclusion/Summary : May cause skin sensitisation.

[Product]

Hi-RPM Hybridization Buffer, 25 ml

SECTION 11: Toxicological information

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
<input checked="" type="checkbox"/> morpholinoethanesulphonic acid	STOT SE 3, H335 (Respiratory tract irritation)
lithium dodecyl sulphate	STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Result

2 -morpholinoethanesulphonic acid	Acute - LC50 - Fresh water	>108 mg/l [96 hours]
	Acute - NOEC - Fresh water	108 mg/l [96 hours]
	Acute - EC50 - Fresh water	>108 mg/l [48 hours]
	Acute - NOEC - Fresh water	108 mg/l [48 hours]
	Acute - EC50 - Fresh water	>108 mg/l [72 hours]
	Acute - NOEC - Fresh water	108 mg/l [72 hours]
lithium chloride	Acute - NOEC - Fresh water	59.4 mg/l [96 hours]
	Acute - EC50 - Fresh water	249 mg/l [48 hours]
	Acute - NOEC - Fresh water	63.4 mg/l [48 hours]
	Acute - EC50 - Fresh water	112 mg/l [72 hours]
	Acute - NOEC - Fresh water	25 mg/l [72 hours]
Polyoxyethylene octyl phenyl ether	Acute - LC50 - Fresh water	4500 µg/l [96 hours]
	Acute - LC50 - Fresh water	5.85 mg/l [48 hours]
	Chronic - NOEC - Fresh water	0.004 mg/l [28 days]
lithium hydroxide	Acute - LC50 - Fresh water	62.2 mg/l [96 hours]
	Chronic - NOEC - Fresh water	9.9 mg/l [34 days]
	Acute - EC50 - Fresh water	23.75 mg/l [72 hours]
	Acute - NOEC - Fresh water	5.71 mg/l [72 hours]
	Acute - EC50 - Fresh water	19.1 mg/l [48 hours]
	Chronic - NOEC - Fresh water	2.3 mg/l [21 days]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2 lithium chloride	-	-	Readily
lithium dodecyl sulphate	-	-	Readily
Polyoxyethylene octyl phenyl ether	-	-	Readily

12.3 Bioaccumulative potential

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Polyoxyethylene octyl phenyl ether	4.86	-	High

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
lithium dodecyl sulphate	3.1	1234.14

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
2-morpholinoethanesulphonic acid	No	N/A	N/A	No	N/A	N/A	N/A
lithium chloride	No	No	No	No	No	No	No
lithium dodecyl sulphate	No	N/A	No	No	No	N/A	No
Polyoxyethylene octyl phenyl ether	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-(trimethylsilyl)oxy]-1-disiloxanyl]propyl] ether	No	N/A	N/A	No	N/A	N/A	N/A
lithium hydroxide	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-morpholinoethanesulphonic acid	No	N/A	N/A	No	N/A	N/A	N/A
lithium chloride	No	No	No	No	No	No	No
lithium dodecyl sulphate	No	N/A	N/A	No	N/A	N/A	N/A
Polyoxyethylene octyl phenyl ether	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-(trimethylsilyl)oxy]-1-disiloxanyl]propyl] ether	No	N/A	N/A	No	N/A	N/A	N/A
lithium hydroxide	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-morpholinoethanesulphonic acid	No	N/A	N/A	No	N/A	N/A	N/A
lithium chloride	No	No	No	No	No	No	No
lithium dodecyl sulphate	No	N/A	N/A	No	N/A	N/A	N/A
Polyoxyethylene octyl phenyl ether	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-(trimethylsilyl)oxy]-1-disiloxanyl]propyl] ether	No	N/A	N/A	No	N/A	N/A	N/A
lithium hydroxide	No	No	No	No	No	No	No

Hi-RPM Hybridization Buffer, 25 ml

SECTION 12: Ecological information

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Conclusion/Summary [Product] : May cause endocrine disruption. May cause endocrine disruption in the environment.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. The generation of waste should be avoided or minimised wherever possible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : Dispose of material(s) and residues under controlled conditions. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

Additional information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Hi-RPM Hybridization Buffer, 25 ml

SECTION 14: Transport information

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
<input checked="" type="checkbox"/> Polyoxyethylene octyl phenyl ether	Endocrine disrupting properties for environment	Listed	42	7/3/2017

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
<input checked="" type="checkbox"/> Polyoxyethylene octyl phenyl ether	Endocrine disrupting properties for environment	Recommended	5th recommendation	2/6/2014

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

None of the components are listed / The components are not impacted by a restriction

Labelling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

 **Hi-RPM Hybridization Buffer, 25 ml**

SECTION 15: Regulatory information


Not listed.

Inventory list

Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments might still be required.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- B = Bioaccumulative
- BCF = Bioconcentration Factor
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- M = Mobile
- N/A = Not available
- P = Persistent
- PBT = Persistent, Bioaccumulative and Toxic
- PMT = Persistent, Mobile and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SGG = Segregation Group
- T = Toxic
- vB = Very Bioaccumulative
- vM = Very Mobile
- vP = Very Persistent
- vPvB = Very Persistent and Very Bioaccumulative
- vPvM = Very Persistent and Very Mobile

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

2X Hi-RPM Hybridization Buffer, 25 ml

SECTION 16: Other information

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412 ED ENV 1, EUH430	Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H228 H302 H314 H315 H318 H319 H332 H335 H400 H410 H412 EUH430	Flammable solid. Harmful if swallowed. Causes severe skin burns and eye damage. Causes skin irritation. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause endocrine disruption in the environment.
--	--

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 ED ENV 1 Eye Dam. 1 Eye Irrit. 2 Flam. Sol. 1 Skin Corr. 1B Skin Irrit. 2 STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ENDOCRINE DISRUPTOR FOR THE ENVIRONMENT - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE SOLIDS - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

Date of issue/ Date of revision : 30/01/2026

Date of previous issue : 27/12/2022

Version : 2

Notice to reader

Disclaimer: The information contained in this document is based on Agilent’s state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.