



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

Revision date 06-Aug-2024

Revision Number 1

1. Identification

Product identifier

Product Name Tantalum Standard: 10000 µg/mL Ta in 2% HF [500ml bottle]

Other means of identification

Product Code(s) 5190-8212

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Reagents and Standards for Analytical Chemical Laboratory Use

Restrictions on use Not to be used for human or animal consumption

Details of the supplier of the safety data sheet

Supplier Address

Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA

800-227-9770

E-mail pdl-msds_author@agilent.com

Emergency telephone number

Emergency Telephone
CHEMTREC®: 1-800-424-9300

2. Hazard(s) identification

Classification

Classified according to OSHA.

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

Corrosive to metals

Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Classified according to OSHA.

Toxic if swallowed

Toxic in contact with skin

Harmful if inhaled

Causes severe skin burns and eye damage

May be corrosive to metals



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dusts or mists

Wear protective gloves/clothing and eye/face protection

Keep only in original packaging

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

Call a POISON CENTER or doctor if you feel unwell

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Rinse mouth

Do NOT induce vomiting



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

Absorb spillage to prevent material damage

Precautionary Statements - Storage

Store in corrosion resistant container with a resistant inner liner

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical nature aqueous solution.

Chemical name	CAS No.	Weight-%	Trade secret
hydrofluoric acid	7664-39-3	1 - <3	*

Additional information

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

4. First-aid measures

Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Inhalation

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical attention.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

	while rinsing. Do not rub affected area. Get immediate medical attention.
Skin contact	Get immediate medical attention. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get immediate medical attention.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors or mists. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Attention! Corrosive material. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
---------------	-----------	----------	-------



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

hydrofluoric acid 7664-39-3	TWA: 0.5 ppm F S* Ceiling: 2 ppm F	TWA: 3 ppm F (vacated) TWA: 3 ppm F (vacated) STEL: 6 ppm F	IDLH: 30 ppm Ceiling: 6 ppm 15 min Ceiling: 5 mg/m ³ 15 min TWA: 3 ppm TWA: 2.5 mg/m ³
--------------------------------	--	---	--

Biological occupational exposure limits

Chemical name	ACGIH
hydrofluoric acid 7664-39-3	3 mg/g creatinine - urine (Fluoride) - prior to shift 10 mg/g creatinine - urine (Fluoride) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
----------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Tight sealing safety goggles. Face protection shield.
Hand protection	Wear protective Neoprene™ gloves. The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374. Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Environmental exposure controls	Do not allow into any sewer, on the ground or into any body of water.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Information on basic physical and chemical properties



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

Physical state	Liquid
Appearance	Liquid
Color	No information available
Odor	No information available
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

<u>Other information</u>	
Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	No information available
Liquid Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Exposure to air or moisture over prolonged periods. Excessive heat.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

Incompatible materials Oxidizing agent. Acids. Bases.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. Harmful by inhalation.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components). Corrosive to the eyes and may cause severe damage including blindness. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. Toxic in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	250.50 mg/kg
ATEmix (dermal)	250.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

ATEmix (inhalation-dust/mist) 2.50 mg/l
ATEmix (inhalation-vapor) 99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
hydrofluoric acid 7664-39-3	-	-	= 0.79 mg/L (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye damage. Causes burns.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]

Revision date 06-Aug-2024

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
hydrofluoric acid 7664-39-3	-	-	-	EC50: =270mg/L (48h, Daphnia species)

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
hydrofluoric acid 7664-39-3	-1.4

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

14. Transport information

DOT

UN number or ID number UN1790
Extended proper shipping name Hydrofluoric acid mixture
Transport hazard class(es) 8
Subsidiary hazard class 6.1
Packing group II
Reportable Quantity (RQ) (hydrofluoric acid: RQ (kg)= 45.40) hydrofluoric acid: RQ (lb)= 100.00
Reportable quantity (kg) (calculated) hydrofluoric acid: RQ (kg)= 2270.00

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

Reportable quantity (lbs) (calculated)	hydrofluoric acid: RQ (lb)= 5000.00
Special Provisions	A7, B15, IB2, N5, N34, T8, TP2,
DOT Marine Pollutant	NP
Description	UN1790, Hydrofluoric acid mixture, 8 (6.1), II
Emergency Response Guide Number	157

TDG

UN number or ID number	UN1790
UN proper shipping name	Hydrofluoric acid mixture
Transport hazard class(es)	8
Subsidiary hazard class	6.1
Packing group	II
Marine pollutant	NP
Description	UN1790, Hydrofluoric acid mixture, 8 (6.1), II

MEX

UN number or ID number	UN1790
UN proper shipping name	Hydrofluoric acid mixture
Transport hazard class(es)	8
Subsidiary hazard class	6.1
Packing group	II
Description	UN1790, Hydrofluoric acid mixture, 8 (6.1), II

IATA

UN number or ID number	UN1790
UN proper shipping name	Hydrofluoric acid mixture
Transport hazard class(es)	8
Subsidiary hazard class	6.1
Packing group	II
Description	UN1790, Hydrofluoric acid mixture, 8 (6.1), II
ERG Code	8P

IMDG

UN number or ID number	UN1790
UN proper shipping name	Hydrofluoric acid mixture
Transport hazard class(es)	8
Subsidiary hazard class	6.1
Packing group	II
EmS-No.	F-A, S-B
Marine pollutant	NP
Description	UN1790, Hydrofluoric acid mixture, 8 (6.1), II

15. Regulatory information



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

International Inventories

TSCA

LGC, to the best of its ability, has confirmed that the chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb 2019, as amended Feb 2021."

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
hydrofluoric acid	7664-39-3	Present	Active

DSL/NDSL

Contact supplier for inventory compliance status.

EINECS/ELINCS

Contact supplier for inventory compliance status.

ENCS

Contact supplier for inventory compliance status.

IECSC

Contact supplier for inventory compliance status.

KECI

Contact supplier for inventory compliance status.

PICCS

Contact supplier for inventory compliance status.

AIIC

Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AIIC - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
hydrofluoric acid - 7664-39-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
hydrofluoric acid 7664-39-3	100 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
hydrofluoric acid 7664-39-3	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5	-	-	X
hydrofluoric acid 7664-39-3	X	X	X
Tantalum 7440-25-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 3	Flammability 0	Instability 0	Special hazards -
HMIS	Health hazards 3	Flammability 0	Physical hazards 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8212 - Tantalum Standard: 10000 µg/mL Ta in 2%
HF [500ml bottle]**

Revision date 06-Aug-2024

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 06-Aug-2024

Revision Note No information available.

Disclaimer

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

End of Safety Data Sheet