



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Hazardous according to criteria of Australian Safety and Compensation Council

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO₃ [100ml bottle]**

· **Part number:** 5190-8250

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Reference material for laboratory use only

· **Manufacturer/Supplier:**

Agilent Technologies Australia Pty Ltd
679 Springvale Road
Mulgrave
Victoria 3170, Australia

Tel: 1800 802 402

· **Further information obtainable from:** e-mail: pdl-msds_author@agilent.com

· **1.4 Emergency telephone number:** CHEMTREC®: +(61) - 290372994

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



health hazard

Carc. 1B H350 May cause cancer.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45: May cause cancer.



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R38-41: Irritating to skin. Risk of serious damage to eyes.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO₃ [100ml bottle]

(Contd. from page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
BERYLLIUM OXYACETATE
- **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
H350 May cause cancer.
- **Precautionary statements**
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Contains BERYLLIUM OXYACETATE. May produce an allergic reaction.
Restricted to professional users.
- **Information concerning particular hazards for human and environment:**
- **Safety phrases:**
53 Avoid exposure - obtain special instructions before use.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
60 This material and its container must be disposed of as hazardous waste.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:**
Aqueous solution.
Mixture: consisting of the following components.

(Contd. on page 3)

AU



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 2)

· Dangerous components:

CAS: 7697-37-2 EINECS: 231-714-2 RTECS: QU5775000	Nitric acid C R35; O R8 Ox. Liq. 3, H272; Skin Corr. 1A, H314	< 5%
CAS: 19049-40-2 EINECS: 242-785-4 RTECS: DS2900000	BERYLLIUM OXYACETATE T+ R26; T Carc. Cat. 2 R45-25-48/23/24/25; Xi R36/38; Xi R43; N R51/53 Acute Tox. 3, H301; Acute Tox. 2, H330; Carc. 1B, H350; STOT RE 1, H372; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	< 0.1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may occur even after several hours; therefore medical observation for at least 48 hours after the accident is recommended.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient in recovery position for transport.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Rinse mouth. Do not induce vomiting.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective clothing.

· **6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 3)

DO NOT USE SAWDUST.

· 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

- Ensure good ventilation/extraction at the workplace.
- Store in cool, dry place in tightly closed receptacles.
- Open and handle receptacle with care.
- Prevent formation of aerosols.

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

- Store in a cool location.
- Please refer to the manufacturer's certificate for specific storage and transport temperature conditions.
- Store only in the original receptacle.
- Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions: Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

7697-37-2 Nitric acid

NES	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5.2 mg/m ³ , 2 ppm

· Additional information: Lists used were valid at the time of SDS preparation.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Chemical-resistant, impervious gloves with an approved standards should be worn at all times.

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 4)

The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

· **Material of gloves**

PVC gloves

Neoprene gloves

· **Penetration time of glove material**

The protection time of the gloves can not be accurately estimated for mixtures consisting of several substances

Refer to and observe manufacturers break through times of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Colour: Colourless

· **Odour:** Odourless

· **Odour threshold:** Not determined.

· **pH-value at 20 °C:** < 2

· **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 100 °C

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapour pressure at 20 °C:** 23 hPa

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 5)

- | | |
|---|--|
| · Solubility in / Miscibility with water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable under normal conditions.
- **10.2 Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Heat.
- **10.5 Incompatible materials:** Strong oxidizing agents.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

7697-37-2 Nitric acid

Oral	LD0	430 mg/kg (Human)
Inhalative	LC50/4 h	130 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Carcinogenic.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Carc. 1B

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

7697-37-2 Nitric acid

LC50/48	180 mg/l (crustacean)
---------	-----------------------

- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO₃ [100ml bottle]


(Contd. from page 6)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
Waste disposal key numbers from EWC have to be assigned depending on origin and processing.
- **Uncleaned packaging:**
- **Recommendation:** Dispose of in accordance with national regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADG, IMDG, IATA · ADG · IMDG, IATA | <p style="margin: 0;">UN2031
2031 NITRIC ACID solution
NITRIC ACID solution</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADG, IMDG, IATA | <p style="margin: 0;"></p> <p style="margin: 0;">8 Corrosive substances.
8</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADG, IMDG, IATA | <p style="margin: 0;">II</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <p style="margin: 0;">No</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups | <p style="margin: 0;">Warning: Corrosive substances.
80
F-A,S-Q
Acids</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <p style="margin: 0;">Not applicable.</p> |

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 7)

· Transport/Additional information:

· ADG

· **Limited quantities (LQ)** 1L

· **Transport category** 2

· **Tunnel restriction code** E

· **UN "Model Regulation":** UN2031, NITRIC ACID solution, 8, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Philippines Inventory of Chemicals and Chemical Substances

7697-37-2	Nitric acid
	Purified water

· Australian Inventory of Chemical Substances

7697-37-2	Nitric acid
	Purified water

· Standard for the Uniform Scheduling of Medicines and Poisons

7697-37-2	Nitric acid	S5, S6
-----------	-------------	--------

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

R25 Toxic if swallowed.

R26 Very toxic by inhalation.

R35 Causes severe burns.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R45 May cause cancer.

R48/23/24/25 Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. from page 8)

R8 Contact with combustible material may cause fire.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Ox. Liq. 3: Oxidising Liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 2: Acute toxicity, Hazard Category 2

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1B: Carcinogenicity, Hazard Category 1B

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

-AU-