



Safety Data Sheet acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

1 Identification

- **Product identifier**
- **Product name:** Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [100ml bottle]
- **Part number:** 5190-8264
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051,
USA
- **Information department:** e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

Tel: 800-227-9770

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1B H350 May cause cancer.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

nitric acid

Beryllium Oxyacetate

(Contd. on page 2)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 1)

• Hazard statements

H290 May be corrosive to metals.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

• Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• Classification system:**• NFPA ratings (scale 0 - 4)**

Health = 3
Fire = 0
Reactivity = 0

• HMIS-ratings (scale 0 - 4)

Health = 3
Fire = 0
Reactivity = 0

• Other hazards**• Results of PBT and vPvB assessment**• **PBT:** Not applicable.• **vPvB:** Not applicable.

3 Composition/information on ingredients

• Chemical characterization: Mixtures**• Description:** Aqueous solution.**• Dangerous components:**

CAS: 7697-37-2	nitric acid	<5%
RTECS: QU5775000	◆ Ox. Liq. 3, H272; ◆ Acute Tox. 3, H331; ◆ Met. Corr. I, H290; Skin Corr. 1A, H314	
CAS: 19049-40-2	Beryllium Oxyacetate	<0.25%
RTECS: DS2900000	◆ Acute Tox. 3, H301; Acute Tox. 2, H330; ◆ Carc. 1B, H350; STOT RE 1, H372; ◆ Aquatic Chronic 2, H411; ◆ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	

• Additional information:

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

US

(Contd. on page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 2)

4 First-aid measures

- Description of first aid measures**
- General information:**

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Seek medical treatment.
- After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:** Rinse mouth. Do not induce vomiting.
- Information for doctor:**
- Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**
- Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.
- Advice for firefighters**
- Protective equipment:**

Mouth respiratory protective device.
Wear self-contained respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:**

Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:**

Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
DO NOT USE SAWDUST.
- Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

· Protective Action Criteria for Chemicals

(Contd. of page 3)

· PAC-1:

CAS: 7697-37-2	nitric acid	0.16 ppm
----------------	-------------	----------

· PAC-2:

CAS: 7697-37-2	nitric acid	24 ppm
----------------	-------------	--------

· PAC-3:

CAS: 7697-37-2	nitric acid	92 ppm
----------------	-------------	--------

7 Handling and storage

· Handling:

· Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Please refer to the manufacturers certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5.2 mg/m³, 2 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

· Material of gloves

PVC gloves

Neoprene gloves

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

Colorless

· Odor:

Odorless

· Odor threshold:

Not determined.

· pH-value:

<2

· Change in condition

Melting point/Melting range:

0 °C (32 °F)

Boiling point/Boiling range:

100 °C (212 °F)

· Flash point:

Not applicable.

· Flammability (solid, gaseous):

Not determined.

· Ignition temperature:

Not determined

(Contd. on page 6)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity

Stable under normal conditions.

No further relevant information available.

· Chemical stability Stable under normal conditions.**· Thermal decomposition / conditions to be avoided:**

Formation of toxic gases is possible during heating or in case of fire.

· Possibility of hazardous reactions No dangerous reactions known.**· Conditions to avoid** Heat.**· Incompatible materials:**

Strong oxidizing agents.

Metals.

· Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

· Information on toxicological effects**· Acute toxicity:****· LD/LC50 values that are relevant for classification:**

CAS: 7697-37-2 nitric acid

Inhalative | LC50/4 h | 2.65 mg/l (rat)

· Primary irritant effect:**· on the skin:** Irritant to skin and mucous membranes.

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 6)

· **on the eye:** Strong irritant with the danger of severe eye injury.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 19049-40-2	Beryllium Oxyacetate	I
-----------------	----------------------	---

· **NTP (National Toxicology Program)**

CAS: 19049-40-2	Beryllium Oxyacetate	K
-----------------	----------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

CAS: 7697-37-2 nitric acid

LC50/48	180 mg/l (crustacean)
---------	-----------------------

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Dispose in accordance with national regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3264
· DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR, IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 8)

· **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara**

- Section 355 (extremely hazardous substances):**

CAS: 7697-37-2 nitric acid

- Section 313 (Specific toxic chemical listings):**

CAS: 7697-37-2 nitric acid

CAS: 19049-40-2 Beryllium Oxyacetate

- TSCA (Toxic Substances Control Act):**

CAS: 7732-18-5 Water

ACTIVE

CAS: 7697-37-2 nitric acid

ACTIVE

- Hazardous Air Pollutants**

None of the ingredients is listed.

- Proposition 65**

- Chemicals known to cause cancer:**

CAS: 19049-40-2 Beryllium Oxyacetate

- Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- Carcinogenic categories**

- EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- TLV (Threshold Limit Value)**

None of the ingredients is listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)**

CAS: 19049-40-2 Beryllium Oxyacetate

- Hazard pictograms**



GHS05



GHS07



GHS08

- Signal word Danger**

(Contd. on page 10)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 9)

• Hazard-determining components of labeling:

nitric acid

Beryllium Oxyacetate

• Hazard statements

H290 May be corrosive to metals.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

• Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• National regulations:

• Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

• Contact:

• Date of preparation / last revision 03/19/2021 / -

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 3: Oxidizing liquids – Category 3

Met. Corr.1: Corrosive to metals – Category 1

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2021

Reviewed on 03/19/2021

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [100ml bottle]

(Contd. of page 10)

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

· Data compared to the previous version altered. All sections have been updated.

US