



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]**

· **Part number: 5190-8265**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Reference material for laboratory use only

· **Manufacturer/Supplier:**

Agilent Technologies Manufacturing GmbH & Co. KG

Tel: 0800 603 1000

Hewlett-Packard-Str. 8

76337 Waldbronn

Germany

· **Further information obtainable from:** e-mail: pdl-msds_author@agilent.com

· **1.4 Emergency telephone number:** CHEMTREC®: +(44)-870-8200418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Carc. 1B H350 May cause cancer.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45: May cause cancer.



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R38-41: Irritating to skin. Risk of serious damage to eyes.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]

(Contd. from page 1)

· **Hazard pictograms**



GHS05 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

BERYLLIUM OXYACETATE

· **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains BERYLLIUM OXYACETATE. May produce an allergic reaction.

Restricted to professional users.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

















· **3.2 Chemical characterisation: Mixtures**

· **Description:**

Aqueous solution.

Mixture: consisting of the following components.

· **Dangerous components:**

CAS: 7697-37-2 EINECS: 231-714-2 RTECS: QU5775000	Nitric acid  C R35;  O R8 -----  Ox. Liq. 3, H272;  Skin Corr. 1A, H314	< 5%
CAS: 19049-40-2 EINECS: 242-785-4 RTECS: DS2900000	BERYLLIUM OXYACETATE  T+ R26;  T Carc. Cat. 2 R45-25-48/23/24/25;  Xi R36/38;  Xi R36/38 ----- Xi R43;  N R51/53 -----  Acute Tox. 3, H301;  Acute Tox. 2, H330;  Carc. 1B, H350; STOT RE 1 , H372;  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315;  Eye Irrit. 2, H319;  Skin Sens. 1, H317	< 0.1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]

(Contd. from page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may occur even after several hours; therefore medical observation for at least 48 hours after the accident is recommended.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient in recovery position for transport.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Rinse mouth. Do not induce vomiting.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/extraction at the workplace.

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. from page 3)

- Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Please refer to the manufacturer's certificate for specific storage and transport temperature conditions.
Store only in the original receptacle.
Keep container in a well-ventilated place. Keep away from sources of ignition and heat.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

7697-37-2 Nitric acid

WEL Short-term value: 2.6 mg/m³, 1 ppm

- **Additional information:** Lists used were valid at the time of SDS preparation.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Chemical-resistant, impervious gloves with an approved standards should be worn at all times.
The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

· **Material of gloves**

- PVC gloves
- Neoprene gloves

· **Penetration time of glove material**

The protection time of the gloves can not be accurately estimated for mixtures consisting of several substances
Refer to and observe manufacturers break through times of the protective gloves.

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]

(Contd. from page 4)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Colourless
Odour:	Odourless
Odour threshold:	Not determined.

· pH-value at 20 °C: < 2

· Change in condition

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	100 °C

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure at 20 °C: 23 hPa

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity Stable under normal conditions.

· 10.2 Chemical stability Stable under normal conditions.

(Contd. on page 6)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. from page 5)

- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Heat.
- **10.5 Incompatible materials:** Strong oxidizing agents.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

7697-37-2 Nitric acid

Oral	LD0	430 mg/kg (Human)
Inhalative	LC50/4 h	130 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Carcinogenic.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Carc. 1B

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

7697-37-2 Nitric acid

LC50/48	180 mg/l (crustacean)
---------	-----------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015


Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. from page 6)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
Waste disposal key numbers from EWC have to be assigned depending on origin and processing.
- **Uncleaned packaging:**
- **Recommendation:** Dispose of in accordance with national regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number	UN2031
· ADR, IMDG, IATA	2031 NITRIC ACID solution
· ADR	NITRIC ACID solution
· IMDG, IATA	NITRIC ACID solution
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	II
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Danger code (Kemler):	80
· EMS Number:	F-A,S-Q
· Segregation groups	Acids
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN2031, NITRIC ACID solution, 8, II

GB

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]

(Contd. from page 7)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

7697-37-2	Nitric acid
	Purified water

· **Australian Inventory of Chemical Substances**

7697-37-2	Nitric acid
	Purified water

· **Standard for the Uniform Scheduling of Medicines and Poisons**

7697-37-2	Nitric acid	S5, S6
-----------	-------------	--------

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Relevant phrases**

H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
R25	Toxic if swallowed.
R26	Very toxic by inhalation.
R35	Causes severe burns.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R45	May cause cancer.
R48/23/24/25	Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R8	Contact with combustible material may cause fire.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.06.2015

Version number 1

Revision: 17.06.2015

Product name: Beryllium AA Standard: 1000 µg/mL Be in 5% HNO₃ [500ml bottle]

(Contd. from page 8)

LD50: Lethal dose, 50 percent

Ox. Liq. 3: Oxidising Liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 2: Acute toxicity, Hazard Category 2

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1B: Carcinogenicity, Hazard Category 1B

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

GB