



Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

1 Identification

- **Product identifier**
- **Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]**
- **Part number:** 5190-8317
- **Application of the substance / the mixture** Reference material for laboratory use only
- **Manufacturer/Supplier:**
Agilent Technologies, Inc. Tel: 800-227-9770
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:** e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
- **Precautionary statements**
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Aqueous solution.

· **Dangerous components:**

CAS: 7697-37-2 RTECS: QU5775000	Nitric acid ⚠ Ox. Liq. 3, H272; ⚠ Skin Corr. 1A, H314	< 5%
CAS: 7440-28-0 RTECS: XG3425000	thallium ⚠ Acute Tox. 2, H300; Acute Tox. 2, H330; ⚠ STOT RE 2, H373; Aquatic Chronic 4, H413	< 0.1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Rinse mouth. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective clothing.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
 Ensure adequate ventilation.
 Absorb liquid components with liquid-binding material.
 DO NOT USE SAWDUST.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Store in cool, dry place in tightly closed receptacles.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store in a cool location.
 Please refer to the manufacturers certificate for specific storage and transport temperature conditions.
 Store only in the original receptacle.
 Keep container in a well-ventilated place. Keep away from sources of ignition and heat.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 3)

· Protection of hands:

Chemical-resistant, impervious gloves with an approved standards should be worn at all times.
The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

· Material of gloves

PVC gloves

Neoprene gloves

· Penetration time of glove material

The protection time of the gloves can not be accurately estimated for mixtures consisting of several substances.

Refer to and observe manufacturers break through times of the protective gloves.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Colorless
· Odor:	Odorless
· Odour threshold:	Not determined.

· pH-value at 20 °C (68 °F): < 2

· Change in condition

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg)

· Density at 20 °C (68 °F): 1.03349 g/cm³ (8.624 lbs/gal)

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not determined.

(Contd. on page 5)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 4)

- **Solubility in / Miscibility with Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** Stable under normal conditions.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** Formation of toxic gases is possible during heating or in case of fire.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7697-37-2 Nitric acid

Oral	LD0	430 mg/kg (Human)
Inhalative	LC50/4 h	130 mg/l (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 5)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

7697-37-2 Nitric acid

LC50/48 | 180 mg/l (crustacean)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Dispose in accordance with national regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN2031

· **DOT**

Nitric acid solution

· **ADR**

2031 Nitric acid solution

· **IMDG, IATA**

NITRIC ACID solution

· **Transport hazard class(es)**

· **DOT**



· **Class**

8 Corrosive substances

· **Label**

8

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO3 [500ml bottle]

(Contd. of page 6)

· ADR, IMDG, IATA



· Class 8 Corrosive substances
· Label 8

· Packing group II
· DOT, ADR, IMDG, IATA

· Environmental hazards:
· Marine pollutant: No

· Special precautions for user Warning: Corrosive substances
· Danger code (Kemler): 80
· EMS Number: F-A,S-Q
· Segregation groups Acids

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": UN2031, Nitric acid solution, 8, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara

· Section 355 (extremely hazardous substances):

7697-37-2 Nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 Nitric acid

7440-28-0 thallium

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2015

Reviewed on 05/22/2015

Product name: Thallium AA Standard: 1000 µg/mL Tl in 5% HNO₃ [500ml bottle]

(Contd. of page 7)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS05

· Signal word Danger
· Hazard statements
H315 Causes skin irritation.
H318 Causes serious eye damage.
· Precautionary statements
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 05/22/2015 / -
· Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Ox. Liq. 3: Oxidising Liquids, Hazard Category 3
Acute Tox. 2: Acute toxicity, Hazard Category 2
Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4
· Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.