



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/17/2015


Reviewed on 06/17/2015

1 Identification

- **Product identifier**
- **Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]**
- **Part number:** 5190-8361
- **Application of the substance / the mixture** Reference material for laboratory use only
- **Manufacturer/Supplier:**
Agilent Technologies, Inc. Tel: 800-227-9770
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:** e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**

 **GHS03 Flame over circle**

Ox. Liq. 3 H272 May intensify fire; oxidizer.

 **GHS08 Health hazard**

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

 **GHS05 Corrosion**

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

 **GHS07**

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS03 GHS05 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric acid

BERYLLIUM OXYACETATE

- **Hazard statements**

H272 May intensify fire; oxidizer.

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

P221 Take any precaution to avoid mixing with combustibles.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 **IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 3

Fire = 3

Reactivity = 0

The substance possesses oxidizing properties.

HMIS-ratings (scale 0 - 4)



Health = 3

Fire = 3

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description:

Aqueous solution.

Mixture: consisting of the following components.

Dangerous components:

CAS: 7697-37-2 RTECS: QU5775000	Nitric acid ⚠ Ox. Liq. 3, H272; ⚠ Skin Corr. 1A, H314	< 10%
CAS: 19049-40-2 RTECS: DS2900000	BERYLLIUM OXYACETATE ⚠ Acute Tox. 3, H301; Acute Tox. 2, H330; ⚠ Carc. 1B, H350; STOT RE 1, H372; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	< 1.0%

4 First-aid measures

Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

**Safety Data Sheet**

acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**· After swallowing:**

Rinse mouth. Do not induce vomiting.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures**· Extinguishing media****· Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters**· Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

6 Accidental release measures**· Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

(Contd. on page 4)

US



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 3)

- Open and handle receptacle with care.
Prevent formation of aerosols.
Information about protection against explosions and fires: Keep respiratory protective device available.
Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:
Store in a cool location.
Please refer to the manufacturers certificate for specific storage and transport temperature conditions.
Store only in the original receptacle.
Keep container in a well-ventilated place. Keep away from sources of ignition and heat.
Information about storage in one common storage facility: Store away from foodstuffs.
Further information about storage conditions: Keep receptacle tightly sealed.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
Control parameters

Components with limit values that require monitoring at the workplace:

7697-37-2 Nitric acid

Table with 2 columns: Limit Value Type and Value. Rows include PEL (Long-term value: 5 mg/m³, 2 ppm), REL (Short-term value: 10 mg/m³, 4 ppm; Long-term value: 5 mg/m³, 2 ppm), and TLV (Short-term value: 10 mg/m³, 4 ppm; Long-term value: 5.2 mg/m³, 2 ppm).

- Additional information: The lists that were valid during the creation were used as basis.
Exposure controls
Personal protective equipment:
General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Breathing equipment:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Protection of hands:
Chemical-resistant, impervious gloves with an approved standards should be worn at all times.
The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

- Material of gloves
PVC gloves
Neoprene gloves
Penetration time of glove material
The protection time of the gloves can not be accurately estimated for mixtures consisting of several substances.
Refer to and observe manufacturers break through times of the protective gloves.

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Colorless
· Odor:	Odorless
· Odour threshold:	Not determined.

· **pH-value at 20 °C (68 °F):** < 2

· **Change in condition**

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17 mm Hg)

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· Organic solvents:	0.0 %
· Water:	93.0 %

· **Solids content:** 1.0 %

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** Stable under normal conditions.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7697-37-2 Nitric acid

Oral	LD0	430 mg/kg (Human)
Inhalative	LC50/4 h	130 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
Carcinogenic.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

19049-40-2	BERYLLIUM OXYACETATE	I
------------	----------------------	---

· **NTP (National Toxicology Program)**

19049-40-2	BERYLLIUM OXYACETATE	K
------------	----------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

7697-37-2 Nitric acid

LC50/48	180 mg/l (crustacean)
---------	-----------------------

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 6)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Dispose in accordance with national regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN2031
- **DOT** Nitric acid solution
- **ADR** 2031 Nitric acid solution
- **IMDG, IATA** NITRIC ACID solution

- **Transport hazard class(es)**

- **DOT**



- **Class** 8 Corrosive substances
- **Label** 8

- **ADR, IMDG, IATA**



- **Class** 8 Corrosive substances
- **Label** 8

- **Packing group**
- **DOT, ADR, IMDG, IATA** II

(Contd. on page 8)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 7)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-Q
· Segregation groups	Acids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN2031, Nitric acid solution, 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· Section 355 (extremely hazardous substances):
7697-37-2 Nitric acid

· Section 313 (Specific toxic chemical listings):
7697-37-2 Nitric acid
19049-40-2 BERYLLIUM OXYACETATE

· TSCA (Toxic Substances Control Act):
7697-37-2 Nitric acid
Purified water

· **Proposition 65**

· Chemicals known to cause cancer:
19049-40-2 BERYLLIUM OXYACETATE

· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

· **Carcinogenic categories**

· EPA (Environmental Protection Agency)
None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)
None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: **Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]**

(Contd. of page 8)

· Hazard pictograms



GHS03 GHS05 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

Nitric acid

BERYLLIUM OXYACETATE

· Hazard statements

H272 May intensify fire; oxidizer.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

P221 Take any precaution to avoid mixing with combustibles.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 06/17/2015 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Ox. Liq. 3: Oxidising Liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 2: Acute toxicity, Hazard Category 2

(Contd. on page 10)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/17/2015

Reviewed on 06/17/2015

Product name: Beryllium Standard: 10000 µg/mL Be in 5% HNO3 [500ml bottle]

(Contd. of page 9)

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 1B: Carcinogenicity, Hazard Category 1B
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

• **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.