Tel: 800-227-9770



Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/28/2018 Printing date 11/28/2018

1 Identification

- · Product identifier
- · Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]
- · Part number: 5190-8406
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Agilent Technologies, Inc. 5301 Stevens Creek Blvd Santa Clara, CA 95051,

USA

- · Information department: e-mail: pdl-msds_author@agilent.com
- · Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS03 Flame over circle

Ox. Liq. 3 H272 May intensify fire; oxidizer.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

H360-H362 May damage fertility or the unborn child. May cause harm to breast-fed Repr. 1A

children.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage. H318

H402 Harmful to aquatic life. Aquatic Acute 3

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS03

GHS05

GHS08





Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

Nitric acid

Lead

· Hazard statements

H272 May intensify fire; oxidizer.

H314 Causes severe skin burns and eye damage.

H351 Suspected of causing cancer.

H360-H362 May damage fertility or the unborn child. May cause harm to breast-fed children.

H372 Causes damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P221 Take any precaution to avoid mixing with combustibles.

P263 Avoid contact during pregnancy/while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 3 Reactivity = 0

The substance possesses oxidizing properties.

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Aqueous solution.

(Contd. on page 3)



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

 CAngerous components:

 CAS: 7697-37-2
 Nitric acid
 <10%</td>

 RTECS: QU5775000
 ♦ Ox. Liq. 2, H272; ♦ Skin Corr. 1A, H314
 <1%</td>

 CAS: 7439-92-1
 Lead
 <1%</td>

 RTECS: OF 7525000
 ♦ Carc. 2, H351; Repr. 1A, H360-H362; STOT RE 1, H372; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410
 <1%</td>

· Additional information:

Agilent Technologies

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Rinse mouth. Do not induce vomiting.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

 $\cdot \textit{Methods and material for containment and cleaning up:} \\$

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

(Contd. on page 4)



Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Action Criteria for Chemicais	
Nitric acid	0.16 ppm
Lead	0.15 mg/m ³
Nitric acid	24 ppm
Lead	120 mg/m³
Nitric acid	92 ppm
Lead	700 mg/m³
	Nitric acid Lead Nitric acid Lead Nitric acid Lead Nitric acid

7 Handling and storage

- · Handling:
- $\cdot \textit{Precautions for safe handling Store in cool, dry place in tightly closed receptacles}.$
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Please refer to the manufacturers certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:	
7697-37-2 Nitric acid	
PFI Long-term value: 5 mg/m ³ 2 nnm	

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)





Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

· Material of gloves

PVC gloves

Neoprene gloves

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Colorless
Odor: Odorless
Odor threshold: Not determined.

· pH-value at 20 °C (68 °F): <2

· Change in condition

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 100 °C (212 °F)

(Contd. on page 6)





Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

	(Contd. of	page
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:	Not determined	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.13368 g/cm³ (9.46056 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity Stable under normal conditions.
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

Formation of toxic gases is possible during heating or in case of fire.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat.
- · Incompatible materials: Strong oxidizing agents.
- · Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7697-37-2 Nitric acid

Inhalative LC50/4 h 130 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.

(Contd. on page 7)



Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 6)

· on the eye:

Strong caustic effect.

Agilent Technologies

Strong irritant with the danger of severe eye injury.

- · Sensitization: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7439-92-1 Lead	2B
· NTP (National Toxicology Program)	
7439-92-1 Lead	R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

7697-37-2 Nitric acid

LC50/48 | 180 mg/l (crustacean)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- \cdot **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

US





Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Dispose in accordance with national regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN2031

DOT Nitric acid solution
 ADR 2031 Nitric acid solution
 IMDG, IATA NITRIC ACID solution

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

· Label 8

· ADR, IMDG, IATA



· Class 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler):
EMS Number:
Segregation groups
Stowage Category

80
F-A,S-B
Acids
D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 9)



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/28/2018 Printing date 11/28/2018

Product name; Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 8)

· Transport/Additional information:

 $\cdot ADR$

· Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN 2031 NITRIC ACID SOLUTION, 8, II · UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 Nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 Nitric acid

7439-92-1 Lead

- · TSCA (Toxic Substances Control Act):
- All ingredients are listed.
- · Proposition 65
- · Chemicals known to cause cancer:

7439-92-1 Lead

· Chemicals known to cause reproductive toxicity for females:

7439-92-1 Lead

· Chemicals known to cause reproductive toxicity for males:

7439-92-1 Lead

· Chemicals known to cause developmental toxicity:

7439-92-1 Lead

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7439-92-1 Lead

*B*2

· TLV (Threshold Limit Value established by ACGIH)

7439-92-1 Lead

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Hazard pictograms







GHS03

GHS05





Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 9)

· Signal word Danger

· Hazard-determining components of labeling:

Nitric acid

Lead

· Hazard statements

H272 May intensify fire; oxidizer.

H314 Causes severe skin burns and eye damage.

H351 Suspected of causing cancer.

H360-H362 May damage fertility or the unborn child. May cause harm to breast-fed children.

H372 Causes damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P221 Take any precaution to avoid mixing with combustibles.

P263 Avoid contact during pregnancy/while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 11/28/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids - Category 2

Ox. Liq. 3: Oxidizing liquids – Category 3

(Contd. on page 11)



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/28/2018 Reviewed on 11/28/2018

Product name: Lead Standard: 10000 µg/mL Pb in 5% HNO3 [100ml bottle]

(Contd. of page 10)

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

· Data compared to the previous version altered. All sections have been updated.

TIC