



Safety Data Sheet acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

1 Identification

- **Product identifier**
- **Product name:** Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]
- **Part number:** 5190-8409
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051,
USA
Tel: 800-227-9770
- **Information department:** e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS03 Flame over circle

Ox. Liq. 3 H272 May intensify fire; oxidizer.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS03



GHS05



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Lithium carbonate

- **Hazard statements**

H272 May intensify fire; oxidizer.

H290 May be corrosive to metals.

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO3 [500ml bottle]

(Contd. of page 1)

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

• **Precautionary statements**

P221 Take any precaution to avoid mixing with combustibles.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

The substance possesses oxidizing properties.

• **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

• **Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

• **Chemical characterization: Mixtures**

• **Description:** Aqueous solution.

• **Dangerous components:**

CAS: 7697-37-2 RTECS: QU5775000	Nitric acid	⚠ Ox. Liq. 2, H272; ⚠ Met. Corr.1, H290	≥5-<10%
CAS: 554-13-2 RTECS: OJ5800000	Lithium carbonate	⚠ STOT RE 2, H373; ⚠ Acute Tox. 4, H302	<2%

• **Additional information:**

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

US

(Contd. on page 3)

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Rinse mouth. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
DO NOT USE SAWDUST.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

• **PAC-1:**

CAS: 7697-37-2	Nitric acid	0.16 ppm
CAS: 554-13-2	Lithium carbonate	3.1 mg/m ³

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]

(Contd. of page 3)

· PAC-2:

CAS: 7697-37-2	Nitric acid	24 ppm
CAS: 554-13-2	Lithium carbonate	34 mg/m ³

· PAC-3:

CAS: 7697-37-2	Nitric acid	92 ppm
CAS: 554-13-2	Lithium carbonate	210 mg/m ³

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Protect from heat.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

Please refer to the manufacturers certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

· Information about storage in one common storage facility: Store away from foodstuffs.
· Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:

CAS: 7697-37-2 Nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

· Additional information: The lists that were valid during the creation were used as basis.
· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO3 [500ml bottle]

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

• **Material of gloves**

PVC gloves

Neoprene gloves

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid

Color: Colorless

• **Odor:** Odorless

• **Odor threshold:** Not determined.

• **pH-value:** <2

• **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 83 °C (181.4 °F)

• **Flash point:** Not applicable.

• **Flammability (solid, gaseous):** Not determined.

• **Ignition temperature:** Not determined

(Contd. on page 6)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.04128 g/cm ³ (8.68948 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
Stable under normal conditions.
No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat.
- **Incompatible materials:**
Strong oxidizing agents.
Metals.
- **Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
- CAS: 7697-37-2 Nitric acid
- Inhalative LC50/4 h 130 mg/l (rat)
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]

(Contd. of page 6)

- **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- **Sensitization:** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

CAS: 7697-37-2 Nitric acid

LC50/48 180 mg/l (crustacean)

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO3 [500ml bottle]

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Dispose in accordance with national regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
 - **DOT, ADR, IMDG, IATA**
 - **DOT**
 - **ADR**
 - **IMDG, IATA**
- UN2031
Nitric acid solution
2031 NITRIC ACID solution
NITRIC ACID solution

- **Transport hazard class(es)**
- **DOT, ADR, IMDG, IATA**



- **Class**
 - **Label**
- 8 Corrosive substances
8

- **Packing group**
- **DOT, ADR, IMDG, IATA**

II

- **Environmental hazards:**
- Not applicable.

- **Special precautions for user**
 - **Danger code (Kemler):**
 - **EMS Number:**
 - **Segregation groups**
 - **Stowage Category**
- Warning: Corrosive substances
80
F-A,S-B
Acids
D

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**
- Not applicable.

- **Transport/Additional information:**

- **ADR**
 - **Excepted quantities (EQ)**
- Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":**
- UN 2031 NITRIC ACID SOLUTION, 8, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

CAS: 7697-37-2 Nitric acid

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO₃ [500ml bottle]

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):

CAS: 7697-37-2 Nitric acid

CAS: 554-13-2 Lithium carbonate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 554-13-2 Lithium carbonate

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Hazard pictograms


GHS03



GHS05



GHS08

· Signal word Danger
· Hazard-determining components of labeling:

Lithium carbonate

· Hazard statements

H272 May intensify fire; oxidizer.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P221 Take any precaution to avoid mixing with combustibles.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/19/2019

Reviewed on 02/19/2019

Product name: Lithium Standard: 10000 µg/mL Li in 5% HNO3 [500ml bottle]

(Contd. of page 9)

- P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- **Date of preparation / last revision** 02/19/2019 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2
Ox. Liq. 3: Oxidizing liquids – Category 3
Met. Corr.1: Corrosive to metals – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

- **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

- **Data compared to the previous version altered.** All sections have been updated.