



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

Revision date 13-Jun-2024

Revision Number 1

1. Identification

Product identifier

Product Name Arsenic Standard: 1000 µg/g As in 75 cSt Hydrocarbon Oil [50g bottle]

Other means of identification

Product Code(s) 5190-8735

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Reagents and Standards for Analytical Chemical Laboratory Use

Restrictions on use Not to be used for human or animal consumption

Details of the supplier of the safety data sheet

Supplier Address

Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA

800-227-9770

E-mail pdl-msds_author@agilent.com

Emergency telephone number

Emergency Telephone
CHEMTREC®: 1-800-424-9300

2. Hazard(s) identification

Classification

Classified according to OSHA.

Carcinogenicity	Category 2
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)
Not applicable

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Label elements

Danger

Hazard statements

Classified according to OSHA.
Suspected of causing cancer
May be fatal if swallowed and enters airways



Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/clothing and eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical nature Mixture.

Chemical name	CAS No.	Weight-%	Trade secret
---------------	---------	----------	--------------



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

White mineral oil, petroleum	8042-47-5	80 - 100	*
Organo Arsenic Compound	-	0.1 - 1	*

4. First-aid measures

Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	---

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Use personal protective equipment as required.
Other information	Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.
---------------------------	--



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 13-Jun-2024

8. Exposure controls/personal protection

Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear safety glasses with side-shields.

Hand protection Wear protective nitrile rubber gloves. The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

General hygiene considerations Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Oily
Color colorless; to; light brown



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Odor Mineral oil-like odor
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
<u>Other information</u>		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
Liquid Density	No information available	
Bulk density	No information available	

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid None known based on information supplied.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 13-Jun-2024

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	100,000.00 mg/kg
ATEmix (dermal)	99,999.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	501.000 mg/l
ATEmix (inhalation-vapor)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
White mineral oil, petroleum 8042-47-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
White mineral oil, petroleum 8042-47-5	-	LC50: >10000mg/L (96h, Lepomis macrochirus)	-	-

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 13-Jun-2024

Component Information

Chemical name	Partition coefficient
White mineral oil, petroleum 8042-47-5	6

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

14. Transport information

DOT Not regulated

TDG Not regulated

MEX Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA LGC has not confirmed that the chemical substances in this product are on the TSCA Inventory, and LGC is distributing this product solely for use either in applications statutorily exempt from TSCA and regulated under other laws (e.g., FFDCA, FIFRA) or in research and development activities in accordance with the TSCA Inventory R&D exemption provided at 40 CFR 720.36. It is the end-user's responsibility to understand and follow the requirements that apply to its use of this product.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
White mineral oil, petroleum	8042-47-5	Present	Active
Organo Arsenic Compound	-	-	-

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECI	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AIIC	Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated under applicable state right-to-know regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 0	Instability 0	Special hazards -
HMIS	Health hazards 2 *	Flammability 0	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>		<i>* = Chronic Health Hazard</i>		

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AELG(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
OSHA HCS2012

**5190-8735 - Arsenic Standard: 1000 µg/g As in 75 cSt
Hydrocarbon Oil [50g bottle]**

Revision date 13-Jun-2024

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 13-Jun-2024
Revision Note No information available.

Disclaimer

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

End of Safety Data Sheet