



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
WHS Regulations

Revision date 29-Jul-2024

Revision Number 1

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name Beryllium Standard: 1000 µg/g Be in 75 cSt Hydrocarbon Oil [50g bottle]

Product Code(s) 5190-8738

Other means of identification

Chemical name
Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Reagents and Standards for Analytical Chemical Laboratory Use.

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Agilent Technologies Australia Pty Ltd
679 Springvale Road
Mulgrave
Victoria 3170, Australia

1800 802 402

For further information, please contact

Contact Point Product Safety Department

E-mail address pdl-msds_author@agilent.com

Emergency telephone number

Emergency telephone number CHEMTREC®: +(61)-290372994

Section 2: Hazard(s) identification

GHS Classification

Aspiration hazard	Category 1
Carcinogenicity	Category 1B

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Label elements

Health hazard



Signal word

DANGER

Hazard statements

May cause cancer.

May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/clothing and eye/face protection.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISONS INFORMATION CENTRE or doctor.

Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other hazards which do not result in classification

No information available.

Section 3: Composition/information on ingredients

Chemical name	CAS No.	Weight-%
White mineral oil, petroleum	8042-47-5	90 - 100%
Organo Beryllium Compound	-	0 - 10%

Section 4: First aid measures

Description of first aid measures

General advice

IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Emergency telephone number

Poisons Information Centre, Australia: 13 11 26

Poisons Information Centre, New Zealand: 0800 764 766

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary oedema may occur.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to doctors Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

Specific hazards arising from the chemical No information available.

Special protective actions for firefighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

precautions for fire-fighters Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

General hygiene considerations Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible materials None known based on information supplied.

Section 8: Exposure controls and personal protection

Control parameters

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Exposure Limits

Chemical name	European Union	United Kingdom	Germany DFG
White mineral oil, petroleum 8042-47-5	-	-	TWA: 5 mg/m ³ Peak: 20 mg/m ³

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing.

Hand protection Wear protective nitrile rubber gloves. The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374. Wear suitable gloves.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

Thermal hazards No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Oily
Colour colourless to light brown
Odour Petroleum distillates.
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	None known
Relative vapour density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Auto-ignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

VOC content	No information available
Particle characteristics	No information available

Section 10: Stability and reactivity

Reactivity

Reactivity	No information available.
------------	---------------------------

Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

Conditions to avoid

Conditions to avoid	None known based on information supplied.
---------------------	---

Incompatible materials

Incompatible materials	None known based on information supplied.
------------------------	---

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary oedema. Pulmonary oedema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary oedema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms Difficulty in breathing. Coughing and/or wheezing. Dizziness.

Acute toxicity

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	100,000.00 mg/kg
ATEmix (dermal)	99,999.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapour)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
White mineral oil, petroleum	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Respiratory or skin sensitisation	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Unknown aquatic toxicity 0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
White mineral oil, petroleum	-	LC50: >10000mg/L (96h, Lepomis macrochirus)	-	-

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Bioaccumulation

Component Information

Chemical name	Partition coefficient
White mineral oil, petroleum	6

Mobility

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

Chemical name	EU - REACH (1907/2006) - Article 59(1) - Candidate List of Substances of Very High Concern (SVHC) for Authorisation	EU - REACH (1907/2006) - Endocrine Disruptor Assessment List of Substances
White mineral oil, petroleum	-	-
Organo Beryllium Compound	-	-

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not re-use empty containers.

See section 8 for more information

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

National regulations

Australia

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Australian Industrial Chemicals Introduction Scheme (AICIS)

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

International Inventories

AIIC

Contact supplier for inventory compliance status.

NZIoC

Contact supplier for inventory compliance status.

TSCA

LGC has not confirmed that the chemical substances in this product are on the TSCA Inventory, and LGC is distributing this product solely for use either in applications statutorily exempt from TSCA and regulated under other laws (e.g., FFDCA, FIFRA) or in research and development activities in accordance with the TSCA Inventory R&D exemption provided at 40 CFR 720.36. It is the end-user's responsibility to understand and follow the requirements that apply to its use of this product.

DSL/NDSL

Contact supplier for inventory compliance status.

EINECS/ELINCS

Contact supplier for inventory compliance status.

ENCS

Contact supplier for inventory compliance status.

IECSC

Contact supplier for inventory compliance status.

KECI

Contact supplier for inventory compliance status.

PICCS

Contact supplier for inventory compliance status.

Legend:

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Revision date 29-Jul-2024

Revision Note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications



SAFETY DATA SHEET

5190-8738 - Beryllium Standard: 1000 µg/g Be in 75 cSt
Hydrocarbon Oil [50g bottle]

Revision date 29-Jul-2024

Organisation for Economic Co-operation and Development High Production Volume Chemicals Program
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

End of Safety Data Sheet