



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Hazardous according to criteria of Australian Safety and Compensation Council

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]**

· **Part number: 5190-8770**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Reference material for laboratory use only

· **Manufacturer/Supplier:**

Agilent Technologies Australia Pty Ltd
679 Springvale Road
Mulgrave
Victoria 3170, Australia

Tel: 1800 802 402

· **Further information obtainable from:** e-mail: pdl-msds_author@agilent.com

· **1.4 Emergency telephone number:** CHEMTREC®: +(61) - 290372994

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360D May damage the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Not applicable.



T; Toxic

R49-61-48/23: May cause cancer by inhalation. May cause harm to the unborn child. Toxic: danger of serious damage to health by prolonged exposure through inhalation.



Xn; Harmful

R68: Possible risk of irreversible effects.



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements**· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS08

· Signal word Danger**· Hazard-determining components of labelling:**

White mineral oil

Organo Nickel Compound

· Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P285 In case of inadequate ventilation wear respiratory protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Restricted to professional users.

· Information concerning particular hazards for human and environment:**· Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

-AU

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 2)

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 8042-47-5 EINECS: 232-455-8 RTECS: PY8047000	White mineral oil ☒ Xn R65 ☒ Asp. Tox. 1, H304	> 99%
RTECS: -	Organo Nickel Compound ☠ T Repr. Cat. 2 R49-61-48/23; ☒ Xn R68; ☒ Xn R42/43; ☠ N R50/53 Carc. Cat. 1, Muta. Cat. 3 ☒ Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B, H360D; STOT RE 1, H372; ☒ Skin Sens. 1, H317	< 1.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may occur even after several hours; therefore medical observation for at least 48 hours after the accident is recommended.
- **After inhalation:**
Supply fresh air and call a doctor.
In case of unconsciousness place patient in recovery position for transport.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Rinse mouth. Do not induce vomiting.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable for surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective clothing.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/extraction at the workplace.

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:** Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Please refer to the manufacturer's certificate for specific storage and transport temperature conditions.

Store only in the original receptacle.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:** None.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** Lists used were valid at the time of SDS preparation.

· 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

· **Protection of hands:**

Chemical-resistant, impervious gloves with an approved standards should be worn at all times.

The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

· **Material of gloves**

Natural rubber, NR

(Contd. on page 5)

AU



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 4)

Nitrile rubber, NBR

· **Penetration time of glove material**

Refer to and observe manufacturers break through times of the protective gloves.

The protection time of the gloves can not be accurately estimated for mixtures consisting of several substances

· **Eye protection: Safety glasses**

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Oily

Colour: Brown

· **Odour:** Mineral-oil-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 218 °C

· **Flash point:** 115 °C

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** 0.862 g/cm³

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **9.2 Other information:** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity:** Stable under normal conditions.

· **10.2 Chemical stability:** Stable under normal conditions.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 5)

- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid Heat.**
- **10.5 Incompatible materials:** Strong oxidizing agents.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritating effect.
- **on the eye:** No irritating effect.
- **Sensitisation:**
Sensitisation possible through inhalation.
Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Carcinogenic if inhaled.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Muta. 2, Carc. 1A, Repr. 1B

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

-AU-



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 6)

- **European waste catalogue**
Waste disposal key numbers from EWC have to be assigned depending on origin and processing.
- **Uncleaned packaging:**
- **Recommendation:** Dispose of in accordance with national regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADG, ADN, IMDG, IATA** Not applicable
- **ADG, ADN, IMDG, IATA** Not applicable
- **14.3 Transport hazard class(es)**
- **ADG, ADN, IMDG, IATA**
- **Class** Not applicable
- **14.4 Packing group**
- **ADG, IMDG, IATA** Not applicable
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Philippines Inventory of Chemicals and Chemical Substances**
All ingredients are listed.
- **Australian Inventory of Chemical Substances**
All ingredients are listed.
- **Standard for the Uniform Scheduling of Medicines and Poisons**
None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- **Relevant phrases**
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H341 Suspected of causing genetic defects.
- H350i May cause cancer by inhalation.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2015

Version number 1

Revision: 22.06.2015

Product name: Nickel Standard: 5000 µg/g Ni in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. from page 7)

R42/43 May cause sensitisation by inhalation and skin contact.

R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.

R49 May cause cancer by inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R61 May cause harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R68 Possible risk of irreversible effects.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 1A: Carcinogenicity, Hazard Category 1Ai

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

-AU-