

Printing date 06/09/2015

Reviewed on 06/09/2015

1 Identification

- · Product identifier
- · Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]
- · Part number: 5190-8792
- · Application of the substance / the mixture Reference material for laboratory use only
- · Manufacturer/Supplier:
- Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

Tel: 800-227-9770

• Information department: e-mail: pdl-msds_author@agilent.com • Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling:
- White mineral oil
- Hazard statements
- H304 May be fatal if swallowed and enters airways.
- · Precautionary statements
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- *P331* Do NOT induce vomiting.
- P405 Store locked up.
- *P501* Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

US



Printing date 06/09/2015

Reviewed on 06/09/2015

(Contd. of page 1)

> 95%

🚸 Asp. Tox. 1, H304

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

- Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Also contains substances at levels not considered to be hazardous.

· Dangerous components:

CAS: 8042-47-5 White mineral oil RTECS: PY8047000

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:
- Rinse mouth. Do not induce vomiting.
- Seek immediate medical advice.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- \cdot Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- Environmental precautions:
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 3)

⁻ US





Printing date 06/09/2015

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. of page 2)

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- \cdot Requirements to be met by storerooms and receptacles:
- Store in a cool location.

Please refer to the manufacturers certificate for specific storage and transport temperature conditions. Store only in the original receptacle.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

· Protection of hands:

Chemical-resistant, impervious gloves with an approved standards should be worn at all times. The selection of the glove material is based on the penetration times, rates of diffusion and its degradation



Protective gloves

• *Material of gloves* Nitrile rubber, NBR Natural rubber, NR

(Contd. on page 4)

US

Printing date 06/09/2015

Reviewed on 06/09/2015

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. of page 3)

· Penetration time of glove material

Agilent Technologies

The protection time of the gloves can not be accurately estimated for mixtures consisting of several susbtances.

• Eye protection: Safety glasses

| Information on basic physical and | chemical properties | |
|--------------------------------------|--|--|
| General Information | | |
| · Appearance: | | |
| Form: | Oily | |
| Color: | Light brown | |
| · Odor: | Mineral-oil-like | |
| Odour threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/Melting range: | Not determined. | |
| Boiling point/Boiling range: | 218 °C (424 °F) | |
| Flash point: | 115 °C (239 °F) | |
| Flammability (solid, gaseous): | Not determined. | |
| Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| Auto igniting: | Product is not selfigniting. | |
| Danger of explosion: | Not determined. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapor pressure: | Not determined. | |
| Density at 20 °C (68 °F): | 0.862 g/cm ³ (7.193 lbs/gal) | |
| Relative density | Not determined. | |
| Vapour density | Not determined. | |
| Evaporation rate | Not determined. | |
| Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| Partition coefficient (n-octanol/wat | er): Not determined. | |
| Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| • Other information | No further relevant information available. | |

10 Stability and reactivity

· Reactivity Stable under normal conditions.

· Chemical stability Stable under normal conditions.

 $(Contd. \ on \ page \ 5)$

Refer to and observe manufacturers break through times of the protective gloves.



Printing date 06/09/2015

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. of page 4)

- · Thermal decomposition / conditions to be avoided:
- Formation of toxic gases is possible during heating or in case of fire.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat.
- · Incompatible materials: Strong oxidizing agents.
- · Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- 8042-47-5 White mineral oil

Oral LD50 > 5000 mg/kg (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 6)



Printing date 06/09/2015

Reviewed on 06/09/2015

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

(Contd. of page 5)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Dispose in accordance with national regulations.*
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

| Transport information | | |
|--|-----------------|--|
| · UN-Number | | |
| · DOT, ADR, ADN, IMDG, IATA | Not applicable | |
| · DOT, ADR, ADN, IMDG, IATA | Not applicable | |
| · Transport hazard class(es) | | |
| · DOT, ADR, ADN, IMDG, IATA | | |
| · Class | Not applicable | |
| · Packing group | | |
| · DOT, ADR, ÎMDG, IATA | Not applicable | |
| · Environmental hazards: | | |
| • Marine pollutant: | No | |
| \cdot Special precautions for user | Not applicable. | |
| • Transport in bulk according to Annex | II of | |
| MARPOL73/78 and the IBC Code | Not applicable. | |
| · UN "Model Regulation": | - | |

15 Regulatory information

- \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara
- Section 355 (extremely hazardous substances):
- None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings):
- None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
- All ingredients are listed.
- · Proposition 65
- · Chemicals known to cause cancer:
- None of the ingredients is listed.
- · Chemicals known to cause reproductive toxicity for females:
- None of the ingredients is listed.
- · Chemicals known to cause reproductive toxicity for males:
 - None of the ingredients is listed.

(Contd. on page 7)

- US



Printing date 06/09/2015

Reviewed on 06/09/2015

(Contd. of page 6)

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

- · Chemicals known to cause developmental toxicity:
- None of the ingredients is listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency)
- None of the ingredients is listed.
- · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Danger

- *Hazard-determining components of labeling:* White mineral oil
- · Hazard statements
- H304 May be fatal if swallowed and enters airways.
- · Precautionary statements
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- *P331* Do NOT induce vomiting.
- P405 Store locked up.
- *P501* Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Date of preparation / last revision 06/09/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1

(Contd. on page 8)

US



Agilent Technologies

Safety Data Sheet acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

(Contd. of page 7)

US

Product name: Tungsten Standard: 5000 µg/g W in 75 cSt Hydrocarbon Oil [50g bottle]

· Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.