



## SAFETY DATA SHEET

Version 8.3  
Revision Date 21.03.2023  
Print Date 05.03.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Methanol InfinityLab gradient grade for LCMS  
Product Number : 5191-5111, 5191-5111-001  
Index-No. : 603-001-00-X  
CAS-No. : 67-56-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemical Laboratory Use

#### 1.3 Details of the supplier of the safety data sheet

Manufactured by : EMD Millipore Corporation  
400 Summit Dr,  
Burlington MA 01803 USA  
An affiliate of Merck KGaA, Darmstadt, Germany.

Company : Agilent Technologies, Inc.  
5301 Stevens Creek Blvd  
Santa Clara, CA 95051, USA

Telephone : 800-227-9770

E-mail address : pdl-msds\_author@agilent.com

#### 1.4 Emergency telephone

Emergency Phone # : 1-800-424-9300 CHEMTREC

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

Flammable liquids (Category 2), H225  
Acute toxicity, Oral (Category 3), H301  
Acute toxicity, Inhalation (Category 3), H331  
Acute toxicity, Dermal (Category 3), H311  
Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system,  
H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

H370

Causes damage to organs (Eyes, Central nervous system).

Precautionary Statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P260

Do not breathe mist or vapors.

P264

Wash skin thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310 + P330

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P311

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

P308 + P311

IF exposed or concerned: Call a POISON CENTER/ doctor.

P361 + P364

Take off immediately all contaminated clothing and wash it before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

- none

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	:	CH4O
Molecular weight	:	32.04 g/mol
CAS-No.	:	67-56-1
EC-No.	:	200-659-6
Index-No.	:	603-001-00-X

Component	Classification	Concentration *
<b>Methanol</b>		
	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	<= 100 %
* Weight %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

#### **SECTION 4: First aid measures**

##### **4.1 Description of first-aid measures**

No data available

##### **4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

##### **4.3 Indication of any immediate medical attention and special treatment needed**

No data available

---

#### **SECTION 5: Firefighting measures**

##### **5.1 Extinguishing media**

No data available

##### **5.2 Special hazards arising from the substance or mixture**

Carbon oxides

##### **5.3 Advice for firefighters**

No data available

##### **5.4 Further information**

No data available

---

#### **SECTION 6: Accidental release measures**

##### **6.1 Personal precautions, protective equipment and emergency procedures**

For personal protection see section 8.

##### **6.2 Environmental precautions**

No data available

##### **6.3 Methods and materials for containment and cleaning up**

No data available

##### **6.4 Reference to other sections**

For disposal see section 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities**

No data available

**7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 262 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		STEL	250 ppm 328 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Substance may be readily absorbed through intact skin			
		TWA	200 ppm	Canada. British Columbia OEL
	Contributes significantly to the overall exposure by the skin route.			
		STEL	250 ppm	Canada. British Columbia OEL
	Contributes significantly to the overall exposure by the skin route.			
		STEV	250 ppm 328 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)			
		TWAEV	200 ppm 262 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)			
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)

## 8.2 Exposure controls

### Personal protective equipment

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

#### Control of environmental exposure

Prevent product from entering drains.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |                                                 |                                                                          |
|-------------------------------------------------|--------------------------------------------------------------------------|
| a) Appearance                                   | Form: liquid<br>Color: colorless                                         |
| b) Odor                                         | characteristic                                                           |
| c) Odor Threshold                               | 10 ppm                                                                   |
| d) pH                                           | No data available                                                        |
| e) Melting point/freezing point                 | Melting point: -97.8 °C (-144.0 °F) - (ECHA)                             |
| f) Initial boiling point and boiling range      | 64.7 °C 148.5 °F at 1,013 hPa - (ECHA)                                   |
| g) Flash point                                  | 9.7 °C (49.5 °F) - closed cup - Regulation (EC) No. 440/2008, Annex, A.9 |
| h) Evaporation rate                             | 6.3 - Diethyl ether 1.9 - n-butyl acetate                                |
| i) Flammability (solid, gas)                    | No data available                                                        |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 44 %(V)<br>Lower explosion limit: 5.5 %(V)        |
| k) Vapor pressure                               | 169.27 hPa at 25 °C (77 °F)                                              |
| l) Vapor density                                | 1.11                                                                     |

m) Density	0.79 g/cm <sup>3</sup> at 20 °C (68 °F)
Relative density	0.79 - 0.820 °C
n) Water solubility	1,000 g/l at 20 °C (68 °F) - completely miscible
o) Partition coefficient: n-octanol/water	log Pow: -0.77 at 25 °C (77 °F) - (HSDB), Bioaccumulation is not expected.
p) Autoignition temperature	455.0 °C (851.0 °F) at 1,013 hPa - DIN 51794
q) Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r) Viscosity	0.54 - 0.59 mm <sup>2</sup> /s at 20 °C (68 °F) -
s) Explosive properties	No data available
t) Oxidizing properties	none

## 9.2 Other safety information

Minimum ignition energy	0.14 mJ
Conductivity	< 1 µS/cm
Relative vapor density	1.11

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

No data available

### 10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents  
perchloric acid  
perchlorates  
salts of oxyhalogenic acids  
chromium(VI) oxide  
halogen oxides  
nitrogen oxides  
nonmetallic oxides  
chromosulfuric acid  
chlorates  
hydrides  
zinc diethyl  
halogens  
powdered magnesium  
hydrogen peroxide  
Nitric acid  
sulfuric acid  
permanganic acid  
sodium hypochlorite  
Exothermic reaction with:  
acid halides

Acid anhydrides  
Reducing agents  
acids  
Bromine  
Chlorine  
Chloroform  
magnesium  
tetrachloromethane  
Risk of ignition or formation of inflammable gases or vapours with:  
Fluorine  
Oxides of phosphorus  
Raney-nickel  
Generates dangerous gases or fumes in contact with:  
Alkaline earth metals  
Alkali metals

#### **10.4 Conditions to avoid**

No data available

#### **10.5 Incompatible materials**

No data available

#### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

##### **Acute toxicity**

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

##### **Skin corrosion/irritation**

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

##### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

##### **Respiratory or skin sensitization**

Sensitisation test: - Guinea pig

Result: negative  
(OECD Test Guideline 406)

**Germ cell mutagenicity**

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

**Carcinogenicity**

Did not show carcinogenic effects in animal experiments.

**Reproductive toxicity**

Based on available data the classification criteria are not met.

**Specific target organ toxicity - single exposure**

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**11.2 Additional Information**

Acute effects: , Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma

Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis

drop in blood pressure

agitation, spasms

inebriation

Dizziness

Drowsiness

Headache

Impairment of vision

Blindness

narcosis

Coma

Symptoms may be delayed.

Damage to:

Liver  
Kidney  
Cardiac  
Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	flow-through test LC50 - <i>Lepomis macrochirus</i> (Bluegill) - 15,400.0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - <i>Daphnia magna</i> (Water flea) - 18,260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (green algae) - ca. 22,000.0 mg/l - 96 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	NOEC - <i>Oryzias latipes</i> (Orange-red killifish) - 7,900 mg/l - 200 h Remarks: (External MSDS)

### **12.2 Persistence and degradability**

Biodegradability	Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D)
Biochemical Oxygen Demand (BOD)	600 - 1,120 mg/g Remarks: (IUCLID)
Chemical Oxygen Demand (COD)	1,420 mg/g Remarks: (IUCLID)
Theoretical oxygen demand	1,500 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	76 % Remarks: Closed Bottle test(IUCLID)

### **12.3 Bioaccumulative potential**

Bioaccumulation	<i>Cyprinus carpio</i> (Carp) - 72 d at 20 °C - 5 mg/l(Methanol)
	Bioconcentration factor (BCF): 1.0

#### 12.4 Mobility in soil

Will not adsorb on soil.

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

Additional ecological information Avoid release to the environment.

Stability in water at 19 °C 83 - 91 % - 72 h  
Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.  
- 2.2 yr  
Remarks: reaction with hydroxyl radicals(IUCLID)

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

No data available

---

### SECTION 14: Transport information

#### **TDG**

UN number: 1230 Class: 3 (6.1) Packing group: II  
Proper shipping name: METHANOL  
Subsidiary risk : 6.1  
Labels: 3  
(6.1)ERG Code: 131  
Marine pollutant: no

#### **IMDG**

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D  
Proper shipping name: METHANOL

#### **IATA**

UN number: 1230 Class: 3 (6.1) Packing group: II  
Proper shipping name: Methanol

---

### SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

---

**SECTION 16: Other information**

The information contained in this document is based on Agilent’s state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.