



# Agilent Technologies

**Kit Name:** Cannabis and Hemp Potency Kit

**Kit PN:** 5610-2036

This product is a kit, composed of the following individual chemical components:

## Kit Components

Component Part Number	Component Name	Volume or mass/ container and unit	No. of component containers/ kit
G2453-85060	Formic acid, 5 ml	5mL	1
699975-302	Agilent InfinityLab Poroshell 120 EC-C18, 3.0 × 50 mm, 2.7 μm	<10mL Solvent	1 LC Column
5183-2072	Vial, screw top, amber, write-on spot, deactivated (silanized), certified, 2 mL, 100/pk	(Only contains hardware/non-chemical containing)	
5182-0718	Cap, screw, green, PTFE/red silicone septa, 100/pk		
5610-2049	50 mL centrifuge tubes, 25/pk		
5190-5107	0.45 μm Regenerated cellulose (RC) syringe filter, 100/pk		
9301-6476	Syringe, 5 mL, 100/pk		
5982-9313	Ceramic Homogenizers, for 50 mL tubes, 100/pk		

SDSs for each component follow this cover sheet.

## Transportation Information for the Kit:

Proper Shipping Names:

DOT	IATA/ICAO	China
UN3316 Chemical Kits, 9, II	UN3316 Chemical Kit, 9, II	UN3316 Chemical Kits, 9, II

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

## 1 化学品及企业标识

- 产品识别者
- 化学品中文(英文)名称, 化学品俗名或商品名: 甲酸, 试剂级 (1 x 5mL)
- 商品编号: G2453-85060
- CAS 编号:  
64-18-6
- 欧盟编号:  
200-579-1
- 欧盟编号:  
607-001-00-0
- 相应纯物质或者混合物的相关下位用途及禁止用途 供分析化学实验室使用的试剂和标准
- 安全技术说明书内供应商详细信息
- 企业名称:  
安捷伦科技贸易 (上海) 有限公司  
中国 (上海) 外高桥自由贸易试验区  
英伦路412号 (邮编:200131)
- 可获取更多资料的部门:  
电话号码:800-820-3278  
传真号码:0086 ( 21 ) 5048 2818
  
- pdl-msds\_author@agilent.com
- 紧急联系电话号码: 0532-83889090

## 2 危险性概述

· 紧急情况概述:  
无色的, 液体, 易燃液体和蒸气。 吞咽有害。 吸入会中毒。 造成严重皮肤灼伤和眼损伤。

· GHS 危险性类别



火焰

易燃液体 第3类

H226 易燃液体和蒸气



骷髅和交叉骨

急性毒性(吸入) 第3类

H331 吸入会中毒



腐蚀

皮肤腐蚀/刺激 第1A类

H314 造成严重皮肤灼伤和眼损伤

严重眼睛损伤/眼睛刺激性 第1类

H318 造成严重眼损伤



急性毒性(经口) 第4类

H302 吞咽有害

(在 2 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 1 页继续)

**· 标签因素**
**· GHS卷标元素** 本化学物质根据化学物质分类及标记全球协调制度(GHS)进行了分类及标记。

**· 图示**


GHS02    GHS05    GHS06

**· 名称 危险**
**· 标签上辨别危险的成份:**

甲酸 (100 %)

**· 危险字句**

易燃液体和蒸气

吞咽有害

吸入会中毒

造成严重皮肤灼伤和眼损伤

**· 警戒字句**

如需求医: 随手携带产品容器或标签

儿童不得接触

使用前请读标签

**· 预防措施**

远离热源/火花/明火/热表面。禁止吸烟

容器和装载设备接地/等势联接

使用防爆的电气/通风/照明/设备

只能使用不产生火花的工具

采取防止静电放电的措施

不要吸入粉尘/气体

作业后彻底清洗

使用本产品时不要进食、饮水或吸烟

只能在室外或通风良好之处使用

戴防护手套/穿防护服/戴防护眼罩/戴防护面具

**· 事故响应**

如误吞咽: 如感觉不适, 呼叫急救中心/医生

如误吞咽: 漱口。不要诱导呕吐

如皮肤(或头发)沾染: 立即脱掉所有沾染的衣服。用水清洗皮肤/淋浴

如误吸入: 将人转移到空气新鲜处, 保持呼吸舒适体位

如进入眼睛: 用水小心冲洗几分钟。如戴隐形眼镜并可方便地取出, 取出隐形眼镜。继续冲洗

立即呼叫急救中心/医生

具体治疗(见本标签上的)

沾染的衣服清洗后方可重新使用

火灾时: 使用二氧化碳、粉末或水性喷雾灭火。

**· 安全储存**

存放在通风良好的地方。保持容器密闭

存放在通风良好的地方。保持低温

存放处须加锁

**· 废弃处置**

处置内装物/容器按照地方/区域/国家/国际规章

**· 其他有害性**
**· PBT(残留性、生物浓缩性、毒性物质) 及 vPvB(高残留性、高生物浓缩性物质) 评价结果**
**· PBT(残留性、生物浓缩性、毒性物质) 不适用的**

(在 3 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名: 甲酸, 试剂级 (1 x 5mL)**

· vPvB(高残留性、高生物浓缩性物质): 不适用的

(在 2 页继续)

## 3 成分/组成信息

- 纯品
- CAS号 化学名, 通用名  
64-18-6 甲酸
- 鉴别编号:
- 欧盟编号: 200-579-1
- 欧盟编号: 607-001-00-0

## 4 急救措施

- 应急措施要领
- 总说明:  
马上脱下染有该产品的衣服。  
中毒的症状可能会在几个小时以后才出现;因此在发生事故之后起码要有 48 小时的医疗观察。  
只在彻底地脱去了已被污染的衣服之后才能移走呼吸仪器。  
万一出现了不规则的呼吸或呼吸的阻碍,请为病人提供人工呼吸。
- 吸入:  
供给新鲜空气或氧气;叫医生。  
万一病人不清醒时,请让病人侧躺以便移动。
- 皮肤接触: 马上用水和肥皂进行彻底的冲洗。
- 眼睛接触: 张开眼睛在流水下冲洗数分钟. 然后咨询医生。
- 食入:  
马上召唤医生。  
喝大量的清水和提供新鲜的空气. 马上召唤医生。
- 给医生的资料:  
· 最重要的急慢性症状及其影响 无相关详细资料。  
· 需要及时的医疗处理及特别处理的症状 无相关详细资料。

## 5 消防措施

- 灭火方法
- 灭火的方法和灭火剂: 二氧化碳 (CO<sub>2</sub>)、灭火粉末或洒水. 使用洒水或抗酒精泡沫灭火剂扑灭较大的火种。
- 特别危险性 在加热期间或失火的情况下,产生有毒气体。
- 特殊灭火方法
- 消防人员特殊的防护装备: 口腔呼吸保护装置。

## 6 泄漏应急处理

- 保护措施  
装上呼吸保护装置。  
带上保护仪器. 让未受到保护的人们远离。
- 环境保护措施:  
用大量的水进行稀释。  
切勿让其进入下水道/水面或地下水。

(在 4 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 3 页继续)

**· 密封及净化方法和材料:**

吸收液体粘合原料 (沙粒、硅藻土、酸性粘合剂、通用粘合剂、锯屑).  
 使用中和剂.  
 根据第 13 条条款弃置受污染物.  
 确保有足够的通风装置.

**· 参照其他部分**

有关安全处理的资料请参阅第 7 节.  
 有关个人防护装备的资料请参阅第 8 节.  
 有关弃置的资料请参阅第 13 节.

## 7 操作处置与储存

**· 操作处置**
**· 储存**

确保工作间有良好的通风/排气装置.  
 小心打开及处理贮藏器.  
 防止气溶胶的形成.

**· 有关火灾及防止爆炸的资料:**

远离火源 - 切勿吸烟.  
 防静电.  
 提供呼吸保护装置.

**· 混合危险性等安全储存条件**
**· 储存:**

**· 储存库和容器须要达到的要求:** 没有特别的要求.  
**· 有关使用一个普通的储存设施来储存的资料:** 不需要.  
**· 有关储存条件的更多资料:** 将容器密封.  
**· 具体的最终用户** 无相关详细资料.

## 8 接触控制和个体防护

**· 工程控制方法:** 没有进一步数据;见第 7 项.

**· 控制变数**
**· 在工作场需要监控的限值成分**
**64-18-6 甲酸**

OEL (CN)	PC-STEL: 20 mg/m <sup>3</sup> PC-TWA: 10 mg/m <sup>3</sup>
PEL (TW)	PC-TWA: 9.4 mg/m <sup>3</sup> , 5 ppm

**· 额外的资料:** 制作期间有效的清单将作为基础来使用.

**· 泄漏控制**
**· 个人防护设备:**
**· 一般保护和卫生措施:**

远离食品、饮料和饲料.  
 立即除去所有的不洁的和被污染的衣服.  
 在休息之前和工作完毕后请清洗双手.  
 分开储存保护性衣服.  
 避免和眼睛接触.  
 避免和眼睛及皮肤接触.

(在 5 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 4 页继续)

**· 呼吸系统防护:**

按照预期用途与 Agilent 仪器一起使用时,在正常实验室条件下使用产品并采用标准做法时,不会产生明显的空气传播接触,因此不需要呼吸保护。

在认为需要呼吸的紧急情况下,将 NIOSH 或同类的获得批准的设备与适用的有机气瓶或酸性气瓶一起使用。

**· 手防护:**

建议在正常使用时佩戴 0.28-0.33 mm 厚、穿透时间为 1 小时的丁腈手套,但不建议在直接接触化学品或清理时使用。

如果在清理溢液时会直接接触化学品,建议佩戴 0.30-0.38 mm 厚、穿透时间超过 4 小时的丁基橡胶手套。应遵循供应商的建议。

**· 手套材料**

正常使用时:

丁腈橡胶,厚度为 0.28mm-0.33mm

直接接触化学品时:

丁基橡胶,厚度为 0.30mm-0.38mm

选择合适的手套不单取决于材料,亦取决于质量特征,以及来自哪一间生产厂家

**· 渗入手套材料的时间**

正常使用时:

丁腈橡胶:

1 小时

直接接触化学品时:

丁基橡胶:

> 4 小时

**· 眼睛防护:**


密封的护目镜

## 9 理化特性

**· 有关基本物理及化学特性的信息**
**· 一般说明**
**· 外观:**

形状: 液体

颜色: 无色的

· 气味: 刺激性的

· 嗅觉阈限: 未决定.

· pH 值: 未决定.

**· 条件的更改**

熔点: -9 °C

沸点/初沸点和沸程: 107 °C

· 闪点: 59 °C

· 可燃性(固体、气体): 不适用的

· 点火温度: 520 °C

· 分解温度: 未决定.

(在 6 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 5 页继续)

· 自燃温度:	未决定.
· 爆炸的危险性:	未决定.
· 爆炸极限:	
较低:	14 Vol %
较高:	33 Vol %
· 蒸气压 在 20 °C:	30 hPa
· 密度 在 20 °C:	1.2 g/cm <sup>3</sup>
· 相对密度	未决定.
· 蒸气密度	未决定.
· 蒸发速率	未决定.
· 溶解性	
水:	完全可拌和的
· n-辛醇/水分配系数:	未决定.
· 黏性:	
动态:	未决定.
运动学的:	未决定.
· 固体成份:	0.0 %
· 其他信息	无相关详细资料。

## 10 稳定性和反应性

- 反应性 无相关详细资料。
- 稳定性
- 热分解/要避免的情况: 如果遵照规格使用则不会分解。
- 有害反应可能性 未有已知的危险反应。
- 应避免的条件 无相关详细资料。
- 不相容的物质: 无相关详细资料。
- 危险的分解产物: 未知有危险的分解产品。

## \* 11 毒理学信息

- 对毒性学影响的信息
- 急性毒性:

### · 与分类相关的 LD/ LC50 值:

#### ATE (急性毒性估计值)

口腔	LD50	730 mg/kg (rat)
吸入	LC50/4 h	7.4 mg/L (rat)

#### 64-18-6 甲酸

口腔	LD50	730 mg/kg (rat)
吸入	LC50/4 h	7.4 mg/L (rat)

- 主要的刺激性影响:
- 皮肤: 在皮肤和粘膜上造成强烈的腐蚀性影响。

(在 7 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 6 页继续)

- **在眼睛上面:**  
强烈的腐蚀性影响。  
强烈的刺激性和造成严重伤害眼睛的危险。
- **致敏作用:** 没有已知的敏化影响。
- **更多毒物的资料:**  
吞咽该产品除了导致口部和喉咙出现强烈的腐蚀性现象之外,还有对食道和胃部造成穿孔的危险。

## 12 生态学信息

- **生态毒性**
- **水生毒性:** 无相关详细资料。
- **持久性和降解性** 无相关详细资料。
- **环境系统习性:**
- **潜在的生物累积性** 无相关详细资料。
- **土壤内移动性** 无相关详细资料。
- **额外的生态学资料:**
- **总括注解:**  
水危害级别 1(德国规例) (评估): 对水是稍微危害的  
不要让未稀释或大量的产品接触地下水、水道或者污水系统。  
不要让未被稀释或未被中和的产品接触下水道或排水沟渠。
- **PBT(残留性、生物浓缩性、毒性物质) 及 vPvB(高残留性、高生物浓缩性物质)评价结果**
- **PBT(残留性、生物浓缩性、毒性物质)** 不适用的
- **vPvB(高残留性、高生物浓缩性物质):** 不适用的
- **其他副作用** 无相关详细资料。

## 13 废弃处置

- **废弃处置方法**
- **建议:** 不能将该产品和家居垃圾一起丢弃. 不要让该产品接触污水系统。
- **受污染的容器和包装:**
- **建议:** 必须根据官方的规章来丢弃。
- **建议的清洗剂:** 如有必要请使用水及清洁剂进行清洁。

## 14 运输信息

- |                          |             |
|--------------------------|-------------|
| · <b>联合国危险货物编号(UN号)</b>  | UN1779      |
| · <b>ADR, IMDG, IATA</b> |             |
| · <b>UN适当装船名</b>         | 1779 甲酸     |
| · <b>ADR</b>             | 1779 甲酸     |
| · <b>IMDG, IATA</b>      | FORMIC ACID |

(在 8 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 7 页继续)

**· 运输危险等级**
**· ADR**

**· 级别**

8 腐蚀性物质

**· 标签**

8+3

**· IMDG**

**· Class**

8 腐蚀性物质

**· Label**

8/3

**· IATA**

**· Class**

8 腐蚀性物质

**· Label**

8 (3)

**· 包装组别**
**· ADR, IMDG, IATA**

II

**· 危害环境:**

不适用的

**· 用户特别预防措施**

警告: 腐蚀性物质

**· 危险编码:**

80

**· EMS 号码:**

8-05

**· Segregation groups**

Acids

**· Stowage Category**

A

**· Segregation Code**

SG36 Stow "separated from" SGG18-alkalis.

SG49 Stow "separated from" SGG6-cyanides

**· MARPOL73/78(针对船舶引起的海洋污染预防协议)**
**附件书2及根据IBC Code(国际装船货物编码)的大量运送**

不适用的

**· 运输/额外的资料:**
**· ADR**
**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· IMDG**
**· Limited quantities (LQ)**

1L

(在 9 页继续)

# 化学品安全技术说明书

根据 GB/T 16483-2008, GB/T 17519-2013

打印日期 2020/04/10

Version Number 4

在 2020/04/10 审核

**化学品中文(英文)名称, 化学品俗名或商品名 : 甲酸, 试剂级 (1 x 5mL)**

(在 8 页继续)

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "标准规定":

UN 1779 甲酸, 8 (3), II

## 15 法规信息

- 对相应纯物质或者混合物的安全、保健及环境法规/法律
- 危险化学品安全管理条例

· 危险化学品目录

64-18-6	甲酸
---------	----

· 新化学物质环境管理办法

· 中国现有化学物质名录

有列出物质.
--------

· 化学物质安全性评价: 尚未进行化学物质安全性评价

## 16 其他信息

本文件所包含的信息是基于安捷伦准备文件时所掌握的知识。安捷伦不就其为特定目的之精确性、完整性或适用性做出明示或暗示的保证。

· 缩写:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: 持久性生物累积性有毒物质

vPvB: very Persistent and very Bioaccumulative

易燃液体 第3类: Flammable liquids – Category 3

急性毒性(径口) 第4类: Acute toxicity – Category 4

急性毒性(吸入) 第3类: Acute toxicity – Category 3

皮肤腐蚀/刺激 第1A类: Skin corrosion/irritation – Category 1A

严重眼睛损伤/眼睛刺激性 第1类: Serious eye damage/eye irritation – Category 1

· \* 与旧版本比较的数据已改变

# SAFETY DATA SHEET

Poroshell 120 EC-C18 Chromatography Columns with Acetonitrile and Water less than 10mL

## Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

### 1.1 Product identifier

**Product name** : Poroshell 120 EC-C18 Chromatography Columns with Acetonitrile and Water less than 10mL

**Part no.** : 690975-902, 693975-902, 695775-922, 695975-902, 697975-902, 699775-922, 699975-902, 691975-902, 693975-302, 695975-302, 697975-302, 699975-302, 691975-302, 693775-902, 695775-902, 697775-902, 699775-902, 691775-902, 821725-911, 823750-911, 820750-911, 699770-902, 695770-902, 693770-902, 650750-902, 699970-302, 695970-302, 693970-302, 690970-302, 699970-902, 695970-902, 693970-902, 690970-902, 821725-916, 823750-916, 820750-916, 650750-902T, 690970-302T, 690970-902T, 690975-902T, 691775-902T, 691975-302T, 691975-902T, 693770-902T, 693775-902T, 693970-302T, 693970-902T, 693975-302T, 693975-902T, 695770-902T, 695775-902T, 695970-302T, 695970-902T, 695975-302T, 695975-902T, 697775-902T, 697975-302T, 697975-902T, 699770-902T, 699775-902T, 699970-302T, 699970-902T, 699975-302T, 699975-902T, 699675-902, 695675-902, 693675-902, 699675-302, 695675-302, 693675-302, 821725-940, 823750-940, 695575-902, 693575-902, 695575-302, 693575-302, 691775-302

**Validation date** : 10/14/2019

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Analytical chemistry.  
HPLC column  
Solvent volume: <10 ml

690975-902	Poroshell 120, EC-C18, 4.6x250mm, 2.7um
693975-902	Poroshell 120, EC-C18, 4.6x150mm, 2.7um
695775-922	Poroshell 120, EC-C18, 2.1x100mm, 2.7um 2pk
695975-902	Poroshell 120, EC-C18, 4.6x100mm, 2.7um
697975-902	Poroshell 120, EC-C18, 4.6x75mm, 2.7um
699775-922	Poroshell 120, EC-C18, 2.1x50mm, 2.7um 2pk
699975-902	Poroshell 120, EC-C18, 4.6x50mm, 2.7um
691975-902	Poroshell 120, EC-C18, 4.6x30mm, 2.7um
693975-302	Poroshell 120, EC-C18, 3.0x150mm, 2.7um
695975-302	Poroshell 120, EC-C18, 3.0x100mm, 2.7um
697975-302	Poroshell 120, EC-C18, 3.0x75mm, 2.7um
699975-302	Poroshell 120, EC-C18, 3.0x50mm, 2.7um
691975-302	Poroshell 120, EC-C18, 3.0x30mm, 2.7um
693775-902	Poroshell 120, EC-C18, 2.1x150mm, 2.7um
695775-902	Poroshell 120, EC-C18, 2.1x100mm, 2.7um
697775-902	Poroshell 120, EC-C18, 2.1x75mm, 2.7um
699775-902	Poroshell 120, EC-C18, 2.1x50mm, 2.7um
691775-902	Poroshell 120, EC-C18, 2.1x30mm, 2.7um
821725-911	Poroshell 120, UHPLC Guard, EC-C18, 2.1mm
823750-911	Poroshell 120, UHPLC Guard, EC-C18, 3.0mm
820750-911	Poroshell 120, UHPLC Guard, EC-C18, 4.6mm
699770-902	Poroshell 120, EC-C18, 2.1x50mm, 4um
695770-902	Poroshell 120, EC-C18, 2.1x100mm, 4um
693770-902	Poroshell 120, EC-C18, 2.1x150mm, 4um
650750-902	Poroshell 120, EC-C18, 2.1x250mm, 4um
699970-302	Poroshell 120, EC-C18, 3x50mm, 4um
695970-302	Poroshell 120, EC-C18, 3x100mm, 4um
693970-302	Poroshell 120, EC-C18, 3x150mm, 4um
690970-302	Poroshell 120, EC-C18, 3x250mm, 4um
699970-902	Poroshell 120, EC-C18, 4.6x50mm, 4um
695970-902	Poroshell 120, EC-C18, 4.6x100mm, 4um

## Section 1. Identification

693970-902	Poroshell 120, EC-C18, 4.6x150mm, 4um
690970-902	Poroshell 120, EC-C18, 4.6x250mm, 4um
821725-916	Poroshell 120, UHPLC Grd, EC-C18, 2.1mm, 4um
823750-916	Poroshell 120, UHPLC Grd, EC-C18, 3mm, 4um
820750-916	Poroshell 120, UHPLC Grd, EC-C18, 4.6mm, 4um
650750-902T	Poroshell 120, EC-C18, 2.1x 250mm, 4um, T
690970-302T	Poroshell 120, EC-C18, 3x 250mm, 4um, T
690970-902T	Poroshell 120, EC-C18, 4.6x 250mm, 4um, T
690975-902T	Poroshell 120, EC-C18, 4.6x 250mm, 2.7um, T
691775-902T	Poroshell 120, EC-C18, 2.1x 30mm, 2.7um, T
691975-302T	Poroshell 120, EC-C18, 3x 30mm, 2.7um, T
691975-902T	Poroshell 120, EC-C18, 4.6x 30mm, 2.7um, T
693770-902T	Poroshell 120, EC-C18, 2.1x 150mm, 4um, T
693775-902T	Poroshell 120, EC-C18, 2.1x 150mm, 2.7um, T
693970-302T	Poroshell 120, EC-C18, 3x 150mm, 4um, T
693970-902T	Poroshell 120, EC-C18, 4.6x 150mm, 4um, T
693975-302T	Poroshell 120, EC-C18, 3x 150mm, 2.7um, T
693975-902T	Poroshell 120, EC-C18, 4.6x 150mm, 2.7um, T
695770-902T	Poroshell 120, EC-C18, 2.1x 100mm, 4um, T
695775-902T	Poroshell 120, EC-C18, 2.1x 100mm, 2.7um, T
695970-302T	Poroshell 120, EC-C18, 3x 100mm, 4um, T
695970-902T	Poroshell 120, EC-C18, 4.6x 100mm, 4um, T
695975-302T	Poroshell 120, EC-C18, 3x 100mm, 2.7um, T
695975-902T	Poroshell 120, EC-C18, 4.6x 100mm, 2.7um, T
697775-902T	Poroshell 120, EC-C18, 2.1x 75mm, 2.7um, T
697975-302T	Poroshell 120, EC-C18, 3x 75mm, 2.7um, T
697975-902T	Poroshell 120, EC-C18, 4.6x 75mm, 2.7um, T
699770-902T	Poroshell 120, EC-C18, 2.1x 50mm, 4um, T
699775-902T	Poroshell 120, EC-C18, 2.1x 50mm, 2.7um, T
699970-302T	Poroshell 120, EC-C18, 3x 50mm, 4um, T
699970-902T	Poroshell 120, EC-C18, 4.6x 50mm, 4um, T
699975-302T	Poroshell 120, EC-C18, 3x 50mm, 2.7um, T
699975-902T	Poroshell 120, EC-C18, 4.6x 50mm, 2.7um, T
699675-902	Poroshell 120 EC-C18, 2.1x50mm, 1.9um, T
695675-902	Poroshell 120 EC-C18, 2.1x100mm, 1.9um, T
693675-902	Poroshell 120 EC-C18, 2.1x150mm, 1.9um, T
699675-302	Poroshell 120 EC-C18, 3x50mm, 1.9um, T
695675-302	Poroshell 120 EC-C18, 3x100mm, 1.9um, T
693675-302	Poroshell 120 EC-C18, 3x150mm, 1.9um, T
821725-940	UHPLC Grd, P120 EC-C18, 2.1mm, 1.9um, 3pk
823750-940	UHPLC Grd, P120 EC-C18, 3mm, 1.9um, 3pk
695575-902	Poroshell 120, EC-C18, 2.1x100mm, 2.7u, 1000bar
693575-902	Poroshell 120, EC-C18, 2.1x150mm, 2.7u, 1000bar
695575-302	Poroshell 120, EC-C18, 3.0x100mm, 2.7u, 1000bar
693575-302	Poroshell 120, EC-C18, 3.0x150mm, 2.7u, 1000bar
691775-302	Poroshell 120, EC-C18, 3.0x30mm, 1.9um, T

### [1.3 Details of the supplier of the safety data sheet](#)

**Supplier/Manufacturer** : Agilent Technologies, Inc.  
5301 Stevens Creek Blvd  
Santa Clara, CA 95051, USA  
800-227-9770

### [1.4 Emergency telephone number](#)

**In case of emergency** : CHEMTREC®: 1-800-424-9300

## Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

### 2.1 Classification of the substance or mixture

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2  
 H319 EYE IRRITATION - Category 2A  
 H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

### 2.2 GHS label elements

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

H225 - Highly flammable liquid and vapor.  
 H319 - Causes serious eye irritation.  
 H373 - May cause damage to organs through prolonged or repeated exposure. (blood system, central nervous system (CNS), kidneys, liver)

### Precautionary statements

**Prevention** :

P280 - Wear protective gloves. Wear eye or face protection.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P233 - Keep container tightly closed.  
 P260 - Do not breathe vapor.  
 P264 - Wash hands thoroughly after handling.

**Response** :

P314 - Get medical attention if you feel unwell.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical attention.

**Storage** :

P403 - Store in a well-ventilated place.  
 P235 - Keep cool.

**Disposal** :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 Other hazards

**Hazards not otherwise classified** :

None known.

## Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

**Substance/mixture** : Mixture (encapsulated in article)

Ingredient name	%	CAS number
Acetonitrile	≥10 - <22	75-05-8

Contains: Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### 4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 4.2 Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.

## Section 4. First aid measures

**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : No specific data.

**Skin contact** : No specific data.

**Ingestion** : No specific data.

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides  
cyanides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not applicable.

## Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Acetonitrile	<p><b>ACGIH TLV (United States, 3/2018).</b>  <b>Absorbed through skin.</b>            TWA: 20 ppm 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 40 ppm 8 hours.            TWA: 70 mg/m<sup>3</sup> 8 hours.            STEL: 60 ppm 15 minutes.            STEL: 105 mg/m<sup>3</sup> 15 minutes.</p> <p><b>NIOSH REL (United States, 10/2016).</b>            TWA: 20 ppm 10 hours.            TWA: 34 mg/m<sup>3</sup> 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b>            TWA: 40 ppm 8 hours.            TWA: 70 mg/m<sup>3</sup> 8 hours.</p>

### 8.2 Exposure controls

#### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

##### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

##### Skin protection

##### Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Solid. (containing flammable liquid)
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: -18 to 23°C (-0.4 to 73.4°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Contains: Flammable liquid.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : Not available.
- Solubility** : Mobile phase: Soluble  
Stationary phase: Insoluble
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

## Section 10. Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

## Section 10. Stability and reactivity

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials  
Incompatible with hydrogen fluoride.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetonitrile	LC50 Inhalation Vapor	Rat	17100 ppm	4 hours
	LD50 Oral	Rat	2460 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 microliters	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

#### Sensitization

Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

#### Teratogenicity

**Conclusion/Summary** : Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Acetonitrile	Category 2	Not determined	blood system, central nervous system (CNS), kidneys and liver

#### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

## Section 11. Toxicological information

- Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

- General** : May cause damage to organs through prolonged or repeated exposure.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Poroshell 120 EC-C18 Chromatography Columns with Acetonitrile and Water less than 10mL	2381	5238.1	N/A	52.4	N/A
Acetonitrile	500	1100	N/A	11	N/A

## Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute IC50 3685000 µg/l Fresh water	Aquatic plants - Lemna minor	96 hours
	Acute LC50 3600000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1000000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 1000000 µg/l Fresh water	Aquatic plants - Lemna minor	96 hours
	Chronic NOEC 160000 µg/l Fresh water	Daphnia - Daphnia magna	21 days

### 12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetonitrile	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Acetonitrile	-0.34	3	low

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Acetonitrile (I,T)	75-05-8	Listed	U003

## Section 13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

**DOT / TDG / Mexico / IMDG / IATA** : Not regulated.

**Remarks:** Special provisions

DOT: 47

TDG: 56

MX: 216

IATA: A46

IMDG: 216

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**U.S. Federal regulations** : **TSCA 8(a) PAIR:** Acetonitrile  
**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**Clean Water Act (CWA) 307:** Acetonitrile

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

**SARA 302/304**

## Section 15. Regulatory information

### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 2  
EYE IRRITATION - Category 2A  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

### Composition/information on ingredients

Name	%	Classification
Organosilane bonded silica gel	≥50 - ≤75	COMBUSTIBLE DUSTS
Acetonitrile	≥10 - <22	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	Acetonitrile	75-05-8	≥10 - <22
<b>Supplier notification</b>	Acetonitrile	75-05-8	≥10 - <22

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

**Massachusetts** : The following components are listed: ACETONITRILE  
**New York** : The following components are listed: Acetonitrile; Ethanenitrile  
**New Jersey** : The following components are listed: ACETONITRILE; CYANOMETHANE  
**Pennsylvania** : The following components are listed: ACETONITRILE

### California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

**Australia** : All components are listed or exempted.

## Section 15. Regulatory information

<b>Canada</b>	: Not determined.
<b>China</b>	: All components are listed or exempted.
<b>Europe</b>	: All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (ENCS)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : All components are listed or exempted.
<b>New Zealand</b>	: All components are listed or exempted.
<b>Philippines</b>	: Not determined.
<b>Republic of Korea</b>	: Not determined.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: Not determined.
<b>Turkey</b>	: All components are listed or exempted.
<b>United States</b>	: All components are listed or exempted.
<b>Viet Nam</b>	: Not determined.

## Section 16. Other information

### History

<b>Date of issue</b>	: 10/14/2019
<b>Date of previous issue</b>	: 05/03/2019
<b>Version</b>	: 9.1

### Key to abbreviations

: ATE = Acute Toxicity Estimate
: BCF = Bioconcentration Factor
: GHS = Globally Harmonized System of Classification and Labelling of Chemicals
: IATA = International Air Transport Association
: IBC = Intermediate Bulk Container
: IMDG = International Maritime Dangerous Goods
: LogPow = logarithm of the octanol/water partition coefficient
: MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
: N/A = Not available
: UN = United Nations

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2	On basis of test data Calculation method Calculation method

Indicates information that has changed from previously issued version.

### Notice to reader

**Disclaimer:** The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.