



Safety Data Sheet acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

1 Identification

- **Product identifier**
- **Product name:** Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF
- **Part number:** 6610030500
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051,
USA
- **Information department:** e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

Tel: 800-227-9770

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

hydrofluoric acid

- **Hazard statements**

H290 May be corrosive to metals.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 1)

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P406 Store in corrosive resistant container with a resistant inner liner.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 0
Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 2
Fire = 0
Reactivity = 0

Other hazards

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description:

Aqueous solution.

Also contains substances at levels not considered to be hazardous.

Dangerous components:

CAS: 7697-37-2 RTECS: QU5775000	nitric acid Ox. Liq. 3, H272; Acute Tox. 3, H331; Met. Corr.1, H290; Skin Corr. 1A, H314	<2%
CAS: 7664-39-3 RTECS: MW7875000	hydrofluoric acid Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; Skin Corr. 1A, H314	<1%

Additional information:

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

US

(Contd. on page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse mouth. Do not induce vomiting.

Seek medical treatment.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

- **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 3)

· Reference to other sections*See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***· Protective Action Criteria for Chemicals****· PAC-1:**

CAS: 7697-37-2	nitric acid	0.16 ppm
CAS: 7664-39-3	hydrofluoric acid	1.0 ppm
CAS: 7439-98-7	Molybdenum	30 mg/m ³
CAS: 7440-28-0	thallium	0.06 mg/m ³
CAS: 7440-31-5	Tin	6 mg/m ³
CAS: 7440-36-0	Antimony	1.5 mg/m ³

· PAC-2:

CAS: 7697-37-2	nitric acid	24 ppm
CAS: 7664-39-3	hydrofluoric acid	24 ppm
CAS: 7439-98-7	Molybdenum	330 mg/m ³
CAS: 7440-28-0	thallium	3.3 mg/m ³
CAS: 7440-31-5	Tin	67 mg/m ³
CAS: 7440-36-0	Antimony	13 mg/m ³

· PAC-3:

CAS: 7697-37-2	nitric acid	92 ppm
CAS: 7664-39-3	hydrofluoric acid	44 ppm
CAS: 7439-98-7	Molybdenum	2,000 mg/m ³
CAS: 7440-28-0	thallium	20 mg/m ³
CAS: 7440-31-5	Tin	400 mg/m ³
CAS: 7440-36-0	Antimony	80 mg/m ³

7 Handling and storage

· Handling:**· Precautions for safe handling***Prevent formation of aerosols.**Ensure good ventilation/exhaustion at the workplace.**Store in cool, dry place in tightly closed receptacles.***· Information about protection against explosions and fires:** *No special measures required.***· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:***Please refer to the manufacturers certificate for specific storage and transport temperature conditions.**Store only in the original receptacle unless other advice is given on the CoA.**Keep container in a well-ventilated place. Keep away from sources of ignition and heat.***· Information about storage in one common storage facility:** *Store away from foodstuffs.***· Further information about storage conditions:** *Keep receptacle tightly sealed.*

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

- *Specific end use(s)* No further relevant information available.

(Contd. of page 4)

8 Exposure controls/personal protection

- *Additional information about design of technical systems:* No further data; see item 7.

- *Control parameters*

- *Components with limit values that require monitoring at the workplace:*

CAS: 7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

CAS: 7664-39-3 hydrofluoric acid

PEL	Long-term value: 1 mg/m ³ , 3 ppm as F, <u>sulfuric acid</u>
REL	Long-term value: 2.5 mg/m ³ , 3 ppm Ceiling limit value: 5 mg/m ³ , 6 ppm 15-min, as F
TLV	Long-term value: 0.41 mg/m ³ , 0.5 ppm Ceiling limit value: 1.64 mg/m ³ , 2 ppm as F; Skin, BEI

- *Ingredients with biological limit values:*

CAS: 7664-39-3 hydrofluoric acid

BEI	3 mg/g creatinine Medium: urine Time: prior to shift Parameter: Fluorides (background, nonspecific)
	10 mg/g creatinine Medium: urine Time: end of shift Parameter: Fluorides (background, nonspecific)

- *Additional information:* The lists that were valid during the creation were used as basis.

- *Exposure controls*

- *Personal protective equipment:*

- *General protective and hygienic measures:*

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- *Breathing equipment:*

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- *Protection of hands:*

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

- Material of gloves**

- PVC gloves

- Neoprene gloves

- Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties**

- General Information**

- Appearance:**

Form:	Liquid
--------------	--------

Color:	Colorless
---------------	-----------

Odor:	Odorless
--------------	----------

Odor threshold:	Not determined.
------------------------	-----------------

pH-value:	Not determined.
------------------	-----------------

- Change in condition**

Melting point/Melting range:	Not determined.
-------------------------------------	-----------------

	Not determined.
--	-----------------

	Not determined.
--	-----------------

Boiling point/Boiling range:	Not applicable.
-------------------------------------	-----------------

Flash point:	Not applicable.
---------------------	-----------------

Flammability (solid, gaseous):	Not determined.
---------------------------------------	-----------------

Ignition temperature:	Not determined
------------------------------	----------------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Auto igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Not determined.
-----------------------------	-----------------

- Explosion limits:**

Lower:	Not determined.
---------------	-----------------

Upper:	Not determined.
---------------	-----------------

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 6)

· Vapor pressure:	<i>Not determined.</i>
· Density:	<i>Not determined.</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Fully miscible.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
VOC content:	<i>0.00 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

· Reactivity*Stable under normal conditions.**No further relevant information available.***· Chemical stability** *Stable under normal conditions.***· Thermal decomposition / conditions to be avoided:***Formation of toxic gases is possible during heating or in case of fire.***· Possibility of hazardous reactions** *No dangerous reactions known.***· Conditions to avoid Heat.****· Incompatible materials:***Strong oxidizing agents.**Metals.***· Hazardous decomposition products:** *Formation of toxic gases is possible during heating or in case of fire.*

11 Toxicological information

· Information on toxicological effects**· Acute toxicity:****· Primary irritant effect:****· on the skin:** *Irritant to skin and mucous membranes.***· on the eye:** *Irritating effect.***· Additional toxicological information:***The product shows the following dangers according to internally approved calculation methods for preparations:**Harmful**Irritant*

(Contd. on page 8)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Dispose in accordance with national regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3264

· **DOT**

Corrosive liquid, acidic, inorganic, n.o.s. (Hydrofluoric acid, Nitric acid)

· **ADR**

3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(HYDROFLUORIC ACID, NITRIC ACID)

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 8)

· IMDG, IATA	<i>CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID)</i>
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR, IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	<i>Not applicable.</i>
· Special precautions for user	<i>Warning: Corrosive substances</i>
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 <i>Clear of living quarters.</i>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	<i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i> <i>Maximum net quantity per outer packaging: 1000 ml</i>
· UN "Model Regulation":	<i>UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID), 8, III</i>

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- Sara**

- Section 355 (extremely hazardous substances):**

CAS: 7697-37-2	<i>nitric acid</i>
----------------	--------------------

(Contd. on page 10)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 9)

CAS: 7664-39-3 hydrofluoric acid

· Section 313 (Specific toxic chemical listings):

CAS: 7697-37-2 nitric acid

CAS: 7664-39-3 hydrofluoric acid

CAS: 7440-28-0 thallium

CAS: 7440-36-0 Antimony

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

CAS: 7664-39-3 hydrofluoric acid

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 7439-98-7 Molybdenum

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Hazard pictograms


GHS05



GHS07

· Signal word Warning

· Hazard-determining components of labeling:

hydrofluoric acid

· Hazard statements

H290 May be corrosive to metals.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 11)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 02/22/2021

Reviewed on 02/22/2021

Product name: Calibration Mix 1: Sb, Mo, Sn, Tl (100 mg/L) in 2% HNO3/0.5% HF

(Contd. of page 10)

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P406 Store in corrosive resistant container with a resistant inner liner.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Contact:**

· **Date of preparation / last revision** 02/22/2021 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Ox. Liq. 3: Oxidizing liquids – Category 3

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

· **Data compared to the previous version altered.** All sections have been updated.