

SAFETY DATA SHEET

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Lubricant, Anti-seize, C-5-A, 4OZ.
Part no. : 695436002

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemistry Laboratory Use
1 x 4 oz
Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Agilent Technologies Deutschland GmbH
Hewlett-Packard-Str. 8
76337 Waldbronn
Germany
0800 603 1000

e-mail address of person responsible for this SDS : pdl-msds_author@agilent.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation) : CHEMTREC®: +353 1 901 4670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| | | |
|------|--|------------|
| H315 | SKIN CORROSION/IRRITATION | Category 2 |
| H318 | SERIOUS EYE DAMAGE/EYE IRRITATION | Category 1 |
| H335 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) | Category 3 |
| H412 | LONG-TERM (CHRONIC) AQUATIC HAZARD | Category 3 |

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 30 - 60%
 Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 10 - 30%
 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 30 - 60%

Ingredients of unknown ecotoxicity : Contains 1% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Lubricant, Anti-seize, C-5-A, 40Z.

SECTION 2: Hazards identification

Hazard statements : H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H335 - May cause respiratory irritation.
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
 P273 - Avoid release to the environment.

Response : P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Calcium dihydroxide

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|--|-----------|--|---|---------|
| Calcium dihydroxide | EC: 215-137-3 CAS: 1305-62-0 | ≥10 - ≤25 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 | - | [1] [2] |
| Distillates (petroleum), hydrotreated heavy naphthenic | EC: 265-155-0 CAS: 64742-52-5 | ≥10 - ≤25 | Not classified. | - | [2] |
| Distillates (petroleum), hydrotreated light naphthenic | EC: 265-156-6 CAS: 64742-53-6 | ≥10 - ≤25 | Not classified. | - | [2] |
| copper | EC: 231-159-6 CAS: 7440-50-8 Index: 029-019-01-X | ≥10 - <25 | Aquatic Acute 1, H400 Aquatic Chronic 2, H411 | M [Acute] = 1 | [1] [2] |
| Graphite | EC: 231-955-3 | ≥10 - ≤25 | Not classified. | - | [2] |

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 3: Composition/information on ingredients

| | | | | | |
|----------------------------|--|----|--|---|-----|
| Quartz (SiO ₂) | CAS: 7782-42-5 EC: 238-878-4 CAS: 14808-60-7 | ≤3 | Not classified. See Section 16 for the full text of the H statements declared above. | - | [2] |
|----------------------------|--|----|--|---|-----|

Contains: Benzene (< 0.1%) ; IP 346 , DMSO (<3%)

Applicable : EC CLP Note L; OIN 8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : Keep away from heat.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 6: Accidental release measures

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Avoid release to the environment. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|--|
| Calcium dihydroxide | NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 15 minutes: 4 mg/m ³ . Form: respirable fraction. OELV 8 hours: 1 mg/m ³ . Form: respirable fraction. EU OEL (Europe, 1/2022) TWA 8 hours: 1 mg/m ³ . Form: Respirable fraction. STEL 15 minutes: 4 mg/m ³ . Form: Respirable fraction. |
| Distillates (petroleum), hydrotreated heavy | NAOSH (Ireland, 4/2024) [Mineral oil, pure, highly & severely |

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 8: Exposure controls/personal protection

| | |
|--|--|
| naphthenic | refined] Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 5 ppm. Form: inhalable dust. |
| Distillates (petroleum), hydrotreated light naphthenic | NAOSH (Ireland, 4/2024) [Mineral oil, pure, highly & severely refined] Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 5 ppm. Form: inhalable dust. |
| copper | NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 0.2 mg/m ³ (as Cu). Form: fume. OELV 8 hours: 1 mg/m ³ (as Cu). Form: dusts and mists. |
| Graphite | NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 2 mg/m ³ . Form: respirable fraction. |
| Quartz (SiO ₂) | NAOSH (Ireland, 4/2024) [silica, crystalline] Notes: EU derived Occupational Exposure Limit Values; List of Carcinogenic Substances, Mixtures and Processes OELV 8 hours: 0.1 mg/m ³ . Form: respirable dust. |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Result

| | | |
|---------------------|---|---------------------|
| calcium dihydroxide | DNEL - General population - Long term - Inhalation | 1 mg/m ³ |
| | DNEL - Workers - Long term - Inhalation | 1 mg/m ³ |
| copper | DNEL - General population - Short term - Inhalation | 4 mg/m ³ |
| | DNEL - Workers - Short term - Inhalation | 4 mg/m ³ |
| copper | DNEL - General population - Long term - Dermal | 137 mg/kg bw/day |
| | DNEL - Workers - Long term - Dermal | 137 mg/kg bw/day |
| | DNEL - General population - Short term - Dermal | 273 mg/kg bw/day |
| | DNEL - Workers - Short term - Dermal | 273 mg/kg bw/day |

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Solid. [Paste.]
- Colour** : Copper
- Odour** : Mild.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : >260°C [<0.01KPa]
- Flammability** : Keep away from heat.
- Lower and upper explosion limit/flammability limit** : Not applicable.
- Flash point** : Closed cup: >93°C
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 9: Physical and chemical properties

| Solubility | Media | Result |
|------------|-------|-----------|
| | water | Insoluble |

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure : <0.67 kPa (<5 mm Hg)

Relative density : 1.3

Relative vapour density : >1 [Air = 1]

Particle characteristics

Median particle size : Not available.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Evaporation rate : Not available.

Physical/chemical properties comments : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : May react or be incompatible with oxidising materials.

Reactive or incompatible with the following materials: acids and alkalis.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result |
|-------------------------|---|
| calcium dihydroxide | Rat - Oral - LD50 7340 mg/kg Rat - Female - Dermal - LD50 >2000 mg/kg Rat - Male, Female - Inhalation - LC50 Dusts and mists >6.04 mg/l [4 hours] |
| copper | Rat - Male, Female - Inhalation - LC50 Dusts and mists >5.11 mg/l [4 hours] |

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 11: Toxicological information

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Calcium dihydroxide | 7340 | N/A | N/A | N/A | N/A |

Skin corrosion/irritation

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

| | | |
|--------------------------------|---------------------------------|--------------------------------------|
| Product/ingredient name | Result | Amount/concentration applied: |
| Calcium dihydroxide | Rabbit - Eyes - Severe irritant | 10 mg |

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Skin Conclusion/Summary [Product] : Not available.

Respiratory Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Conclusion/Summary [Product] : Contains crystalline silica, which may cause lung disease and/or cancer. (Avoid dust generation.)

Reproductive toxicity

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

| | |
|--------------------------------|--|
| Product/ingredient name | Result |
| Calcium dihydroxide | STOT SE 3, H335 (Respiratory tract irritation) |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 11: Toxicological information

Information on likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

- Conclusion/Summary [Product]** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

- Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result |
|-------------------------|--------|
|-------------------------|--------|

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 12: Ecological information

| | | |
|-------------------------------|-------------------------------|------------------------|
| calcium dihydroxide copper | Acute - LC50 - Fresh water | 160 ppm [96 hours] |
| | Acute - EC50 - Fresh water | 184.57 mg/l [72 hours] |
| | Acute - LC50 - Marine water | 0.072 µg/l [48 hours] |
| | Chronic - NOEC - Marine water | 2.5 µg/l [72 hours] |
| | Chronic - NOEC - Fresh water | 0.8 µg/l [6 weeks] |
| | Acute - LC50 - Marine water | 7.56 µg/l [96 hours] |
| | Chronic - NOEC - Fresh water | 2 µg/l [21 days] |
| | Acute - IC50 - Fresh water | 13 µg/l [72 hours] |

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient

Not available.

Results of PMT and vPvM assessment

| Product/ingredient name | PMT | P | M | T | vPvM | vP | vM |
|-------------------------|-----|----|----|----|------|----|----|
| calcium dihydroxide | No | No | No | No | No | No | No |
| copper | No | No | No | No | No | No | No |

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|-------------------------|-----|----|----|----|------|----|----|
| calcium dihydroxide | No | No | No | No | No | No | No |
| copper | No | No | No | No | No | No | No |

Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|-------------------------|-----|----|----|----|------|----|----|
| calcium dihydroxide | No | No | No | No | No | No | No |
| copper | No | No | No | No | No | No | No |

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Lubricant, Anti-seize, C-5-A, 40Z.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. The generation of waste should be avoided or minimised wherever possible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|---------------------------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - |
| 14.4 Packing group | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. |

Additional information

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 15: Regulatory information

None of the components are listed / The components are not impacted by a restriction

Labelling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) : Listed

- Air

Industrial emissions (integrated pollution prevention and control) : Listed

- Water

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list


| | |
|--------------------------------|--|
| Australia | : Not determined. |
| Canada | : All components are listed or exempted. |
| China | : Not determined. |
| Eurasian Economic Union | : Russian Federation inventory : Not determined. |
| Japan | : Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined. |
| New Zealand | : Not determined. |
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States | : All components are active or exempted. |
| Viet Nam | : Not determined. |

Lubricant, Anti-seize, C-5-A, 40Z.

SECTION 15: Regulatory information

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments might still be required.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.


Abbreviations and acronyms :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- B = Bioaccumulative
- BCF = Bioconcentration Factor
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- M = Mobile
- N/A = Not available
- P = Persistent
- PBT = Persistent, Bioaccumulative and Toxic
- PMT = Persistent, Mobile and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SGG = Segregation Group
- T = Toxic
- vB = Very Bioaccumulative
- vM = Very Mobile
- vP = Very Persistent
- vPvB = Very Persistent and Very Bioaccumulative
- vPvM = Very Persistent and Very Mobile


Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|---|--|
| Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412 | Calculation method Calculation method Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|---|---|
|  H315 H318 H335 H400 H411 H412 | Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. |
|---|---|

Full text of classifications [CLP/GHS]

| | |
|--|---|
|  Aquatic Acute 1 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Skin Irrit. 2 STOT SE 3 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|--|---|

Date of issue/ Date of revision : 23/03/2026

Lubricant, Anti-seize, C-5-A, 4OZ.

SECTION 16: Other information

Date of previous issue : 29/05/2023

Version : 2

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.