

Section 1 - Product and Company Identification

Product Name: SB-C8 Guard Cartridges, 2.1x12.5mm 5u 4/PK
Agilent Part Number: 821125-915
Date Prepared: 1/24/03
Distributed By: Agilent Technologies, Inc.
Chemical Analysis Logistics Center of America
300 Century Blvd
Wilmington, DE 19808

Number of Pages: 3

U.S.A. Information/Emergency Telephone No: 1-302-633-8000 or 1-877-424-4536

European Information Telephone No.: (7243) 602-0

European Emergency Telephone Number: 0049 (0) 6151/722440

When Calling From Outside the USA, Dial Your International Access Code for the USA, then 1, then 302-633-8000

Section 2 - Composition/Information on Ingredients

A 2.1x12.5mm HPLC Guard Cartridge containing 5 µm particle size, 80 Angstrom pore size SB-C8 - a reaction product of silica [7631-86-9] with octylsilane functional group

Chemical Families: Surface modified amorphous silica**Chemical Synonyms:** SB-C8 is also known as *StableBond®-C8* or *SB-8 silica*.**Silica gel** is also known as *precipitated silica* and *amorphous silica***Section 3 - Hazards Identification**

May cause eye irritation. Do not breathe dust.

Section 4 - First-Aid Measures

Inhalation: Symptoms of overexposure may include cough and discomfort. If large amounts are inhaled, move affected person to fresh air. If breathing is difficult give oxygen. If breathing has stopped begin resuscitation measures. Contact physician. **Skin Contact:** Wash with soap and water. **Eye Contact:** May be a mild eye irritant. Contamination of the eyes should be treated by immediate and prolonged irrigation with copious amounts of water by separating the eyelids with fingers. If redness or discomfort persist, contact a physician. **Ingestion:** This compound is not likely to be hazardous by ingestion. However, if swallowed, wash out mouth with water provided affected person is conscious. Consult a physician.

Section 5 - Fire-Fighting Measures

Extinguishing Media: Appropriate to surroundings. **Special Fire Fighting Procedures:** Wear full protective clothing and self contained positive pressure breathing apparatus certified by NIOSH when fighting chemically related fires. **Unusual Fire and Explosion Hazards:** Small amounts of flammable vapor may be produced if heated to approximately 500°F.

Section 6 - Accidental Release Measures

Wearing appropriate personal protective equipment, shovel or sweep up using a dust suppresser. Vacuum the remainder of the smaller quantities using a HEPA-type vacuum. Avoid inhaling dust. Place waste in a plastic bag or other suitable container and dispose of as residual waste. Unused material is not defined as hazardous waste by RCRA (40 CFR Part 261) and may be landfilled according to federal, state and local regulations.

Section 7 - Handling and Storage

Do not breathe dust and avoid contact with skin and eyes. Wash thoroughly after handling. Maintain good housekeeping practices. Avoid creating dust. Keep containers closed. Do not store with incompatible materials. Store in a cool, dry place.

Section 8 - Exposure Controls/Personal Protection

Ventilation: Adequate ventilation is required to protect personnel from exposure to chemical vapors or dusts exceeding PEL and to minimize fire hazards. See Section 15 for regulatory standards of exposure.

Respiratory: Use NIOSH approved respirator equipment. See Section 15.

Eyes: Safety glasses are considered minimum protection. Chemical safety goggles or face shield may be necessary depending on quantity of material and conditions of use. Emergency eye wash fountains should be available in the vicinity of any possible exposure.

Skin: Chemical-resistant protective gloves and clothing are recommended. The choice of protective gloves or clothing must be based on chemical resistance and other user requirements. Generally BUNA-N offers acceptable chemical resistance. Individuals who are acutely and specifically sensitive to this chemical may require additional protective clothing.

Section 9 - Physical and Chemical Properties

Flash Point (Method Used): **NA**

Explosion Potential: LEL (**NA**)/UEL (**NA**)

Specific Gravity (H₂O = 1): **ND**

Melting Point (Degree C): **Decomposes above approximately 250°C (500°F)**

Evaporation Rate (n-butyl acetate =1) **NA**

Boiling Point (Degree C): **ND**

Vapor Pressure (mm Hg at 25°C): **ND**

Vapor Density (Air =1): **NA**

Odor Threshold: **ND**

Octanol/Water Partition Coefficient: **NA**

Solubility in Water: Insoluble (**X**) /Soluble (**)**

Appearance and Odor: **White/off-white powder, faint odor**

Section 10 - Stability and Reactivity

Stability: Stable (**x**) / Unstable (**)**

Conditions to Avoid: **NA**

Incompatibility (Materials to Avoid): Reacts with hydrofluoric acid (HF)

Hazardous Decomposition or Byproducts: **NA**

Hazardous Polymerization: May Occur (**)** / Will Not Occur (**x**)

Section 11 - Toxicological Information

Route(s) of Entry: Inhalation? **Yes** Skin? **No** Ingestion? **Yes** May be harmful if inhaled or swallowed.

Health Hazard Acute/Chronic: This product does not contain crystalline silica (CA), which is considered hazardous by inhalation.

Carcinogenicity: NTP? **No** IARC Monographs? **No** OSHA Regulated? **No** OTHER? **No**

Medical Conditions Generally Aggravated by Exposure: Preclude from exposure to dust those persons with preexisting upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

Section 12 - Ecological Information

Persistence/Degradability: Based on chemical experience, will degrade over very long periods of time.

Biodegradability: Will not biodegrade

Bioaccumulation: **NA**

Section 13 - Disposal Considerations

Unused product is not hazardous as defined by RCRA (40 CFR Part 261). Unused material may be landfilled as a residual waste according to federal, state and local regulations.

Section 14 - Transport Information**DOT Regulations:****Shipping Name:** Non-regulated Material**RID/ADR:** NA**IATA-DGR Regulations:****Shipping Name:** Non-regulated Material**ADNR:** NA**Section 15 - Regulatory Information****Exposure Limits:** There are no established exposure limits for this product-however if dust is generated by grinding or other means the following standard would apply: *Particulate Matter Not Otherwise Classified:*

| | | | |
|--------|------------|--|--|
| (PNOC) | OSHA PEL: | 5 mg/m ³ (Respirable fraction) | 15 mg/m ³ (Total dust) |
| | ACGIH TWA: | 3 mg/m ³ (Respirable particulate) | 10 mg/m ³ (Inhalable particulate) |

SARA Reporting: Section 302: None **Section 304:** None **Section 313:** None **OSHA Labeling Requirements:** None**TSCA Inventory List:** Reaction product not on list**Section 16 - Other Information**

Unless otherwise noted, the above information pertains only for the base material and similar types of components in the sample. When no toxicity data is provided, it is prudent to handle this chemical as hazardous. Furthermore, since individual chemical hypersensitivity cannot be predicted, every chemical should be handled with due respect.

EUROPEAN INFORMATION (Silica)

CAUTION: SUBSTANCE NOT YET FULLY TESTED.

HARMFUL

R 20: Harmful by inhalation.

R 36/37: Irritating to eyes and respiratory system.

S 26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36: Wear suitable protective clothing.

S 22: Do not breathe dust.

KEY TO ABBREVIATIONS

ACGIH - American Conference of Governmental Industrial Hygienists` **ADNR** - Regulations concerning the carriage of dangerous goods on the Rhine **CAS** - Chemical Abstract Service **DOT** - US. Department of Transportation 49 Code of Federal Regulations **IARC** - International Agency for Research on Cancer **IATA-DGR** - International Air Transport Association- Dangerous Goods Regulation **LEL** - Lower Explosion Limit **NA** - Not Applicable **ND** - No Data **NIOSH** - National Institute for Occupational Safety and Health **NTP** - National Toxicology Program **OSHA** - Occupational Safety and Health Administration **PEL** - Permissible Exposure Limit **RID/ADR** - Regulations Concerning the International Carriage of Dangerous Goods by Rail/European Agreement Concerning the International Carriage of Dangerous Goods by Road **TLV** - Threshold Limit Value **TWA** - Time Weighted Average **UEL** - Upper Explosion Limit [] - Indicates CAS Number

StableBond® is a registered trademark of Agilent Technologies