

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/10/2018

Reviewed on 09/10/2018

## 1 Identification

- **Product identifier**
- **Product Name:** Bismuth Internal Standard Stock Solution, Part Number 8500-6936
- **Part Number:** 8500-6936
- **Application of the substance / the mixture**  
Reagents and Standards for Analytical Chemistry Laboratory Use  
A 100mL Solution
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA
- **Information department:** product safety department
- **Emergency telephone number:**  
Emergency Phone Number (24 hours)  
CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.
- **Precautionary statements**  
Wash thoroughly after handling.  
Wear protective gloves / eye protection / face protection.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



(Contd. on page 2)

**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

7697-37-2	nitric acid	2.0%
-----------	-------------	------

**Chemical identification of the substance/preparation**

7440-69-9	bismuth	0.001%
7732-18-5	water, distilled, conductivity or of similar purity	97.999%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**PAC-1:**

7697-37-2	nitric acid	0.16 ppm
7440-69-9	bismuth	15 mg/m <sup>3</sup>

**PAC-2:**

7697-37-2	nitric acid	24 ppm
7440-69-9	bismuth	170 mg/m <sup>3</sup>

**PAC-3:**

7697-37-2	nitric acid	92 ppm
-----------	-------------	--------

(Contd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 2)

7440-69-9 bismuth

990 mg/m<sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

**Components with limit values that require monitoring at the workplace:**

**7697-37-2 nitric acid**

PEL Long-term value: 5 mg/m<sup>3</sup>, 2 ppm

REL Short-term value: 10 mg/m<sup>3</sup>, 4 ppm

Long-term value: 5 mg/m<sup>3</sup>, 2 ppm

TLV Short-term value: 10 mg/m<sup>3</sup>, 4 ppm

Long-term value: 5.2 mg/m<sup>3</sup>, 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile Glove

Thickness: ≥0.11 mm

Breakthrough time: > 480 minutes

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 3)

**· Eye protection:**


Tightly sealed goggles

**9 Physical and chemical properties**
**· Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

**Form:** Liquid  
**Color:** Colorless

**· Odor:** Odorless

**· Odour Threshold:** Not applicable.

**· pH-value:** <1

**· Change in condition**

**Melting point/Melting range:** 0°C (32°F)  
**Boiling point/Boiling range:** 100°C (212°F)

**· Flash point:** Not applicable.

**· Flammability (solid, gaseous):** Not applicable.

**· Decomposition temperature:** Not applicable.

**· Auto igniting:** Product is not selfigniting.

**· Danger of explosion:** Product does not present an explosion hazard.

**· Explosion limits:**

**Lower:** Not applicable.  
**Upper:** Not applicable.

**· Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

**· Density** 1.0 g/mL @ 20°C

**· Relative density** Not applicable.

**· Vapor density** Not applicable.

**· Evaporation rate** Not applicable.

**· Solubility in / Miscibility with**

**Water:** Miscible

**· Partition coefficient (n-octanol/water):** Not applicable.

**· Viscosity:**

**Dynamic:** Not applicable.  
**Kinematic:** Not applicable.

**· Solvent content:**

**Water:** 98.0 %  
**VOC content:** 0.00 %

**Solids content:** 0.0 %

**· Other information** No further relevant information available.

**10 Stability and reactivity**

**· Reactivity** No further relevant information available.

**· Chemical stability**

**· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**· Possibility of hazardous reactions** No dangerous reactions known.

**· Conditions to avoid** No further relevant information available.

(Contd. on page 5)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 4)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**

**· IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

**· NTP (National Toxicology Program)**

None of the ingredients is listed.

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN3264
- **UN proper shipping name**
- **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)
- **ADR** 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)

(Contd. on page 6)



**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 5)

· <b>IMDG, IATA</b>	<b>CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION)</b>
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Corrosive substances
· <b>Danger code (Kemler):</b>	80
· <b>EMS Number:</b>	F-A,S-B
· <b>Segregation groups</b>	Acids
· <b>Stowage Category</b>	A
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION), 8, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

 · **Section 313 (Specific toxic chemical listings):**

7697-37-2 nitric acid

 · **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 6)

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Precautionary statements**

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.*

· **Department issuing SDS:** product safety department

· **Contact:**

Agilent Technologies, Inc.

800-227-9770

· **Date of preparation / last revision** 09/10/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 8)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 09/10/2018

Reviewed on 09/10/2018

**Product Name: Bismuth Internal Standard Stock Solution, Part Number 8500-6936**

(Contd. of page 7)

NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

US