

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

- English additional compounds
- Product identifier
- Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944
- Part Number: 8500-6944
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture  
Reagents and Standards for Analytical Chemistry Laboratory Use  
A 100mL Solution
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
Agilent Technologies Australia Pty Ltd  
679 Springvale Road  
Muggrave  
Victoria 3170, Australia
- Further information obtainable from: product safety department
- Emergency telephone number: CHEMTREC®: +(61) - 290372994

## 2 Hazard(s) Identification

- Classification of the substance or mixture



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.  
Eye Dam. 1 H318 Causes serious eye damage.

- Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS05

- Signal word Danger
- Hazard-determining components of labelling:  
nitric acid
- Hazard statements  
H314 Causes severe skin burns and eye damage.
- Precautionary statements  
If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER/doctor.  
Specific treatment (see on this label).  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.
- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 2)

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 1)

· **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

- **Chemical characterisation:** Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

7697-37-2	nitric acid	☠ Ox. Liq. 2, H272; ☠ Skin Corr. 1A, H314	5.0%
-----------	-------------	---	------

**CHEMICAL IDENTIFICATION OF THE SUBSTANCE/PREPARATION**

7429-91-6	Dysprosium from Didysprosium trioxide		0.001%
7439-91-0	Lanthanum from Lanthanum(III) nitrate hexahydrate	☠ Ox. Sol. 2, H272; ☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7439-94-3	Lutetium from Lutetium (III) Oxide	☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-00-8	Neodymium from Neodymium Oxide		0.001%
7440-10-0	Praseodymium from Praseodymium(III,IV) oxide	☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-19-9	Samarium from Samarium (III) oxide		0.001%
7440-20-2	Scandium from Scandium oxide		0.001%
7440-27-9	Terbium from Terbium (III,IV) oxide		0.001%
7440-29-1	Thorium from Thorium nitrate hydrate	☠ Ox. Liq. 2, H272; ☠ Acute Tox. 3, H301; ☠ STOT RE 2, H373; ☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-30-4	Thulium from Thulium oxide	☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-45-1	cerium	☠ Ox. Liq. 2, H272; ☠ Eye Dam. 1, H318	0.001%
7440-52-0	Erbium from Erbium(III) oxide	☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-53-1	Europium from Europium(III) oxide	☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.001%
7440-54-2	Gadolinium from Digadolinium trioxide		0.001%
7440-60-0	Holmium from Holmium oxide		0.001%
7440-64-4	Ytterbium from Ytterbium (III) oxide		0.001%
7440-65-5	yttrium		0.001%
7732-18-5	water, distilled, conductivity or of similar purity		94.983%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

WES	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm
	Long-term value: 5.2 mg/m <sup>3</sup> , 2 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 3)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile Glove

Thickness:  $\geq 0.11$  mm

Breakthrough time: &gt; 480 minutes

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
-------	--------

Colour:	Colourless
---------	------------

· Odour:	Odourless
----------	-----------

· Odour threshold:	Not applicable.
--------------------	-----------------

· pH-value:	<1
-------------	----

- **Change in condition**

Melting point/freezing point:	0°C (32°F)
-------------------------------	------------

Initial boiling point and boiling range:	100°C (212°F)
--	---------------

· Flash point:	Not applicable.
----------------	-----------------

· Flammability (solid, gas):	Not applicable.
------------------------------	-----------------

· Decomposition temperature:	Not applicable.
------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
------------------------------	------------------------------

· Explosive properties:	Product does not present an explosion hazard.
-------------------------	---

- **Explosion limits:**

Lower:	Not applicable.
--------	-----------------

Upper:	Not applicable.
--------	-----------------

· Vapour pressure at 20 °C:	23 hPa
-----------------------------	--------

· Density:	1.0 g/mL @ 20°C
------------	-----------------

· Relative density	Not applicable.
--------------------	-----------------

· Vapour density	Not applicable.
------------------	-----------------

· Evaporation rate	Not applicable.
--------------------	-----------------

- **Solubility in / Miscibility with water:**

Miscible

· Partition coefficient: n-octanol/water:	Not applicable.
---	-----------------

- **Viscosity:**

Dynamic:	Not applicable.
----------	-----------------

Kinematic:	Not applicable.
------------	-----------------

- **Solvent content:**

Water:	95.0 %
--------	--------

VOC (EC)	0.00 %
----------	--------

Solids content:	0.0 %
-----------------	-------

(Contd. on page 5)

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 4)

**· Other information** No further relevant information available.**10 Stability and Reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological Information**

- **Information on toxicological effects**
- **Acute toxicity**
- **Primary irritant effect:**
- **Skin corrosion/irritation** Caustic effect on skin and mucous membranes.
- **Serious eye damage/irritation** Strong caustic effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Corrosive  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

**12 Ecological Information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

-AU-  
(Contd. on page 6)

**Safety Data Sheet**  
according to WHS Regulations


Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard I, Part Number 8500-6944**

(Contd. of page 5)

**14 Transport information**

· <b>UN-Number</b> · <b>ADG, IMDG, IATA</b>	UN3264
· <b>UN proper shipping name</b> · <b>ADG</b> · <b>IMDG, IATA</b>	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION)
· <b>Transport hazard class(es)</b> · <b>ADG, IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	8 Corrosive substances. 8
· <b>Packing group</b> · <b>ADG, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Segregation groups</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Corrosive substances. 80 F-A,S-B Acids A SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	3 E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION), 8, III

**15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· <b>Australian Inventory of Chemical Substances</b>	
7697-37-2	nitric acid
7429-91-6	Dysprosium from Didysprosium trioxide
7439-91-0	Lanthanum from Lanthanum(III) nitrate hexahydrate
7439-94-3	Lutetium from Lutetium (III) Oxide
7440-00-8	Neodymium from Neodymium Oxide

(Contd. on page 7)

**Safety Data Sheet**  
according to WHS Regulations

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 6)

7440-10-0	Praseodymium from Praseodymium(III,IV) oxide	
7440-19-9	Samarium from Samarium (III) oxide	
7440-20-2	Scandium from Scandium oxide	
7440-29-1	Thorium from Thorium nitrate hydrate	
7440-30-4	Thulium from Thulium oxide	
7440-45-1	cerium	
7440-52-0	Erbium from Erbium(III) oxide	
7440-53-1	Europium from Europium(III) oxide	
7440-54-2	Gadolinium from Digadolinium trioxide	
7440-60-0	Holmium from Holmium oxide	
7440-64-4	Ytterbium from Ytterbium (III) oxide	
7440-65-5	yttrium	
7732-18-5	water, distilled, conductivity or of similar purity	
<b>Standard for the Uniform Scheduling of Medicines and Poisons</b>		
7697-37-2	nitric acid	S5, S6
7439-91-0	Lanthanum from Lanthanum(III) nitrate hexahydrate	S4

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
nitric acid
- **Hazard statements**  
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**  
If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER/doctor.  
Specific treatment (see on this label).  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.*

- **Relevant phrases**  
H272 May intensify fire; oxidiser.  
H301 Toxic if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

(Contd. on page 8)



**Safety Data Sheet**  
**according to WHS Regulations**

Printing date 11.09.2018

Revision: 11.09.2018

**Product Name: Multi-element Calibration Standard 1, Part Number 8500-6944**

(Contd. of page 7)

*H373 May cause damage to organs through prolonged or repeated exposure.*

· **Department issuing SDS:** product safety department

· **Contact:**

Agilent Technologies Australia Pty Ltd  
1800 802 402

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*ELINCS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Ox. Liq. 2: Oxidizing liquids – Category 2*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

AU