

# SAFETY DATA SHEET



Probe Sample Kit - 5 mm, Part Number 94906514

## Section 1. Identification

This product is considered an article. This Material Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

### 1.1 Product identifier

<b>Product name</b>	: Probe Sample Kit - 5 mm, Part Number 94906514	
<b>Part No. (Chemical Kit)</b>	: 94906514	
<b>Part No.</b>	: 13C S/N ASTM	96812069
	1H S/N	96812070
	19F S/N	96812082
	15N S/N	96812083
	31P S/N	96812087
	1H Lineshape	96812089
	13C S/N ASTM doped	96812091
<b>Validation date</b>	: 12/31/2015	

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

<b>Material uses</b>	: Analytical chemistry.	
	13C S/N ASTM	860 µl
	1H S/N	860 µl
	19F S/N	860 µl
	15N S/N	860 µl
	31P S/N	860 µl
	1H Lineshape	860 µl
	13C S/N ASTM doped	860 µl

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer** : Agilent Technologies, Inc.  
 5301 Stevens Creek Blvd  
 Santa Clara, CA 95051, USA  
 800-227-9770

### 1.4 Emergency telephone number

**In case of emergency** : CHEMTREC®: 1-800-424-9300

## Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

### 2.1 Classification of the substance or mixture

<b>OSHA/HCS status</b>	: 13C S/N ASTM	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
	1H S/N	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
	19F S/N	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
	15N S/N	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
	31P S/N	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

## Section 2. Hazards identification

1H Lineshape	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
13C S/N ASTM doped	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Classification of the substance or mixture

#### 13C S/N ASTM

H225	FLAMMABLE LIQUIDS - Category 2
H302	ACUTE TOXICITY (oral) - Category 4
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H340	GERM CELL MUTAGENICITY - Category 1
H350	CARCINOGENICITY - Category 1A
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, kidneys and liver) - Category 1
H304	ASPIRATION HAZARD - Category 1

#### 1H S/N

H302	ACUTE TOXICITY (oral) - Category 4
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H351	CARCINOGENICITY - Category 2
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys and liver) - Category 2

#### 19F S/N

H225	FLAMMABLE LIQUIDS - Category 2
H302	ACUTE TOXICITY (oral) - Category 4
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H340	GERM CELL MUTAGENICITY - Category 1
H350	CARCINOGENICITY - Category 1A
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system) - Category 1
H304	ASPIRATION HAZARD - Category 1

#### 15N S/N

H227	FLAMMABLE LIQUIDS - Category 4
H319	EYE IRRITATION - Category 2A
H360	TOXIC TO REPRODUCTION (Unborn child) - Category 1B

#### 31P S/N

H302	ACUTE TOXICITY (oral) - Category 4
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H351	CARCINOGENICITY - Category 2
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

## Section 2. Hazards identification

H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys and liver) - Category 2

### 1H Lineshape

H225	FLAMMABLE LIQUIDS - Category 2
H319	EYE IRRITATION - Category 2A
H351	CARCINOGENICITY - Category 2
H361	TOXIC TO REPRODUCTION (Unborn child) - Category 2
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, kidneys and liver) - Category 1

### 13C S/N ASTM doped

H225	FLAMMABLE LIQUIDS - Category 2
H302	ACUTE TOXICITY (oral) - Category 4
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H340	GERM CELL MUTAGENICITY - Category 1
H350	CARCINOGENICITY - Category 1A
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, kidneys and liver) - Category 1
H304	ASPIRATION HAZARD - Category 1

## 2.2 GHS label elements

### Hazard pictograms



### Signal word

:	13C S/N ASTM	Danger
	1H S/N	Warning
	19F S/N	Danger
	15N S/N	Danger
	31P S/N	Warning
	1H Lineshape	Danger
	13C S/N ASTM doped	Danger

### Hazard statements

:	13C S/N ASTM	GHS SYMBOL - <b>Flame</b> - <b>Exclamation mark</b> - <b>Health hazard</b> -
		H225 - Highly flammable liquid and vapor.
		H302 - Harmful if swallowed.
		H319 - Causes serious eye irritation.
		H315 - Causes skin irritation.
		H340 - May cause genetic defects.
		H350 - May cause cancer.
		H304 - May be fatal if swallowed and enters airways.
		H335 - May cause respiratory irritation.
		H336 - May cause drowsiness or dizziness.
		H372 - Causes damage to organs through prolonged or repeated exposure. (blood system, kidneys, liver)

## Section 2. Hazards identification

1H S/N	<p>GHS SYMBOL - <b>Exclamation mark - Health hazard</b> -</p> <p>H302 - Harmful if swallowed.  H319 - Causes serious eye irritation.  H315 - Causes skin irritation.  H351 - Suspected of causing cancer.  H335 - May cause respiratory irritation.  H336 - May cause drowsiness or dizziness.  H373 - May cause damage to organs through prolonged or repeated exposure. (kidneys, liver)</p>
19F S/N	<p>GHS SYMBOL - <b>Flame - Exclamation mark - Health hazard</b> -</p> <p>H225 - Highly flammable liquid and vapor.  H302 - Harmful if swallowed.  H319 - Causes serious eye irritation.  H315 - Causes skin irritation.  H340 - May cause genetic defects.  H350 - May cause cancer.  H304 - May be fatal if swallowed and enters airways.  H335 - May cause respiratory irritation.  H336 - May cause drowsiness or dizziness.  H372 - Causes damage to organs through prolonged or repeated exposure. (blood system)</p>
15N S/N	<p>H227 - Combustible liquid.  GHS SYMBOL - <b>Exclamation mark - Health hazard</b> -</p> <p>H319 - Causes serious eye irritation.  H360 - May damage the unborn child.</p>
31P S/N	<p>GHS SYMBOL - <b>Exclamation mark - Health hazard</b> -</p> <p>H302 - Harmful if swallowed.  H319 - Causes serious eye irritation.  H315 - Causes skin irritation.  H351 - Suspected of causing cancer.  H335 - May cause respiratory irritation.  H336 - May cause drowsiness or dizziness.  H373 - May cause damage to organs through prolonged or repeated exposure. (kidneys, liver)</p>
1H Lineshape	<p>GHS SYMBOL - <b>Flame - Exclamation mark - Health hazard</b> -</p> <p>H225 - Highly flammable liquid and vapor.  H319 - Causes serious eye irritation.  H361 - Suspected of damaging the unborn child.  H351 - Suspected of causing cancer.  H336 - May cause drowsiness or dizziness.  H372 - Causes damage to organs through prolonged or repeated exposure. (blood system, kidneys, liver)</p>
13C S/N ASTM doped	<p>GHS SYMBOL - <b>Flame - Exclamation mark - Health hazard</b> -</p> <p>H225 - Highly flammable liquid and vapor.  H302 - Harmful if swallowed.  H319 - Causes serious eye irritation.  H315 - Causes skin irritation.  H340 - May cause genetic defects.  H350 - May cause cancer.  H304 - May be fatal if swallowed and enters airways.</p>

## Section 2. Hazards identification

H335 - May cause respiratory irritation.  
 H336 - May cause drowsiness or dizziness.  
 H372 - Causes damage to organs through prolonged or repeated exposure. (blood system, kidneys, liver)

### Precautionary statements

#### Prevention

:  3C S/N ASTM

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P233 - Keep container tightly closed.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash hands thoroughly after handling.

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash hands thoroughly after handling.

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P233 - Keep container tightly closed.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash hands thoroughly after handling.

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions

1H S/N

19F S/N

15N S/N

## Section 2. Hazards identification

31P S/N

have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P210 - Keep away from flames and hot surfaces. - No smoking.  
 P264 - Wash hands thoroughly after handling.  
 P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.

1H Lineshape

P264 - Wash hands thoroughly after handling.  
 P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P233 - Keep container tightly closed.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.

13C S/N ASTM doped

P264 - Wash hands thoroughly after handling.  
 P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P233 - Keep container tightly closed.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash hands thoroughly after handling.

## Section 2. Hazards identification

**Response**

: 13C S/N ASTM

P314 - Get medical attention if you feel unwell.  
 P308 + P313 - IF exposed or concerned: Get medical attention.  
 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
 P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.  
 P332 + P313 - If skin irritation occurs: Get medical attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical attention.

P314 - Get medical attention if you feel unwell.  
 P308 + P313 - IF exposed or concerned: Get medical attention.  
 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
 P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth.  
 P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.  
 P332 + P313 - If skin irritation occurs: Get medical attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical attention.

P314 - Get medical attention if you feel unwell.  
 P308 + P313 - IF exposed or concerned: Get medical attention.  
 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
 P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P302 + P352 + P362+P364 - IF ON SKIN: Wash

1H S/N

19F S/N

## Section 2. Hazards identification

15N S/N	<p>with plenty of soap and water. Take off contaminated clothing and wash it before reuse.</p> <p>P332 + P313 - If skin irritation occurs: Get medical attention.</p> <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 - If eye irritation persists: Get medical attention.</p> <p>P308 + P313 - IF exposed or concerned: Get medical attention.</p> <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 - If eye irritation persists: Get medical attention.</p>
31P S/N	<p>P314 - Get medical attention if you feel unwell.</p> <p>P308 + P313 - IF exposed or concerned: Get medical attention.</p> <p>P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.</p> <p>P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth.</p> <p>P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.</p> <p>P332 + P313 - If skin irritation occurs: Get medical attention.</p> <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 - If eye irritation persists: Get medical attention.</p>
1H Lineshape	<p>P314 - Get medical attention if you feel unwell.</p> <p>P308 + P313 - IF exposed or concerned: Get medical attention.</p> <p>P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.</p> <p>P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 - If eye irritation persists: Get medical attention.</p>
13C S/N ASTM doped	<p>P314 - Get medical attention if you feel unwell.</p> <p>P308 + P313 - IF exposed or concerned: Get medical attention.</p> <p>P304 + P340 + P312 - IF INHALED: Remove</p>

## Section 2. Hazards identification

### Storage

: 13C S/N ASTM

1H S/N  
19F S/N

15N S/N

31P S/N  
1H Lineshape

13C S/N ASTM doped

### Disposal

: 13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

P332 + P313 - If skin irritation occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

P405 - Store locked up.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

P405 - Store locked up.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Section 2. Hazards identification

### Supplemental label elements

:  13C S/N ASTM  
 1H S/N  
 19F S/N  
  
 15N S/N  
 31P S/N  
 1H Lineshape  
  
 13C S/N ASTM doped

Avoid contact with skin and clothing. Wash thoroughly after handling.  
 None known.  
 Avoid contact with skin and clothing. Wash thoroughly after handling.  
 None known.  
 None known.  
 Avoid contact with skin and clothing. Wash thoroughly after handling.  
 Avoid contact with skin and clothing. Wash thoroughly after handling.

### 2.3 Other hazards

#### Hazards not otherwise classified

:  13C S/N ASTM  
 1H S/N  
 19F S/N  
  
 15N S/N  
 31P S/N  
 1H Lineshape  
  
 13C S/N ASTM doped

Prolonged or repeated contact may dry skin and cause irritation.  
 None known.  
 Prolonged or repeated contact may dry skin and cause irritation.  
 None known.  
 None known.  
 Prolonged or repeated contact may dry skin and cause irritation.  
 Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

### Substance/mixture

:  13C S/N ASTM  
 1H S/N  
 19F S/N  
 15N S/N  
 31P S/N  
 1H Lineshape  
 13C S/N ASTM doped

Mixture (encapsulated in article)  
 Mixture (encapsulated in article)

Ingredient name	%	CAS number
<input checked="" type="checkbox"/> 13C S/N ASTM (2H6)benzene 1,4-Dioxane	≥50 - ≤75 ≥25 - ≤50	1076-43-3 123-91-1
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform ethylbenzene	≥90 ≤0.3	865-49-6 100-41-4
<b>19F S/N</b> (2H6)benzene	≥90	1076-43-3
<b>15N S/N</b> Formamide di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	≥90 ≥10 - ≤25	75-12-7 2206-27-1
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	≥90	865-49-6

### Section 3. Composition/information on ingredients

<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone Trichloromethane	≥90 ≤3	666-52-4 67-66-3
<b>13C S/N ASTM doped</b> ( <sup>2</sup> H <sub>6</sub> )benzene 1,4-Dioxane	≥50 - ≤75 ≥25 - ≤50	1076-43-3 123-91-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### 4.1 Description of necessary first aid measures

<b>Eye contact</b>	: 13C S/N ASTM	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	1H S/N	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	19F S/N	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	15N S/N	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	31P S/N	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	1H Lineshape	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	13C S/N ASTM doped	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

## Section 4. First aid measures

### Inhalation

: 13C S/N ASTM

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

1H S/N

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

19F S/N

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

15N S/N

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of

## Section 4. First aid measures

31P S/N

inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

1H Lineshape

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

13C S/N ASTM doped

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Section 4. First aid measures

<b>Skin contact</b>	: 13C S/N ASTM	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	1H S/N	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	19F S/N	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	15N S/N	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	31P S/N	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	1H Lineshape	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
	13C S/N ASTM doped	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
<b>Ingestion</b>	: 13C S/N ASTM	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Section 4. First aid measures

1H S/N

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

19F S/N

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

15N S/N

31P S/N

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person.

## Section 4. First aid measures

1H Lineshape

If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

13C S/N ASTM doped

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 4.2 Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : 13C S/N ASTM  
 1H S/N  
 19F S/N  
 15N S/N  
 31P S/N  
 1H Lineshape  
 13C S/N ASTM doped

Causes serious eye irritation.  
 Causes serious eye irritation.

**Inhalation** :  13C S/N ASTM

1H S/N

Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

19F S/N

Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

15N S/N

Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

31P S/N

No known significant effects or critical hazards. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

## Section 4. First aid measures

	1H Lineshape	May cause respiratory irritation. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
	13C S/N ASTM doped	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
<b>Skin contact</b>	: 13C S/N ASTM	Causes skin irritation. Defatting to the skin.
	1H S/N	Causes skin irritation.
	19F S/N	Causes skin irritation. Defatting to the skin.
	15N S/N	No known significant effects or critical hazards.
	31P S/N	Causes skin irritation.
	1H Lineshape	Defatting to the skin. May cause skin dryness and irritation.
	13C S/N ASTM doped	Causes skin irritation. Defatting to the skin.
<b>Ingestion</b>	: 13C S/N ASTM	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
	1H S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression.
	19F S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
	15N S/N	No known significant effects or critical hazards.
	31P S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression.
	1H Lineshape	Can cause central nervous system (CNS) depression.
	13C S/N ASTM doped	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
<b><u>Over-exposure signs/symptoms</u></b>		
<b>Eye contact</b>	: 13C S/N ASTM	Adverse symptoms may include the following: pain or irritation watering redness
	1H S/N	Adverse symptoms may include the following: pain or irritation watering redness
	19F S/N	Adverse symptoms may include the following: pain or irritation watering redness
	15N S/N	Adverse symptoms may include the following: pain or irritation watering redness
	31P S/N	Adverse symptoms may include the following: pain or irritation watering redness
	1H Lineshape	Adverse symptoms may include the following: pain or irritation watering redness
	13C S/N ASTM doped	Adverse symptoms may include the following: pain or irritation watering

## Section 4. First aid measures

### Inhalation

: 13C S/N ASTM

redness

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

1H S/N

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

19F S/N

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

15N S/N

Adverse symptoms may include the following:

reduced fetal weight

increase in fetal deaths

skeletal malformations

31P S/N

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

1H Lineshape

Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

reduced fetal weight

increase in fetal deaths

skeletal malformations

13C S/N ASTM doped

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

unconsciousness

## Section 4. First aid measures

<b>Skin contact</b>	: 13C S/N ASTM	Adverse symptoms may include the following: irritation redness dryness cracking
	1H S/N	Adverse symptoms may include the following: irritation redness
	19F S/N	Adverse symptoms may include the following: irritation redness dryness cracking
	15N S/N	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	31P S/N	Adverse symptoms may include the following: irritation redness
	1H Lineshape	Adverse symptoms may include the following: irritation dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
	13C S/N ASTM doped	Adverse symptoms may include the following: irritation redness dryness cracking
<b>Ingestion</b>	: 13C S/N ASTM	Adverse symptoms may include the following: nausea or vomiting
	1H S/N	No specific data.
	19F S/N	Adverse symptoms may include the following: nausea or vomiting
	15N S/N	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	31P S/N	No specific data.
	1H Lineshape	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	13C S/N ASTM doped	Adverse symptoms may include the following: nausea or vomiting

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

<b>Notes to physician</b>	: 13C S/N ASTM	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	1H S/N	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
	19F S/N	Treat symptomatically. Contact poison treatment

## Section 4. First aid measures

specialist immediately if large quantities have been ingested or inhaled.

15N S/N  
In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

31P S/N  
In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

1H Lineshape  
In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

13C S/N ASTM doped  
Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : 13C S/N ASTM  
1H S/N  
19F S/N  
15N S/N  
31P S/N  
1H Lineshape  
13C S/N ASTM doped

No specific treatment.  
No specific treatment.

**Protection of first-aiders** : 13C S/N ASTM

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

1H S/N  
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

19F S/N  
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

15N S/N  
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

31P S/N  
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person



## Section 5. Fire-fighting measures

		burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
	31P S/N	In a fire or if heated, a pressure increase will occur and the container may burst.
	1H Lineshape	Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
	13C S/N ASTM doped	Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
<b>Hazardous thermal decomposition products</b>	: 13C S/N ASTM	Decomposition products may include the following materials: carbon dioxide carbon monoxide
	1H S/N	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
	19F S/N	Decomposition products may include the following materials: carbon dioxide carbon monoxide
	15N S/N	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides
	31P S/N	Decomposition products may include the following materials: carbon dioxide carbon monoxide phosphorus oxides halogenated compounds carbonyl halides
	1H Lineshape	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
	13C S/N ASTM doped	Decomposition products may include the following materials: carbon dioxide carbon monoxide

### 5.3 Advice for firefighters

## Section 5. Fire-fighting measures

**Special protective actions for fire-fighters** : 13C S/N ASTM

1H S/N

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

19F S/N

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

15N S/N

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

31P S/N

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

1H Lineshape

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

13C S/N ASTM doped

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : 13C S/N ASTM

1H S/N

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

19F S/N

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

15N S/N

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

31P S/N

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

1H Lineshape

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighters should wear appropriate protective

## Section 5. Fire-fighting measures

13C S/N ASTM doped

equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  
Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : 13C S/N ASTM

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

1H S/N

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

19F S/N

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

15N S/N

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

31P S/N

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6. Accidental release measures

1H Lineshape	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
13C S/N ASTM doped	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
<b>For emergency responders :</b> 13C S/N ASTM	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
1H S/N	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
19F S/N	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
15N S/N	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
31P S/N	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
1H Lineshape	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
13C S/N ASTM doped	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
<b>6.2 Environmental precautions :</b> 13C S/N ASTM	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
1H S/N	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

## Section 6. Accidental release measures

19F S/N	waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
15N S/N	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
31P S/N	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
1H Lineshape	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
13C S/N ASTM doped	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

**Methods for cleaning up** : 13C S/N ASTM

1H S/N	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
19F S/N	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
15N S/N	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
31P S/N	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an

## Section 6. Accidental release measures

1H Lineshape	<p>inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p> <p>Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p>
13C S/N ASTM doped	<p>Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p>

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

**Protective measures** : 13C S/N ASTM

1H S/N	<p>Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.</p> <p>Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.</p>
19F S/N	<p>Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only</p>

## Section 7. Handling and storage

	with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
15N S/N	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
31P S/N	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
1H Lineshape	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open

## Section 7. Handling and storage

flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

13C S/N ASTM doped

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene**

: 13C S/N ASTM

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

1H S/N

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

19F S/N

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

15N S/N

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

31P S/N

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove

## Section 7. Handling and storage

	<p>1H Lineshape</p> <p>13C S/N ASTM doped</p>	<p>contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.</p> <p>Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.</p>
<p><b>7.2 Conditions for safe storage, including any incompatibilities</b></p>	<p>: 13C S/N ASTM</p>	<p>Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.</p>
	<p>1H S/N</p>	<p>Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.</p>
	<p>19F S/N</p>	<p>Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.</p>
	<p>15N S/N</p>	<p>Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food</p>

## Section 7. Handling and storage

31P S/N	and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
1H Lineshape	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
13C S/N ASTM doped	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

#### Recommendations

: 13C S/N ASTM	Industrial applications, Professional applications.
1H S/N	Industrial applications, Professional applications.
19F S/N	Industrial applications, Professional applications.
15N S/N	Industrial applications, Professional applications.
31P S/N	Industrial applications, Professional applications.
1H Lineshape	Industrial applications, Professional applications.
13C S/N ASTM doped	Industrial applications, Professional applications.

## Section 7. Handling and storage

<b>Industrial sector specific solutions</b>	<b>13C S/N ASTM</b>	Not applicable.
	1H S/N	Not applicable.
	19F S/N	Not applicable.
	15N S/N	Not applicable.
	31P S/N	Not applicable.
	1H Lineshape	Not applicable.
	13C S/N ASTM doped	Not applicable.

## Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
<b>13C S/N ASTM</b> (2H6)benzene	<b>ACGIH TLV (United States, 3/2015).</b> <b>Absorbed through skin.</b> TWA: 0.5 ppm 8 hours. TWA: 1.6 mg/m <sup>3</sup> 8 hours. STEL: 2.5 ppm 15 minutes. STEL: 8 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1 ppm 8 hours. STEL: 5 ppm 15 minutes. <b>OSHA PEL Z2 (United States, 2/2013).</b> TWA: 10 ppm 8 hours. CEIL: 25 ppm AMP: 50 ppm 10 minutes. <b>NIOSH REL (United States, 10/2013).</b> TWA: 0.1 ppm 10 hours. STEL: 1 ppm 15 minutes. <b>OSHA PEL (United States, 2/2013).</b> TWA: 1 ppm 8 hours. STEL: 5 ppm 15 minutes.
1,4-Dioxane	<b>OSHA PEL 1989 (United States, 3/1989).</b> <b>Absorbed through skin.</b> TWA: 25 ppm 8 hours. TWA: 90 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2013).</b> CEIL: 1 ppm 30 minutes. CEIL: 3.6 mg/m <sup>3</sup> 30 minutes. <b>ACGIH TLV (United States, 3/2015).</b> <b>Absorbed through skin.</b> TWA: 20 ppm 8 hours. <b>OSHA PEL (United States, 2/2013).</b> <b>Absorbed through skin.</b> TWA: 100 ppm 8 hours. TWA: 360 mg/m <sup>3</sup> 8 hours.
<b>1H S/N</b> (2H)Chloroform	<b>ACGIH TLV (United States, 3/2015).</b> TWA: 10 ppm 8 hours. TWA: 49 mg/m <sup>3</sup> 8 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 2 ppm 8 hours.

## Section 8. Exposure controls/personal protection

ethylbenzene

TWA: 9.78 mg/m<sup>3</sup> 8 hours.  
**NIOSH REL (United States, 10/2013).**  
 STEL: 2 ppm 60 minutes.  
 STEL: 9.78 mg/m<sup>3</sup> 60 minutes.  
**OSHA PEL (United States, 2/2013).**  
 CEIL: 50 ppm  
 CEIL: 240 mg/m<sup>3</sup>  
**ACGIH TLV (United States, 3/2015).**  
 TWA: 20 ppm 8 hours.  
**OSHA PEL 1989 (United States, 3/1989).**  
 TWA: 100 ppm 8 hours.  
 TWA: 435 mg/m<sup>3</sup> 8 hours.  
 STEL: 125 ppm 15 minutes.  
 STEL: 545 mg/m<sup>3</sup> 15 minutes.  
**NIOSH REL (United States, 10/2013).**  
 TWA: 100 ppm 10 hours.  
 TWA: 435 mg/m<sup>3</sup> 10 hours.  
 STEL: 125 ppm 15 minutes.  
 STEL: 545 mg/m<sup>3</sup> 15 minutes.  
**OSHA PEL (United States, 2/2013).**  
 TWA: 100 ppm 8 hours.  
 TWA: 435 mg/m<sup>3</sup> 8 hours.

**19F S/N**  
 (2H6)benzene

**ACGIH TLV (United States, 3/2015).**  
**Absorbed through skin.**  
 TWA: 0.5 ppm 8 hours.  
 TWA: 1.6 mg/m<sup>3</sup> 8 hours.  
 STEL: 2.5 ppm 15 minutes.  
 STEL: 8 mg/m<sup>3</sup> 15 minutes.  
**OSHA PEL 1989 (United States, 3/1989).**  
 TWA: 1 ppm 8 hours.  
 STEL: 5 ppm 15 minutes.  
**OSHA PEL Z2 (United States, 2/2013).**  
 TWA: 10 ppm 8 hours.  
 CEIL: 25 ppm  
 AMP: 50 ppm 10 minutes.  
**NIOSH REL (United States, 10/2013).**  
 TWA: 0.1 ppm 10 hours.  
 STEL: 1 ppm 15 minutes.  
**OSHA PEL (United States, 2/2013).**  
 TWA: 1 ppm 8 hours.  
 STEL: 5 ppm 15 minutes.

**15N S/N**  
 Formamide

**ACGIH TLV (United States, 3/2015).**  
**Absorbed through skin.**  
 TWA: 10 ppm 8 hours.  
 TWA: 18 mg/m<sup>3</sup> 8 hours.  
**OSHA PEL 1989 (United States, 3/1989).**  
 TWA: 20 ppm 8 hours.  
 TWA: 30 mg/m<sup>3</sup> 8 hours.  
 STEL: 30 ppm 15 minutes.  
 STEL: 45 mg/m<sup>3</sup> 15 minutes.  
**NIOSH REL (United States, 10/2013).**  
**Absorbed through skin.**  
 TWA: 10 ppm 10 hours.

## Section 8. Exposure controls/personal protection

di[(<sup>2</sup>H<sub>3</sub>)Methyl] sulphoxide

**31P S/N**  
(<sup>2</sup>H)Chloroform

**1H Lineshape**  
(<sup>2</sup>H<sub>6</sub>)Acetone

Trichloromethane

**13C S/N ASTM doped**  
(<sup>2</sup>H<sub>6</sub>)benzene

TWA: 15 mg/m<sup>3</sup> 10 hours.  
**AIHA WEEL (United States, 10/2011).**  
TWA: 250 ppm 8 hours.

**ACGIH TLV (United States, 3/2015).**  
TWA: 10 ppm 8 hours.  
TWA: 49 mg/m<sup>3</sup> 8 hours.  
**OSHA PEL 1989 (United States, 3/1989).**  
TWA: 2 ppm 8 hours.  
TWA: 9.78 mg/m<sup>3</sup> 8 hours.  
**NIOSH REL (United States, 10/2013).**  
STEL: 2 ppm 60 minutes.  
STEL: 9.78 mg/m<sup>3</sup> 60 minutes.  
**OSHA PEL (United States, 2/2013).**  
CEIL: 50 ppm  
CEIL: 240 mg/m<sup>3</sup>

**ACGIH TLV (United States, 3/2015).**  
TWA: 250 ppm 8 hours.  
STEL: 500 ppm 15 minutes.  
**OSHA PEL 1989 (United States, 3/1989).**  
TWA: 750 ppm 8 hours.  
TWA: 1800 mg/m<sup>3</sup> 8 hours.  
STEL: 1000 ppm 15 minutes.  
STEL: 2400 mg/m<sup>3</sup> 15 minutes.  
**NIOSH REL (United States, 10/2013).**  
TWA: 250 ppm 10 hours.  
TWA: 590 mg/m<sup>3</sup> 10 hours.  
**OSHA PEL (United States, 2/2013).**  
TWA: 1000 ppm 8 hours.  
TWA: 2400 mg/m<sup>3</sup> 8 hours.

**ACGIH TLV (United States, 3/2015).**  
TWA: 10 ppm 8 hours.  
TWA: 49 mg/m<sup>3</sup> 8 hours.  
**OSHA PEL 1989 (United States, 3/1989).**  
TWA: 2 ppm 8 hours.  
TWA: 9.78 mg/m<sup>3</sup> 8 hours.  
**NIOSH REL (United States, 10/2013).**  
STEL: 2 ppm 60 minutes.  
STEL: 9.78 mg/m<sup>3</sup> 60 minutes.  
**OSHA PEL (United States, 2/2013).**  
CEIL: 50 ppm  
CEIL: 240 mg/m<sup>3</sup>

**ACGIH TLV (United States, 3/2015).**  
**Absorbed through skin.**  
TWA: 0.5 ppm 8 hours.  
TWA: 1.6 mg/m<sup>3</sup> 8 hours.  
STEL: 2.5 ppm 15 minutes.  
STEL: 8 mg/m<sup>3</sup> 15 minutes.  
**OSHA PEL 1989 (United States, 3/1989).**  
TWA: 1 ppm 8 hours.  
STEL: 5 ppm 15 minutes.  
**OSHA PEL Z2 (United States, 2/2013).**

## Section 8. Exposure controls/personal protection

1,4-Dioxane

TWA: 10 ppm 8 hours.  
 CEIL: 25 ppm  
 AMP: 50 ppm 10 minutes.  
**NIOSH REL (United States, 10/2013).**  
 TWA: 0.1 ppm 10 hours.  
 STEL: 1 ppm 15 minutes.  
**OSHA PEL (United States, 2/2013).**  
 TWA: 1 ppm 8 hours.  
 STEL: 5 ppm 15 minutes.  
**OSHA PEL 1989 (United States, 3/1989).**  
**Absorbed through skin.**  
 TWA: 25 ppm 8 hours.  
 TWA: 90 mg/m<sup>3</sup> 8 hours.  
**NIOSH REL (United States, 10/2013).**  
 CEIL: 1 ppm 30 minutes.  
 CEIL: 3.6 mg/m<sup>3</sup> 30 minutes.  
**ACGIH TLV (United States, 3/2015).**  
**Absorbed through skin.**  
 TWA: 20 ppm 8 hours.  
**OSHA PEL (United States, 2/2013).**  
**Absorbed through skin.**  
 TWA: 100 ppm 8 hours.  
 TWA: 360 mg/m<sup>3</sup> 8 hours.

### 8.2 Exposure controls

#### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

##### Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	: 13C S/N ASTM	Liquid.
	1H S/N	Liquid.
	19F S/N	Liquid.
	15N S/N	Liquid.
	31P S/N	Liquid.
	1H Lineshape	Liquid.
	13C S/N ASTM doped	Liquid.
<b>Color</b>	: 13C S/N ASTM	Colorless.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Colorless.
<b>Odor</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>Odor threshold</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>pH</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.

## Section 9. Physical and chemical properties

<b>Melting point</b>	: 13C S/N ASTM	6.8°C (44.2°F)
	1H S/N	-64°C (-83.2°F)
	19F S/N	5°C (41°F)
	15N S/N	Not available.
	31P S/N	-64°C (-83.2°F)
	1H Lineshape	-95°C (-139°F)
<b>Boiling point</b>	: 13C S/N ASTM doped	6.8°C (44.2°F)
	: 13C S/N ASTM	79.1°C (174.4°F)
	1H S/N	60.9°C (141.6°F)
	19F S/N	80°C (176°F)
	15N S/N	Not available.
	31P S/N	62°C (143.6°F)
<b>Flash point</b>	1H Lineshape	55.5°C (131.9°F)
	13C S/N ASTM doped	79.1°C (174.4°F)
	: 13C S/N ASTM	Closed cup: -18 to 23°C (-0.4 to 73.4°F)
	1H S/N	Not available.
	19F S/N	Closed cup: -11.11°C (12°F)
	15N S/N	Closed cup: 87.8°C (190°F)
<b>Evaporation rate</b>	31P S/N	Not available.
	1H Lineshape	Closed cup: -17°C (1.4°F)
	13C S/N ASTM doped	Closed cup: 21.1°C (70°F)
	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
<b>Flammability (solid, gas)</b>	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
	: 13C S/N ASTM	Not applicable.
	1H S/N	Not applicable.
<b>Lower and upper explosive (flammable) limits</b>	19F S/N	Not applicable.
	15N S/N	Not applicable.
	31P S/N	Not applicable.
	1H Lineshape	Not applicable.
	13C S/N ASTM doped	Not applicable.
	: 13C S/N ASTM	Lower: 1.3%
<b>Vapor pressure</b>	1H S/N	Upper: 8%
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>Vapor density</b>	: 13C S/N ASTM	22.1 kPa (166 mm Hg) [room temperature]
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	22.1 kPa (166 mm Hg) [room temperature]

## Section 9. Physical and chemical properties

	13C S/N ASTM	>1 [Air = 1]
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	2.77 [Air = 1]
<b>Relative density</b>	: 13C S/N ASTM	0.95
	1H S/N	1.5
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	0.872
	13C S/N ASTM doped	0.98
<b>Solubility</b>	: 13C S/N ASTM	Easily soluble in the following materials: cold water and hot water.
	1H S/N	Very slightly soluble in the following materials: cold water and hot water.
	19F S/N	Insoluble in the following materials: cold water and hot water.
	15N S/N	Soluble in the following materials: cold water and hot water.
	31P S/N	Very slightly soluble in the following materials: cold water and hot water.
	1H Lineshape	Easily soluble in the following materials: cold water, hot water and acetone.
	13C S/N ASTM doped	Easily soluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/water</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>Auto-ignition temperature</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>Decomposition temperature</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.
<b>Viscosity</b>	: 13C S/N ASTM	Not available.
	1H S/N	Not available.
	19F S/N	Not available.
	15N S/N	Not available.
	31P S/N	Not available.
	1H Lineshape	Not available.
	13C S/N ASTM doped	Not available.

## Section 10. Stability and reactivity

<b>10.1 Reactivity</b>	: 13C S/N ASTM 1H S/N 19F S/N 15N S/N 31P S/N 1H Lineshape 13C S/N ASTM doped	No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients. No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: 13C S/N ASTM 1H S/N 19F S/N 15N S/N 31P S/N 1H Lineshape 13C S/N ASTM doped	The product is stable. The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: 13C S/N ASTM 1H S/N 19F S/N 15N S/N 31P S/N 1H Lineshape 13C S/N ASTM doped	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: 13C S/N ASTM  1H S/N 19F S/N  15N S/N  31P S/N 1H Lineshape	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. No specific data. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. No specific data. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

## Section 10. Stability and reactivity

13C S/N ASTM doped

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

### 10.5 Incompatible materials : 13C S/N ASTM

1H S/N

Reactive or incompatible with the following materials:

oxidizing materials

May react or be incompatible with oxidizing materials.

19F S/N

Reactive or incompatible with the following materials:

oxidizing materials

15N S/N

Reactive or incompatible with the following materials:

oxidizing materials

31P S/N

May react or be incompatible with oxidizing materials.

1H Lineshape

Reactive or incompatible with the following materials:

oxidizing materials

13C S/N ASTM doped

Reactive or incompatible with the following materials:

oxidizing materials

### 10.6 Hazardous decomposition products : 13C S/N ASTM

1H S/N

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

19F S/N

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

15N S/N

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

31P S/N

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

1H Lineshape

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

13C S/N ASTM doped

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### [11.1 Information on toxicological effects](#)

#### [Acute toxicity](#)

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
<b>13C S/N ASTM</b> (2H6)benzene 1,4-Dioxane	LD50 Oral	Rat	930 mg/kg	-
	LD50 Oral	Rat	4200 mg/kg	-
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform  ethylbenzene	LC50 Inhalation Vapor	Rat	47702 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Oral	Rat	300 mg/kg	-
	LC50 Inhalation Vapor	Rat	17200 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	4000 ppm	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
<b>19F S/N</b> (2H6)benzene	LD50 Oral	Rat	930 mg/kg	-
<b>15N S/N</b> Formamide  di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	LD50 Dermal	Rabbit	17 g/kg	-
	LD50 Oral	Rat	4000 mg/kg	-
	LD50 Dermal	Rat	40000 mg/kg	-
	LD50 Oral	Rat	14500 mg/kg	-
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	LC50 Inhalation Vapor	Rat	47702 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Oral	Rat	300 mg/kg	-
<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone Trichloromethane	LD50 Oral	Rat	5800 mg/kg	-
	LC50 Inhalation Vapor	Rat	47702 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Oral	Rat	300 mg/kg	-
<b>13C S/N ASTM doped</b> (2H6)benzene 1,4-Dioxane	LD50 Oral	Rat	930 mg/kg	-
	LD50 Oral	Rat	4200 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<b>13C S/N ASTM</b> (2H6)benzene    1,4-Dioxane	Eyes - Moderate irritant	Rabbit	-	88 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	Skin - Mild irritant	Rabbit	-	515 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

## Section 11. Toxicological information

	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
<b>19F S/N</b> (2H6)benzene	Eyes - Moderate irritant	Rabbit	-	88 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
<b>15N S/N</b> Formamide	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	100 milligrams	-
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone	Eyes - Mild irritant	Rabbit	-	10 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	395 milligrams	-
Trichloromethane	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
<b>13C S/N ASTM doped</b> (2H6)benzene	Eyes - Moderate irritant	Rabbit	-	88 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
1,4-Dioxane	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-

## Section 11. Toxicological information

	Skin - Mild irritant	Rabbit	-	milligrams 515 milligrams	-
--	----------------------	--------	---	---------------------------------	---

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
<b>13C S/N ASTM</b> (2H6)benzene 1,4-Dioxane	+ -	1 2B	Known to be a human carcinogen. Reasonably anticipated to be a human carcinogen.
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform ethylbenzene	- -	2B 2B	Reasonably anticipated to be a human carcinogen. -
<b>19F S/N</b> (2H6)benzene	+	1	Known to be a human carcinogen.
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	-	2B	Reasonably anticipated to be a human carcinogen.
<b>1H Lineshape</b> Trichloromethane	-	2B	Reasonably anticipated to be a human carcinogen.
<b>13C S/N ASTM doped</b> (2H6)benzene 1,4-Dioxane	+ -	1 2B	Known to be a human carcinogen. Reasonably anticipated to be a human carcinogen.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
<b>13C S/N ASTM</b> (2H6)benzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
1,4-Dioxane	Category 3	Not applicable.	Respiratory tract irritation
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and

## Section 11. Toxicological information

<b>19F S/N</b> (2H6)benzene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and Narcotic effects
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone Trichloromethane	Category 3 Category 3	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation and Narcotic effects
<b>13C S/N ASTM doped</b> (2H6)benzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
1,4-Dioxane	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
<b>13C S/N ASTM</b> (2H6)benzene	Category 1	Oral Inhalation	blood system blood system
1,4-Dioxane	Category 1	Oral	kidneys and liver
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	Category 2	Not determined	kidneys and liver
<b>19F S/N</b> (2H6)benzene	Category 1	Oral Inhalation	blood system blood system
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	Category 2	Not determined	kidneys and liver
<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone Trichloromethane	Category 2 Category 1	Not determined Not determined	blood system kidneys and liver
<b>13C S/N ASTM doped</b> (2H6)benzene	Category 1	Oral Inhalation	blood system blood system
1,4-Dioxane	Category 1	Oral	kidneys and liver

### Aspiration hazard

## Section 11. Toxicological information

Name	Result
<b>13C S/N ASTM</b> 13C S/N ASTM (2H6)benzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
<b>1H S/N</b> (2H)Chloroform ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
<b>19F S/N</b> 19F S/N (2H6)benzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
<b>31P S/N</b> (2H)Chloroform	ASPIRATION HAZARD - Category 1
<b>13C S/N ASTM doped</b> 13C S/N ASTM doped (2H6)benzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure**

- : **13C S/N ASTM** Routes of entry anticipated: Oral, Dermal, Inhalation.
- 1H S/N Routes of entry anticipated: Oral, Dermal, Inhalation.
- 19F S/N Routes of entry anticipated: Oral, Dermal, Inhalation.
- 15N S/N Routes of entry anticipated: Oral, Dermal, Inhalation.
- 31P S/N Routes of entry anticipated: Oral, Dermal, Inhalation.
- 1H Lineshape Routes of entry anticipated: Oral, Dermal, Inhalation.
- 13C S/N ASTM doped Routes of entry anticipated: Oral, Dermal, Inhalation.

**Potential acute health effects**

**Eye contact**

- : 13C S/N ASTM Causes serious eye irritation.
- 1H S/N Causes serious eye irritation.
- 19F S/N Causes serious eye irritation.
- 15N S/N Causes serious eye irritation.
- 31P S/N Causes serious eye irritation.
- 1H Lineshape Causes serious eye irritation.
- 13C S/N ASTM doped Causes serious eye irritation.

**Inhalation**

- : **13C S/N ASTM** Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- 1H S/N Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- 19F S/N Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- 15N S/N No known significant effects or critical hazards.
- 31P S/N Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- 1H Lineshape Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

## Section 11. Toxicological information

	13C S/N ASTM doped	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
<b>Skin contact</b>	: 13C S/N ASTM	Causes skin irritation. Defatting to the skin.
	1H S/N	Causes skin irritation.
	19F S/N	Causes skin irritation. Defatting to the skin.
	15N S/N	No known significant effects or critical hazards.
	31P S/N	Causes skin irritation.
	1H Lineshape	Defatting to the skin. May cause skin dryness and irritation.
<b>Ingestion</b>	13C S/N ASTM doped	Causes skin irritation. Defatting to the skin.
	: <input checked="" type="checkbox"/> 13C S/N ASTM	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
	1H S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression.
	19F S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
	15N S/N	No known significant effects or critical hazards.
	31P S/N	Harmful if swallowed. Can cause central nervous system (CNS) depression.
	1H Lineshape	Can cause central nervous system (CNS) depression.
	13C S/N ASTM doped	Harmful if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: 13C S/N ASTM	Adverse symptoms may include the following: pain or irritation watering redness
	1H S/N	Adverse symptoms may include the following: pain or irritation watering redness
	19F S/N	Adverse symptoms may include the following: pain or irritation watering redness
	15N S/N	Adverse symptoms may include the following: pain or irritation watering redness
	31P S/N	Adverse symptoms may include the following: pain or irritation watering redness
	1H Lineshape	Adverse symptoms may include the following: pain or irritation watering redness
	13C S/N ASTM doped	Adverse symptoms may include the following: pain or irritation watering redness

## Section 11. Toxicological information

<b>Inhalation</b>	:  13C S/N ASTM	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
	1H S/N	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
	19F S/N	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
	15N S/N	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	31P S/N	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
	1H Lineshape	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
	13C S/N ASTM doped	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness

## Section 11. Toxicological information

<b>Skin contact</b>	: 13C S/N ASTM	Adverse symptoms may include the following: irritation redness dryness cracking
	1H S/N	Adverse symptoms may include the following: irritation redness
	19F S/N	Adverse symptoms may include the following: irritation redness dryness cracking
	15N S/N	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	31P S/N	Adverse symptoms may include the following: irritation redness
	1H Lineshape	Adverse symptoms may include the following: irritation dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
	13C S/N ASTM doped	Adverse symptoms may include the following: irritation redness dryness cracking
<b>Ingestion</b>	: 13C S/N ASTM	Adverse symptoms may include the following: nausea or vomiting
	1H S/N	No specific data.
	19F S/N	Adverse symptoms may include the following: nausea or vomiting
	15N S/N	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	31P S/N	No specific data.
	1H Lineshape	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
	13C S/N ASTM doped	Adverse symptoms may include the following: nausea or vomiting

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

## Section 11. Toxicological information

**Potential delayed effects** : Not available.

### Potential chronic health effects

**General** :  13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

May cause damage to organs through prolonged or repeated exposure.

Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

No known significant effects or critical hazards.

May cause damage to organs through prolonged or repeated exposure.

Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : 13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

May cause cancer. Risk of cancer depends on duration and level of exposure.

Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

May cause cancer. Risk of cancer depends on duration and level of exposure.

No known significant effects or critical hazards.

Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : 13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

May cause genetic defects.

No known significant effects or critical hazards.

May cause genetic defects.

No known significant effects or critical hazards.

No known significant effects or critical hazards.

No known significant effects or critical hazards.

May cause genetic defects.

**Teratogenicity** :  13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

No known significant effects or critical hazards.

No known significant effects or critical hazards.

No known significant effects or critical hazards.

May damage the unborn child.

No known significant effects or critical hazards.

Suspected of damaging the unborn child.

No known significant effects or critical hazards.

**Developmental effects** : 13C S/N ASTM

1H S/N

19F S/N

15N S/N

31P S/N

1H Lineshape

13C S/N ASTM doped

No known significant effects or critical hazards.

## Section 11. Toxicological information

<b>Fertility effects</b>	<b>:</b> 13C S/N ASTM	No known significant effects or critical hazards.
	1H S/N	No known significant effects or critical hazards.
	19F S/N	No known significant effects or critical hazards.
	15N S/N	No known significant effects or critical hazards.
	31P S/N	No known significant effects or critical hazards.
	1H Lineshape	No known significant effects or critical hazards.
	13C S/N ASTM doped	No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
<b>13C S/N ASTM</b> Oral	1356.8 mg/kg
<b>1H S/N</b> Oral	500.6 mg/kg
<b>19F S/N</b> Oral	930.5 mg/kg
<b>15N S/N</b> Oral	4444.4 mg/kg
<b>31P S/N</b> Oral	504.6 mg/kg
<b>1H Lineshape</b> Oral Inhalation (vapors)	50000 mg/kg 300 mg/l
<b>13C S/N ASTM doped</b> Oral	1360.7 mg/kg

## Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
<b>13C S/N ASTM</b> (2H6)benzene	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9230 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Chronic NOEC 98 mg/l Fresh water Chronic NOEC 1.5 to 5.4 ul/L Marine water	Daphnia - Daphnia magna Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	21 days 4 weeks
1,4-Dioxane	Acute LC50 6700000 µg/l Marine water	Fish - Menidia beryllina	96 hours
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	Acute EC50 13.3 mg/l Fresh water	Algae - Chlamydomonas	72 hours

## Section 12. Ecological information

ethylbenzene	Acute EC50 2.803 mg/l Fresh water	reinhardtii - Exponential growth phase	
	Acute LC50 29000 µg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 13300 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Chronic EC10 3.61 mg/l Fresh water	Fish - Lepomis macrochirus	96 hours
		Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
		Daphnia - Daphnia magna	21 days
19F S/N (2H6)benzene	Chronic NOEC 1.8 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 3600 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 6530 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2970 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 4200 µg/l Fresh water		
15N S/N di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9230 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
31P S/N ( <sup>2</sup> H)Chloroform	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks
	Acute LC50 25000 ppm Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 34000000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 100 ul/L Marine water	Algae - Ulva lactuca	72 hours
	Acute EC50 13.3 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Acute EC50 2.803 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
1H Lineshape ( <sup>2</sup> H <sub>6</sub> )Acetone	Acute LC50 29000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 13300 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Chronic EC10 3.61 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Chronic NOEC 1.8 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 20.565 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
Acute LC50 10000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours	
Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours	
Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days	
Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna -	21 days	

## Section 12. Ecological information

Trichloromethane	Chronic NOEC 5 µg/l Marine water	Neonate Fish - Gasterosteus aculeatus - Larvae	42 days
	Acute EC50 13.3 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
<b>13C S/N ASTM doped</b> (2H6)benzene	Acute EC50 2.803 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 29 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 13.3 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Chronic EC10 3.61 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Chronic NOEC 1.8 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9230 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
1,4-Dioxane	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks
	Acute LC50 6700000 µg/l Marine water	Fish - Menidia beryllina	96 hours

### 12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<b>1H S/N</b> ethylbenzene	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<b>13C S/N ASTM</b> (2H6)benzene	2.13	11	low
1,4-Dioxane	-0.42	0.3 to 0.7	low
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	1.97	690	high
ethylbenzene	3.6	-	low
<b>19F S/N</b> (2H6)benzene	2.13	11	low
<b>15N S/N</b> Formamide	-0.82	-	low
di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	-1.35	3.16	low
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	1.97	690	high
<b>1H Lineshape</b>			

## Section 12. Ecological information

( <sup>2</sup> H <sub>6</sub> )Acetone	-0.23	-	low
Trichloromethane	1.97	690	high
<b>13C S/N ASTM doped</b>			
( <sup>2</sup> H <sub>6</sub> )benzene	2.13	11	low
1,4-Dioxane	-0.42	0.3 to 0.7	low

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

12.5 Other adverse effects :  No known significant effects or critical hazards.

## Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
<input checked="" type="checkbox"/> <b>13C S/N ASTM</b> 1,4-Dioxane; 1,4-Diethyleneoxide	123-91-1	Listed	U108
<b>1H S/N</b> Chloroform; Methane, trichloro-	865-49-6	Listed	U044
<b>31P S/N</b> Chloroform; Methane, trichloro-	865-49-6	Listed	U044
<b>1H Lineshape</b> Acetone (I); 2-Propanone (I) Chloroform; Methane, trichloro-	666-52-4 67-66-3	Listed Listed	U002 U044
<b>13C S/N ASTM doped</b> 1,4-Dioxane; 1,4-Diethyleneoxide	123-91-1	Listed	U108

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

## Section 13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

### Regulatory information

**Additional information** : **Remarks**  
De minimis quantities

**DOT / IMDG / IATA** : Not regulated.

## Section 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**U.S. Federal regulations** : **TSCA 8(a) PAIR**: Formamide  
 **United States inventory (TSCA 8b)**: Not determined.  
 **Clean Water Act (CWA) 307**: Chromium(III) 4-oxopent-2-ene-2-olate; Trichloromethane; (<sup>2</sup>H)Chloroform; ethylbenzene  
 **Clean Water Act (CWA) 311**: Trichloromethane; (<sup>2</sup>H)Chloroform; ethylbenzene

**Clean Air Act (CAA) 112 regulated toxic substances**: (<sup>2</sup>H)Chloroform

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Listed

### SARA 302/304

#### Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
<input checked="" type="checkbox"/> <b>1H S/N</b> ( <sup>2</sup> H)Chloroform	≥90	Yes.	-	-	-	-
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	≥90	Yes.	-	-	-	-
<b>1H Lineshape</b> Trichloromethane	≤3	Yes.	10000	803.8	10	0.8

**SARA 304 RQ** :  1000 lbs / 3178 kg

### SARA 311/312

## Section 15. Regulatory information

**Classification** : Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
<b>13C S/N ASTM</b> (2H6)benzene 1,4-Dioxane	≥50 - ≤75 ≥25 - ≤50	Yes. Yes.	No. No.	No. No.	Yes. Yes.	Yes. Yes.
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform ethylbenzene	≥90 ≤0.3	No. Yes.	No. No.	No. No.	Yes. Yes.	Yes. Yes.
<b>19F S/N</b> (2H6)benzene	≥90	Yes.	No.	No.	Yes.	Yes.
<b>15N S/N</b> Formamide di[( <sup>2</sup> H <sub>3</sub> )Methyl] sulphoxide	≥90 ≥10 - ≤25	No. Yes.	No. No.	No. No.	Yes. Yes.	Yes. No.
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	≥90	No.	No.	No.	Yes.	Yes.
<b>1H Lineshape</b> ( <sup>2</sup> H <sub>6</sub> )Acetone Trichloromethane	≥90 ≤3	Yes. No.	No. No.	No. No.	Yes. Yes.	Yes. Yes.
<b>13C S/N ASTM doped</b> (2H6)benzene 1,4-Dioxane	≥50 - ≤75 ≥25 - ≤50	Yes. Yes.	No. No.	No. No.	Yes. Yes.	Yes. Yes.

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	<b>13C S/N ASTM</b> (2H6)benzene 1,4-Dioxane	1076-43-3 123-91-1	≥50 - ≤75 ≥25 - ≤50
	<b>1H S/N</b> ( <sup>2</sup> H)Chloroform ethylbenzene	865-49-6 100-41-4	≥90 ≤0.3
	<b>19F S/N</b> (2H6)benzene	1076-43-3	≥90
	<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	865-49-6	≥90
	<b>1H Lineshape</b> Trichloromethane	67-66-3	≤3
	<b>13C S/N ASTM doped</b> (2H6)benzene 1,4-Dioxane	1076-43-3 123-91-1	≥50 - ≤75 ≥25 - ≤50

## Section 15. Regulatory information

<b>Supplier notification</b>	<b>13C S/N ASTM</b> (2H6)benzene 1,4-Dioxane	1076-43-3 123-91-1	≥50 - ≤75 ≥25 - ≤50
	<b>1H S/N</b> ( <sup>2</sup> H)Chloroform ethylbenzene	865-49-6 100-41-4	≥90 ≤0.3
	<b>19F S/N</b> (2H6)benzene	1076-43-3	≥90
	<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	865-49-6	≥90
	<b>1H Lineshape</b> Trichloromethane	67-66-3	≤3
	<b>13C S/N ASTM doped</b> (2H6)benzene 1,4-Dioxane	1076-43-3 123-91-1	≥50 - ≤75 ≥25 - ≤50

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

#### Massachusetts

: The following components are listed: BENZENE; 1,4-DIOXANE; ACETONE; CHLOROFORM; FORMAMIDE

#### New York

: The following components are listed: Benzene; 1,4-Dioxane; Acetone; 2-Propanone; Chloroform; Methane, trichloro-; Chloroform; Methane, trichloro-

#### New Jersey

: The following components are listed: BENZENE; 1,4-DIOXANE; 1,4-DIETHYLENE DIOXIDE; ACETONE; 2-PROPANONE; CHLOROFORM; METHANE, TRICHLORO-; CHLOROFORM; METHANE, TRICHLORO-; FORMAMIDE; DIMETHYL SULFOXIDE; METHANE, SULFINYLBIS-

#### Pennsylvania

: The following components are listed: BENZENE; 1,4-DIOXANE; 2-PROPANONE; METHANE, TRICHLORO-; METHANE, TRICHLORO-; FORMAMIDE; di[(<sup>2</sup>H<sub>3</sub>)Methyl] sulphoxide

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
<b>13C S/N ASTM</b> (2H6)benzene	Yes.	Yes.	6.4 µg/day (ingestion) 13 µg/day (inhalation)	24 µg/day (ingestion) 49 µg/day (inhalation)
1,4-Dioxane	Yes.	No.	Yes.	No.
<b>1H S/N</b> ( <sup>2</sup> H)Chloroform	Yes.	Yes.	20 µg/day (ingestion) 40 µg/day (inhalation)	No.
ethylbenzene	Yes.	No.	41 µg/day (ingestion) 54 µg/day (inhalation)	No.

## Section 15. Regulatory information

<b>19F S/N</b> (2H6)benzene	Yes.	Yes.	6.4 µg/day (ingestion) 13 µg/day (inhalation)	24 µg/day (ingestion) 49 µg/day (inhalation)
<b>31P S/N</b> ( <sup>2</sup> H)Chloroform	Yes.	Yes.	20 µg/day (ingestion) 40 µg/day (inhalation)	No.
<b>1H Lineshape</b> Trichloromethane	Yes.	Yes.	20 µg/day (ingestion) 40 µg/day (inhalation)	No.
<b>13C S/N ASTM doped</b> (2H6)benzene	Yes.	Yes.	6.4 µg/day (ingestion) 13 µg/day (inhalation)	24 µg/day (ingestion) 49 µg/day (inhalation)
1,4-Dioxane	Yes.	No.	Yes.	No.

**Canada inventory** :  Not determined.

### International regulations

#### **International lists**

- Australia inventory (AICS)**: Not determined.
- China inventory (IECSC)**: Not determined.
- Japan inventory (ENCS)**: All components are listed or exempted.
- Japan inventory (ISHL)**: Not determined.
- Korea inventory**: Not determined.
- Malaysia Inventory (EHS Register)**: Not determined.
- New Zealand Inventory of Chemicals (NZIoC)**: All components are listed or exempted.
- Philippines inventory (PICCS)**: Not determined.
- Taiwan Chemical Substances Inventory (TCSI)**: Not determined.
- Turkey inventory**: Not determined.

**Chemical Weapons** : Not listed

#### **Convention List Schedule I Chemicals**

**Chemical Weapons** : Not listed

#### **Convention List Schedule II Chemicals**

**Chemical Weapons** : Not listed

#### **Convention List Schedule III Chemicals**

## Section 16. Other information

### History

**Date of issue** : 12/31/2015

**Date of previous issue** : 10/31/2013.

**Version** : 3

Indicates information that has changed from previously issued version.

### Notice to reader

## Section 16. Other information

**Disclaimer:** The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.