

Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

### 1 Identification

· Product identifier

· Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

· Part number: CLP-102-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department: Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

## 2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS06 Skull and crossbones

Acute Toxicity (Inhalation) - Category 3

H331 Toxic if inhaled.



GHS08 Health hazard

Germ Cell Mutagenicity - Category 1B

Carcinogenicity - Category 1A

Reproductive Toxicity - Category 2

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn

child.

Specific Target Organ Toxicity - Single Exposure -

Category 1

H370 Causes damage to the central nervous system and

the visual organs.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: methanol

(Contd. on page 2)



Printing date 07/04/2024 Reviewed on 07/04/2024 Version Number 5

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 1)

benzene

toluene

trichloroethylene

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H331 Toxic if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

#### · Precautionary statements

P101	TC 1:1	_ 1:	: 1 - 1	1			1-11 -	411
P101	If medical	advice	is needed,	nave	product	container	or label a	a nana.

P102 Keep out of reach of children.

P103 Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray. P260

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground and bond container and receiving equipment.

Use non-sparking tools. P242

Take actions to prevent static discharges. P243

Wash thoroughly after handling. P264

P270 Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. P271

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

Store locked up. P405

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = \*1Fire = 3



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 2)

## 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

U	· Dangerous components:		
67-56-1	methanol	80-100% w/w *	
71-43-2	benzene	0.1-1% w/w *	
75-35-4	1,1-dichloroethylene	0.1-1% w/w *	
79-01-6	trichloroethylene	0.1-1% w/w *	
108-88-3	toluene	0.1-1% w/w *	

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.

## 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **6 Accidental release measures**

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 3)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

## · Components with limit values that require monitoring at the workplace:

#### **67-56-1** methanol

EL STEL: 250 ppm TWA: 200 ppm

Skin

EV STEL: 325 mg/m³, 250 ppm TWA: 260 mg/m³, 200 ppm Skin

#### 71-43-2 benzene

EL STEL: 2.5 ppm TWA: 0.5 ppm

Skin; ACGIH A1; IARC 1

EV STEL: 2.5 ppm TWA: 0.5 ppm

Skin

(Contd. on page 5)



Printing date 07/04/2024 Reviewed on 07/04/2024 Version Number 5

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

	(Contd. of page 4)
75-3	35-4 1,1-dichloroethylene
EL	TWA: 1 ppm IARC 2B
EV	STEL: 80 mg/m³, 20 ppm TWA: 4 mg/m³, 1 ppm
79-0	01-6 trichloroethylene
EL	STEL: 25 ppm TWA: 10 ppm ACGIH A2, IARC 1
EV	STEL: 25 ppm TWA: 10 ppm
108	-88-3 toluene
EL	TWA: 20 ppm R
	TWA: 20 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

## **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

### · Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

### · Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

### · Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 5)

Information on basic physical and o	chemical properties	
General Information		
Appearance:		
Form:	Fluid	
Color:	Colorless	
Odor: Odor threshold:	Alcohol-like Not determined.	
pH-value:	Not determined.	
<u>-</u>	Not determined.	
Change in condition Melting point/Melting range:	-98 °C	
Boiling point/Boiling range:	64 °C	
Flash point:	9 °C	
Flammability (solid, gaseous):	Highly flammable.	
Auto igniting:	455 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
Explosion limits:		
Lower:	5.5 Vol %	
Upper:	44 Vol %	
Vapor pressure at 20 °C:	100 hPa	
Density at 20 °C:	0.80485 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water): Not determined.		
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	99.4 %	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 6)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	v			
.]	· LD/LC50 values that are relevant for classification:			
1	ATE (Acute Toxicity Estimate)			
(	Oral	LD50	63,271 mg/kg (rat)	
]	Dermal	LD50	15,185 mg/kg (mouse)	
]	Inhalative	LC50/4 h	3.05 mg/L	
=				
(	67-56-1 m	ethanol		
(	Oral	LD50	5,628 mg/kg (rat)	
]	Dermal	LD50	15,800 mg/kg (rabbit)	
1	71-43-2 benzene			
(	Oral	LD50	3 340 mg/kg (rat)	

Oral	LD50	3,340 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
		>8,260 mg/kg (rabbit)
Inhalative		9,980 mg/L (mouse)

75-35-4 1,1-dichloroethylene

		200 mg/kg (rat)
Inhalative	LC50/4 h	6,350 mg/L (mouse)

#### 79-01-6 trichloroethylene

108-88-3 toluene		
Dermal	LD50	8,450 mg/kg (mouse)
		4,290 mg/kg (rat)
Oral	LD50	2,402 mg/kg (mouse)

Oral	LD50	5,580 mg/kg (rat)
	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse)
		28.1 mg/L (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

The product can cause inheritable damage.

(Contd. on page 8)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 7)

· Carcinogenic categories

· IARC (Iı	nternational Agency for Research on Cancer)	
71-43-2	benzene	1
75-35-4	1,1-dichloroethylene	2B
79-01-6	trichloroethylene	1
108-88-3	toluene	3
· NTP (Na	tional Toxicology Program)	
71-43-2	benzene	K
79-01-6	trichloroethylene	K

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 4 71	•		r , •
14	ransnor	m	formation

· Not Regulated, De minimis Quantities	-
· UN-Number · DOT/TDG, ADR, IMDG, IATA	UN1230
· UN proper shipping name · DOT/TDG	Methanol
· ADR	1230 Methanol

(Contd. on page 9)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 8)

· IMDG, IATA **METHANOL** 

· Transport hazard class(es)

· DOT/TDG (Transport dangerous goods):





3 Flammable liquids · Class

·Label 3, 6.1

 $\cdot$  ADR





· Class 3 Flammable liquids

·Label 3+6.1

· IMDG





3 Flammable liquids · Class

·Label 3/6.1

 $\cdot$  IATA





3 Flammable liquids · Class ·Label

3(6.1)

· Packing group

· DOT/TDG, ADR, IMDG, IATA Π

· Environmental hazards: Not applicable.

Warning: Flammable liquids · Special precautions for user

· Hazard identification number (Kemler code): 336 F-E,S-D · EMS Number:

· Segregation groups (SGG10) Liquid halogenated hydrocarbons

· Stowage Category

SW2 Clear of living quarters. · Stowage Code

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 10)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 9)

· Transport/Additional information:

· DOT/TDG

• Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L

· ADR

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1230 METHANOL, 3 (6.1), II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

71-43-2 benzene

· Canadian Ingredient Disclosure list (limit 1%)

All ingredients are listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

(Contd. on page 11)



Printing date 07/04/2024 Version Number 5 Reviewed on 07/04/2024

Trade name: Volatiles Matrix Spiking Standard (1X1 mL)

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: pdl-acg-regulatory-cq@agilent.com
- · Date of the latest revision of the safety data sheet 07/04/2024 / 4
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

\* \* Data compared to the previous version altered.

CA ·