

Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

1 Identification

· Product identifier

· Trade name: Volatiles System Performance Check Standard (1X1 mL)

· Part number: CLP-120-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:
 Agilent Technologies, Inc.
 5301 Stevens Creek Blvd.
 Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds_author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS06 Skull and crossbones

Acute Toxicity (Inhalation) - Category 3

H331 Toxic if inhaled.



GHS08 Health hazard

Carcinogenicity - Category 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Single Exposure - Category 1

H370 Causes damage to the central nervous system and

the visual organs.



Acute Toxicity (Dermal) - Category 4

H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS06

GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 07/04/2024 Reviewed on 07/04/2024 Version Number 6

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 1)

· Hazard-determining components of labeling:

methanol

1,1,2,2-tetrachloroethane

chloromethane

bromoform

· Hazard statements

H225 Highly flammable liquid and vapour.

H312 Harmful in contact with skin.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H370 Causes damage to the central nervous system and the visual organs.

· Precautionary statements

P101 If med	dical advice is needed,	have product co	ontainer or labe	l at hand.
-------------	-------------------------	-----------------	------------------	------------

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

Do not breathe dust/fume/gas/mist/vapours/spray. P260

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

Take actions to prevent static discharges. P243

Wash thoroughly after handling. P264

Do not eat, drink or smoke when using this product. P270 P271 Use only outdoors or in a well-ventilated area. Obtain special instructions before use. P201

Do not handle until all safety precautions have been read and understood. P202

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

Specific measures (see on this label). P322

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell. P363 Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention. P308+P313 In case of fire: Use CO2, powder or water spray to extinguish. P370+P378

P405 Store locked up.

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P403+P235 Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)





Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 2)

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Danger	· Dangerous components:		
67-56-1	methanol	80-100% w/w *	
74-87-3	chloromethane	0.1-1% w/w *	
75-25-2	bromoform	0.1-1% w/w *	
79-34-5	1,1,2,2-tetrachloroethane	0.1-1% w/w *	

^{*} Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 3)

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- $\cdot \ Further \ information \ about \ storage \ conditions:$

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-56-1 methanol

EL STEL: 250 ppm TWA: 200 ppm

Skin

EV STEL: 325 mg/m³, 250 ppm TWA: 260 mg/m³, 200 ppm

Skin

74-87-3 chloromethane

EL STEL: 100 ppm TWA: 50 ppm Skin: R

(Contd. on page 5)



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

EV	STEL: 205 mg/m³, 100 ppm	TWA: 103 mg/m³, 50 ppm				
EL	TWA: 0.5 ppm	EV	TWA: 5 mg/m³, 0.5 ppm	Skin		
79-34-5 1,1,2,2-tetrachloroethane	EL	TWA: 1 ppm	Skin, IARC 2B	EV	TWA: 7 mg/m³, 1 ppm	Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

Eye protection:



Tightly sealed goggles

CΔ



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 5)

9 Physical and chemical properties		
· Information on basic physical and o	chemical properties	
· General Information	• •	
· Appearance:		
Form:	Fluid	
Color:	Colorless	
· Odor:	Alcohol-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-98 °C	
Boiling point/Boiling range:	64.7 °C	
· Flash point:	9 °C	
· Flammability (solid, gaseous):	Highly flammable.	
· Auto igniting:	455 °C	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
Lower:	5.5 Vol %	
Upper:	44 Vol %	
· Vapor pressure at 20 °C:	100 hPa	
· Density at 20 °C:	0.80928 g/cm ³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	99.0 %	
Solids content:	0.3 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.



Printing date 07/04/2024 Reviewed on 07/04/2024 Version Number 6

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 6)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects

· Acute toxi	· Acute toxicity:		
· LD/LC50	· LD/LC50 values that are relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	79,114 mg/kg (rat)	
Dermal	LD50	1,978 mg/kg	
Inhalative	LC50/4 h	2.98 mg/L	
67-56-1 m	67-56-1 methanol		
Oral	LD50	5,628 mg/kg (rat)	
Dermal	LD50	15,800 mg/kg (rabbit)	
74-87-3 ch	74-87-3 chloromethane		
Oral	LD50	1,800 mg/kg (rat)	
Inhalative	LC50/4 h	>21,800 mg/L (rat)	
75-25-2 bi	75-25-2 bromoform		
Oral	LD50	933 mg/kg (rat)	
79-34-5 1,	79-34-5 1,1,2,2-tetrachloroethane		

- · Primary irritant effect:
- on the skin: No irritant effect.

LD50

- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

200 mg/kg (rat)

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic Harmful

Oral

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
74-87-3	chloromethane	3
75-25-2	bromoform	3
79-34-5	1,1,2,2-tetrachloroethane	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT/TDG, ADR, IMDG, IATA UN1230

· UN proper shipping name

DOT/TDG
 ADR
 IMDG, IATA
 Methanol solution
 METHANOL solution

- · Transport hazard class(es)
- · DOT/TDG (Transport dangerous goods):





Class 3 Flammable liquids

(Contd. on page 9)



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 8) ·Label 3, 6.1 · ADR · Class 3 Flammable liquids ·Label 3+6.1·IMDG · Class 3 Flammable liquids ·Label 3/6.1 \cdot IATA · Class 3 Flammable liquids ·Label 3(6.1)· Packing group · DOT/TDG, ADR, IMDG, IATA II Not applicable. · Environmental hazards: Warning: Flammable liquids · Special precautions for user · Hazard identification number (Kemler code): 336 · EMS Number: F-E,S-D · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT/TDG · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L · ADR · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG 1L · Limited quantities (LQ)



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 9)

· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	
· UN "Model Regulation":	UN 1230 METHANOL SOLUTION, 3 (6.1), II	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- ·Sara

· Section 355	(extremely	hazardous	substances):
---------------	------------	-----------	------------	----

75-34-3 1,1-dichloroethane

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Canadian substance listings:

· Canadia	· Canadian Domestic Substances List (DSL)	
	methanol	
74-87-3	chloromethane	
79-34-5	1,1,2,2-tetrachloroethane	
108-90-7	chlorobenzene	

- · Canadian Non-Domestic Substances List (NDSL)
- 75-34-3 1,1-dichloroethane
- · Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

- · Canadian Ingredient Disclosure list (limit 1%)
- All ingredients are listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: pdl-acg-regulatory-cq@agilent.com
- Date of the latest revision of the safety data sheet 07/04/2024 / 5
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)



Printing date 07/04/2024 Version Number 6 Reviewed on 07/04/2024

Trade name: Volatiles System Performance Check Standard (1X1 mL)

(Contd. of page 10)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* * Data compared to the previous version altered.

`A -