

# SAFETY DATA SHEET



ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

### 1.1 Product identifier

**Product name** : ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509  
**Part no.** : CP28509

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** :  Reagents and Standards for Analytical Chemistry Laboratory Use  
HPLC Column  
ChromSpher 5 Lipids 250 x 10.0mm, 19.6ml tube ,11.8ml solvent

### 1.3 Details of the supplier of the safety data sheet

Agilent Technologies Manufacturing GmbH & Co. KG  
Hewlett-Packard-Str. 8  
76337 Waldbronn  
Germany  
0800 603 1000

**e-mail address of person responsible for this SDS** : pdl-msds\_author@agilent.com

### 1.4 Emergency telephone number

**Emergency telephone number (with hours of operation)** : CHEMTREC®: +(44)-870-8200418

## SECTION 2: Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture (encapsulated in article)

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

H225	FLAMMABLE LIQUIDS - Category 2
H315	SKIN CORROSION/IRRITATION - Category 2
H361fd	REPRODUCTIVE TOXICITY (Fertility and Unborn child) - Category 2
H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
H373	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
H304	ASPIRATION HAZARD - Category 1
H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Date of issue/Date of revision** : 28/06/2018

1/15

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 2: Hazards identification

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.  
H304 - May be fatal if swallowed and enters airways.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

### Precautionary statements

Prevention : P201 - Obtain special instructions before use.  
P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.  
P260 - Do not breathe vapour.

Response : P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : n-hexane  
- toluene

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

### Special packaging requirements

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

3.1 Substances : Mixture (encapsulated in article)

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Hexane	EC: 203-777-6 CAS: 110-54-3 Index: 601-037-00-0	≥25 - ≤50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f (Fertility) STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]
Ethyl acetate	EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	≤5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
Toluene	EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child) STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304  <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

Contains: Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

*ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509*

## SECTION 4: First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

*ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509*

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

**Date of issue/Date of revision** : 28/06/2018

5/15

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E2	5000 200	50000 500

### 7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not applicable.

## SECTION 8: Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
n-Hexane	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> TWA: 72 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
Ethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.
Toluene	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 384 mg/m <sup>3</sup> 15 minutes.

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 8: Exposure controls/personal protection

TWA: 191 mg/m<sup>3</sup> 8 hours.  
TWA: 50 ppm 8 hours.  
STEL: 100 ppm 15 minutes.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

No DNELs/DMELs available.

### PNECs

No PNECs available

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

*ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509*

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Solid. (containing flammable liquid)
- Colour** : Not available.
- Odour** : Odourless.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: -18 to 23°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Contains: Flammable liquid
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : Not available.
- Solubility(ies)** : Mobile phase / Stationary phase: Insoluble
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Date of issue/Date of revision** : 28/06/2018



ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 10: Stability and reactivity

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials  
Incompatible with hydrogen fluoride.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-Hexane	LC50 Inhalation Vapour	Rat - Male, Female	>31.86 mg/l	4 hours
Ethyl acetate	LC50 Inhalation Vapour	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
Toluene	LC50 Inhalation Vapour	Rat	4000 ppm	4 hours
	LD50 Oral	Rat	5620 mg/kg	-
Toluene	LC50 Inhalation Vapour	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-

#### Acute toxicity estimates

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-Hexane	Eyes - Mild irritant	Rabbit	-	10 milligrams	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
Toluene	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
				870 Micrograms	-
Toluene	Skin - Mild irritant	Rabbit	-	435 milligrams	-
				24 hours 20 milligrams	-
Toluene	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
				500 milligrams	-

**Skin** : Repeated exposure may cause skin dryness or cracking.

#### Sensitiser

**Conclusion/Summary** : Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

#### Teratogenicity

**Conclusion/Summary** : Not available.

#### Specific target organ toxicity (single exposure)

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
n-Hexane	Category 3	Not applicable.	Narcotic effects
Ethyl acetate	Category 3	Not applicable.	Narcotic effects
Toluene	Category 3	Not applicable.	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-Hexane	Category 2	Not determined	Not determined
Toluene	Category 2	Not determined	Not determined

### Aspiration hazard

Product/ingredient name	Result
ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509	ASPIRATION HAZARD - Category 1
n-Hexane	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
- Skin contact** : Causes skin irritation.
- Eye contact** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 11: Toxicological information

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

**General** : May cause damage to organs through prolonged or repeated exposure.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : Suspected of damaging the unborn child.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : Suspected of damaging fertility.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
n-Hexane Ethyl acetate	Acute LC50 2500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 2500000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 750000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 154000 µg/l Fresh water	Daphnia - Daphnia cucullata	48 hours
	Acute LC50 212500 µg/l Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Toluene	Chronic NOEC 75.6 mg/l Fresh water	Fish - Pimephales promelas - Embryo	32 days
	Acute EC50 433 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 0.74 mg/l	Daphnia - Ceriodaphnia dubia	7 days

### 12.2 Persistence and degradability

Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Ethyl acetate	-	-	Readily
Toluene	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-Hexane	4	501.187	high
Ethyl acetate	0.68	30	low
Toluene	2.73	90	low

### 12.4 Mobility in soil

Date of issue/Date of revision : 28/06/2018

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 12: Ecological information

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.






#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	UN3175	UN3175	UN3175
<b>14.2 UN proper shipping name</b>	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (n-Hexane, Ethyl acetate)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (n-Hexane, Ethyl acetate)	Solids containing flammable liquid, n.o.s. (n-Hexane, Ethyl acetate)
<b>14.3 Transport hazard class(es)</b>	4.1  	4.1  	4.1 
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Yes.	Yes.	<input checked="" type="checkbox"/> Yes. The environmentally hazardous substance mark is not required.

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 14: Transport information

### Additional information

Remarks: Excepted Quantity

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Hazard identification number** 40  
**Limited quantity** 1 kg  
**Special provisions** 216, 274, 601  
**Tunnel code** (E)
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Emergency schedules** F-A, S-I  
**Special provisions** 216, 274
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.  
**Quantity limitation** Passenger and Cargo Aircraft: 15 kg. Packaging instructions: 445. Cargo Aircraft Only: 50 kg. Packaging instructions: 448. Limited Quantities - Passenger Aircraft: 5 kg. Packaging instructions: Y441.
- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

###### Category

P5c  
E2

#### International regulations

**Date of issue/Date of revision** : 28/06/2018

ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509

## SECTION 15: Regulatory information

### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol (Annexes A, B, C, E)

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

<b>Australia</b>	: All components are listed or exempted.
<b>Canada</b>	: Not determined.
<b>China</b>	: All components are listed or exempted.
<b>Europe</b>	: All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (ENCS)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : All components are listed or exempted.
<b>Malaysia</b>	: All components are listed or exempted.
<b>New Zealand</b>	: <input checked="" type="checkbox"/> All components are listed or exempted.
<b>Philippines</b>	: Not determined.
<b>Republic of Korea</b>	: Not determined.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: <input checked="" type="checkbox"/> Not determined.
<b>Turkey</b>	: <input checked="" type="checkbox"/> All components are listed or exempted.
<b>United States</b>	: All components are listed or exempted.
<b>Viet Nam</b>	: <input checked="" type="checkbox"/> Not determined.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments might still be required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Repr. 2, H361fd (Fertility and Unborn child)	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method
Asp. Tox. 1, H304	Expert judgment
Aquatic Chronic 2, H411	Calculation method

### Full text of abbreviated H statements

**Date of issue/Date of revision** : 28/06/2018

**ChromSpher 5 Lipids 250 x 10.0mm, Part Number CP28509**

**SECTION 16: Other information**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

[Full text of classifications \[CLP/GHS\]](#)

<p>Aquatic Chronic 2, H411                  Asp. Tox. 1, H304                  EUH066                  Eye Irrit. 2, H319                  Flam. Liq. 2, H225                  Repr. 2, H361d                  Repr. 2, H361f                  Repr. 2, H361fd</p> <p>Skin Irrit. 2, H315                  STOT RE 2, H373</p> <p>STOT SE 3, H336</p>	<p>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                  ASPIRATION HAZARD - Category 1                  Repeated exposure may cause skin dryness or cracking.                  SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  FLAMMABLE LIQUIDS - Category 2                  REPRODUCTIVE TOXICITY (Unborn child) - Category 2                  REPRODUCTIVE TOXICITY (Fertility) - Category 2                  REPRODUCTIVE TOXICITY (Fertility and Unborn child) - Category 2                  SKIN CORROSION/IRRITATION - Category 2                  SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2                  SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3</p>
---	--

**Date of issue/ Date of revision** : 28/06/2018

**Date of previous issue** : 20/06/2016

**Version** : 2

[Notice to reader](#)

**Disclaimer:** The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.