

SAFETY DATA SHEET

Testmix, Part Number CP299103

Section 1. Identification

1.1 Product identifier

Product name : Testmix, Part Number CP299103
Part No. : CP299103
Validation date : 3/23/2017

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Analytical chemistry.
 1 ml vials

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer : Agilent Technologies, Inc.
 5301 Stevens Creek Blvd
 Santa Clara, CA 95051, USA
 800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2
 H315 SKIN IRRITATION - Category 2
 H319 EYE IRRITATION - Category 2A
 H340 GERM CELL MUTAGENICITY - Category 1
 H350 CARCINOGENICITY - Category 1A
 H361 TOXIC TO REPRODUCTION (Fertility) - Category 2
 H361 TOXIC TO REPRODUCTION (Unborn child) - Category 2
 H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
 H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys) - Category 1
 H304 ASPIRATION HAZARD - Category 1

Ingredients of unknown toxicity : Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 40.2%

2.2 GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards identification

Hazard statements : H225 - Highly flammable liquid and vapor.
 H319 - Causes serious eye irritation.
 H315 - Causes skin irritation.
 H340 - May cause genetic defects.
 H350 - May cause cancer.
 H361 - Suspected of damaging fertility or the unborn child.
 H304 - May be fatal if swallowed and enters airways.
 H335 - May cause respiratory irritation.
 H336 - May cause drowsiness or dizziness.
 H372 - Causes damage to organs through prolonged or repeated exposure. (blood system, central nervous system (CNS), kidneys)

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P233 - Keep container tightly closed.
 P271 - Use only outdoors or in a well-ventilated area.
 P260 - Do not breathe vapor.
 P270 - Do not eat, drink or smoke when using this product.
 P264 - Wash hands thoroughly after handling.

Response : P314 - Get medical attention if you feel unwell.
 P308 + P313 - IF exposed or concerned: Get medical attention.
 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
 P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
 P332 + P313 - If skin irritation occurs: Get medical attention.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical attention.

Storage : P405 - Store locked up.
 P403 - Store in a well-ventilated place.
 P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Isopropylcyclohexane	≤5	696-29-7
Octane	≤5	111-65-9
nonane	≤5	111-84-2
Ethylcyclohexane	≤5	1678-91-7
Cyclohexane	≤5	110-82-7
2-Methylpentane	≤5	107-83-5
methylcyclohexane	≤5	108-87-2
Heptane	≤5	142-82-5
Hept-1-ene	≤5	592-76-7
n-Hexane	≤5	110-54-3
oct-1-ene	≤5	111-66-0
Non-1-ene	≤5	124-11-8
Decane	≤5	124-18-5
undecane	≤5	1120-21-4
dodecane	≤5	112-40-3
Dec-1-ene	≤3	872-05-9
pentamethylbenzene	≤3	700-12-9
cyclopentane	≤3	287-92-3
Toluene	≤3	108-88-3
o-xylene	≤3	95-47-6
sec-butylbenzene	≤3	135-98-8
benzene	≤3	71-43-2
ethylbenzene	≤3	100-41-4
cumene	≤3	98-82-8
1,2,3-Trimethylbenzene	≤3	526-73-8
cis-bicyclo[4.4.0]decane	≤3	493-01-6
Hex-1-ene	≤3	592-41-6
1-Methylcyclopentene	≤3	693-89-0
pentane	≤3	109-66-0
pent-1-ene	≤3	109-67-1
2-Methylhexane	≤3	591-76-4
2-methylheptane	≤3	592-27-8
2-methylnonane	≤3	871-83-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First aid measures

- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 4. First aid measures

- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not applicable.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Isopropylcyclohexane Octane	None. OSHA PEL 1989 (United States, 3/1989). TWA: 300 ppm 8 hours. TWA: 1450 mg/m ³ 8 hours. STEL: 375 ppm 15 minutes. STEL: 1800 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 75 ppm 10 hours. TWA: 350 mg/m ³ 10 hours. CEIL: 385 ppm 15 minutes. CEIL: 1800 mg/m ³ 15 minutes.

Section 8. Exposure controls/personal protection

<p>nonane</p>	<p>ACGIH TLV (United States, 3/2016). TWA: 300 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 500 ppm 8 hours. TWA: 2350 mg/m³ 8 hours. ACGIH TLV (United States, 3/2016). TWA: 200 ppm 8 hours. TWA: 1050 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 200 ppm 8 hours. TWA: 1050 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 200 ppm 10 hours. TWA: 1050 mg/m³ 10 hours.</p>
<p>Ethylcyclohexane Cyclohexane</p>	<p>None. ACGIH TLV (United States, 3/2016). TWA: 100 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 300 ppm 8 hours. TWA: 1050 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 300 ppm 10 hours. TWA: 1050 mg/m³ 10 hours. OSHA PEL (United States, 6/2016). TWA: 300 ppm 8 hours. TWA: 1050 mg/m³ 8 hours.</p>
<p>2-Methylpentane</p>	<p>ACGIH TLV (United States, 3/2016). TWA: 500 ppm 8 hours. TWA: 1760 mg/m³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 500 ppm 8 hours. TWA: 1800 mg/m³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3600 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 350 mg/m³ 10 hours. CEIL: 510 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes.</p>
<p>methylcyclohexane</p>	<p>ACGIH TLV (United States, 3/2016). TWA: 1610 mg/m³ 8 hours. TWA: 400 ppm 8 hours. NIOSH REL (United States, 10/2013). TWA: 1600 mg/m³ 10 hours. TWA: 400 ppm 10 hours. OSHA PEL (United States, 6/2016). TWA: 2000 mg/m³ 8 hours. TWA: 500 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1600 mg/m³ 8 hours. TWA: 400 ppm 8 hours.</p>
<p>Heptane</p>	<p>ACGIH TLV (United States, 3/2016). TWA: 400 ppm 8 hours. TWA: 1640 mg/m³ 8 hours. STEL: 500 ppm 15 minutes.</p>

Section 8. Exposure controls/personal protection

	<p>STEL: 2050 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 1600 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2000 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 85 ppm 10 hours. TWA: 350 mg/m³ 10 hours. CEIL: 440 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 500 ppm 8 hours. TWA: 2000 mg/m³ 8 hours.</p>
<p>Hept-1-ene n-Hexane</p>	<p>None. ACGIH TLV (United States, 3/2016). Absorbed through skin. TWA: 50 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 50 ppm 8 hours. TWA: 180 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 50 ppm 10 hours. TWA: 180 mg/m³ 10 hours. OSHA PEL (United States, 6/2016). TWA: 500 ppm 8 hours. TWA: 1800 mg/m³ 8 hours.</p>
<p>oct-1-ene Non-1-ene Decane undecane dodecane Dec-1-ene</p>	<p>AIHA WEEL (United States, 10/2011). TWA: 75 ppm 8 hours. None. None. None. None.</p>
<p>pentamethylbenzene cyclopentane</p>	<p>AIHA WEEL (United States, 10/2011). TWA: 100 ppm 8 hours. None. ACGIH TLV (United States, 3/2016). TWA: 1720 mg/m³ 8 hours. TWA: 600 ppm 8 hours. NIOSH REL (United States, 10/2013). TWA: 1720 mg/m³ 10 hours. TWA: 600 ppm 10 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1720 mg/m³ 8 hours. TWA: 600 ppm 8 hours.</p>
<p>Toluene</p>	<p>OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 375 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m³ 15 minutes. OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 375 mg/m³ 10 hours.</p>

Section 8. Exposure controls/personal protection

o-xylene

STEL: 150 ppm 15 minutes.
 STEL: 560 mg/m³ 15 minutes.
ACGIH TLV (United States, 3/2016).
 TWA: 20 ppm 8 hours.
ACGIH TLV (United States, 3/2016).
 TWA: 100 ppm 8 hours.
 TWA: 434 mg/m³ 8 hours.
 STEL: 150 ppm 15 minutes.
 STEL: 651 mg/m³ 15 minutes.
OSHA PEL 1989 (United States, 3/1989).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.
 STEL: 150 ppm 15 minutes.
 STEL: 655 mg/m³ 15 minutes.
NIOSH REL (United States, 10/2013).
 TWA: 100 ppm 10 hours.
 TWA: 435 mg/m³ 10 hours.
 STEL: 150 ppm 15 minutes.
 STEL: 655 mg/m³ 15 minutes.
OSHA PEL (United States, 6/2016).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.

sec-butylbenzene
 benzene

None.
ACGIH TLV (United States, 3/2016).
Absorbed through skin.
 TWA: 0.5 ppm 8 hours.
 TWA: 1.6 mg/m³ 8 hours.
 STEL: 2.5 ppm 15 minutes.
 STEL: 8 mg/m³ 15 minutes.
OSHA PEL 1989 (United States, 3/1989).
 TWA: 1 ppm 8 hours.
 STEL: 5 ppm 15 minutes.
OSHA PEL Z2 (United States, 2/2013).
 TWA: 10 ppm 8 hours.
 CEIL: 25 ppm
 AMP: 50 ppm 10 minutes.
NIOSH REL (United States, 10/2013).
 TWA: 0.1 ppm 10 hours.
 STEL: 1 ppm 15 minutes.
OSHA PEL (United States, 6/2016).
 TWA: 1 ppm 8 hours.
 STEL: 5 ppm 15 minutes.

ethylbenzene

ACGIH TLV (United States, 3/2016).
 TWA: 20 ppm 8 hours.
OSHA PEL 1989 (United States, 3/1989).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.
 STEL: 125 ppm 15 minutes.
 STEL: 545 mg/m³ 15 minutes.
NIOSH REL (United States, 10/2013).
 TWA: 100 ppm 10 hours.
 TWA: 435 mg/m³ 10 hours.
 STEL: 125 ppm 15 minutes.
 STEL: 545 mg/m³ 15 minutes.
OSHA PEL (United States, 6/2016).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.

Section 8. Exposure controls/personal protection

cumene	<p>ACGIH TLV (United States, 3/2016). TWA: 50 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 245 mg/m³ 8 hours.</p> <p>NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 50 ppm 10 hours. TWA: 245 mg/m³ 10 hours.</p> <p>OSHA PEL (United States, 6/2016). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 245 mg/m³ 8 hours.</p>
1,2,3-Trimethylbenzene	<p>ACGIH TLV (United States, 3/2016). TWA: 25 ppm 8 hours. TWA: 123 mg/m³ 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 25 ppm 8 hours. TWA: 125 mg/m³ 8 hours.</p> <p>NIOSH REL (United States, 10/2013). TWA: 25 ppm 10 hours. TWA: 125 mg/m³ 10 hours.</p>
cis-bicyclo[4.4.0]decane Hex-1-ene	None.
1-Methylcyclopentene pentane	<p>ACGIH TLV (United States, 3/2016). TWA: 50 ppm 8 hours.</p> <p>None.</p> <p>ACGIH TLV (United States, 3/2016). TWA: 1000 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 600 ppm 8 hours. TWA: 1800 mg/m³ 8 hours. STEL: 750 ppm 15 minutes. STEL: 2250 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 120 ppm 10 hours. TWA: 350 mg/m³ 10 hours. CEIL: 610 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 6/2016). TWA: 1000 ppm 8 hours. TWA: 2950 mg/m³ 8 hours.</p>
pent-1-ene 2-Methylhexane	<p>None.</p> <p>ACGIH TLV (United States, 3/2016). TWA: 400 ppm 8 hours. TWA: 1640 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2050 mg/m³ 15 minutes.</p>
2-methylheptane	<p>ACGIH TLV (United States, 3/2016). TWA: 300 ppm 8 hours.</p>
2-methylnonane	None.

[8.2 Exposure controls](#)

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid. [Clear.]
- Color** : Colorless.
- Odor** : Gasoline-like
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Not available.

Section 9. Physical and chemical properties

Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.8 [Water = 1]
Density	: 0.8 g/cm ³
Solubility	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

Section 10. Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropylcyclohexane	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5.04 mg/l	4 hours
	LD50 Oral	Rat - Male, Female	>10000 mg/kg	-
Octane	LC50 Inhalation Vapor	Rat	118 g/m ³	4 hours
	LC50 Inhalation Vapor	Rat	25260 ppm	4 hours
nonane	LC50 Inhalation Vapor	Rat	3200 ppm	4 hours
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Cyclohexane	LD50 Oral	Rat	6240 mg/kg	-
Heptane	LC50 Inhalation Vapor	Rat	103 g/m ³	4 hours
	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
n-Hexane	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Section 11. Toxicological information

oct-1-ene	LD50 Oral	Rat	>10000 mg/kg	-
Decane	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
undecane	LD50 Oral	Rat - Male, Female	>15000 mg/kg	-
dodecane	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
cyclopentane	LD50 Oral	Rat	11400 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
o-xylene	LC50 Inhalation Vapor	Rat	5300 ppm	4 hours
	LD50 Oral	Rat	3000 mg/kg	-
sec-butylbenzene	LD50 Oral	Rat	6300 mg/kg	-
benzene	LD50 Oral	Rat	930 mg/kg	-
ethylbenzene	LC50 Inhalation Vapor	Rat	17200 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	4000 ppm	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
cumene	LC50 Inhalation Dusts and mists	Rat	39000 mg/m ³	4 hours
	LD50 Oral	Rat	1400 mg/kg	-
Hex-1-ene	LC50 Inhalation Vapor	Rat	32000 ppm	4 hours
pentane	LC50 Inhalation Vapor	Rat	364 g/m ³	4 hours
pent-1-ene	LC50 Inhalation Dusts and mists	Rat	175000 mg/m ³	4 hours

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
nonane	Skin - Moderate irritant	Rat	-	96 hours 300 microliters	-
methylcyclohexane	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
n-Hexane	Eyes - Mild irritant	Rabbit	-	10 milligrams	-
oct-1-ene	Skin - Irritant	Rat	-	-	-
dodecane	Skin - Moderate irritant	Rat	-	96 hours 300 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 0.05 Milliliters	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
sec-butylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
benzene	Eyes - Moderate irritant	Rabbit	-	88 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60	-

Section 11. Toxicological information

ethylbenzene cumene	Skin - Mild irritant	Rabbit	-	microliters 24 hours 15	-
	Skin - Moderate irritant	Rabbit	-	milligrams 24 hours 20	-
	Skin - Mild irritant	Rabbit	-	milligrams 24 hours 15	-
	Eyes - Mild irritant	Rabbit	-	milligrams 24 hours 500	-
	Eyes - Mild irritant	Rabbit	-	milligrams 86 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 10	-
	Skin - Moderate irritant	Rabbit	-	milligrams 24 hours 100	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Oct-1-ene	skin	Guinea pig	Not sensitizing
Hex-1-ene	skin	Guinea pig	Not sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
o-xylene	-	3	-
benzene	+	1	Known to be a human carcinogen.
ethylbenzene	-	2B	-
cumene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Octane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
nonane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Cyclohexane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2-Methylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
methylcyclohexane	Category 3	Not applicable.	Respiratory tract irritation and

Section 11. Toxicological information

Heptane	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
n-Hexane	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
oct-1-ene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation
Non-1-ene	Category 3	Not applicable.	Respiratory tract irritation
Dec-1-ene	Category 3	Not applicable.	Respiratory tract irritation
pentamethylbenzene	Category 3	Not applicable.	Respiratory tract irritation
cyclopentane	Category 3	Not applicable.	Respiratory tract irritation and
Toluene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
o-xylene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
benzene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
ethylbenzene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and
cumene	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation
1,2,3-Trimethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and
cis-bicyclo[4.4.0]decane	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation
pentane	Category 3	Not applicable.	Narcotic effects
2-Methylhexane	Category 3	Not applicable.	Respiratory tract irritation and
2-methylheptane	Category 3	Not applicable.	Narcotic effects Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
n-Hexane	Category 2	Not determined	nervous system and peripheral nervous system
Toluene	Category 2	Oral	central nervous system (CNS) and kidneys
benzene	Category 1	Skin Inhalation	blood system blood system

Aspiration hazard

Section 11. Toxicological information

Name	Result
Testmix, Part Number CP299103	ASPIRATION HAZARD - Category 1
isopropylcyclohexane	ASPIRATION HAZARD - Category 1
Octane	ASPIRATION HAZARD - Category 1
nonane	ASPIRATION HAZARD - Category 1
Ethylcyclohexane	ASPIRATION HAZARD - Category 1
Cyclohexane	ASPIRATION HAZARD - Category 1
2-Methylpentane	ASPIRATION HAZARD - Category 1
methylcyclohexane	ASPIRATION HAZARD - Category 1
Heptane	ASPIRATION HAZARD - Category 1
Hept-1-ene	ASPIRATION HAZARD - Category 1
n-Hexane	ASPIRATION HAZARD - Category 1
oct-1-ene	ASPIRATION HAZARD - Category 1
Non-1-ene	ASPIRATION HAZARD - Category 1
Decane	ASPIRATION HAZARD - Category 1
undecane	ASPIRATION HAZARD - Category 1
dodecane	ASPIRATION HAZARD - Category 1
Dec-1-ene	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
benzene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
cumene	ASPIRATION HAZARD - Category 1
1,2,3-Trimethylbenzene	ASPIRATION HAZARD - Category 1
Hex-1-ene	ASPIRATION HAZARD - Category 1
1-Methylcyclopentene	ASPIRATION HAZARD - Category 1
pentane	ASPIRATION HAZARD - Category 1
pent-1-ene	ASPIRATION HAZARD - Category 1
2-Methylhexane	ASPIRATION HAZARD - Category 1
2-methylheptane	ASPIRATION HAZARD - Category 1
2-methylnonane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight

Section 11. Toxicological information

- Skin contact** : increase in fetal deaths
skeletal malformations
: Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

- General** : Causes damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : May cause genetic defects.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
<input checked="" type="checkbox"/> Oral	7510.8 mg/kg
Dermal	32890 mg/kg
Inhalation (vapors)	200.6 mg/l

- Other information** : Adverse symptoms may include the following: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Section 12. Ecological information

12.1 Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Ethylcyclohexane	Acute LC50 8800 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
Cyclohexane	Acute LC50 8300 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
methylcyclohexane	Acute LC50 5800 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
Heptane	Acute LC50 375000 µg/l Fresh water	Fish - Oreochromis mossambicus	96 hours
n-Hexane	Acute LC50 113000 µg/l Fresh water	Fish - Oreochromis mossambicus	96 hours
oct-1-ene	Acute LC50 4.8 mg/l Fresh water	Fish - Danio rerio - Young	96 hours
Non-1-ene	Acute EC50 3.2 to 10 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
Decane	Acute LC50 10 mg/l Fresh water	Fish - Danio rerio - Young	96 hours
	Acute EC50 89 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute LC50 18000 to 24000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
Toluene	Acute LC50 >500 ppm Marine water	Fish - Cyprinodon variegatus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
o-xylene	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 0.74 mg/l	Daphnia - Ceriodaphnia dubia	7 days
benzene	Acute EC50 4700 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 12700 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 1390 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
ethylbenzene	Acute LC50 7600 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
cumene	Acute EC50 9230 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
cumene	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2970 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
cumene	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7500 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours

Section 12. Ecological information

Hex-1-ene	Acute EC50 11200 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
pent-1-ene	Acute EC50 4.4 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute NOEC 0.0034 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	EC50 34 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	EC50 35 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	NOEC 20 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
o-xylene	-	-	Inherent
ethylbenzene	-	-	Readily
Hex-1-ene	-	-	Not readily
pentane	-	-	Readily
pent-1-ene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Octane	5.18	198.7	low
nonane	5.65	105	low
Ethylcyclohexane	4.56	-	high
Cyclohexane	3.44	167	low
2-Methylpentane	3.21	-	low
methylcyclohexane	3.61	186.21	low
Heptane	4.66	552	high
Hept-1-ene	3.99	-	low
n-Hexane	4	501.187	high
oct-1-ene	4.47	3.1	low
Non-1-ene	5.15	1479.11	high
Decane	5.86	-	high
undecane	6.42	-	high
dodecane	6.98	239.88	low
Dec-1-ene	5.12	3.65	low
pentamethylbenzene	4.56	-	high
cyclopentane	3	70.8	low
Toluene	2.73	90	low
o-xylene	3.12	8.1 to 25.9	low
sec-butylbenzene	4.57	481.2	low
benzene	2.13	11	low
ethylbenzene	3.6	-	low
cumene	3.55	35.48	low
1,2,3-Trimethylbenzene	3.66	194.98	low
cis-bicyclo[4.4.0]decane	-	1621.81	high
Hex-1-ene	3.87	2.59	low
pentane	3.45	171	low
pent-1-ene	2.66	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Section 12. Ecological information

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Cyclohexane (I); Benzene, hexahydro- (I)	110-82-7	Listed	U056
Cumene (I); Benzene, (1-methylethyl)- (I)	98-82-8	Listed	U055
Benzene (I,T)	71-43-2	Listed	U019
Xylene	95-47-6	Listed	U239
Toluene; Benzene, methyl-	108-88-3	Listed	U220

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

Regulatory information

Additional information : **Remarks**
De minimis quantities

DOT / IMDG / IATA : Not regulated.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations :

- TSCA 4(a) final test rules:** nonane
- TSCA 8(a) PAIR:** nonane; Heptane; methylcyclohexane; cyclopentane; pentane
- TSCA 12(b) one-time export:** nonane
- United States inventory (TSCA 8b):** Not determined.
- Clean Water Act (CWA) 307:** ethylbenzene; benzene; Toluene
- Clean Water Act (CWA) 311:** Cyclohexane; ethylbenzene; benzene; o-xylene; Toluene

Section 15. Regulatory information

 Clean Air Act (CAA) 112 regulated flammable substances: pentane; pent-1-ene

Clean Air Act Section 112 : Listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Isopropylcyclohexane	≤5	Yes.	No.	No.	No.	No.
Octane	≤5	Yes.	No.	No.	Yes.	No.
nonane	≤5	Yes.	No.	No.	Yes.	No.
Ethylcyclohexane	≤5	Yes.	No.	No.	No.	No.
Cyclohexane	≤5	Yes.	No.	No.	Yes.	No.
2-Methylpentane	≤5	Yes.	No.	No.	Yes.	No.
methylcyclohexane	≤5	Yes.	No.	No.	Yes.	No.
Heptane	≤5	Yes.	No.	No.	Yes.	No.
Hept-1-ene	≤5	Yes.	No.	No.	No.	No.
n-Hexane	<5	Yes.	No.	No.	Yes.	Yes.
oct-1-ene	≤5	Yes.	No.	No.	Yes.	No.
Non-1-ene	≤5	Yes.	No.	No.	Yes.	No.
Decane	≤5	Yes.	No.	No.	Yes.	No.
undecane	≤5	Yes.	No.	No.	Yes.	No.
dodecane	≤5	Yes.	No.	No.	Yes.	No.
Dec-1-ene	≤3	Yes.	No.	No.	Yes.	No.
pentamethylbenzene	≤3	Yes.	No.	No.	Yes.	No.
cyclopentane	≤3	Yes.	No.	No.	Yes.	No.
Toluene	≤3	Yes.	No.	No.	Yes.	Yes.
o-xylene	≤3	Yes.	No.	No.	Yes.	No.
sec-butylbenzene	≤3	Yes.	No.	No.	Yes.	No.
benzene	≤3	Yes.	No.	No.	Yes.	Yes.
ethylbenzene	≤3	Yes.	No.	No.	Yes.	Yes.
cumene	≤3	Yes.	No.	No.	Yes.	Yes.
1,2,3-Trimethylbenzene	≤3	Yes.	No.	No.	Yes.	No.
cis-bicyclo[4.4.0]decane	≤3	Yes.	No.	No.	Yes.	No.
Hex-1-ene	≤3	Yes.	No.	No.	Yes.	No.
1-Methylcyclopentene	≤3	Yes.	No.	No.	No.	No.

Section 15. Regulatory information

pentane	≤3	Yes.	No.	No.	Yes.	No.
pent-1-ene	≤3	Yes.	No.	No.	No.	No.
2-Methylhexane	≤3	Yes.	No.	No.	Yes.	No.
2-methylheptane	≤3	Yes.	No.	No.	Yes.	No.
2-methylnonane	≤3	Yes.	No.	No.	No.	No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	<input checked="" type="checkbox"/> Cyclohexane	110-82-7	≤5
	n-Hexane	110-54-3	<5
	Toluene	108-88-3	≤3
	o-xylene	95-47-6	≤3
	benzene	71-43-2	≤3
	ethylbenzene	100-41-4	≤3
	cumene	98-82-8	≤3
Supplier notification	<input checked="" type="checkbox"/> Cyclohexane	110-82-7	≤5
	n-Hexane	110-54-3	<5
	Toluene	108-88-3	≤3
	o-xylene	95-47-6	≤3
	benzene	71-43-2	≤3
	ethylbenzene	100-41-4	≤3
	cumene	98-82-8	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ETHYL CYCLOHEXANE; NONANE; 1-OCTENE; OCTANE; HEXANE; N-HEXANE; HEPTANE; N-HEPTANE; METHYLCYCLOHEXANE; ISOHEXANE; CYCLOHEXANE; HEXAHYDROBENZENE; CYCLOPENTANE; DECAHYDRONAPHTHALENE; TRIMETHYL BENZENE; CUMENE; 1-METHYLETHYLBENZENE; ETHYL BENZENE; ETHYLBENZENE; BENZENE; SEC-BUTYLBENZENE; O-XYLENE; O-DIMETHYLBENZENE; TOLUENE; METHYLBENZENE; 1-HEXENE; PENTANE; 1-PENTENE; ISOHEPTANE; 2-METHYLOCTANE

New York

: The following components are listed: Hexane; Cyclohexane; Benzene, hexahydro-; Cumene; Benzene, 1-methylethyl-; Ethylbenzene; Benzene; o-Xylene; Toluene

New Jersey

: The following components are listed: ETHYLCYCLOHEXANE; CYCLOHEXANE, ETHYL-; UNDECANE; HENDECANE; DECANE; NONANE; OCTANE; n-HEXANE; HEXANE; n-HEPTANE; HEPTANE; METHYLCYCLOHEXANE; CYCLOHEXANE, METHYL-; 2-METHYLPENTANE; ISOHEXANE; CYCLOHEXANE; CYCLOPENTANE; TRIMETHYL BENZENE (mixed isomers); BENZENE, TRIMETHYL-; CUMENE; BENZENE, (1-METHYLETHYL)-; ETHYL BENZENE; BENZENE, ETHYL-; BENZENE; o-XYLENE; BENZENE, 1,2-DIMETHYL-; TOLUENE; BENZENE, METHYL-; 1-HEXENE; PENTANE; 1-PENTENE

Pennsylvania

: The following components are listed: CYCLOHEXANE, ETHYL-; DECANE; NONANE; 1-OCTENE; OCTANE; HEXANE; 1-HEPTENE; HEPTANE; CYCLOHEXANE, METHYL-; PENTANE, 2-METHYL-; CYCLOHEXANE; CYCLOPENTANE; BENZENE, (1-METHYLETHYL)-; BENZENE, ETHYL-; BENZENE; BENZOL DILUENT; BENZENE, (1-METHYLPROPYL)-; BENZENE, 1,2-DIMETHYL-; BENZENE, METHYL-; 1-HEXENE; PENTANE; 1-PENTENE; HEXANE, 2-METHYL-; OCTANE, 2-METHYL-

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 15. Regulatory information

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
<input checked="" type="checkbox"/> Toluene	No.	Yes.	No.	7000 µg/day (ingestion)
<input type="checkbox"/> benzene	Yes.	Yes.	6.4 µg/day (ingestion) 13 µg/day (inhalation)	24 µg/day (ingestion) 49 µg/day (inhalation)
<input type="checkbox"/> ethylbenzene	Yes.	No.	41 µg/day (ingestion) 54 µg/day (inhalation)	No.
<input type="checkbox"/> cumene	Yes.	No.	No.	No.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: Not determined.
Canada inventory	: Not determined.
China	: Not determined.
Europe	: All components are listed or exempted.
Japan	: <input checked="" type="checkbox"/> Japan inventory (ENCS) : Not determined. Japan inventory (ISHL) : Not determined.
Malaysia	: Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: All components are listed or exempted.
Turkey	: <input checked="" type="checkbox"/> Not determined.

Section 16. Other information

History

Date of issue : 03/23/2017

Date of previous issue : 07/30/2015.

Version : 4

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.