

# SAFETY DATA SHEET

Testmix, Part Number CP299103

## Section 1. Identification

### 1.1 Product identifier

**Product name** : Testmix, Part Number CP299103  
**Part no.** : CP299103  
**Validation date** : 4/26/2023

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** :  Reagents and Standards for Analytical Chemistry Laboratory Use  
 1 ml vials

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer** : Agilent Technologies, Inc.  
 5301 Stevens Creek Blvd  
 Santa Clara, CA 95051, USA  
 800-227-9770

### 1.4 Emergency telephone number

**In case of emergency** : CHEMTREC®: 1-800-424-9300

## Section 2. Hazards identification

### 2.1 Classification of the substance or mixture

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2  
 H315 SKIN IRRITATION - Category 2  
 H319 EYE IRRITATION - Category 2A  
 H340 GERM CELL MUTAGENICITY - Category 1  
 H350 CARCINOGENICITY - Category 1A  
 H361 TOXIC TO REPRODUCTION - Category 2  
 H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
 H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
 H304 ASPIRATION HAZARD - Category 1  
 H400 AQUATIC HAZARD (ACUTE) - Category 1  
 H410 AQUATIC HAZARD (LONG-TERM) - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 22.6%

### 2.2 GHS label elements

**Hazard pictograms** : 

**Signal word** : Danger

## Section 2. Hazards identification

- Hazard statements** : H225 - Highly flammable liquid and vapor.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS), haematopoietic system, hearing organs, nervous system)  
H410 - Very toxic to aquatic life with long lasting effects.
- Precautionary statements**
- Prevention** : P201 - Obtain special instructions before use.  
P280 - Wear protective gloves, protective clothing and eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 - Use explosion-proof electrical, ventilating or lighting equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P273 - Avoid release to the environment.  
P260 - Do not breathe vapor.  
P270 - Do not eat, drink or smoke when using this product.  
P264 - Wash thoroughly after handling.
- Response** : P391 - Collect spillage.  
P308 + P313 - IF exposed or concerned: Get medical advice or attention.  
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 - Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 Other hazards

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Isopropylcyclohexane	≤5	696-29-7
Octane	≤5	111-65-9
nonane	≤5	111-84-2
Ethylcyclohexane	≤5	1678-91-7
Cyclohexane	≤5	110-82-7
2-Methylpentane	≤5	107-83-5

**Section 3. Composition/information on ingredients**

methyloyclohexane	≤5	108-87-2
Heptane	≤5	142-82-5
Hept-1-ene	≤5	592-76-7
n-Hexane	<5	110-54-3
oct-1-ene	≤5	111-66-0
Non-1-ene	≤5	124-11-8
Decane	≤5	124-18-5
undecane	≤5	1120-21-4
dodecane	≤5	112-40-3
tert-butylcyclohexane	≤5	3178-22-1
Dec-1-ene	≤3	872-05-9
pentamethylbenzene	≤3	700-12-9
cyclopentane	≤3	287-92-3
Toluene	≤3	108-88-3
o-xylene	≤3	95-47-6
sec-butylbenzene	≤3	135-98-8
benzene	≤3	71-43-2
ethylbenzene	≤3	100-41-4
cumene	≤3	98-82-8
1,2,3-Trimethylbenzene	≤3	526-73-8
1,2,3,4-Tetramethylbenzene	≤3	488-23-3
cis-bicyclo[4.4.0]decane	≤3	493-01-6
Hex-1-ene	≤3	592-41-6
1-Methylcyclopentene	≤3	693-89-0
pentane	≤1.5	109-66-0
pent-1-ene	≤3	109-67-1
2-Methylhexane	≤3	591-76-4
2-methylheptane	≤3	592-27-8
2-Methyloctane	≤3	3221-61-2
2-methylnonane	≤3	871-83-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### 4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 4.2 Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 nausea or vomiting  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.

## Section 7. Handling and storage

**Industrial sector specific solutions** : Not available.

## Section 8. Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Isopropylcyclohexane Octane	None. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 300 ppm 8 hours. TWA: 1450 mg/m <sup>3</sup> 8 hours. STEL: 375 ppm 15 minutes. STEL: 1800 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2020).</b> TWA: 75 ppm 10 hours. TWA: 350 mg/m <sup>3</sup> 10 hours. CEIL: 385 ppm 15 minutes. CEIL: 1800 mg/m <sup>3</sup> 15 minutes. <b>ACGIH TLV (United States, 1/2022).</b> <b>[Octane]</b> TWA: 300 ppm 8 hours. <b>OSHA PEL (United States, 5/2018).</b> TWA: 500 ppm 8 hours. TWA: 2350 mg/m <sup>3</sup> 8 hours.
nonane	<b>ACGIH TLV (United States, 1/2022).</b> TWA: 200 ppm 8 hours. TWA: 1050 mg/m <sup>3</sup> 8 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 200 ppm 8 hours. TWA: 1050 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2020).</b> TWA: 200 ppm 10 hours. TWA: 1050 mg/m <sup>3</sup> 10 hours.
Ethylcyclohexane	<b>ACGIH TLV (United States, 1/2022).</b> <b>[Octane]</b> TWA: 300 ppm 8 hours.
Cyclohexane	<b>ACGIH TLV (United States, 1/2022).</b> TWA: 100 ppm 8 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 300 ppm 8 hours. TWA: 1050 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2020).</b> TWA: 300 ppm 10 hours. TWA: 1050 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 5/2018).</b> TWA: 300 ppm 8 hours. TWA: 1050 mg/m <sup>3</sup> 8 hours.
2-Methylpentane	<b>ACGIH TLV (United States, 1/2022).</b> <b>[Hexane isomers, other than n-Hexane]</b> TWA: 500 ppm 8 hours. TWA: 1760 mg/m <sup>3</sup> 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> <b>[Hexane isomers]</b> TWA: 500 ppm 8 hours.

## Section 8. Exposure controls/personal protection

methylcyclohexane	<p>TWA: 1800 mg/m<sup>3</sup> 8 hours.          STEL: 1000 ppm 15 minutes.          STEL: 3600 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2020).</b>  <b>[HEXANE ISOMERS]</b>          TWA: 100 ppm 10 hours.          TWA: 350 mg/m<sup>3</sup> 10 hours.          CEIL: 510 ppm 15 minutes.          CEIL: 1800 mg/m<sup>3</sup> 15 minutes.</p>
Heptane	<p><b>ACGIH TLV (United States, 1/2022).</b>          TWA: 400 ppm 8 hours.          TWA: 1610 mg/m<sup>3</sup> 8 hours.  <b>OSHA PEL 1989 (United States, 3/1989).</b>          TWA: 400 ppm 8 hours.          TWA: 1600 mg/m<sup>3</sup> 8 hours.  <b>NIOSH REL (United States, 10/2020).</b>          TWA: 400 ppm 10 hours.          TWA: 1600 mg/m<sup>3</sup> 10 hours.  <b>OSHA PEL (United States, 5/2018).</b>          TWA: 500 ppm 8 hours.          TWA: 2000 mg/m<sup>3</sup> 8 hours.</p>
Hept-1-ene n-Hexane	<p><b>ACGIH TLV (United States, 1/2022).</b>  <b>[Heptane]</b>          TWA: 400 ppm 8 hours.          TWA: 1640 mg/m<sup>3</sup> 8 hours.          STEL: 500 ppm 15 minutes.          STEL: 2050 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL 1989 (United States, 3/1989).</b>          TWA: 400 ppm 8 hours.          TWA: 1600 mg/m<sup>3</sup> 8 hours.          STEL: 500 ppm 15 minutes.          STEL: 2000 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2020).</b>          TWA: 85 ppm 10 hours.          TWA: 350 mg/m<sup>3</sup> 10 hours.          CEIL: 440 ppm 15 minutes.          CEIL: 1800 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL (United States, 5/2018).</b>          TWA: 500 ppm 8 hours.          TWA: 2000 mg/m<sup>3</sup> 8 hours.</p>
oct-1-ene	<p>None.  <b>ACGIH TLV (United States, 1/2022).</b>  <b>Absorbed through skin.</b>          TWA: 50 ppm 8 hours.  <b>OSHA PEL 1989 (United States, 3/1989).</b>          TWA: 50 ppm 8 hours.          TWA: 180 mg/m<sup>3</sup> 8 hours.  <b>NIOSH REL (United States, 10/2020).</b>          TWA: 50 ppm 10 hours.          TWA: 180 mg/m<sup>3</sup> 10 hours.  <b>OSHA PEL (United States, 5/2018).</b>          TWA: 500 ppm 8 hours.          TWA: 1800 mg/m<sup>3</sup> 8 hours.</p>
Non-1-ene Decane undecane	<p><b>OARS WEEL (United States, 1/2021).</b>          TWA: 75 ppm 8 hours.          None.          None.          None.</p>

## Section 8. Exposure controls/personal protection

<p>dodecane tert-butylcyclohexane Dec-1-ene</p> <p>pentamethylbenzene cyclopentane</p>	<p>None. None. <b>OARS WEEL (United States, 1/2021).</b> TWA: 100 ppm 8 hours. None. <b>ACGIH TLV (United States, 1/2022).</b> <b>Explosive potential.</b> TWA: 1720 mg/m<sup>3</sup> 8 hours. TWA: 1000 ppm 8 hours. <b>NIOSH REL (United States, 10/2020).</b> TWA: 1720 mg/m<sup>3</sup> 10 hours. TWA: 600 ppm 10 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1720 mg/m<sup>3</sup> 8 hours. TWA: 600 ppm 8 hours.</p>
<p>Toluene</p>	<p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 100 ppm 8 hours. TWA: 375 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m<sup>3</sup> 15 minutes. <b>OSHA PEL Z2 (United States, 2/2013).</b> TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. <b>NIOSH REL (United States, 10/2020).</b> TWA: 100 ppm 10 hours. TWA: 375 mg/m<sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m<sup>3</sup> 15 minutes. <b>ACGIH TLV (United States, 1/2022).</b> <b>Ototoxicant.</b> TWA: 20 ppm 8 hours.</p>
<p>o-xylene</p>	<p><b>ACGIH TLV (United States, 1/2022). [xylene]</b> TWA: 20 ppm 8 hours. TWA: 434 mg/m<sup>3</sup> 8 hours. STEL: 651 mg/m<sup>3</sup> 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> <b>[Xylenes (o-, m-, p-isomers)]</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m<sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2020).</b> TWA: 100 ppm 10 hours. TWA: 435 mg/m<sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m<sup>3</sup> 15 minutes. <b>OSHA PEL (United States, 5/2018).</b> <b>[Xylenes]</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p>
<p>sec-butylbenzene benzene</p>	<p>None. <b>ACGIH TLV (United States, 1/2022).</b> <b>Absorbed through skin.</b> TWA: 0.5 ppm 8 hours. TWA: 1.6 mg/m<sup>3</sup> 8 hours. STEL: 2.5 ppm 15 minutes. STEL: 8 mg/m<sup>3</sup> 15 minutes.</p>


## Section 8. Exposure controls/personal protection

ethylbenzene	<p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1 ppm 8 hours. STEL: 5 ppm 15 minutes.</p> <p><b>OSHA PEL Z2 (United States, 2/2013).</b> TWA: 10 ppm 8 hours. CEIL: 25 ppm AMP: 50 ppm 10 minutes.</p> <p><b>NIOSH REL (United States, 10/2020).</b> TWA: 0.1 ppm 10 hours. STEL: 1 ppm 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b> TWA: 1 ppm 8 hours. STEL: 5 ppm 15 minutes.</p> <p><b>ACGIH TLV (United States, 1/2022).</b> <b>Ototoxicant.</b> TWA: 20 ppm 8 hours.</p>
cumene	<p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m<sup>3</sup> 15 minutes.</p> <p><b>NIOSH REL (United States, 10/2020).</b> TWA: 100 ppm 10 hours. TWA: 435 mg/m<sup>3</sup> 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2022).</b> TWA: 5 ppm 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 245 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b> <b>Absorbed through skin.</b> TWA: 50 ppm 10 hours. TWA: 245 mg/m<sup>3</sup> 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 245 mg/m<sup>3</sup> 8 hours.</p>
1,2,3-Trimethylbenzene	<p><b>ACGIH TLV (United States, 1/2022).</b> <b>[trimethyl benzene, isomers]</b> TWA: 10 ppm 8 hours. TWA: 123 mg/m<sup>3</sup> 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b> <b>[Trimethyl benzene]</b> TWA: 25 ppm 8 hours. TWA: 125 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b> TWA: 25 ppm 10 hours. TWA: 125 mg/m<sup>3</sup> 10 hours.</p>
1,2,3,4-Tetramethylbenzene cis-bicyclo[4.4.0]decane Hex-1-ene	<p>None. None.</p> <p><b>ACGIH TLV (United States, 1/2022).</b> TWA: 50 ppm 8 hours.</p>

## Section 8. Exposure controls/personal protection

1-Methylcyclopentene pentane	None. <b>ACGIH TLV (United States, 1/2022).</b> <b>[Pentane]</b> TWA: 1000 ppm 8 hours. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 600 ppm 8 hours. TWA: 1800 mg/m <sup>3</sup> 8 hours. STEL: 750 ppm 15 minutes. STEL: 2250 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2020).</b> TWA: 120 ppm 10 hours. TWA: 350 mg/m <sup>3</sup> 10 hours. CEIL: 610 ppm 15 minutes. CEIL: 1800 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL (United States, 5/2018).</b> TWA: 1000 ppm 8 hours. TWA: 2950 mg/m <sup>3</sup> 8 hours.
pent-1-ene 2-Methylhexane	None. <b>ACGIH TLV (United States, 1/2022).</b> <b>[Heptane]</b> TWA: 400 ppm 8 hours. TWA: 1640 mg/m <sup>3</sup> 8 hours. STEL: 500 ppm 15 minutes. STEL: 2050 mg/m <sup>3</sup> 15 minutes.
2-methylheptane	<b>ACGIH TLV (United States, 1/2022).</b> <b>[Octane]</b> TWA: 300 ppm 8 hours.
2-Methyloctane 2-methylnonane	None. None.

### Biological exposure indices

Ingredient name	Exposure indices
 Cyclohexane	<b>ACGIH BEI (United States, 1/2022)</b> BEI: 50 mg/g creatinine, 1,2-cyclohexanediol [in urine]. Sampling time: end of shift at end of workweek.
n-Hexane	<b>ACGIH BEI (United States, 1/2022)</b> BEI: 0.5 mg/l, 2,5-hexanedion [in urine]. Sampling time: end of shift.
Toluene	<b>ACGIH BEI (United States, 1/2022)</b> BEI: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift. BEI: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift. BEI: 0.02 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.
o-xylene	<b>ACGIH BEI (United States, 1/2022)</b> <b>[XYLENES]</b> BEI: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
benzene	<b>ACGIH BEI (United States, 1/2022)</b> BEI: 25 µg/g creatinine, S-phenylmercapturic acid [in urine]. Sampling time: end of shift. BEI: 500 µg/g creatinine, t,t-muconic acid [in

## Section 8. Exposure controls/personal protection

ethylbenzene

urine]. Sampling time: end of shift.

**ACGIH BEI (United States, 1/2022)**

BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine].

Sampling time: end of shift.

### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

##### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

##### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

##### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

<b>Physical state</b>	: Liquid. [Clear.]
<b>Color</b>	: Colorless.
<b>Odor</b>	: Gasoline-like
<b>Odor threshold</b>	: Not available.
<b>pH</b>	: Not available.
<b>Melting point/freezing point</b>	: Not available.
<b>Boiling point, initial boiling point, and boiling range</b>	: Not available.
<b>Flash point</b>	: Closed cup: -18 to 23°C (-0.4 to 73.4°F)
<b>Evaporation rate</b>	: Not available.
<b>Flammability</b>	: Not applicable.
<b>Lower and upper explosion limit/flammability limit</b>	: Not available.
<b>Vapor pressure</b>	:

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
pent-1-ene	634.85	84.6				
pentane	442.84	59				

<b>Relative vapor density</b>	: Not available.
<b>Relative density</b>	: 0.8
<b>Density</b>	: 0.8 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	:

Media	Result
Water	Insoluble

<b>Miscible with water</b>	: No.
<b>Partition coefficient: n-octanol/water</b>	: Not applicable.
<b>Auto-ignition temperature</b>	:

Ingredient name	°C	°F	Method
dodecane	200	392	
undecane	202	395.6	

<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.
<b>Particle characteristics</b>	:
<b>Median particle size</b>	: Not applicable.

## Section 10. Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.

## Section 10. Stability and reactivity

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropylcyclohexane	LC50 Inhalation Dusts and mists	Rat	>5.04 mg/l	4 hours
	LD50 Dermal	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>10000 mg/kg	-
Octane	LC50 Inhalation Vapor	Rat	118 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	25260 ppm	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
nonane	LC50 Inhalation Vapor	Rat	17000 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	3200 ppm	4 hours
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Cyclohexane	LC50 Inhalation Vapor	Rat - Male, Female	>32880 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	6240 mg/kg	-
Heptane	LC50 Inhalation Vapor	Rat	103 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
n-Hexane	LC50 Inhalation Vapor	Rat	169.2 mg/l	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
oct-1-ene	LD50 Oral	Rat	>10000 mg/kg	-
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
Decane	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
undecane	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
dodecane	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Dec-1-ene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat - Male, Female	>25.3 mg/l	4 hours
cyclopentane	LD50 Oral	Rat	11400 mg/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
Toluene	LD50 Dermal	Rat	12000 mg/kg	-
	LD50 Oral	Rat	636 mg/kg	-
	LC50 Inhalation Vapor	Rat	27.559 mg/l	4 hours
o-xylene	LD50 Oral	Rat	6300 mg/kg	-
	LD50 Oral	Rat	930 mg/kg	-
sec-butylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
benzene	LC50 Inhalation Dusts and mists	Rat	39000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	1400 mg/kg	-
ethylbenzene	LD50 Oral	Rat	6408 mg/kg	-
	LD50 Dermal	Rabbit	5900 mg/kg	-
cumene	LD50 Oral	Rat	4.2 g/kg	-
	LD50 Oral	Rat	4.2 g/kg	-
1,2,3,4-Tetramethylbenzene	LD50 Oral	Rat	6408 mg/kg	-
	LD50 Dermal	Rabbit	5900 mg/kg	-
cis-bicyclo[4.4.0]decane	LD50 Oral	Rat	4.2 g/kg	-
	LD50 Oral	Rat	4.2 g/kg	-

## Section 11. Toxicological information

Hex-1-ene pentane	LC50 Inhalation Vapor LC50 Inhalation Vapor LD50 Oral	Rat Rat Rat - Male, Female	32000 ppm 364 g/m <sup>3</sup> >2000 mg/kg	4 hours 4 hours -
pent-1-ene	LC50 Inhalation Dusts and mists	Rat	175000 mg/m <sup>3</sup>	4 hours

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
nonane	Skin - Moderate irritant	Rat	-	96 hours 300 uL	-
methylcyclohexane	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-
n-Hexane dodecane	Eyes - Mild irritant	Rabbit	-	10 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 0.05 MI	-
Toluene	Skin - Moderate irritant	Rat	-	96 hours 300 uL	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
sec-butylbenzene	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Mild irritant	Rabbit	-	500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
benzene	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	88 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
ethylbenzene	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
cumene	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	86 mg	-
1,2,3,4-Tetramethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 10 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 100 mg	-

### Conclusion/Summary

**Skin** : Repeated exposure may cause skin dryness or cracking.

### Sensitization

Product/ingredient name	Route of exposure	Species	Result
oct-1-ene	skin	Guinea pig	Not sensitizing

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

## Section 11. Toxicological information

**Conclusion/Summary** : Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
o-xylene	-	3	-
benzene	+	1	Known to be a human carcinogen.
ethylbenzene	-	2B	-
cumene	-	2B	Reasonably anticipated to be a human carcinogen.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
isopropylcyclohexane	Category 3	-	Narcotic effects
Octane	Category 3	-	Respiratory tract irritation
nonane	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Ethylcyclohexane	Category 3	-	Narcotic effects
Cyclohexane	Category 3	-	Respiratory tract irritation
2-Methylpentane	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
methylcyclohexane	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Heptane	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Hept-1-ene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
n-Hexane	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
oct-1-ene	Category 3	-	Narcotic effects
Non-1-ene	Category 3	-	Respiratory tract irritation
Decane	Category 3	-	Narcotic effects
dodecane	Category 3	-	Respiratory tract irritation
tert-butylcyclohexane	Category 3	-	Narcotic effects
Dec-1-ene	Category 3	-	Narcotic effects
pentamethylbenzene	Category 3	-	Respiratory tract irritation
cyclopentane	Category 3	-	Narcotic effects
Toluene	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects

**Section 11. Toxicological information**

o-xylene	Category 3	-	Respiratory tract irritation
sec-butylbenzene	Category 3	-	Narcotic effects
benzene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
ethylbenzene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
cumene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
1,2,3-Trimethylbenzene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
1,2,3,4-Tetramethylbenzene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
cis-bicyclo[4.4.0]decane	Category 3	-	Respiratory tract irritation
Hex-1-ene	Category 3	-	Narcotic effects
1-Methylcyclopentene	Category 3	-	Narcotic effects
pentane	Category 3	-	Narcotic effects
pent-1-ene	Category 3	-	Narcotic effects
2-Methylhexane	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects
2-methylheptane	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects
2-Methyloctane	Category 3	-	Narcotic effects
2-methylnonane	Category 3	-	Narcotic effects

**Specific target organ toxicity (repeated exposure)**

<b>Name</b>	<b>Category</b>	<b>Route of exposure</b>	<b>Target organs</b>
nonane	Category 2	-	central nervous system (CNS)
n-Hexane	Category 2	inhalation	nervous system
Toluene	Category 2	inhalation	nervous system
benzene	Category 1	oral, inhalation	haematopoietic system
ethylbenzene	Category 2	-	hearing organs

**Aspiration hazard**

<b>Name</b>	<b>Result</b>
Testmix, Part Number CP299103	ASPIRATION HAZARD - Category 1
isopropylcyclohexane	ASPIRATION HAZARD - Category 1
Octane	ASPIRATION HAZARD - Category 1
nonane	ASPIRATION HAZARD - Category 1
Ethylcyclohexane	ASPIRATION HAZARD - Category 1
Cyclohexane	ASPIRATION HAZARD - Category 1
2-Methylpentane	ASPIRATION HAZARD - Category 1
methylcyclohexane	ASPIRATION HAZARD - Category 1
Heptane	ASPIRATION HAZARD - Category 1
Hept-1-ene	ASPIRATION HAZARD - Category 1
n-Hexane	ASPIRATION HAZARD - Category 1
oct-1-ene	ASPIRATION HAZARD - Category 1
Non-1-ene	ASPIRATION HAZARD - Category 1

## Section 11. Toxicological information

Decane	ASPIRATION HAZARD - Category 1
undecane	ASPIRATION HAZARD - Category 1
dodecane	ASPIRATION HAZARD - Category 1
tert-butylcyclohexane	ASPIRATION HAZARD - Category 1
Dec-1-ene	ASPIRATION HAZARD - Category 1
cyclopentane	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
o-xylene	ASPIRATION HAZARD - Category 1
sec-butylbenzene	ASPIRATION HAZARD - Category 1
benzene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
cumene	ASPIRATION HAZARD - Category 1
1,2,3-Trimethylbenzene	ASPIRATION HAZARD - Category 1
cis-bicyclo[4.4.0]decane	ASPIRATION HAZARD - Category 1
Hex-1-ene	ASPIRATION HAZARD - Category 1
1-Methylcyclopentene	ASPIRATION HAZARD - Category 1
pentane	ASPIRATION HAZARD - Category 1
pent-1-ene	ASPIRATION HAZARD - Category 1
2-Methylhexane	ASPIRATION HAZARD - Category 1
2-methylheptane	ASPIRATION HAZARD - Category 1
2-Methyloctane	ASPIRATION HAZARD - Category 1
2-methylnonane	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 11. Toxicological information

**Ingestion** : Adverse symptoms may include the following:  
 nausea or vomiting  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

**General** : Causes damage to organs through prolonged or repeated exposure.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : May cause genetic defects.

**Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Testmix, Part Number CP299103	7920.3	30305.0	N/A	48.6	N/A
Octane	N/A	N/A	N/A	118	N/A
nonane	N/A	N/A	N/A	17	N/A
Cyclohexane	6240	N/A	N/A	N/A	N/A
Heptane	N/A	N/A	N/A	103	N/A
n-Hexane	15840	N/A	N/A	169.2	N/A
cyclopentane	11400	N/A	N/A	N/A	N/A
Toluene	636	N/A	N/A	49	N/A
o-xylene	3000	1100	N/A	11	N/A
sec-butylbenzene	6300	N/A	N/A	N/A	N/A
benzene	930	N/A	N/A	N/A	N/A
ethylbenzene	3500	N/A	N/A	11	N/A
cumene	1400	N/A	N/A	N/A	39
1,2,3,4-Tetramethylbenzene	6408	N/A	N/A	N/A	N/A
cis-bicyclo[4.4.0]decane	4200	5900	N/A	11	N/A
pentane	2500	N/A	N/A	364	N/A
pent-1-ene	N/A	N/A	N/A	N/A	175

## Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Ethylcyclohexane	Acute EC50 0.406 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 8800 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute NOEC 0.218 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Cyclohexane methylcyclohexane	Acute LC50 4530 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 0.326 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5800 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
Heptane n-Hexane oct-1-ene Non-1-ene	Acute LC50 375000 µg/l Fresh water	Fish - Oreochromis mossambicus	96 hours
	Acute LC50 2500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 4.8 mg/l Fresh water	Fish - Danio rerio - Young	96 hours
Decane	Acute EC50 3.2 to 10 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 mg/l Fresh water	Fish - Danio rerio - Young	96 hours
	Acute EC50 >500000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
Toluene	Acute LC50 18 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 >500 mg/l Marine water	Fish - Cyprinodon variegatus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute EC50 >433 ppm Marine water	Algae - Skeletonema costatum	96 hours
o-xylene	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
benzene	Chronic NOEC 0.74 mg/l	Daphnia - Ceriodaphnia dubia	7 days
	Acute EC50 10.7 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 1.39 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
ethylbenzene	Acute LC50 7600 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 1.57 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.714 mg/l Fresh water	Fish - Danio rerio	35 days
cumene	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9.23 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21 mg/l Marine water	Crustaceans - Artemia salina	48 hours
ethylbenzene	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Chronic EC10 >1360 mg/l Fresh water	Algae - Desmodesmus subspicatus	96 hours
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
ethylbenzene	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks
	Acute EC50 4900 µg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
cumene	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
cumene	Acute EC50 7.4 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 10.6 mg/l Fresh water	Daphnia - Daphnia magna -	48 hours

## Section 12. Ecological information

	Acute LC50 2700 µg/l Fresh water Chronic NOEC 0.35 mg/l Fresh water	Neonate Fish - Oncorhynchus mykiss Daphnia - Daphnia Magna	96 hours 21 days
--	--	--	---------------------

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
isopropylcyclohexane	OECD 310 Ready Biodegradability - CO <sub>2</sub> in Sealed Vessels (Headspace Test)	1 % - Not readily - 28 days	15 mg/l	-
Ethylcyclohexane	OECD 301C Ready Biodegradability - Modified MITI Test (I)	0 % - Not readily - 28 days	-	-
2-Methylpentane	OECD 301C Ready Biodegradability - Modified MITI Test (I)	93 to 94 % - Readily - 28 days	-	Activated sludge
methylcyclohexane	OECD 301D Ready Biodegradability - Closed Bottle Test	0 % - Not readily - 28 days	2.45 mg/l	-
cyclopentane	OECD 301F Ready Biodegradability - Manometric Respirometry Test	0 % - Not readily - 28 days	50.31 mg/l	Activated sludge
o-xylene	OECD 301F Ready Biodegradability - Manometric Respirometry Test	98 % - Readily - 28 days	-	-
ethylbenzene	ISO	70 to 80 % - Readily - 28 days	-	Activated sludge
pentane	OECD 301F Ready Biodegradability - Manometric Respirometry Test	87 % - Readily - 28 days	-	Activated sludge

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
isopropylcyclohexane	-	-	Not readily
Octane	-	-	Readily
nonane	-	-	Readily
Ethylcyclohexane	-	-	Not readily
Cyclohexane	-	-	Readily
2-Methylpentane	-	-	Readily
methylcyclohexane	-	-	Not readily
Heptane	-	-	Readily
n-Hexane	-	-	Readily
oct-1-ene	-	-	Readily

## Section 12. Ecological information

Decane	-	-	Readily
undecane	-	-	Readily
dodecane	-	-	Readily
Dec-1-ene	-	-	Readily
cyclopentane	-	-	Not readily
Toluene	-	-	Readily
o-xylene	-	-	Readily
benzene	-	-	Readily
ethylbenzene	-	-	Readily
cumene	-	-	Not readily
Hex-1-ene	-	-	Readily
pentane	-	-	Readily
pent-1-ene	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Isopropylcyclohexane	6	-	high
Octane	5.18	198.7	low
nonane	5.65	105	low
Ethylcyclohexane	4.56	-	high
Cyclohexane	3.44	167	low
methylcyclohexane	3.61	186.21	low
Heptane	4.66	552	high
Hept-1-ene	3.99	-	low
n-Hexane	4	501.187	high
oct-1-ene	4.47	3.1	low
Non-1-ene	5.15	1479.11	high
Decane	5.86	-	high
undecane	6.42	-	high
dodecane	6.98	239.88	low
tert-butylcyclohexane	5.04	-	high
Dec-1-ene	5.12	3.65	low
pentamethylbenzene	4.56	-	high
cyclopentane	3	70.8	low
Toluene	2.73	90	low
o-xylene	3.12	8.1 to 25.9	low
sec-butylbenzene	4.57	-	high
benzene	2.13	11	low
ethylbenzene	3.6	-	low
cumene	3.55	35.48	low
1,2,3-Trimethylbenzene	3.66	194.98	low
1,2,3,4-Tetramethylbenzene	4	-	high
cis-bicyclo[4.4.0]decane	-	1621.81	high
Hex-1-ene	3.87	2.59	low
pentane	3.45	171	low
pent-1-ene	2.66	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**12.5 Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Cyclohexane (l)	110-82-7	Listed	U056
Toluene	108-88-3	Listed	U220
Xylene	95-47-6	Listed	U239
Benzene (l,T)	71-43-2	Listed	U019
Cumene (l)	98-82-8	Listed	U055

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

**DOT / TDG / Mexico / IMDG / IATA** : Not regulated.

### Additional information

**Remarks:** De minimis quantities

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**U.S. Federal regulations** : TSCA 4(a) final test rules: nonane; 2-Methyloctane  
 TSCA 8(a) PAIR: nonane; methylcyclohexane; Heptane; cyclopentane; pentane  
 TSCA 8(a) CDR Exempt/Partial exemption: Not determined  
 TSCA 12(b) one-time export: nonane  
 Clean Water Act (CWA) 307: Toluene; benzene; ethylbenzene  
 Clean Water Act (CWA) 311: Cyclohexane; Toluene; o-xylene; benzene; ethylbenzene  
 Clean Air Act (CAA) 112 regulated flammable substances: pentane; pent-1-ene

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

#### SARA 302/304

##### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

#### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 2  
 SKIN IRRITATION - Category 2  
 EYE IRRITATION - Category 2A  
 GERM CELL MUTAGENICITY - Category 1  
 CARCINOGENICITY - Category 1A  
 TOXIC TO REPRODUCTION - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
 ASPIRATION HAZARD - Category 1

##### Composition/information on ingredients

Name	%	Classification
isopropylcyclohexane	≤5	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Octane	≤5	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
nonane	≤5	ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

## Section 15. Regulatory information

Ethylcyclohexane	≤5	<p>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            HNOC - Defatting irritant            FLAMMABLE LIQUIDS - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            HNOC - Defatting irritant</p>
Cyclohexane	≤5	<p>FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2A            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2A</p>
2-Methylpentane	≤5	<p>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2A            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid</p>
methylcyclohexane	≤5	<p>FLAMMABLE LIQUIDS - Category 2            EYE IRRITATION - Category 2B            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            HNOC - Defatting irritant</p>
Heptane	≤5	<p>FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2A            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid            HNOC - Defatting irritant</p>
Hept-1-ene	≤5	<p>FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2A            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid</p>
n-Hexane	<5	<p>FLAMMABLE LIQUIDS - Category 2            SKIN IRRITATION - Category 2            EYE IRRITATION - Category 2B            TOXIC TO REPRODUCTION - Category 2            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid</p>
oct-1-ene	≤5	<p>FLAMMABLE LIQUIDS - Category 2            SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3            ASPIRATION HAZARD - Category 1            HNOC - Static-accumulating flammable liquid</p>

## Section 15. Regulatory information

Non-1-ene	≤5	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
Decane	≤5	HNOC - Static-accumulating flammable liquid FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
undecane	≤5	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 4 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
dodecane	≤5	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
tert-butylcyclohexane	≤5	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
Dec-1-ene	≤3	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
pentamethylbenzene	≤3	HNOC - Defatting irritant FLAMMABLE SOLIDS - Category 1 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
cyclopentane	≤3	FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
Toluene	≤3	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
o-xylene	≤3	ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid

## Section 15. Regulatory information

sec-butylbenzene	≤3	FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
benzene	≤3	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1 HNOC - Defatting irritant
ethylbenzene	≤3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid HNOC - Defatting irritant
cumene	≤3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid HNOC - Defatting irritant
1,2,3-Trimethylbenzene	≤3	FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
1,2,3,4-Tetramethylbenzene	≤3	FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
cis-bicyclo[4.4.0]decane	≤3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
Hex-1-ene	≤3	FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid HNOC - Defatting irritant
1-Methylcyclopentene	≤3	FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid

## Section 15. Regulatory information

pentane	≤1.5	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
pent-1-ene	≤3	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
2-Methylhexane	≤3	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
2-methylheptane	≤3	HNOC - Defatting irritant FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
2-Methyloctane	≤3	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid HNOC - Defatting irritant
2-methylnonane	≤3	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid HNOC - Defatting irritant

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	Cyclohexane	110-82-7	≤5
	n-Hexane	110-54-3	<5
	Toluene	108-88-3	≤3
	o-xylene	95-47-6	≤3
	benzene	71-43-2	≤3
	ethylbenzene	100-41-4	≤3
	cumene	98-82-8	≤3
<b>Supplier notification</b>	Cyclohexane	110-82-7	≤5
	n-Hexane	110-54-3	<5
	Toluene	108-88-3	≤3
	o-xylene	95-47-6	≤3
	benzene	71-43-2	≤3
	ethylbenzene	100-41-4	≤3
	cumene	98-82-8	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

## Section 15. Regulatory information

- Massachusetts** : The following components are listed: OCTANE; NONANE; ETHYL CYCLOHEXANE; CYCLOHEXANE; ISOHEXANE; METHYLCYCLOHEXANE; HEPTANE; HEXANE; 1-OCTENE; CYCLOPENTANE; TOLUENE; O-XYLENE; SEC-BUTYLBENZENE; BENZENE; ETHYL BENZENE; CUMENE; TRIMETHYL BENZENE; DECAHYDRONAPHTHALENE; 1-HEXENE; PENTANE; 1-PENTENE; ISOHEPTANE; 2-METHYLOCTANE
- New York** : The following components are listed: Cyclohexane; Hexane; Toluene; o-Xylene; Benzene; Ethylbenzene; Cumene
- New Jersey** : The following components are listed: OCTANE; NONANE; ETHYLCYCLOHEXANE; CYCLOHEXANE; 2-METHYLPENTANE; METHYLCYCLOHEXANE; n-HEPTANE; n-HEXANE; DECANE; UNDECANE; CYCLOPENTANE; TOLUENE; o-XYLENE; BENZENE; ETHYL BENZENE; CUMENE; TRIMETHYL BENZENE (mixed isomers); 1-HEXENE; PENTANE; 1-PENTENE
- Pennsylvania** : The following components are listed: OCTANE; NONANE; CYCLOHEXANE, ETHYL-; CYCLOHEXANE; PENTANE, 2-METHYL-; CYCLOHEXANE, METHYL-; HEPTANE; 1-HEPTENE; HEXANE; 1-OCTENE; DECANE; CYCLOPENTANE; BENZENE, METHYL-; BENZENE, 1,2-DIMETHYL-; BENZENE, (1-METHYLPROPYL)-; BENZENE; BENZENE, ETHYL-; BENZENE, (1-METHYLETHYL)-; 1-HEXENE; PENTANE; 1-PENTENE; HEXANE, 2-METHYL-; OCTANE, 2-METHYL-

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Ethylbenzene and cumene, which are known to the State of California to cause cancer, and n-hexane and Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Ingredient name	No significant risk level	Maximum acceptable dosage level
n-hexane	-	Yes.
Toluene	-	Yes.
Benzene	Yes.	Yes.
Ethylbenzene	Yes.	-
cumene	-	-

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.


#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

- Australia** : Not determined.
- Canada** : Not determined.
- China** : Not determined.
- Eurasian Economic Union** : **Russian Federation inventory:** All components are listed or exempted.

## Section 15. Regulatory information

<b>Japan</b>	: <b>Japan inventory (CSCL):</b> Not determined. <b>Japan inventory (ISHL):</b> Not determined.
<b>New Zealand</b>	: Not determined.
<b>Philippines</b>	: Not determined.
<b>Republic of Korea</b>	: Not determined.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: Not determined.
<b>Turkey</b>	: Not determined.
<b>United States</b>	: Not determined.
<b>Viet Nam</b>	:  All components are listed or exempted.

## Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
GERM CELL MUTAGENICITY - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method
ASPIRATION HAZARD - Category 1	Expert judgment
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

### History

<b>Date of issue</b>	: 04/26/2023
<b>Date of previous issue</b>	: 12/23/2021
<b>Version</b>	: 8

### Key to abbreviations

: ATE = Acute Toxicity Estimate
: BCF = Bioconcentration Factor
: GHS = Globally Harmonized System of Classification and Labelling of Chemicals
: IATA = International Air Transport Association
: IBC = Intermediate Bulk Container
: IMDG = International Maritime Dangerous Goods
: LogPow = logarithm of the octanol/water partition coefficient
: MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
: N/A = Not available
: UN = United Nations

 Indicates information that has changed from previously issued version.

### Notice to reader

**Disclaimer:** The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.