

SAFETY DATA SHEET

AFREGELMIX Gasahol Analyzer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AFREGELMIX Gasahol Analyzer
Part no. : CP80262

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemistry Laboratory Use
50 ml
Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Agilent Technologies LDA UK Ltd.
5500 Lakeside Cheadle Royal Business Park,
Cheadle, Cheshire, SK8 3GR
United Kingdom
Tel: +44 (0) 345 712 5292
e-mail address of person responsible for this SDS : pdl-msds_author@agilent.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation) : CHEMTREC®: +44 20 3807 3798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

H225	FLAMMABLE LIQUIDS	Category 2
H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects)	Category 3
H304	ASPIRATION HAZARD	Category 1
H411	LONG-TERM (CHRONIC) AQUATIC HAZARD	Category 2

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

AFREGELMIX Gasahol Analyzer

SECTION 2: Hazards identification

- Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
- Response** : P391 - Collect spillage.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : pentane
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
pentane	EC: 203-692-4 CAS: 109-66-0 Index: 601-006-00-1	≥90	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1] [2]
2-methoxy-2-methylbutane	EC: 213-611-4 CAS: 994-05-8 Index: 603-213-00-2	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H302 STOT SE 3, H336	[1]
tert-butyl methyl ether	EC: 216-653-1 CAS: 1634-04-4 Index: 603-181-00-X	≤3	Flam. Liq. 2, H225 Skin Irrit. 2, H315	[1] [2]
n-Heptane	EC: 205-563-8 CAS: 142-82-5 Index: 601-008-00-2	≤3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1] [2]
cyclohexane	EC: 203-806-2	<1	Flam. Liq. 2, H225	[1] [2]

AFREGELMIX Gasahol Analyzer

SECTION 3: Composition/information on ingredients

	CAS: 110-82-7 Index: 601-017-00-1		Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.
--	--------------------------------------	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

AFREGELMIX Gasahol Analyzer

SECTION 4: First aid measures

- Skin contact** : No specific data.
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

AFREGELMIX Gasahol Analyzer

SECTION 6: Accidental release measures

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Avoid release to the environment. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Do not swallow.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E2	5000 tonnes 200 tonnes	50000 tonnes 500 tonnes

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific solutions : Not available.

AFREGELMIX Gasahol Analyzer

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
pentane	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 600 ppm. TWA 8 hours: 1800 mg/m ³ .
tert-butyl methyl ether	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 367 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 183.5 mg/m ³ . STEL 15 minutes: 100 ppm.
heptane	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 500 ppm. TWA 8 hours: 2085 mg/m ³ .
cyclohexane	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 1050 mg/m ³ . STEL 15 minutes: 300 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 350 mg/m ³ .

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
pentane	DNEL - General population - Long term - Oral 214 mg/kg bw/day
	DNEL - General population - Long term - Dermal 214 mg/kg bw/day
	DNEL - Workers - Long term - Dermal 432 mg/kg bw/day
	DNEL - General population - Long term - Inhalation 643 mg/m ³
	DNEL - Workers - Long term - Inhalation 3000 mg/m ³
2-methoxy-2-methylbutane	DNEL - General population - Long term - Oral 1 mg/kg bw/day
	DNEL - General population - Long term - Inhalation 26.5 mg/m ³
	DNEL - Workers - Long term - Inhalation 88.8 mg/m ³
	DNEL - General population - Short term - Inhalation 212 mg/m ³
	DNEL - Workers - Short term - Inhalation 353.3 mg/m ³
	DNEL - General population - Long term - Dermal 961 mg/kg bw/day
tert-butyl methyl ether	DNEL - Workers - Long term - Dermal 1601 mg/kg bw/day
	DNEL - General population - Long term - Oral 7.1 mg/kg bw/day
	DNEL - General population - Long term - Inhalation 53.6 mg/m ³
	DNEL - Workers - Long term - Inhalation 178.5 mg/m ³

SECTION 8: Exposure controls/personal protection

	DNEL - General population - Short term - Inhalation	214 mg/m ³
	DNEL - Workers - Short term - Inhalation	357 mg/m ³
	DNEL - General population - Long term - Dermal	3570 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	5100 mg/kg bw/day
heptane	DNEL - General population - Long term - Oral	149 mg/kg bw/day
	DNEL - General population - Long term - Dermal	149 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	300 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	447 mg/m ³
	DNEL - Workers - Long term - Inhalation	2085 mg/m ³
cyclohexane	DNEL - General population - Long term - Oral	59.4 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	206 mg/m ³
	DNEL - General population - Long term - Inhalation	206 mg/m ³
	DNEL - General population - Short term - Inhalation	412 mg/m ³
	DNEL - General population - Short term - Inhalation	412 mg/m ³
	DNEL - Workers - Long term - Inhalation	700 mg/m ³
	DNEL - Workers - Long term - Inhalation	700 mg/m ³
	DNEL - General population - Long term - Dermal	1186 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	1400 mg/m ³
	DNEL - Workers - Short term - Inhalation	1400 mg/m ³
	DNEL - Workers - Long term - Dermal	2016 mg/kg bw/day

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

AFREGELMIX Gasahol Analyzer

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to British Standard BS EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid. [Clear.]
- Colour** : Colourless.
- Odour** : Characteristic. Gasoline-like
- Odour threshold** : Not available.
- Melting point/freezing point** : -130°C
- Initial boiling point and boiling range** : 36°C
- Flammability** : Not applicable.
- Lower and upper explosion limit/flammability limit** : Lower: 1.5%
Upper: 7.8%
- Flash point** : Closed cup: -50°C
- Auto-ignition temperature** : 260°C
- Decomposition temperature** : Not available.
- pH** : Not available.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Solubility	Media	Result
	Water	Insoluble

- Partition coefficient: n-octanol/water** : Not applicable.
- Vapour pressure** : 56.8 kPa (426 mm Hg)

AFREGELMIX Gasahol Analyzer

SECTION 9: Physical and chemical properties

Relative density : 0.63
Density : 0.63 g/cm³
Vapour density : 2.5 [Air = 1]

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.
Oxidising properties : Not available.

9.2.2 Other safety characteristics

Miscible with water : No.
Evaporation rate : 28.6 (butyl acetate = 1)
Physical/chemical properties comments : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
 oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name

Result

pentane	Rat - Male, Female - Oral - LD50	>2000 mg/kg
	Rat - Inhalation - LC50 Vapour	364 g/m ³ [4 hours]
2-methoxy-2-methylbutane	Rat - Oral - LD50	1602 mg/kg
tert-butyl methyl ether	Rat - Oral - LD50	4 g/kg
	Rat - Inhalation - LC50 Vapour	23576 ppm [4 hours]
	Rat - Inhalation - LC50 Vapour	41000 mg/m ³ [4 hours]
heptane	Rat - Inhalation - LC50 Vapour	103 g/m ³ [4 hours]
	Rat - Inhalation - LC50 Vapour	48000 ppm [4 hours]
cyclohexane	Rat - Oral - LD50	6240 mg/kg
	Rabbit - Dermal - LD50	>5500 mg/kg
	Rat - Male, Female - Inhalation - LC50 Vapour	>32880 mg/m ³ [4 hours]

Conclusion/Summary : Not available.

[Product]

Acute toxicity estimates

AFREGELMIX Gasahol Analyzer

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AFREGELMIX Gasahol Analyzer	123230.8	N/A	N/A	N/A	N/A
pentane	N/A	N/A	N/A	364	N/A
2-methoxy-2-methylbutane	1602	N/A	N/A	N/A	N/A
tert-butyl methyl ether	4000	N/A	N/A	41	N/A
heptane	N/A	N/A	N/A	103	N/A
cyclohexane	6240	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

Result

2-methoxy-2-methylbutane

Rabbit - Skin - Severe irritant

Duration of treatment/
exposure: 4 hours
Amount/concentration
applied: 500 uL

Conclusion/Summary : Repeated exposure may cause skin dryness or cracking.
[Product]

Serious eye damage/eye irritation

Product/ingredient name

Result

2-methoxy-2-methylbutane

Rabbit - Eyes - Severe irritant

Duration of treatment/
exposure: 24 hours
Amount/concentration
applied: 100 uL
Amount/concentration
applied: 0.1 MI

cyclohexane

Rabbit - Eyes - Severe irritant

Conclusion/Summary : Not available.
[Product]

Respiratory corrosion/irritation

Conclusion/Summary : Not available.
[Product]

Respiratory or skin sensitization

Skin

Conclusion/Summary : Not available.
[Product]

Respiratory

Conclusion/Summary : Not available.
[Product]

Germ cell mutagenicity

Conclusion/Summary : Not available.
[Product]

Carcinogenicity

Conclusion/Summary : Not available.
[Product]

Reproductive toxicity

Conclusion/Summary : Not available.
[Product]

SECTION 11: Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
pentane	STOT SE 3, H336 (Narcotic effects)
2-methoxy-2-methylbutane	STOT SE 3, H336 (Narcotic effects)
heptane	STOT SE 3, H336 (Narcotic effects)
cyclohexane	STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
AFREGELMIX Gasahol Analyzer	ASPIRATION HAZARD - Category 1
pentane	ASPIRATION HAZARD - Category 1
heptane	ASPIRATION HAZARD - Category 1
cyclohexane	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	: Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

AFREGELMIX Gasahol Analyzer

SECTION 11: Toxicological information

- Conclusion/Summary [Product]** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result		
2-methoxy-2-methylbutane	Acute - LC50 - Fresh water	-	-
	Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>		
	>100 mg/l [96 hours] Mortality		
	Acute - EC50 - Fresh water	-	-
	Daphnia - Water flea - <i>Daphnia magna</i>		
	>100 mg/l [48 hours] Intoxication		
tert-butyl methyl ether	Chronic - NOEC EPA Crustaceans	-	-
	3.39 mg/l [28 days]		
	Acute - NOEC - Fresh water	-	-
OECD Algae			
77 mg/l [72 hours]			
tert-butyl methyl ether	Acute - EC50 - Fresh water	-	-
	OECD Algae		
	230 mg/l [72 hours]		
tert-butyl methyl ether	Acute - LC50 - Fresh water	-	-
	Fish - Fathead minnow - <i>Pimephales promelas</i>		
	Age: 33 days		
	672 mg/l [96 hours] Mortality		
	Acute - EC50 - Fresh water	-	-
	EPA 850.1010 Daphnia		
472 mg/l [48 hours]			
tert-butyl methyl ether	Chronic - NOEC - Marine water	-	-
	EPA 850.1300 Daphnia		
	26 mg/l [28 days]		
tert-butyl methyl ether	Chronic - NOEC - Fresh water	-	-

AFREGELMIX Gasahol Analyzer

SECTION 12: Ecological information

	water STDMETH, ASTM and USEPA E1241-92 Fish 3.04 mg/l [21 days]		
heptane	Acute - LC50 - Fresh water Fish - Mozambique tilapia - <i>Oreochromis mossambicus</i> Size: 99 mm; Weight: 10 g 375 mg/l [96 hours] Mortality	-	-
cyclohexane	Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> Age: 30 days; Size: 20.5 mm; Weight: 0.119 g 4530 µg/l [96 hours] Mortality	-	-

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name	Result		
pentane	OECD [Ready Biodegradability - Manometric Respirometry Test]	87% [28 days] - Readily	Aerobic
2-methoxy-2-methylbutane	OECD [Ready Biodegradability - Closed Bottle Test]	4% [28 days] - Readily	-
tert-butyl methyl ether	OECD [Ready Biodegradability - Closed Bottle Test]	0% [28 days] - Not readily	Aerobic

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pentane	-	-	Readily
2-methoxy-2-methylbutane	-	-	Not readily
tert-butyl methyl ether	-	50%; 3.2 day(s)	Not readily
heptane	-	-	Readily
cyclohexane	-	-	Readily

12.3 Bioaccumulative potential

AFREGELMIX Gasahol Analyzer

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
pentane	3.45	171	Low
2-methoxy-2-methylbutane	1.55	-	Low
tert-butyl methyl ether	1.04	1.5	Low
heptane	4.66	552	High
cyclohexane	3.44	167	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
pentane	1.5	34.1828
2-methoxy-2-methylbutane	1.7	53.372
tert-butyl methyl ether	1.3	18.7752
heptane	2.5	321.749
cyclohexane	2	96.5031

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
pentane	No	No	No	No	No	No	No
2-methoxy-2-methylbutane	No	No	No	No	No	No	No
tert-butyl methyl ether	No	No	No	No	No	No	No
heptane	No	No	No	No	No	No	No
cyclohexane	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
pentane	No	N/A	No	No	No	N/A	No
2-methoxy-2-methylbutane	No	N/A	N/A	No	N/A	N/A	N/A
tert-butyl methyl ether	No	N/A	No	No	No	N/A	No
heptane	No	N/A	No	No	No	N/A	No
cyclohexane	No	N/A	No	No	No	N/A	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
pentane	No	No	No	No	No	No	No
2-methoxy-2-methylbutane	No	No	No	No	No	No	No
tert-butyl methyl ether	No	No	No	No	No	No	No
heptane	No	No	No	No	No	No	No
cyclohexane	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

AFREGELMIX Gasahol Analyzer

SECTION 12: Ecological information

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. The generation of waste should be avoided or minimised wherever possible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.






Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (pentane, tert-Butyl methyl ether)	FLAMMABLE LIQUID, N.O.S. (pentane, tert-Butyl methyl ether)	Flammable liquid, n.o.s. (pentane, tert-Butyl methyl ether)
14.3 Transport hazard class(es)	3  	3  	3 
14.4 Packing group	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Hazard identification number 33
Limited quantity 1 L
Special provisions 601, 274, 640D
Tunnel code (D/E)

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-E, _S-E_
Special provisions 274

AFREGELMIX Gasahol Analyzer

SECTION 14: Transport information

- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353.
 Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.
Special provisions A3
- 14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Transport in bulk according to IMO instruments** : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

None of the components are listed / The components are not impacted by a restriction

Labelling : Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E2

EU regulations

- Industrial emissions (integrated pollution prevention and control) - Air** : Not listed
- Industrial emissions (integrated pollution prevention and control) - Water** : Not listed
- 15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments might still be required.

AFREGELMIX Gasahol Analyzer

SECTION 15: Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States : All components are active or exempted.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	On basis of test data Calculation method Expert judgment Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

AFREGELMIX Gasahol Analyzer

SECTION 16: Other information

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 24/09/2025

Date of previous issue : 23/12/2022

Version : 5

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.