

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

### 1 Identification

- **Product identifier**
- **Trade name:** VOC Standard with MTBE (1X1 mL)
- **Part number:** DWM-596-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Agilent Technologies, Inc.  
 5301 Stevens Creek Blvd.  
 Santa Clara, CA 95051 USA
- **Information department:**  
 Telephone: 800-227-9770  
 e-mail: pdl-msds\_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 1)

**· Hazard pictograms****· Signal word Danger****· Hazard-determining components of labeling:**

methanol  
1,2-dibromo-3-chloropropane  
benzene  
1,1,2,2-tetrachloroethane  
(Z)-1,3-dichloropropene  
trans-1,3-dichloropropene  
tetrachloroethylene  
carbon tetrachloride

**· Hazard statements**

Highly flammable liquid and vapor.  
Harmful in contact with skin.  
Toxic if inhaled.  
May cause an allergic skin reaction.  
May cause genetic defects.  
May cause cancer.  
May damage fertility or the unborn child.  
Causes damage to organs.  
May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
Call a poison center/doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*1

Fire = 3

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:**

87-68-3	hexachlorobuta-1,3-diene
87-61-6	1,2,3-trichlorobenzene
120-82-1	1,2,4-trichlorobenzene

- **vPvB:**

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-56-1	methanol	86.096%
75-27-4	bromodichloromethane	0.253%
67-66-3	trichloromethane	0.253%
96-12-8	1,2-dibromo-3-chloropropane	0.253%
106-93-4	1,2-dibromoethane	0.253%
10061-01-5	(Z)-1,3-dichloropropene	0.253%
10061-02-6	trans-1,3-dichloropropene	0.253%
106-46-7	1,4-dichlorobenzene	0.253%
87-68-3	hexachlorobuta-1,3-diene	0.253%
630-20-6	1,1,1,2-Tetrachloroethane	0.253%
79-34-5	1,1,2,2-tetrachloroethane	0.253%
87-61-6	1,2,3-trichlorobenzene	0.253%
96-18-4	1,2,3-trichloropropane	0.253%
120-82-1	1,2,4-trichlorobenzene	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
91-20-3	naphthalene	0.253%

(Contd. on page 4)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 3)

127-18-4	tetrachloroethylene	0.253%
103-65-1	propylbenzene	0.253%
71-43-2	benzene	0.253%
108-88-3	toluene	0.253%
100-41-4	ethylbenzene	0.253%
98-82-8	cumene	0.253%
100-42-5	styrene	0.253%
75-09-2	dichloromethane	0.253%
56-23-5	carbon tetrachloride	0.253%
107-06-2	1,2-dichloroethane	0.253%
71-55-6	1,1,1-trichloroethane	0.253%
79-01-6	trichloroethylene	0.253%

#### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

US

(Contd. on page 5)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 4)

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-56-1	methanol	530 ppm
74-97-5	bromochloromethane	600 ppm
75-27-4	bromodichloromethane	1.3 mg/m <sup>3</sup>
75-25-2	bromoform	1.5 ppm
67-66-3	trichloromethane	2 ppm
104-51-8	butylbenzene	3.6 ppm
135-98-8	2-Phenylbutane	1.2 ppm
98-06-6	tert-butylbenzene	1.7 ppm
1634-04-4	tert-butyl methyl ether	50 ppm
95-49-8	2-chlorotoluene	75 ppm
106-43-4	4-chlorotoluene	1.2 ppm
96-12-8	1,2-dibromo-3-chloropropane	0.003 ppm
74-95-3	dibromomethane	3 ppm
124-48-1	dibromochloromethane	1.1 mg/m <sup>3</sup>
99-87-6	p-cymene	120 mg/m <sup>3</sup>
106-93-4	1,2-dibromoethane	17 ppm
594-20-7	2,2-dichloropropane	2.6 ppm
563-58-6	1,1-dichloropropene	1.3 ppm
142-28-9	1,3-dichloropropane	5.4 ppm
95-50-1	1,2-dichlorobenzene	50 ppm
541-73-1	1,3-dichlorobenzene	6 ppm
106-46-7	1,4-dichlorobenzene	30 ppm
156-60-5	trans-dichloroethylene	280 ppm
75-34-3	1,1-dichloroethane	300 ppm
156-59-2	cis-dichloroethylene	140 ppm
75-35-4	1,1-dichloroethylene	45 ppm
87-68-3	hexachlorobuta-1,3-diene	1 ppm
630-20-6	1,1,1,2-Tetrachloroethane	0.2 ppm

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 5)

79-34-5	1,1,2,2-tetrachloroethane	3 ppm
87-61-6	1,2,3-trichlorobenzene	15 mg/m <sup>3</sup>

**· PAC-2:**

67-56-1	methanol	2,100 ppm
74-97-5	bromochloromethane	830 ppm
75-27-4	bromodichloromethane	14 mg/m <sup>3</sup>
75-25-2	bromoform	6.8 ppm
67-66-3	trichloromethane	64 ppm
104-51-8	butylbenzene	40 ppm
135-98-8	2-Phenylbutane	13 ppm
98-06-6	tert-butylbenzene	18 ppm
1634-04-4	tert-butyl methyl ether	570 ppm
95-49-8	2-chlorotoluene	310 ppm
106-43-4	4-chlorotoluene	13 ppm
96-12-8	1,2-dibromo-3-chloropropane	2.2 ppm
74-95-3	dibromomethane	33 ppm
124-48-1	dibromochloromethane	12 mg/m <sup>3</sup>
99-87-6	p-cymene	1,300 mg/m <sup>3</sup>
106-93-4	1,2-dibromoethane	24 ppm
594-20-7	2,2-dichloropropane	29 ppm
563-58-6	1,1-dichloropropene	15 ppm
142-28-9	1,3-dichloropropane	59 ppm
95-50-1	1,2-dichlorobenzene	170 ppm
541-73-1	1,3-dichlorobenzene	66 ppm
106-46-7	1,4-dichlorobenzene	170 ppm
156-60-5	trans-dichloroethylene	1,000 ppm
75-34-3	1,1-dichloroethane	670 ppm
156-59-2	cis-dichloroethylene	500 ppm
75-35-4	1,1-dichloroethylene	500 ppm
87-68-3	hexachlorobuta-1,3-diene	3 ppm
630-20-6	1,1,1,2-Tetrachloroethane	2.2 ppm
79-34-5	1,1,2,2-tetrachloroethane	120 ppm
87-61-6	1,2,3-trichlorobenzene	60 mg/m <sup>3</sup>

**· PAC-3:**

67-56-1	methanol	7200* ppm
74-97-5	bromochloromethane	5,000 ppm
75-27-4	bromodichloromethane	85 mg/m <sup>3</sup>
75-25-2	bromoform	41 ppm
67-66-3	trichloromethane	3,200 ppm
104-51-8	butylbenzene	240 ppm
135-98-8	2-Phenylbutane	81 ppm

(Contd. on page 7)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 6)

98-06-6	tert-butylbenzene	110 ppm
1634-04-4	tert-butyl methyl ether	5300* ppm
95-49-8	2-chlorotoluene	1,800 ppm
106-43-4	4-chlorotoluene	80 ppm
96-12-8	1,2-dibromo-3-chloropropane	4.3 ppm
74-95-3	dibromomethane	200 ppm
124-48-1	dibromochloromethane	73 mg/m <sup>3</sup>
99-87-6	p-cymene	1,900 mg/m <sup>3</sup>
106-93-4	1,2-dibromoethane	46 ppm
594-20-7	2,2-dichloropropane	170 ppm
563-58-6	1,1-dichloropropene	87 ppm
142-28-9	1,3-dichloropropane	350 ppm
95-50-1	1,2-dichlorobenzene	1,000 ppm
541-73-1	1,3-dichlorobenzene	400 ppm
106-46-7	1,4-dichlorobenzene	1,000 ppm
156-60-5	trans-dichloroethylene	1,700 ppm
75-34-3	1,1-dichloroethane	4,000 ppm
156-59-2	cis-dichloroethylene	850 ppm
75-35-4	1,1-dichloroethylene	1,000 ppm
87-68-3	hexachlorobuta-1,3-diene	10 ppm
630-20-6	1,1,1,2-Tetrachloroethane	13 ppm
79-34-5	1,1,2,2-tetrachloroethane	150 ppm
87-61-6	1,2,3-trichlorobenzene	360 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 8)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

 · **Specific end use(s)** No further relevant information available.

(Contd. of page 7)

## 8 Exposure controls/personal protection

 · **Additional information about design of technical systems:** No further data; see item 7.

 · **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**
**67-56-1 methanol**

 PEL Long-term value: 260 mg/m<sup>3</sup>, 200 ppm

 REL Short-term value: 325 mg/m<sup>3</sup>, 250 ppm  
 Long-term value: 260 mg/m<sup>3</sup>, 200 ppm  
 Skin

 TLV Short-term value: 328 mg/m<sup>3</sup>, 250 ppm  
 Long-term value: 262 mg/m<sup>3</sup>, 200 ppm  
 Skin; BEI

**67-66-3 trichloromethane**

 PEL Ceiling limit value: 240 mg/m<sup>3</sup>, 50 ppm

 REL Short-term value: 9.78\* mg/m<sup>3</sup>, 2\* ppm  
 \*60-min; See Pocket Guide App. A

 TLV Long-term value: 49 mg/m<sup>3</sup>, 10 ppm

**96-12-8 1,2-dibromo-3-chloropropane**

 PEL Long-term value: 0.001 ppm  
 see 29 CFR 1910.1044

REL See Pocket Guide App. A

**106-93-4 1,2-dibromoethane**

 PEL Long-term value: 20 ppm  
 Ceiling limit value: 30; 50\* ppm  
 \*5-min peak per 8-hr shift

 REL Long-term value: 0.045 ppm  
 Ceiling limit value: 0.13\* ppm  
 \*15-min; See Pocket Guide App. A

TLV Skin

**106-46-7 1,4-dichlorobenzene**

 PEL Long-term value: 450 mg/m<sup>3</sup>, 75 ppm

REL See Pocket Guide App. A

 TLV Long-term value: 60 mg/m<sup>3</sup>, 10 ppm

**87-68-3 hexachlorobuta-1,3-diene**

 REL Long-term value: 0.24 mg/m<sup>3</sup>, 0.02 ppm  
 Skin; See Pocket Guide App. A

 TLV Long-term value: 0.21 mg/m<sup>3</sup>, 0.02 ppm  
 Skin

**630-20-6 1,1,1,2-Tetrachloroethane**

REL Handle with caution; See Pocket Guide App. C

(Contd. on page 9)



## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 8)

**79-34-5 1,1,2,2-tetrachloroethane**

PEL	Long-term value: 35 mg/m <sup>3</sup> , 5 ppm Skin
REL	Long-term value: 7 mg/m <sup>3</sup> , 1 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 6.9 mg/m <sup>3</sup> , 1 ppm Skin

**96-18-4 1,2,3-trichloropropane**

PEL	Long-term value: 300 mg/m <sup>3</sup> , 50 ppm
REL	Long-term value: 60 mg/m <sup>3</sup> , 10 ppm Skin, See Pocket Guide App. A
TLV	Long-term value: 0.03 mg/m <sup>3</sup> , 0.005 ppm

**120-82-1 1,2,4-trichlorobenzene**

REL	Ceiling limit value: 40 mg/m <sup>3</sup> , 5 ppm
TLV	Ceiling limit value: 37 mg/m <sup>3</sup> , 5 ppm

**79-00-5 1,1,2-trichloroethane**

PEL	Long-term value: 45 mg/m <sup>3</sup> , 10 ppm Skin
REL	Long-term value: 45 mg/m <sup>3</sup> , 10 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 55 mg/m <sup>3</sup> , 10 ppm Skin

**91-20-3 naphthalene**

PEL	Long-term value: 50 mg/m <sup>3</sup> , 10 ppm
REL	Short-term value: 75 mg/m <sup>3</sup> , 15 ppm Long-term value: 50 mg/m <sup>3</sup> , 10 ppm
TLV	Long-term value: 52 mg/m <sup>3</sup> , 10 ppm Skin; BEI

**127-18-4 tetrachloroethylene**

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
REL	Minimize workplace exp. concs.; Pocket Guide App. A
TLV	Short-term value: 685 mg/m <sup>3</sup> , 100 ppm Long-term value: 170 mg/m <sup>3</sup> , 25 ppm BEI

**71-43-2 benzene**

PEL	Short-term value: 15* mg/m <sup>3</sup> , 5* ppm Long-term value: 3* mg/m <sup>3</sup> , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: 8 mg/m <sup>3</sup> , 2.5 ppm Long-term value: 1.6 mg/m <sup>3</sup> , 0.5 ppm Skin; BEI

(Contd. on page 10)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 9)

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

**98-82-8 cumene**

PEL	Long-term value: 245 mg/m <sup>3</sup> , 50 ppm Skin
REL	Long-term value: 245 mg/m <sup>3</sup> , 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m <sup>3</sup> , (50) NIC-0.1 ppm NIC-A3

**100-42-5 styrene**

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: (170) mg/m <sup>3</sup> , (40) ppm Long-term value: (85) NIC-8.5 mg/m <sup>3</sup> , (20) NIC-2 ppm BEI, NIC-A3, NIC-OTO

**75-09-2 dichloromethane**

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m <sup>3</sup> , 50 ppm BEI

**56-23-5 carbon tetrachloride**

PEL	Long-term value: 10 ppm Ceiling limit value: 25; 200* ppm *5-min peak in any 4 hrs
REL	Short-term value: 12.6* mg/m <sup>3</sup> , 2* ppm *60-min; See Pocket Guide App. A
TLV	Short-term value: 63 mg/m <sup>3</sup> , 10 ppm Long-term value: 31 mg/m <sup>3</sup> , 5 ppm Skin

(Contd. on page 11)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 10)

**107-06-2 1,2-dichloroethane**

PEL	Long-term value: 50 ppm Ceiling limit value: 100; 200* ppm *5-min peak in any 3 hrs
REL	Short-term value: 8 mg/m <sup>3</sup> , 2 ppm Long-term value: 4 mg/m <sup>3</sup> , 1 ppm See Pocket Guide Apps. A and C
TLV	Long-term value: 40 mg/m <sup>3</sup> , 10 ppm

**71-55-6 1,1,1-trichloroethane**

PEL	Long-term value: 1900 mg/m <sup>3</sup> , 350 ppm
REL	Ceiling limit value: 1900* mg/m <sup>3</sup> , 350* ppm *15-min; See Pocket Guide App. C
TLV	Short-term value: 2460 mg/m <sup>3</sup> , 450 ppm Long-term value: 1910 mg/m <sup>3</sup> , 350 ppm BEI

**79-01-6 trichloroethylene**

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 2 hrs
REL	See Pocket Guide Apps. A and C
TLV	Short-term value: 135 mg/m <sup>3</sup> , 25 ppm Long-term value: 54 mg/m <sup>3</sup> , 10 ppm BEI

**Ingredients with biological limit values:**
**67-56-1 methanol**

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

**127-18-4 tetrachloroethylene**

BEI	3 ppm Medium: end-exhaled air Time: prior to shift Parameter: Tetrachloroethylene
	0.5 mg/L Medium: blood Time: prior to shift Parameter: Tetrachloroethylene

(Contd. on page 12)

US

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 11)

**71-43-2 benzene**

BEI 25 µg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: S-Phenylmercapturic acid (background)

500 µg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: t,t-Muconic acid (background)

**108-88-3 toluene**

BEI 0.02 mg/L  
 Medium: blood  
 Time: prior to last shift of workweek  
 Parameter: Toluene

0.03 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Toluene

0.3 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: o-Cresol with hydrolysis (background)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

**100-42-5 styrene**

BEI 400 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

0.2 mg/L  
 Medium: venous blood  
 Time: end of shift  
 Parameter: Styrene (semi-quantitative)

**75-09-2 dichloromethane**

BEI 0.3 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Dichloromethane (semi-quantitative)

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 12)

**71-55-6 1,1,1-trichloroethane**

BEI	40 ppm Medium: end-exhaled air Time: prior to last shift of workweek Parameter: Methyl chloroform  10 mg/L Medium: urine Time: end of workweek Parameter: Trichloroacetic acid (nonspecific, semi-quantitative)  30 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Total trichloroethanol (nonspecific, semi-quantitative)  1 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Total trichloroethanol (nonspecific)
-----	---

**79-01-6 trichloroethylene**

BEI	15 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)  0.5 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethanol without hydrolysis (nonspecific)  - Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)  - Medium: end-exhaled air Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

(Contd. on page 14)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 13)

- **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

- **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Fluid

**Color:** According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 64 °C (147.2 °F)

- **Flash point:** 9 °C (48.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 455 °C (851 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

**Lower:** 5.5 Vol %

(Contd. on page 15)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 14)

<b>Upper:</b>	44 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	100 hPa (75 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.87191 g/cm <sup>3</sup> (7.27609 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	93.4 %
<b>VOC content:</b>	92.67 %
	808.0 g/l / 6.74 lb/gal
· <b>Solids content:</b>	0.8 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

**LD/LC50 values that are relevant for classification:**
**ATE (Acute Toxicity Estimate)**

Oral	LD50	6,156 mg/kg
Dermal	LD50	1,550 mg/kg
Inhalative	LC50/4 h	3.39 mg/L

**67-56-1 methanol**

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

(Contd. on page 16)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 15)

<b>75-27-4 bromodichloromethane</b>		
Oral	LD50	450 mg/kg (mouse)
<b>67-66-3 trichloromethane</b>		
Oral	LD50	908 mg/kg (rat)
Dermal	LD50	75 mg/kg (rat) >20,000 mg/kg (rabbit)
<b>96-12-8 1,2-dibromo-3-chloropropane</b>		
Oral	LD50	170 mg/kg (rat)
Dermal	LD50	1,420 mg/kg (rat) 1,400 mg/kg (rabbit)
<b>106-93-4 1,2-dibromoethane</b>		
Oral	LD50	108 mg/kg (rat) 55 mg/kg (rabbit)
Dermal	LD50	300 mg/kg (rabbit)
<b>10061-01-5 (Z)-1,3-dichloropropene</b>		
Oral	LD50	250 mg/kg (rat)
<b>10061-02-6 trans-1,3-dichloropropene</b>		
Oral	LD50	250 mg/kg (rat)
<b>95-50-1 1,2-dichlorobenzene</b>		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
<b>106-46-7 1,4-dichlorobenzene</b>		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.07 mg/L (rat)
<b>87-68-3 hexachlorobuta-1,3-diene</b>		
Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)
<b>630-20-6 1,1,1,2-Tetrachloroethane</b>		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,100 mg/L (rat)
<b>79-34-5 1,1,2,2-tetrachloroethane</b>		
Oral	LD50	200 mg/kg (rat)
<b>87-61-6 1,2,3-trichlorobenzene</b>		
Oral	LD50	1,830 mg/kg (rat)
<b>96-18-4 1,2,3-trichloropropane</b>		
Oral	LD50	152 mg/kg (rat)
Dermal	LD50	523 mg/kg (rabbit)
Inhalative	LC50/4 h	4,800 mg/L (rat)

(Contd. on page 17)



## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 16)

**120-82-1 1,2,4-trichlorobenzene**

Oral	LD50	756 mg/kg (rat)
Dermal	LD50	6,139 mg/kg (rat)

**79-00-5 1,1,2-trichloroethane**

Oral	LD50	836 mg/kg (rat)
------	------	-----------------

**91-20-3 naphthalene**

Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat) 20,000 mg/kg (rabbit)

**127-18-4 tetrachloroethylene**

Oral	LD50	2,629 mg/kg (rat)
Inhalative	LC50/4 h	4,000 mg/L (rat)

**103-65-1 propylbenzene**

Oral	LD50	6,040 mg/kg (rat)
------	------	-------------------

**71-43-2 benzene**

Oral	LD50	3,340 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse) >8,260 mg/kg (rabbit)
Inhalative	LC50/4 h	9,980 mg/L (mouse)

**108-88-3 toluene**

Oral	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse) 28.1 mg/L (rat)

**100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,354 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/L (rat)

**98-82-8 cumene**

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/L (mouse)

**100-42-5 styrene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/L (rat)

**75-09-2 dichloromethane**

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/L (rat)

(Contd. on page 18)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 17)

**56-23-5 carbon tetrachloride**

Oral	LD50	2,350 mg/kg (rat)
Dermal	LD50	5,070 mg/kg (rat)

**107-06-2 1,2-dichloroethane**

Oral	LD50	670 mg/kg (rat)
Dermal	LD50	2,800 mg/kg (rat) 2,800 mg/kg (rabbit)

**71-55-6 1,1,1-trichloroethane**

Oral	LD50	10,300 mg/kg (rat)
------	------	--------------------

**79-01-6 trichloroethylene**

Oral	LD50	2,402 mg/kg (mouse) 4,290 mg/kg (rat)
Dermal	LD50	8,450 mg/kg (mouse)

**· Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Irritant

The product can cause inheritable damage.

**· Carcinogenic categories**
**· IARC (International Agency for Research on Cancer)**

75-27-4	bromodichloromethane	2B
75-25-2	bromoform	3
67-66-3	trichloromethane	2B
1634-04-4	tert-butyl methyl ether	3
96-12-8	1,2-dibromo-3-chloropropane	2B
124-48-1	dibromochloromethane	3
106-93-4	1,2-dibromoethane	2A
95-50-1	1,2-dichlorobenzene	3
541-73-1	1,3-dichlorobenzene	3
106-46-7	1,4-dichlorobenzene	2B
75-35-4	1,1-dichloroethylene	3
87-68-3	hexachlorobuta-1,3-diene	3
630-20-6	1,1,1,2-Tetrachloroethane	2B
79-34-5	1,1,2,2-tetrachloroethane	2B
96-18-4	1,2,3-trichloropropane	2A
95-47-6	o-xylene	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3

(Contd. on page 19)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 18)

79-00-5	1,1,2-trichloroethane	3
91-20-3	naphthalene	2B
127-18-4	tetrachloroethylene	2A
71-43-2	benzene	1
108-88-3	toluene	3
100-41-4	ethylbenzene	2B
98-82-8	cumene	2B
100-42-5	styrene	2B
75-09-2	dichloromethane	2A
56-23-5	carbon tetrachloride	2B
107-06-2	1,2-dichloroethane	2B
71-55-6	1,1,1-trichloroethane	3

**· NTP (National Toxicology Program)**

75-27-4	bromodichloromethane	R
67-66-3	trichloromethane	R
96-12-8	1,2-dibromo-3-chloropropane	R
106-93-4	1,2-dibromoethane	R
106-46-7	1,4-dichlorobenzene	R
96-18-4	1,2,3-trichloropropane	R
91-20-3	naphthalene	R
127-18-4	tetrachloroethylene	R
71-43-2	benzene	K
98-82-8	cumene	R
100-42-5	styrene	R
75-09-2	dichloromethane	R
56-23-5	carbon tetrachloride	R
107-06-2	1,2-dichloroethane	R
79-01-6	trichloroethylene	K

**· OSHA-Ca (Occupational Safety & Health Administration)**

96-12-8	1,2-dibromo-3-chloropropane	
71-43-2	benzene	
75-09-2	dichloromethane	

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 20)

US

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 19)

**· Additional ecological information:**
**· General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water  
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
 Danger to drinking water if even extremely small quantities leak into the ground.

**· Results of PBT and vPvB assessment**
**· PBT:**

87-68-3	hexachlorobuta-1,3-diene
87-61-6	1,2,3-trichlorobenzene
120-82-1	1,2,4-trichlorobenzene

**· vPvB:**

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

**· Other adverse effects** No further relevant information available.

### 13 Disposal considerations

**· Waste treatment methods**
**· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:**
**· Recommendation:** Disposal must be made according to official regulations.

### \* 14 Transport information

**· Not Regulated, De minimus Quantities** -

**· UN-Number**
**· DOT, IMDG, IATA** UN1230

**· UN proper shipping name**
**· DOT** Methanol solution  
**· IMDG, IATA** METHANOL solution

**· Transport hazard class(es)**
**· DOT**

**· Class** 3 Flammable liquids  
**· Label** 3, 6.1

(Contd. on page 21)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 20)

**· IMDG**


· **Class** 3 Flammable liquids  
 · **Label** 3/6.1

**· IATA**


· **Class** 3 Flammable liquids  
 · **Label** 3 (6.1)

· **Packing group**  
 · **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids  
 · **Danger code (Kemler):** 336  
 · **EMS Number:** F-E,S-D  
 · **Stowage Category** B  
 · **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

**· Transport/Additional information:**

· **DOT**  
 · **Quantity limitations** On passenger aircraft/rail: 1 L  
 On cargo aircraft only: 60 L

**· IMDG**

· **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1230 METHANOL SOLUTION, 3 (6.1), II

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 · **Sara**

· **Section 355 (extremely hazardous substances):**

67-66-3	trichloromethane
75-34-3	1,1-dichloroethane

(Contd. on page 22)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 21)

**Section 313 (Specific toxic chemical listings):**

67-56-1	methanol
75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
1634-04-4	tert-butyl methyl ether
96-12-8	1,2-dibromo-3-chloropropane
74-95-3	dibromomethane
106-93-4	1,2-dibromoethane
10061-02-6	trans-1,3-dichloropropene
95-50-1	1,2-dichlorobenzene
541-73-1	1,3-dichlorobenzene
106-46-7	1,4-dichlorobenzene
75-34-3	1,1-dichloroethane
75-35-4	1,1-dichloroethylene
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
96-18-4	1,2,3-trichloropropane
120-82-1	1,2,4-trichlorobenzene
95-47-6	o-xylene
108-38-3	m-xylene
106-42-3	p-xylene
79-00-5	1,1,2-trichloroethane
91-20-3	naphthalene
127-18-4	tetrachloroethylene
71-43-2	benzene
108-88-3	toluene
100-41-4	ethylbenzene
98-82-8	cumene
100-42-5	styrene

**TSCA (Toxic Substances Control Act):**

67-56-1	methanol
74-97-5	bromochloromethane
75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
104-51-8	butylbenzene
135-98-8	2-Phenylbutane
98-06-6	tert-butylbenzene
1634-04-4	tert-butyl methyl ether

(Contd. on page 23)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 22)

95-49-8	2-chlorotoluene
106-43-4	4-chlorotoluene
96-12-8	1,2-dibromo-3-chloropropane
74-95-3	dibromomethane
124-48-1	dibromochloromethane
99-87-6	p-cymene
106-93-4	1,2-dibromoethane
594-20-7	2,2-dichloropropane
142-28-9	1,3-dichloropropane
10061-02-6	trans-1,3-dichloropropene
95-50-1	1,2-dichlorobenzene
541-73-1	1,3-dichlorobenzene
106-46-7	1,4-dichlorobenzene
156-60-5	trans-dichloroethylene
75-34-3	1,1-dichloroethane
156-59-2	cis-dichloroethylene
75-35-4	1,1-dichloroethylene
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
87-61-6	1,2,3-trichlorobenzene

**· TSCA new (21st Century Act): (Substances not listed)**

75-27-4	bromodichloromethane
96-12-8	1,2-dibromo-3-chloropropane
10061-01-5	(Z)-1,3-dichloropropene
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene

**· Proposition 65**
**· Chemicals known to cause cancer:**

75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
106-46-7	1,4-dichlorobenzene
75-34-3	1,1-dichloroethane
75-35-4	1,1-dichloroethylene
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
96-18-4	1,2,3-trichloropropane

(Contd. on page 24)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 23)

79-00-5	1,1,2-trichloroethane
91-20-3	naphthalene
127-18-4	tetrachloroethylene
71-43-2	benzene
100-41-4	ethylbenzene
98-82-8	cumene
100-42-5	styrene
75-09-2	dichloromethane
56-23-5	carbon tetrachloride
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
79-01-6	trichloroethylene

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
71-43-2	benzene
79-01-6	trichloroethylene

**· Chemicals known to cause developmental toxicity:**

67-56-1	methanol
67-66-3	trichloromethane
106-93-4	1,2-dibromoethane
71-43-2	benzene
108-88-3	toluene
79-01-6	trichloroethylene

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

74-97-5	bromochloromethane	D
75-27-4	bromodichloromethane	B2
75-25-2	bromoform	B2
67-66-3	trichloromethane	B2, L, NL
124-48-1	dibromochloromethane	C
106-93-4	1,2-dibromoethane	L
95-50-1	1,2-dichlorobenzene	D
541-73-1	1,3-dichlorobenzene	D
156-60-5	trans-dichloroethylene	II
75-34-3	1,1-dichloroethane	C
156-59-2	cis-dichloroethylene	II
75-35-4	1,1-dichloroethylene	C, S (inh.), I (oral)
87-68-3	hexachlorobuta-1,3-diene	C

(Contd. on page 25)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 24)

630-20-6	1,1,1,2-Tetrachloroethane	C
79-34-5	1,1,2,2-tetrachloroethane	L
96-18-4	1,2,3-trichloropropane	L
120-82-1	1,2,4-trichlorobenzene	D
95-47-6	o-xylene	I
108-38-3	m-xylene	I
106-42-3	p-xylene	I
79-00-5	1,1,2-trichloroethane	C
91-20-3	naphthalene	C, CBD
127-18-4	tetrachloroethylene	L
71-43-2	benzene	A, K/L
108-88-3	toluene	II
100-41-4	ethylbenzene	D
98-82-8	cumene	D, CBD
108-67-8	mesitylene	II
95-63-6	1,2,4-trimethylbenzene	II
75-09-2	dichloromethane	L

**TLV (Threshold Limit Value established by ACGIH)**

75-25-2	bromoform	A3
67-66-3	trichloromethane	A3
1634-04-4	tert-butyl methyl ether	A3
106-93-4	1,2-dibromoethane	A3
95-50-1	1,2-dichlorobenzene	A4
106-46-7	1,4-dichlorobenzene	A3
75-34-3	1,1-dichloroethane	A4
75-35-4	1,1-dichloroethylene	A4
87-68-3	hexachlorobuta-1,3-diene	A3
79-34-5	1,1,2,2-tetrachloroethane	A3
96-18-4	1,2,3-trichloropropane	A3
95-47-6	o-xylene	A4
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
79-00-5	1,1,2-trichloroethane	A3
91-20-3	naphthalene	A4
127-18-4	tetrachloroethylene	A3
71-43-2	benzene	A1
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
100-42-5	styrene	A4
75-09-2	dichloromethane	A3
56-23-5	carbon tetrachloride	A2

(Contd. on page 26)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 25)

107-06-2	1,2-dichloroethane	A4
71-55-6	1,1,1-trichloroethane	A4
78-87-5	1,2-dichloropropane	A4
79-01-6	trichloroethylene	A2
108-90-7	chlorobenzene	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

67-66-3	trichloromethane
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
106-46-7	1,4-dichlorobenzene
75-35-4	1,1-dichloroethylene
87-68-3	hexachlorobuta-1,3-diene
79-34-5	1,1,2,2-tetrachloroethane
96-18-4	1,2,3-trichloropropane
79-00-5	1,1,2-trichloroethane
127-18-4	tetrachloroethylene
71-43-2	benzene
75-09-2	dichloromethane
56-23-5	carbon tetrachloride
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
79-01-6	trichloroethylene

**· National regulations:**
**· Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

**· Information about limitation of use:**

 Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
 Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

 The information contained in this document is based on Agilent's state of knowledge at the time of preparation.  
 No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

**· Department issuing SDS:** Document Control / Regulatory

**· Contact:** regulatory@ultrasci.com

**· Date of preparation / last revision** 03/28/2019 / 2

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 27)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/28/2019

Version Number 3

Reviewed on 03/23/2019

**Trade name: VOC Standard with MTBE (1X1 mL)**

(Contd. of page 26)

CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flam. Liq. 2: Flammable liquids – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 3: Acute toxicity – Category 3  
Skin Sens. 1: Skin sensitisation – Category 1  
Muta. 1B: Germ cell mutagenicity – Category 1B  
Carc. 1A: Carcinogenicity – Category 1A  
Repr. 1A: Reproductive toxicity – Category 1A  
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**\* Data compared to the previous version altered.**