

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**1 Identification**

- **Product identifier**
- **Trade name:** VOC Standard (1X1 mL)
- **Part number:** DWM-650-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA
- **Information department:**  
Telephone: 800-227-9770  
e-mail: pdl-msds\_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT SE 1 H370 Causes damage to organs.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methanol

- **Hazard statements**

Highly flammable liquid and vapor.

Toxic if inhaled.

Causes damage to organs.

(Contd. on page 2)

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 1)

**· Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF exposed: Call a POISON CENTER or doctor/physician.
- Specific treatment (see on this label).
- In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**
**· NFPA ratings (scale 0 - 4)**

**· HMIS-ratings (scale 0 - 4)**

**· Other hazards**
**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

**· Dangerous components:**

67-56-1	methanol	99.469%
---------	----------	---------

### 4 First-aid measures

**· Description of first aid measures**
**· General information:**

- Immediately remove any clothing soiled by the product.

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 2)

- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-56-1	methanol	530 ppm
74-83-9	bromomethane	19 ppm
108-90-7	chlorobenzene	10 ppm
74-87-3	chloromethane	150 ppm
95-49-8	2-chlorotoluene	75 ppm
124-48-1	dibromochloromethane	1.1 mg/m <sup>3</sup>
541-73-1	1,3-dichlorobenzene	6 ppm
75-34-3	1,1-dichloroethane	300 ppm

(Contd. on page 4)

**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 3)

107-06-2	1,2-dichloroethane	50 ppm
156-59-2	cis-dichloroethylene	140 ppm
78-87-5	1,2-dichloropropane	30 ppm
87-68-3	hexachlorobuta-1,3-diene	1 ppm
75-09-2	dichloromethane	200 ppm
71-55-6	1,1,1-trichloroethane	230 ppm
79-00-5	1,1,2-trichloroethane	30 ppm
75-69-4	trichlorofluoromethane	91 ppm
100-42-5	styrene	20 ppm
96-18-4	1,2,3-trichloropropane	0.015 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
108-38-3	m-xylene	130 ppm

**· PAC-2:**

67-56-1	methanol	2,100 ppm
74-83-9	bromomethane	210 ppm
108-90-7	chlorobenzene	150 ppm
74-87-3	chloromethane	910 ppm
95-49-8	2-chlorotoluene	310 ppm
124-48-1	dibromochloromethane	12 mg/m <sup>3</sup>
541-73-1	1,3-dichlorobenzene	66 ppm
75-34-3	1,1-dichloroethane	670 ppm
107-06-2	1,2-dichloroethane	200 ppm
156-59-2	cis-dichloroethylene	500 ppm
78-87-5	1,2-dichloropropane	220 ppm
87-68-3	hexachlorobuta-1,3-diene	3 ppm
75-09-2	dichloromethane	560 ppm
71-55-6	1,1,1-trichloroethane	600 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
75-69-4	trichlorofluoromethane	1,000 ppm
100-42-5	styrene	130 ppm
96-18-4	1,2,3-trichloropropane	170 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-38-3	m-xylene	920 ppm

**· PAC-3:**

67-56-1	methanol	7200* ppm
74-83-9	bromomethane	740 ppm
108-90-7	chlorobenzene	400 ppm
74-87-3	chloromethane	3,000 ppm
95-49-8	2-chlorotoluene	1,800 ppm
124-48-1	dibromochloromethane	73 mg/m <sup>3</sup>
541-73-1	1,3-dichlorobenzene	400 ppm

(Contd. on page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 4)

75-34-3	1,1-dichloroethane	4,000 ppm
107-06-2	1,2-dichloroethane	300 ppm
156-59-2	cis-dichloroethylene	850 ppm
78-87-5	1,2-dichloropropane	2,000 ppm
87-68-3	hexachlorobuta-1,3-diene	10 ppm
75-09-2	dichloromethane	6,900 ppm
71-55-6	1,1,1-trichloroethane	4,200 ppm
79-00-5	1,1,2-trichloroethane	500 ppm
75-69-4	trichlorofluoromethane	10,000 ppm
100-42-5	styrene	1100* ppm
96-18-4	1,2,3-trichloropropane	1,000 ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-38-3	m-xylene	2500* ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

#### 67-56-1 methanol

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm
	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
	Skin

(Contd. on page 6)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 5)

TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI
-----	--

**· Ingredients with biological limit values:**
**67-56-1 methanol**

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness  
For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour  
For direct contact with the chemical: butyl rubber: >4 hours

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	Colorless
<b>Odor:</b>	Alcohol-like

(Contd. on page 7)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 6)

· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b> <b>Melting point/Melting range:</b> <b>Boiling point/Boiling range:</b>	-98 °C (-144.4 °F) 64.7 °C (148.5 °F)
· <b>Flash point:</b>	9 °C (48.2 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	455 °C (851 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b> <b>Lower:</b> <b>Upper:</b>	5.5 Vol % 44 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	100 hPa (75 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.80301 g/cm <sup>3</sup> (6.70112 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b> <b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent content:</b> <b>Organic solvents:</b> <b>VOC content:</b>	99.7 % 99.65 % 800.2 g/l / 6.68 lb/gal
· <b>Solids content:</b>	0.0 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 8)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 7)

 · **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**
**ATE (Acute Toxicity Estimate)**

Inhalative	LC50/4 h	3.02 mg/L
------------	----------	-----------

**67-56-1 methanol**

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

 · **Primary irritant effect:**

 · **on the skin:** No irritant effect.

 · **on the eye:** No irritating effect.

 · **Sensitization:** No sensitizing effects known.

 · **Additional toxicological information:**

 The product shows the following dangers according to internally approved calculation methods for preparations:  
 Toxic

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

74-83-9	bromomethane	3
74-87-3	chloromethane	3
124-48-1	dibromochloromethane	3
541-73-1	1,3-dichlorobenzene	3
107-06-2	1,2-dichloroethane	2B
78-87-5	1,2-dichloropropane	1
87-68-3	hexachlorobuta-1,3-diene	3
75-09-2	dichloromethane	2A
71-55-6	1,1,1-trichloroethane	3
79-00-5	1,1,2-trichloroethane	3
100-42-5	styrene	2B
96-18-4	1,2,3-trichloropropane	2A
108-38-3	m-xylene	3

 · **NTP (National Toxicology Program)**

107-06-2	1,2-dichloroethane	R
75-09-2	dichloromethane	R
100-42-5	styrene	R
96-18-4	1,2,3-trichloropropane	R

(Contd. on page 9)



## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 8)

 · **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2 | dichloromethane



### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **Not Regulated, De minimus Quantities** -
- **UN-Number**
- **DOT, IMDG, IATA** UN1230
- **UN proper shipping name**
- **DOT** Methanol solution
- **IMDG, IATA** METHANOL solution
- **Transport hazard class(es)**
- **DOT**
- 

- **Class** 3 Flammable liquids

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS



Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 9)

· <b>Label</b>	3, 6.1
· <b>IMDG</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3/6.1
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3 (6.1)
· <b>Packing group</b>	II
· <b>DOT, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	336
· <b>EMS Number:</b>	F-E,S-D
· <b>Stowage Category</b>	B
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1230 METHANOL SOLUTION, 3 (6.1), II

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· <b>Section 355 (extremely hazardous substances):</b>	
74-83-9	bromomethane
75-34-3	1,1-dichloroethane

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 10)

**Section 313 (Specific toxic chemical listings):**

67-56-1	methanol
74-83-9	bromomethane
108-90-7	chlorobenzene
74-87-3	chloromethane
541-73-1	1,3-dichlorobenzene
75-34-3	1,1-dichloroethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
71-55-6	1,1,1-trichloroethane
79-00-5	1,1,2-trichloroethane
75-69-4	trichlorofluoromethane
100-42-5	styrene
96-18-4	1,2,3-trichloropropane
95-63-6	1,2,4-trimethylbenzene
108-38-3	m-xylene

**TSCA (Toxic Substances Control Act):**

67-56-1	methanol
74-83-9	bromomethane
108-90-7	chlorobenzene
74-87-3	chloromethane
95-49-8	2-chlorotoluene
124-48-1	dibromochloromethane
541-73-1	1,3-dichlorobenzene
75-34-3	1,1-dichloroethane
107-06-2	1,2-dichloroethane
156-59-2	cis-dichloroethylene
78-87-5	1,2-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
71-55-6	1,1,1-trichloroethane
79-00-5	1,1,2-trichloroethane
75-69-4	trichlorofluoromethane
100-42-5	styrene
96-18-4	1,2,3-trichloropropane
95-63-6	1,2,4-trimethylbenzene
108-38-3	m-xylene

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 11)

**· Proposition 65**
**· Chemicals known to cause cancer:**

75-34-3	1,1-dichloroethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
79-00-5	1,1,2-trichloroethane
100-42-5	styrene
96-18-4	1,2,3-trichloropropane

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

74-87-3	chloromethane
---------	---------------

**· Chemicals known to cause developmental toxicity:**

67-56-1	methanol
74-83-9	bromomethane
74-87-3	chloromethane

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

74-83-9	bromomethane	D
108-90-7	chlorobenzene	D
74-87-3	chloromethane	D, CBD
124-48-1	dibromochloromethane	C
541-73-1	1,3-dichlorobenzene	D
75-34-3	1,1-dichloroethane	C
107-06-2	1,2-dichloroethane	B2
156-59-2	cis-dichloroethylene	II
87-68-3	hexachlorobuta-1,3-diene	C
75-09-2	dichloromethane	L
71-55-6	1,1,1-trichloroethane	II
79-00-5	1,1,2-trichloroethane	C
96-18-4	1,2,3-trichloropropane	L
95-63-6	1,2,4-trimethylbenzene	II
108-38-3	m-xylene	I

**· TLV (Threshold Limit Value established by ACGIH)**

74-83-9	bromomethane	A4
108-90-7	chlorobenzene	A3
74-87-3	chloromethane	A4
75-34-3	1,1-dichloroethane	A4
107-06-2	1,2-dichloroethane	A4

(Contd. on page 13)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 12)

78-87-5	1,2-dichloropropane	A4
87-68-3	hexachlorobuta-1,3-diene	A3
75-09-2	dichloromethane	A3
71-55-6	1,1,1-trichloroethane	A4
79-00-5	1,1,2-trichloroethane	A3
75-69-4	trichlorofluoromethane	A4
100-42-5	styrene	A4
96-18-4	1,2,3-trichloropropane	A3
108-38-3	m-xylene	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

74-83-9	bromomethane
74-87-3	chloromethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
79-00-5	1,1,2-trichloroethane
96-18-4	1,2,3-trichloropropane

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

**· Date of preparation / last revision** 03/29/2019 / 1

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

**· \* Data compared to the previous version altered.**