

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** Calibration Standard (1X1 mL)
- **Part number:** DWM-660-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS07



GHS08

(Contd. on page 2)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 1)

· **Signal word** Danger· **Hazard-determining components of labeling:**

methanol
1,2,3-trichloropropane
1,1,2,2-tetrachloroethane
dichloromethane
(Z)-1,3-dichloropropene
trans-1,3-dichloropropene

· **Hazard statements**

Highly flammable liquid and vapor.
Harmful in contact with skin.
Toxic if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Call a poison center/doctor if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	*1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT:

87-68-3	hexachlorobuta-1,3-diene
87-61-6	1,2,3-trichlorobenzene
120-82-1	1,2,4-trichlorobenzene

· vPvB:

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-56-1	methanol	90.141%
75-27-4	bromodichloromethane	0.253%
75-00-3	chloroethane	0.253%
67-66-3	trichloromethane	0.253%
74-87-3	chloromethane	0.253%
10061-01-5	(Z)-1,3-dichloropropene	0.253%
10061-02-6	trans-1,3-dichloropropene	0.253%
87-68-3	hexachlorobuta-1,3-diene	0.253%
75-09-2	dichloromethane	0.253%
91-20-3	naphthalene	0.253%
103-65-1	propylbenzene	0.253%
630-20-6	1,1,1,2-Tetrachloroethane	0.253%
79-34-5	1,1,2,2-tetrachloroethane	0.253%
87-61-6	1,2,3-trichlorobenzene	0.253%
120-82-1	1,2,4-trichlorobenzene	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
96-18-4	1,2,3-trichloropropane	0.253%
98-82-8	cumene	0.253%

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 3)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 Remove breathing apparatus only after contaminated clothing have been completely removed.
 In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
 Supply fresh air or oxygen; call for doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

 · **PAC-1:**

67-56-1	methanol	530 ppm
108-86-1	bromobenzene	0.96 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 4)

74-97-5	bromochloromethane	600 ppm
75-27-4	bromodichloromethane	1.3 mg/m ³
75-25-2	bromoform	1.5 ppm
74-83-9	bromomethane	19 ppm
104-51-8	butylbenzene	3.6 ppm
135-98-8	2-Phenylbutane	1.2 ppm
98-06-6	tert-butylbenzene	1.7 ppm
75-00-3	chloroethane	300 ppm
67-66-3	trichloromethane	2 ppm
74-87-3	chloromethane	150 ppm
95-49-8	2-chlorotoluene	75 ppm
106-43-4	4-chlorotoluene	1.2 ppm
124-48-1	dibromochloromethane	1.1 mg/m ³
74-95-3	dibromomethane	3 ppm
541-73-1	1,3-dichlorobenzene	6 ppm
75-71-8	dichlorodifluoromethane	3,000 ppm
75-34-3	1,1-dichloroethane	300 ppm
78-87-5	1,2-dichloropropane	30 ppm
142-28-9	1,3-dichloropropane	5.4 ppm
594-20-7	2,2-dichloropropane	2.6 ppm
563-58-6	1,1-dichloropropene	1.3 ppm
87-68-3	hexachlorobuta-1,3-diene	1 ppm
75-09-2	dichloromethane	200 ppm
91-20-3	naphthalene	15 ppm
103-65-1	propylbenzene	3.7 ppm
630-20-6	1,1,1,2-Tetrachloroethane	0.2 ppm
79-34-5	1,1,2,2-tetrachloroethane	3 ppm
87-61-6	1,2,3-trichlorobenzene	15 mg/m ³

· PAC-2:

67-56-1	methanol	2,100 ppm
108-86-1	bromobenzene	11 ppm
74-97-5	bromochloromethane	830 ppm
75-27-4	bromodichloromethane	14 mg/m ³
75-25-2	bromoform	6.8 ppm
74-83-9	bromomethane	210 ppm
104-51-8	butylbenzene	40 ppm
135-98-8	2-Phenylbutane	13 ppm
98-06-6	tert-butylbenzene	18 ppm
75-00-3	chloroethane	5100* ppm
67-66-3	trichloromethane	64 ppm
74-87-3	chloromethane	910 ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 5)

95-49-8	2-chlorotoluene	310 ppm
106-43-4	4-chlorotoluene	13 ppm
124-48-1	dibromochloromethane	12 mg/m ³
74-95-3	dibromomethane	33 ppm
541-73-1	1,3-dichlorobenzene	66 ppm
75-71-8	dichlorodifluoromethane	10,000 ppm
75-34-3	1,1-dichloroethane	670 ppm
78-87-5	1,2-dichloropropane	220 ppm
142-28-9	1,3-dichloropropane	59 ppm
594-20-7	2,2-dichloropropane	29 ppm
563-58-6	1,1-dichloropropene	15 ppm
87-68-3	hexachlorobuta-1,3-diene	3 ppm
75-09-2	dichloromethane	560 ppm
91-20-3	naphthalene	83 ppm
103-65-1	propylbenzene	41 ppm
630-20-6	1,1,1,2-Tetrachloroethane	2.2 ppm
79-34-5	1,1,2,2-tetrachloroethane	120 ppm
87-61-6	1,2,3-trichlorobenzene	60 mg/m ³

PAC-3:

67-56-1	methanol	7200* ppm
108-86-1	bromobenzene	240 ppm
74-97-5	bromochloromethane	5,000 ppm
75-27-4	bromodichloromethane	85 mg/m ³
75-25-2	bromoform	41 ppm
74-83-9	bromomethane	740 ppm
104-51-8	butylbenzene	240 ppm
135-98-8	2-Phenylbutane	81 ppm
98-06-6	tert-butylbenzene	110 ppm
75-00-3	chloroethane	20000** ppm
67-66-3	trichloromethane	3,200 ppm
74-87-3	chloromethane	3,000 ppm
95-49-8	2-chlorotoluene	1,800 ppm
106-43-4	4-chlorotoluene	80 ppm
124-48-1	dibromochloromethane	73 mg/m ³
74-95-3	dibromomethane	200 ppm
541-73-1	1,3-dichlorobenzene	400 ppm
75-71-8	dichlorodifluoromethane	50,000 ppm
75-34-3	1,1-dichloroethane	4,000 ppm
78-87-5	1,2-dichloropropane	2,000 ppm
142-28-9	1,3-dichloropropane	350 ppm
594-20-7	2,2-dichloropropane	170 ppm

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 6)

563-58-6	1,1-dichloropropene	87 ppm
87-68-3	hexachlorobuta-1,3-diene	10 ppm
75-09-2	dichloromethane	6,900 ppm
91-20-3	naphthalene	500 ppm
103-65-1	propylbenzene	240 ppm
630-20-6	1,1,1,2-Tetrachloroethane	13 ppm
79-34-5	1,1,2,2-tetrachloroethane	150 ppm
87-61-6	1,2,3-trichlorobenzene	360 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

67-56-1 methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

75-00-3 chloroethane

PEL	Long-term value: 2600 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 7)

REL	Handle with caution; See Pocket Guide App. C
TLV	Long-term value: 264 mg/m ³ , 100 ppm Skin
67-66-3 trichloromethane	
PEL	Ceiling limit value: 240 mg/m ³ , 50 ppm
REL	Short-term value: 9.78* mg/m ³ , 2* ppm *60-min; See Pocket Guide App. A
TLV	Long-term value: 49 mg/m ³ , 10 ppm
74-87-3 chloromethane	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
REL	See Pocket Guide App. A
TLV	Short-term value: 207 mg/m ³ , 100 ppm Long-term value: 103 mg/m ³ , 50 ppm Skin
87-68-3 hexachlorobuta-1,3-diene	
REL	Long-term value: 0.24 mg/m ³ , 0.02 ppm Skin; See Pocket Guide App. A
TLV	Long-term value: 0.21 mg/m ³ , 0.02 ppm Skin
75-09-2 dichloromethane	
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m ³ , 50 ppm BEI
91-20-3 naphthalene	
PEL	Long-term value: 50 mg/m ³ , 10 ppm
REL	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
630-20-6 1,1,1,2-Tetrachloroethane	
REL	Handle with caution; See Pocket Guide App. C
79-34-5 1,1,2,2-tetrachloroethane	
PEL	Long-term value: 35 mg/m ³ , 5 ppm Skin
REL	Long-term value: 7 mg/m ³ , 1 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 6.9 mg/m ³ , 1 ppm Skin

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 8)

120-82-1 1,2,4-trichlorobenzene
REL Ceiling limit value: 40 mg/m³, 5 ppmTLV Ceiling limit value: 37 mg/m³, 5 ppm
79-00-5 1,1,2-trichloroethane
PEL Long-term value: 45 mg/m³, 10 ppm
SkinREL Long-term value: 45 mg/m³, 10 ppm
Skin; See Pocket Guide Apps.A and CTLV Long-term value: 55 mg/m³, 10 ppm
Skin
96-18-4 1,2,3-trichloropropane
PEL Long-term value: 300 mg/m³, 50 ppmREL Long-term value: 60 mg/m³, 10 ppm
Skin, See Pocket Guide App. ATLV Long-term value: 0.03 mg/m³, 0.005 ppm
98-82-8 cumene
PEL Long-term value: 245 mg/m³, 50 ppm
SkinREL Long-term value: 245 mg/m³, 50 ppm
SkinTLV Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm
NIC-A3
· Ingredients with biological limit values:
67-56-1 methanol
BEI 15 mg/L
Medium: urine
Time: end of shift
Parameter: Methanol (background, nonspecific)
75-09-2 dichloromethane
BEI 0.3 mg/L
Medium: urine
Time: end of shift
Parameter: Dichloromethane (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 9)

device/equipment with appropriate organic or acid gas cartridge.

- **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)

- **Flash point:** 9 °C (48.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 455 °C (851 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	5.5 Vol %
Upper:	44 Vol %

- **Vapor pressure at 20 °C (68 °F):** 100 hPa (75 mm Hg)

- **Density at 20 °C (68 °F):** 0.8558 g/cm³ (7.14165 lbs/gal)

- **Relative density** Not determined.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 10)

· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	93.9 %
VOC content:	93.43 %
	799.5 g/l / 6.67 lb/gal
Solids content:	0.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	9,922 mg/kg
Dermal	LD50	1,720 mg/kg
Inhalative	LC50/4 h	3.26 mg/L

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

75-27-4 bromodichloromethane

Oral	LD50	450 mg/kg (mouse)
------	------	-------------------

74-83-9 bromomethane

Oral	LD50	214 mg/kg (rat)
Inhalative	LC50/4 h	302 mg/L (rat)

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 11)

75-00-3 chloroethane		
Inhalative	LC50/4 h	>19,000 mg/L (rat)
67-66-3 trichloromethane		
Oral	LD50	908 mg/kg (rat)
Dermal	LD50	75 mg/kg (rat) >20,000 mg/kg (rabbit)
74-87-3 chloromethane		
Oral	LD50	1,800 mg/kg (rat)
Inhalative	LC50/4 h	>21,800 mg/L (rat)
10061-01-5 (Z)-1,3-dichloropropene		
Oral	LD50	250 mg/kg (rat)
10061-02-6 trans-1,3-dichloropropene		
Oral	LD50	250 mg/kg (rat)
87-68-3 hexachlorobuta-1,3-diene		
Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)
75-09-2 dichloromethane		
Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/L (rat)
91-20-3 naphthalene		
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat) 20,000 mg/kg (rabbit)
103-65-1 propylbenzene		
Oral	LD50	6,040 mg/kg (rat)
630-20-6 1,1,1,2-Tetrachloroethane		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,100 mg/L (rat)
79-34-5 1,1,2,2-tetrachloroethane		
Oral	LD50	200 mg/kg (rat)
87-61-6 1,2,3-trichlorobenzene		
Oral	LD50	1,830 mg/kg (rat)
120-82-1 1,2,4-trichlorobenzene		
Oral	LD50	756 mg/kg (rat)
Dermal	LD50	6,139 mg/kg (rat)
79-00-5 1,1,2-trichloroethane		
Oral	LD50	836 mg/kg (rat)

(Contd. on page 13)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 12)

75-69-4 trichlorofluoromethane		
Oral	LD50	>15,000 mg/kg (rat)
96-18-4 1,2,3-trichloropropane		
Oral	LD50	152 mg/kg (rat)
Dermal	LD50	523 mg/kg (rabbit)
Inhalative	LC50/4 h	4,800 mg/L (rat)
98-82-8 cumene		
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/L (mouse)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

75-27-4	bromodichloromethane	2B
75-25-2	bromoform	3
74-83-9	bromomethane	3
75-00-3	chloroethane	3
67-66-3	trichloromethane	2B
74-87-3	chloromethane	3
124-48-1	dibromochloromethane	3
541-73-1	1,3-dichlorobenzene	3
78-87-5	1,2-dichloropropane	1
87-68-3	hexachlorobuta-1,3-diene	3
75-09-2	dichloromethane	2A
91-20-3	naphthalene	2B
630-20-6	1,1,1,2-Tetrachloroethane	2B
79-34-5	1,1,2,2-tetrachloroethane	2B
79-00-5	1,1,2-trichloroethane	3
96-18-4	1,2,3-trichloropropane	2A
98-82-8	cumene	2B

- **NTP (National Toxicology Program)**

75-27-4	bromodichloromethane	R
67-66-3	trichloromethane	R
75-09-2	dichloromethane	R

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 13)

91-20-3	naphthalene	R
96-18-4	1,2,3-trichloropropane	R
98-82-8	cumene	R
· OSHA-Ca (Occupational Safety & Health Administration)		
75-09-2	dichloromethane	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**

· PBT:		
87-68-3	hexachlorobuta-1,3-diene	
87-61-6	1,2,3-trichlorobenzene	
120-82-1	1,2,4-trichlorobenzene	
· vPvB:		
87-68-3	hexachlorobuta-1,3-diene	

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Not Regulated, De minimus Quantities	-
· UN-Number	
· DOT, IMDG, IATA	UN1230
· UN proper shipping name	
· DOT	Methanol solution

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 14)

 · **IMDG, IATA** METHANOL solution

 · **Transport hazard class(es)**

 · **DOT**

 · **Class** 3 Flammable liquids
 · **Label** 3, 6.1

 · **IMDG**

 · **Class** 3 Flammable liquids
 · **Label** 3/6.1

 · **IATA**

 · **Class** 3 Flammable liquids
 · **Label** 3 (6.1)

 · **Packing group**

 · **DOT, IMDG, IATA** II

 · **Environmental hazards:** Not applicable.

 · **Special precautions for user** Warning: Flammable liquids
 · **Danger code (Kemler):** 336
 · **EMS Number:** F-E,S-D
 · **Stowage Category** B
 · **Stowage Code** SW2 Clear of living quarters.

 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

 · **Transport/Additional information:**

 · **DOT**

 · **Quantity limitations** On passenger aircraft/rail: 1 L
 On cargo aircraft only: 60 L

 · **IMDG**

 · **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 15)

UN "Model Regulation": UN 1230 METHANOL SOLUTION, 3 (6.1), II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

74-83-9	bromomethane
67-66-3	trichloromethane
75-34-3	1,1-dichloroethane

· Section 313 (Specific toxic chemical listings):

67-56-1	methanol
75-27-4	bromodichloromethane
75-25-2	bromoform
74-83-9	bromomethane
75-00-3	chloroethane
67-66-3	trichloromethane
74-87-3	chloromethane
74-95-3	dibromomethane
541-73-1	1,3-dichlorobenzene
75-71-8	dichlorodifluoromethane
75-34-3	1,1-dichloroethane
78-87-5	1,2-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
91-20-3	naphthalene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
120-82-1	1,2,4-trichlorobenzene
79-00-5	1,1,2-trichloroethane
75-69-4	trichlorofluoromethane
96-18-4	1,2,3-trichloropropane
95-63-6	1,2,4-trimethylbenzene
98-82-8	cumene

· TSCA (Toxic Substances Control Act):

67-56-1	methanol
108-86-1	bromobenzene
74-97-5	bromochloromethane
75-27-4	bromodichloromethane

(Contd. on page 17)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 16)

75-25-2	bromoform
74-83-9	bromomethane
104-51-8	butylbenzene
135-98-8	2-Phenylbutane
98-06-6	tert-butylbenzene
75-00-3	chloroethane
67-66-3	trichloromethane
74-87-3	chloromethane
95-49-8	2-chlorotoluene
106-43-4	4-chlorotoluene
124-48-1	dibromochloromethane
74-95-3	dibromomethane
541-73-1	1,3-dichlorobenzene
75-71-8	dichlorodifluoromethane
75-34-3	1,1-dichloroethane
78-87-5	1,2-dichloropropane
142-28-9	1,3-dichloropropane
594-20-7	2,2-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane
91-20-3	naphthalene
103-65-1	propylbenzene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
87-61-6	1,2,3-trichlorobenzene

· TSCA new (21st Century Act): (Substances not listed)

75-27-4	bromodichloromethane
10061-01-5	(Z)-1,3-dichloropropene
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene

· Proposition 65
· Chemicals known to cause cancer:

75-27-4	bromodichloromethane
75-25-2	bromoform
75-00-3	chloroethane
67-66-3	trichloromethane
75-34-3	1,1-dichloroethane
78-87-5	1,2-dichloropropane
87-68-3	hexachlorobuta-1,3-diene
75-09-2	dichloromethane

(Contd. on page 18)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 17)

91-20-3	naphthalene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
79-00-5	1,1,2-trichloroethane
96-18-4	1,2,3-trichloropropane
98-82-8	cumene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

74-87-3 chloromethane

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

74-83-9 bromomethane

67-66-3 trichloromethane

74-87-3 chloromethane

· Carcinogenic categories
· EPA (Environmental Protection Agency)

108-86-1	bromobenzene	II
74-97-5	bromochloromethane	D
75-27-4	bromodichloromethane	B2
75-25-2	bromoform	B2
74-83-9	bromomethane	D
67-66-3	trichloromethane	B2, L, NL
74-87-3	chloromethane	D, CBD
124-48-1	dibromochloromethane	C
541-73-1	1,3-dichlorobenzene	D
75-34-3	1,1-dichloroethane	C
87-68-3	hexachlorobuta-1,3-diene	C
75-09-2	dichloromethane	L
91-20-3	naphthalene	C, CBD
630-20-6	1,1,1,2-Tetrachloroethane	C
79-34-5	1,1,2,2-tetrachloroethane	L
120-82-1	1,2,4-trichlorobenzene	D
79-00-5	1,1,2-trichloroethane	C
96-18-4	1,2,3-trichloropropane	L
95-63-6	1,2,4-trimethylbenzene	II
98-82-8	cumene	D, CBD
108-67-8	mesitylene	II

· TLV (Threshold Limit Value established by ACGIH)

75-25-2	bromoform	A3
74-83-9	bromomethane	A4

(Contd. on page 19)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 18)

75-00-3	chloroethane	A3
67-66-3	trichloromethane	A3
74-87-3	chloromethane	A4
75-71-8	dichlorodifluoromethane	A4
75-34-3	1,1-dichloroethane	A4
78-87-5	1,2-dichloropropane	A4
87-68-3	hexachlorobuta-1,3-diene	A3
75-09-2	dichloromethane	A3
91-20-3	naphthalene	A4
79-34-5	1,1,2,2-tetrachloroethane	A3
79-00-5	1,1,2-trichloroethane	A3
75-69-4	trichlorofluoromethane	A4
96-18-4	1,2,3-trichloropropane	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

74-83-9	bromomethane	
67-66-3	trichloromethane	
74-87-3	chloromethane	
78-87-5	1,2-dichloropropane	
87-68-3	hexachlorobuta-1,3-diene	
75-09-2	dichloromethane	
79-34-5	1,1,2,2-tetrachloroethane	
79-00-5	1,1,2-trichloroethane	
96-18-4	1,2,3-trichloropropane	

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 03/29/2019 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 20)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 19)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

· *** Data compared to the previous version altered.**

US