

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

1 Identification

- **Product identifier**
- **Trade name:** Ethyl Methacrylate Standard (1X1 mL)
- **Part number:** EPA-1036-1
- **Relevant identified uses of the substance or mixture and uses advised against**
Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies Australia Pty Ltd
679 Springvale Road
Mulgrave
Victoria 3170, Australia
- **Further information obtainable from:**
Telephone: 1800 802 402
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: +(61) - 290372994

2 Hazard(s) Identification

- **Classification of the substance or mixture**



flame

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.



skull and crossbones

Acute toxicity - inhalation – Category 3

H331 Toxic if inhaled.



health hazard

Specific target organ toxicity (single exposure) – Category H370 Causes damage to the central nervous system and the visual organs.

- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
methanol (>60 %)
- **Hazard statements**
H225 Highly flammable liquid and vapour.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 1)

H331 Toxic if inhaled.

H370 Causes damage to the central nervous system and the visual organs.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P260 Do not breathe vapours.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P280 Wear protective gloves / protective clothing.
- P240 Ground/bond container and receiving equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

67-56-1	methanol	>60%
	 Flammable liquids – Category 2, H225;  Acute toxicity - oral – Category 3, H301; Acute toxicity - dermal – Category 3, H311; Acute toxicity - inhalation – Category 3, H331;  Specific target organ toxicity (single exposure) – Category 1, H370	
97-63-2	ethyl methacrylate	<10%
	 Flammable liquids – Category 2, H225;  Acute toxicity - oral – Category 4, H302; Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319; Skin sensitisation – Category 1, H317; Specific target organ toxicity (single exposure) – Category 3, H335	

Additional information: For the wording of the listed hazard phrases refer to section 16.

AU

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 2)

4 First Aid Measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**· After swallowing:** If symptoms persist consult doctor.**· Information for doctor:****· Most important symptoms and effects, both acute and delayed** No further relevant information available.**· Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire Fighting Measures

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet**· Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· Protective equipment: Mouth respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 3)

- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

67-56-1 methanol

WES	Short-term value: 328 mg/m ³ , 250 ppm
	Long-term value: 262 mg/m ³ , 200 ppm
Sk	

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
 When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
 Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.
- **Protection of hands:**
 Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.
- **Material of gloves**
 For normal use: nitrile rubber, 11-13 mil thickness
 For direct contact with the chemical: butyl rubber, 12-15 mil thickness
- **Penetration time of glove material**
 For normal use: nitrile rubber: 1 hour
 For direct contact with the chemical: butyl rubber: > 4 hours

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information

· Appearance:

- **Form:** Fluid
- **Colour:** Colourless
- **Odour:** Alcohol-like
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.

· Change in condition

- **Melting point/freezing point:** -98 °C
- **Initial boiling point and boiling range:** 64 °C
- **Flash point:** 9 °C
- **Flammability (solid, gas):** Highly flammable.
- **Auto-ignition temperature:** 455 °C
- **Decomposition temperature:** Not determined.
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

- **Lower:** 5.5 Vol %
- **Upper:** 44 Vol %
- **Vapour pressure at 20 °C:** 100 hPa
- **Density at 20 °C:** 0.80015 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic:** Not determined.
- **Solvent content:**
- **Organic solvents:** 99.9 %
- **VOC (EC)** 99.87 %

· **Other information** No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Toxic if inhaled.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	3 mg/L
------------	----------	--------

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

97-63-2 ethyl methacrylate

Oral	LD50	1,223 mg/kg (rat)
Inhalative	LC50/4 h	8,300 mg/L (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Causes damage to the central nervous system and the visual organs.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

AU
(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Not Regulated, De minimus Quantities	-
· UN-Number · ADG, IMDG, IATA	UN1992
· UN proper shipping name · ADG · IMDG, IATA	1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL) FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)
· Transport hazard class(es) · ADG	
 	
· Class · Label	3 Flammable liquids. 3+6.1
· IMDG	
 	
· Class · Label	3 Flammable liquids. 3/6.1
· IATA	
 	
· Class · Label	3 Flammable liquids. 3 (6.1)
· Packing group · ADG, IMDG, IATA	II
· Environmental hazards:	Not applicable.

(Contd. on page 8)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 7)

· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	336
· EMS Number:	F-E,S-D
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL), 3 (6.1), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

All ingredients are listed.

· **Standard for the Uniform Scheduling of Medicines and Poisons**

67-56-1	methanol	S5, S6, S10
97-63-2	ethyl methacrylate	S5

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

AU

(Contd. on page 9)

Safety Data Sheet

according to WHS Regulations

Printing date 25.03.2025

Revision: 25.03.2025

Trade name: Ethyl Methacrylate Standard (1X1 mL)

(Contd. of page 8)

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H370 Causes damage to organs.

· **Department issuing SDS:** Document Control / Regulatory

· **Contact:** pdl-acg-regulatory-cq@agilent.com

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flammable liquids – Category 2: Flammable liquids – Category 2

Acute toxicity - oral – Category 3: Acute toxicity – Category 3

Acute toxicity - oral – Category 4: Acute toxicity – Category 4

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Skin sensitisation – Category 1: Skin sensitisation – Category 1

Specific target organ toxicity (single exposure) – Category 1: Specific target organ toxicity (single exposure) – Category 1

Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

AU