# Safety Data Sheet according to HPR, Schedule 1

Printing date 03/28/2019

Agilent

Version Number 2

Reviewed on 03/23/2019

**1 Identification** 

· Product identifier

• Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

- · Part number: EPA-1219-1
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: 1-800-424-9300

# **2** Hazard identification

# · Classification of the substance or mixture

GHS02 Flame

Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour. GHS06 Skull and crossbones Acute Toxicity (Inhalation) - Category 3 H331 Toxic if inhaled. GHS08 Health hazard Germ Cell Mutagenicity - Category 1B H340 May cause genetic defects. Carcinogenicity - Category 1B H350 May cause cancer. Specific Target Organ Toxicity - Single Exposure -H370 Causes damage to organs. Category 1

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: methanol 2,2'-bioxirane

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet according to HPR, Schedule 1

Printing date 03/28/2019

· Hazard statements

May cause genetic defects. May cause cancer. Causes damage to organs. · Precautionary statements

Keep out of reach of children. Read label before use.

Toxic if inhaled.

Version Number 2

Reviewed on 03/23/2019

## Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

Highly flammable liquid and vapour. If medical advice is needed, have product container or label at hand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment.



## · HMIS-ratings (scale 0 - 4)



# **3** Composition/Information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

## · Dangerous components:

67-56-1 methanol

99.874% w/w
(Contd. on page 3)



- Use explosion-proof [electrical/ventilating/lighting] equipment.
- Use non-sparking tools.
- Take actions to prevent static discharges.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

- Store in a well-ventilated place. Keep cool.
- Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)

(Contd. of page 2)

0.126% w/w

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/28/2019

Reviewed on 03/23/2019

Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

1464-53-5 2,2'-bioxirane

# **4 First aid measures**

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

#### · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **5** Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

# **6** Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.





according to HPR, Schedule 1

Printing date 03/28/2019

#### Version Number 2

Reviewed on 03/23/2019

#### Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

(Contd. of page 3)

# 7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

#### · Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

# **8 Exposure controls/ Personal protection**

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

# 67-56-1 methanol

- EL Short-term value: 250 ppm Long-term value: 200 ppm Skin
- EV Short-term value: 325 mg/m<sup>3</sup>, 250 ppm Long-term value: 260 mg/m<sup>3</sup>, 200 ppm Skin

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

# · Personal protective equipment:

- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### <sup>•</sup> Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

• Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is



# Safety Data Sheet according to HPR, Schedule 1

Version Number 2

Reviewed on 03/23/2019

# Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

(Contd. of page 4) direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

# · Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

# · Penetration time of glove material

- For normal use: nitrile rubber: 1 hour
- For direct contact with the chemical: butyl rubber: >4 hours
- Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and elements</li> <li>General Information</li> </ul>	chemical properties
· Appearance:	
Form:	Fluid
Color:	Colorless
· Odor:	Alcohol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-98 °C
<b>Boiling point/Boiling range:</b>	64.7 °C
· Flash point:	9 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C:	100 hPa
· Density at 20 °C:	0.8002 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
	(Contd. on page



Printing date 03/28/2019

according to HPR, Schedule 1

Reviewed on 03/23/2019

Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	99.9 %	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

# **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

**ATE (Acute Toxicity Estimate)** 

Oral	LD50	56,962 mg/kg (mouse)
Dermal	LD50	63,291 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/L

#### 67-56-1 methanol

1464-53-5 2,2'-bioxirane		
Dermal LD50 15,80	0 mg/kg (rabbit)	
Oral LD50 5,628	mg/kg (rat)	

Oral	LD50	72 mg/kg (mouse)
Dermal	LD50	80 mg/kg (rabbit)
Inhalative	LC50/4 h	90 mg/L (rat)

#### · Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

CA



Printing date 03/28/2019

according to HPR, Schedule 1

Printing date 03/28/2019

Version Number 2

Reviewed on 03/23/2019

# Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

(Contd. of page 6)

R

Toxic The product can cause inheritable damage.

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

## · NTP (National Toxicology Program)

1464-53-5 2,2'-bioxirane

# **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- $\cdot$  Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# **13 Disposal considerations**

## · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

# **14 Transport information**

· Not Regulated, De minimus Quantit	ies -	
· UN-Number · DOT, TDG, IMDG, IATA	UN1230	
· UN proper shipping name		
·DOT	Methanol	
· TDG	1230 METHANOL	
· IMDG, IATA	METHANOL	



according to HPR, Schedule 1

Reviewed on 03/23/2019

Printing date 03/28/2019

Agilent

Version Number 2

Printing date 03/28/2019	Version Number 2	Reviewed on 03/23/2019
Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)		
		(Contd. of page 7)
· Transport hazard class(es)		
·DOT		
· Class	3 Flammable liquids	
· Label · TDG (Transport dangerous goo	3, 6.1	
· Class	3 Flammable liquids	
·Label	3+6.1	
· IMDG		
· Class · Label	3 Flammable liquids 3/6.1	
· IATA		
· Class · Label	3 Flammable liquids	

· Label 3 (6.1) · Packing group · DOT, TDG, IMDG, IATA Π Not applicable. · Environmental hazards: Warning: Flammable liquids · Special precautions for user · Danger code (Kemler): 336 • EMS Number: F-E,S-D · Stowage Category В · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L

(Contd. on page 9)

CA

according to HPR, Schedule 1

Reviewed on 03/23/2019

Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

	(Contd. of page 8
· TDG	
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
·IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1230 METHANOL, 3 (6.1), II

# **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

1464-53-5 2,2'-bioxirane

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

67-56-1 methanol

· Canadian Ingredient Disclosure list (limit 0.1%)

1464-53-5 2,2'-bioxirane · Canadian Ingredient Disclosure list (limit 1%)

All ingredients are listed.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com

· Date of the latest revision of the safety data sheet 03/28/2019 / 1

(Contd. on page 10)



Printing date 03/28/2019

# Safety Data Sheet according to HPR, Schedule 1

Reviewed on 03/23/2019

#### Trade name: 1,2:3,4-Diepoxybutane Standard (1X1 mL)

(Contd. of page 9)

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative \* **Data compared to the previous version altered.**



Printing date 03/28/2019