

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

1 Identification

- **Product identifier**
- **Trade name:** Combined F List Standard (1X1 mL)
- **Part number:** FLM-010-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 1)

· Hazard pictograms**· Signal word** Danger**· Hazard-determining components of labeling:**

methanol
benzene
nitrobenzene
2-ethoxyethanol
tetrachloroethylene
carbon tetrachloride

· Hazard statements

Highly flammable liquid and vapor.
Toxic if inhaled.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs.
May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-56-1	methanol	91.91%
79-46-9	2-nitropropane	0.253%
98-95-3	nitrobenzene	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
127-18-4	tetrachloroethylene	0.253%
71-43-2	benzene	0.253%
108-88-3	toluene	0.253%
100-41-4	ethylbenzene	0.253%
75-09-2	dichloromethane	0.253%
56-23-5	carbon tetrachloride	0.253%
71-55-6	1,1,1-trichloroethane	0.253%
79-01-6	trichloroethylene	0.253%
75-15-0	carbon disulphide	0.253%
110-80-5	2-ethoxyethanol	0.253%
108-10-1	4-methylpentan-2-one	0.253%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- Remove breathing apparatus only after contaminated clothing have been completely removed.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 3)

- In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-56-1	methanol	530 ppm
95-50-1	1,2-dichlorobenzene	50 ppm
79-46-9	2-nitropropane	30 ppm
98-95-3	nitrobenzene	3 ppm
110-86-1	pyridine	3 ppm
75-69-4	trichlorofluoromethane	91 ppm
76-13-1	1,1,2-trichlorotrifluoroethane	1,250 ppm
108-38-3	m-xylene	130 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 4)

79-00-5	1,1,2-trichloroethane	30 ppm
127-18-4	tetrachloroethylene	35 ppm
60-29-7	diethyl ether	500 ppm
78-83-1	butanol	150 ppm
71-43-2	benzene	52 ppm
108-88-3	toluene	67 ppm
100-41-4	ethylbenzene	33 ppm
75-09-2	dichloromethane	200 ppm
56-23-5	carbon tetrachloride	1.2 ppm
71-55-6	1,1,1-trichloroethane	230 ppm
79-01-6	trichloroethylene	130 ppm
108-90-7	chlorobenzene	10 ppm
75-15-0	carbon disulphide	13 ppm
71-36-3	butan-1-ol	60 ppm
110-80-5	2-ethoxyethanol	15 ppm
67-64-1	acetone	200 ppm
78-93-3	butanone	200 ppm
108-10-1	4-methylpentan-2-one	75 ppm
108-94-1	cyclohexanone	60 ppm
141-78-6	ethyl acetate	1,200 ppm

PAC-2:

67-56-1	methanol	2,100 ppm
95-50-1	1,2-dichlorobenzene	170 ppm
79-46-9	2-nitropropane	380 ppm
98-95-3	nitrobenzene	20 ppm
110-86-1	pyridine	19 ppm
75-69-4	trichlorofluoromethane	1,000 ppm
76-13-1	1,1,2-trichlorotrifluoroethane	3,900 ppm
108-38-3	m-xylene	920 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
127-18-4	tetrachloroethylene	230 ppm
60-29-7	diethyl ether	3200* ppm
78-83-1	butanol	1,300 ppm
71-43-2	benzene	800 ppm
108-88-3	toluene	560 ppm
100-41-4	ethylbenzene	1100* ppm
75-09-2	dichloromethane	560 ppm
56-23-5	carbon tetrachloride	13 ppm
71-55-6	1,1,1-trichloroethane	600 ppm
79-01-6	trichloroethylene	450 ppm
108-90-7	chlorobenzene	150 ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 5)

75-15-0	carbon disulphide	160 ppm
71-36-3	butan-1-ol	800 ppm
110-80-5	2-ethoxyethanol	1,000 ppm
67-64-1	acetone	3200* ppm
78-93-3	butanone	2700* ppm
108-10-1	4-methylpentan-2-one	500 ppm
108-94-1	cyclohexanone	830 ppm
141-78-6	ethyl acetate	1,700 ppm

PAC-3:

67-56-1	methanol	7200* ppm
95-50-1	1,2-dichlorobenzene	1,000 ppm
79-46-9	2-nitropropane	2,300 ppm
98-95-3	nitrobenzene	200 ppm
110-86-1	pyridine	3600* ppm
75-69-4	trichlorofluoromethane	10,000 ppm
76-13-1	1,1,2-trichlorotrifluoroethane	4,500 ppm
108-38-3	m-xylene	2500* ppm
79-00-5	1,1,2-trichloroethane	500 ppm
127-18-4	tetrachloroethylene	1,200 ppm
60-29-7	diethyl ether	19000*** ppm
78-83-1	butanol	8000* ppm
71-43-2	benzene	4000* ppm
108-88-3	toluene	3700* ppm
100-41-4	ethylbenzene	1800* ppm
75-09-2	dichloromethane	6,900 ppm
56-23-5	carbon tetrachloride	340 ppm
71-55-6	1,1,1-trichloroethane	4,200 ppm
79-01-6	trichloroethylene	3,800 ppm
108-90-7	chlorobenzene	400 ppm
75-15-0	carbon disulphide	480 ppm
71-36-3	butan-1-ol	8000** ppm
110-80-5	2-ethoxyethanol	6000* ppm
67-64-1	acetone	5700* ppm
78-93-3	butanone	4000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
108-94-1	cyclohexanone	5000* ppm
141-78-6	ethyl acetate	10000** ppm

US

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 6)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**
67-56-1 methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

79-46-9 2-nitropropane

PEL	Long-term value: 90 mg/m ³ , 25 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 36 mg/m ³ , 10 ppm

98-95-3 nitrobenzene

PEL	Long-term value: 5 mg/m ³ , 1 ppm Skin
REL	Long-term value: 5 mg/m ³ , 1 ppm Skin
TLV	Long-term value: 5 mg/m ³ , 1 ppm Skin; BEIm

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 7)

79-00-5 1,1,2-trichloroethane

PEL	Long-term value: 45 mg/m ³ , 10 ppm Skin
REL	Long-term value: 45 mg/m ³ , 10 ppm Skin; See Pocket Guide Apps.A and C
TLV	Long-term value: 55 mg/m ³ , 10 ppm Skin

127-18-4 tetrachloroethylene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
REL	Minimize workplace exp. concs.:Pocket Guide App. A
TLV	Short-term value: 685 mg/m ³ , 100 ppm Long-term value: 170 mg/m ³ , 25 ppm BEI

71-43-2 benzene

PEL	Short-term value: 15* mg/m ³ , 5* ppm Long-term value: 3* mg/m ³ , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: 8 mg/m ³ , 2.5 ppm Long-term value: 1.6 mg/m ³ , 0.5 ppm Skin; BEI

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

75-09-2 dichloromethane

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 8)

TLV Long-term value: 174 mg/m³, 50 ppm
BEI

56-23-5 carbon tetrachloride

PEL Long-term value: 10 ppm
Ceiling limit value: 25; 200* ppm
*5-min peak in any 4 hrs

REL Short-term value: 12.6* mg/m³, 2* ppm
*60-min; See Pocket Guide App. A

TLV Short-term value: 63 mg/m³, 10 ppm
Long-term value: 31 mg/m³, 5 ppm
Skin

71-55-6 1,1,1-trichloroethane

PEL Long-term value: 1900 mg/m³, 350 ppm

REL Ceiling limit value: 1900* mg/m³, 350* ppm
*15-min; See Pocket Guide App. C

TLV Short-term value: 2460 mg/m³, 450 ppm
Long-term value: 1910 mg/m³, 350 ppm
BEI

79-01-6 trichloroethylene

PEL Long-term value: 100 ppm
Ceiling limit value: 200; 300* ppm
*5-min peak in any 2 hrs

REL See Pocket Guide Apps. A and C

TLV Short-term value: 135 mg/m³, 25 ppm
Long-term value: 54 mg/m³, 10 ppm
BEI

75-15-0 carbon disulphide

PEL Long-term value: 20 ppm
Ceiling limit value: 30; 100* ppm
*30-min peak per 8-hr shift

REL Short-term value: 30 mg/m³, 10 ppm
Long-term value: 3 mg/m³, 1 ppm
Skin

TLV Long-term value: 3.13 mg/m³, 1 ppm
Skin, BEI

110-80-5 2-ethoxyethanol

PEL Long-term value: 740 mg/m³, 200 ppm
Skin

REL Long-term value: 1.8 mg/m³, 0.5 ppm
Skin

TLV Long-term value: 18 mg/m³, 5 ppm
Skin; BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 9)

REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

Ingredients with biological limit values:
67-56-1 methanol

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

98-95-3 nitrobenzene

BEI	5 mg/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Total p-nitrophenol (nonspecific)
	1.5 % of hemoglobin Medium: blood Time: end of shift Parameter: Methemoglobin (background, nonspecific, semi-quantitative)

127-18-4 tetrachloroethylene

BEI	3 ppm Medium: end-exhaled air Time: prior to shift Parameter: Tetrachloroethylene
	0.5 mg/L Medium: blood Time: prior to shift Parameter: Tetrachloroethylene

71-43-2 benzene

BEI	25 µg/g creatinine Medium: urine Time: end of shift Parameter: S-Phenylmercapturic acid (background)
	500 µg/g creatinine Medium: urine Time: end of shift Parameter: t,t-Muconic acid (background)

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 10)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

75-09-2 dichloromethane

BEI 0.3 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Dichloromethane (semi-quantitative)

71-55-6 1,1,1-trichloroethane

BEI 40 ppm
 Medium: end-exhaled air
 Time: prior to last shift of workweek
 Parameter: Methyl chloroform

10 mg/L
 Medium: urine
 Time: end of workweek
 Parameter: Trichloroacetic acid (nonspecific, semi-quantitative)

30 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Total trichloroethanol (nonspecific, semi-quantitative)

1 mg/L
 Medium: blood
 Time: end of shift at end of workweek
 Parameter: Total trichloroethanol (nonspecific)

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 11)

79-01-6 trichloroethylene

BEI	15 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)
	0.5 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethanol without hydrolysis (nonspecific)
	- Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)
	- Medium: end-exhaled air Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)

75-15-0 carbon disulphide

BEI	0.5 mg/g creatinine Medium: urine Time: end of shift Parameter: 2-Thioxothiazolidine-4-carboxylic acid (background, nonspecific)
-----	---

110-80-5 2-ethoxyethanol

BEI	100 mg/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: 2-Ethoxyacetic acid
-----	---

108-10-1 4-methylpentan-2-one

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 12)

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)

· Flash point: 9 °C (48.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44 Vol %

· Vapor pressure at 20 °C (68 °F): 100 hPa (75 mm Hg)

· Density at 20 °C (68 °F): 0.82235 g/cm³ (6.86251 lbs/gal)

· Relative density Not determined.

· Vapor density Not determined.

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 13)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	98.2 %
VOC content:	96.71 % 795.3 g/l / 6.64 lb/gal
Solids content:	0.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	9,189 mg/kg (rat)
Dermal	LD50	>4,040 mg/kg
Inhalative	LC50/4 h	>3.26 mg/L

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

95-50-1 1,2-dichlorobenzene

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

79-46-9 2-nitropropane

Oral	LD50	500 mg/kg (rat)
------	------	-----------------

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 14)

98-95-3 nitrobenzene

Oral	LD50	390 mg/kg (rat)
Dermal	LD50	2,100 mg/kg (rat)
Inhalative	LC50/4 h	556 mg/L (rat)

75-69-4 trichlorofluoromethane

Oral	LD50	>15,000 mg/kg (rat)
------	------	---------------------

76-13-1 1,1,2-trichlorotrifluoroethane

Oral	LD50	43 mg/kg (rat)
Inhalative	LC50/4 h	52,500 mg/L (rat)

79-00-5 1,1,2-trichloroethane

Oral	LD50	836 mg/kg (rat)
------	------	-----------------

127-18-4 tetrachloroethylene

Oral	LD50	2,629 mg/kg (rat)
Inhalative	LC50/4 h	4,000 mg/L (rat)

71-43-2 benzene

Oral	LD50	3,340 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse) >8,260 mg/kg (rabbit)
Inhalative	LC50/4 h	9,980 mg/L (mouse)

108-88-3 toluene

Oral	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse) 28.1 mg/L (rat)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,354 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/L (rat)

75-09-2 dichloromethane

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/L (rat)

56-23-5 carbon tetrachloride

Oral	LD50	2,350 mg/kg (rat)
Dermal	LD50	5,070 mg/kg (rat)

71-55-6 1,1,1-trichloroethane

Oral	LD50	10,300 mg/kg (rat)
------	------	--------------------

79-01-6 trichloroethylene

Oral	LD50	2,402 mg/kg (mouse) 4,290 mg/kg (rat)
Dermal	LD50	8,450 mg/kg (mouse)

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 15)

75-15-0 carbon disulphide

Oral	LD50	1,200 mg/kg (rat)
Inhalative	LC50/4 h	10.35 mg/L (rat)

110-80-5 2-ethoxyethanol

Oral	LD50	1,746 mg/kg (rat)
Dermal	LD50	3,300 mg/kg (rat) 3,300 mg/kg (rabbit)
Inhalative	LC50/4 h	15.2 mg/L (rat)

108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab) >16,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>8.2 mg/L (rat)

· Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Irritant

The product can cause inheritable damage.

· Carcinogenic categories
· IARC (International Agency for Research on Cancer)

95-50-1	1,2-dichlorobenzene	3
79-46-9	2-nitropropane	2B
98-95-3	nitrobenzene	2B
110-86-1	pyridine	3
95-47-6	o-xylene	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3
79-00-5	1,1,2-trichloroethane	3
127-18-4	tetrachloroethylene	2A
71-43-2	benzene	1
108-88-3	toluene	3
100-41-4	ethylbenzene	2B
75-09-2	dichloromethane	2A
56-23-5	carbon tetrachloride	2B
71-55-6	1,1,1-trichloroethane	3
79-01-6	trichloroethylene	1
108-10-1	4-methylpentan-2-one	2B
108-94-1	cyclohexanone	3

(Contd. on page 17)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 16)

· NTP (National Toxicology Program)		
79-46-9	2-nitropropane	R
98-95-3	nitrobenzene	R
127-18-4	tetrachloroethylene	R
71-43-2	benzene	K
75-09-2	dichloromethane	R
56-23-5	carbon tetrachloride	R
79-01-6	trichloroethylene	K
· OSHA-Ca (Occupational Safety & Health Administration)		
71-43-2	benzene	
75-09-2	dichloromethane	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

· Not Regulated, De minimus Quantities	-
· UN-Number	
· DOT, IMDG, IATA	UN1230

(Contd. on page 18)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 17)

· **UN proper shipping name**
 · **DOT** Methanol solution
 · **IMDG, IATA** METHANOL solution

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3, 6.1

· **IMDG**



· **Class** 3 Flammable liquids
 · **Label** 3/6.1

· **IATA**



· **Class** 3 Flammable liquids
 · **Label** 3 (6.1)

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids
 · **Danger code (Kemler):** 336
 · **EMS Number:** F-E,S-D
 · **Stowage Category** B
 · **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 1 L
 On cargo aircraft only: 60 L

· **IMDG**
 · **Limited quantities (LQ)** 1L

(Contd. on page 19)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 18)

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1230 METHANOL SOLUTION, 3 (6.1), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (extremely hazardous substances):

95-48-7	o-cresol
98-95-3	nitrobenzene
75-15-0	carbon disulphide

· Section 313 (Specific toxic chemical listings):

67-56-1	methanol
95-48-7	o-cresol
108-39-4	m-cresol
106-44-5	p-cresol
95-50-1	1,2-dichlorobenzene
79-46-9	2-nitropropane
98-95-3	nitrobenzene
110-86-1	pyridine
75-69-4	trichlorofluoromethane
76-13-1	1,1,2-trichlorotrifluoroethane
95-47-6	o-xylene
108-38-3	m-xylene
106-42-3	p-xylene
79-00-5	1,1,2-trichloroethane
127-18-4	tetrachloroethylene
71-43-2	benzene
108-88-3	toluene
100-41-4	ethylbenzene
75-09-2	dichloromethane
56-23-5	carbon tetrachloride
71-55-6	1,1,1-trichloroethane
79-01-6	trichloroethylene
108-90-7	chlorobenzene
75-15-0	carbon disulphide
71-36-3	butan-1-ol
110-80-5	2-ethoxyethanol
78-93-3	butanone

(Contd. on page 20)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 19)

108-10-1	4-methylpentan-2-one
----------	----------------------

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65
· Chemicals known to cause cancer:

79-46-9	2-nitropropane
---------	----------------

98-95-3	nitrobenzene
---------	--------------

110-86-1	pyridine
----------	----------

79-00-5	1,1,2-trichloroethane
---------	-----------------------

127-18-4	tetrachloroethylene
----------	---------------------

71-43-2	benzene
---------	---------

100-41-4	ethylbenzene
----------	--------------

75-09-2	dichloromethane
---------	-----------------

56-23-5	carbon tetrachloride
---------	----------------------

79-01-6	trichloroethylene
---------	-------------------

108-10-1	4-methylpentan-2-one
----------	----------------------

· Chemicals known to cause reproductive toxicity for females:

75-15-0	carbon disulphide
---------	-------------------

· Chemicals known to cause reproductive toxicity for males:

98-95-3	nitrobenzene
---------	--------------

71-43-2	benzene
---------	---------

79-01-6	trichloroethylene
---------	-------------------

75-15-0	carbon disulphide
---------	-------------------

110-80-5	2-ethoxyethanol
----------	-----------------

· Chemicals known to cause developmental toxicity:

67-56-1	methanol
---------	----------

71-43-2	benzene
---------	---------

108-88-3	toluene
----------	---------

79-01-6	trichloroethylene
---------	-------------------

75-15-0	carbon disulphide
---------	-------------------

110-80-5	2-ethoxyethanol
----------	-----------------

108-10-1	4-methylpentan-2-one
----------	----------------------

· Carcinogenic categories
· EPA (Environmental Protection Agency)

95-48-7	o-cresol	C
---------	----------	---

108-39-4	m-cresol	C
----------	----------	---

106-44-5	p-cresol	C
----------	----------	---

95-50-1	1,2-dichlorobenzene	D
---------	---------------------	---

98-95-3	nitrobenzene	L
---------	--------------	---

95-47-6	o-xylene	I
---------	----------	---

108-38-3	m-xylene	I
----------	----------	---

(Contd. on page 21)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 20)

106-42-3	p-xylene	I
79-00-5	1,1,2-trichloroethane	C
127-18-4	tetrachloroethylene	L
71-43-2	benzene	A, K/L
108-88-3	toluene	II
100-41-4	ethylbenzene	D
75-09-2	dichloromethane	L
56-23-5	carbon tetrachloride	L
71-55-6	1,1,1-trichloroethane	II
79-01-6	trichloroethylene	CaH
108-90-7	chlorobenzene	D
71-36-3	butan-1-ol	D
67-64-1	acetone	I
78-93-3	butanone	I
108-10-1	4-methylpentan-2-one	I

· TLV (Threshold Limit Value established by ACGIH)

95-50-1	1,2-dichlorobenzene	A4
79-46-9	2-nitropropane	A3
98-95-3	nitrobenzene	A3
110-86-1	pyridine	A3
75-69-4	trichlorofluoromethane	A4
76-13-1	1,1,2-trichlorotrifluoroethane	A4
95-47-6	o-xylene	A4
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
79-00-5	1,1,2-trichloroethane	A3
127-18-4	tetrachloroethylene	A3
71-43-2	benzene	A1
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
75-09-2	dichloromethane	A3
56-23-5	carbon tetrachloride	A2
71-55-6	1,1,1-trichloroethane	A4
79-01-6	trichloroethylene	A2
108-90-7	chlorobenzene	A3
75-15-0	carbon disulphide	A4
67-64-1	acetone	A4
108-94-1	cyclohexanone	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

79-46-9	2-nitropropane
79-00-5	1,1,2-trichloroethane

(Contd. on page 22)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2019

Version Number 3

Reviewed on 03/28/2019

Trade name: Combined F List Standard (1X1 mL)

(Contd. of page 21)

127-18-4	tetrachloroethylene
71-43-2	benzene
75-09-2	dichloromethane
56-23-5	carbon tetrachloride
79-01-6	trichloroethylene

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- **Department issuing SDS:** Document Control / Regulatory
- **Contact:** regulatory@ultrasci.com
- **Date of preparation / last revision** 03/28/2019 / 2
- **Abbreviations and acronyms:**
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 1B: Germ cell mutagenicity – Category 1B
 Carc. 1A: Carcinogenicity – Category 1A
 Repr. 1B: Reproductive toxicity – Category 1B
 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- *** Data compared to the previous version altered.**