

SAFETY DATA SHEET



Glass Indicating O2 Trap

SECTION 1: Identification of the substance/mixture and of the company/undertaking

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

Product name : Glass Indicating O2 Trap
Part no. : 5182-9201, 5182-9202, 5182-9401, 5182-9402

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Analytical chemistry.
 Tube (Glass.)
 1 x 100 ml
 5182-9201 - Glass Indicating O2 Trap, 1/8"
 5182-9202 - Glass Indicating O2 Trap, 1/8", SS
 5182-9401 - Glass Indicating O2 Trap, 1/4"
 5182-9402 - Glass Indicating O2 Trap, 1/4", SS

Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Agilent Technologies LDA UK Ltd.
 5500 Lakeside Cheadle Royal Business Park,
 Cheadle, Cheshire, SK8 3GR
 United Kingdom
 Tel: +44 (0) 345 712 5292
 0800 603 1000

e-mail address of person responsible for this SDS : pdl-msds_author@agilent.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation) : CHEMTREC®: +(44)-870-8200418

SECTION 2: Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

Product definition : Mixture (encapsulated in article)

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

<input checked="" type="checkbox"/> H302	ACUTE TOXICITY (oral)	Category 4
H315	SKIN CORROSION/IRRITATION	Category 2
H318	SERIOUS EYE DAMAGE/EYE IRRITATION	Category 1
H373	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	Category 2
H400	SHORT-TERM (ACUTE) AQUATIC HAZARD	Category 1
H410	LONG-TERM (CHRONIC) AQUATIC HAZARD	Category 1

Glass Indicating O2 Trap

SECTION 2: Hazards identification

Ingredients of unknown toxicity : Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 1 - 10%
 Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 10 - 30%
 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 10 - 30%

Ingredients of unknown ecotoxicity : Contains 8.5% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 - Harmful if swallowed.
 H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
 P273 - Avoid release to the environment.
 P260 - Do not breathe dust.
 P270 - Do not eat, drink or smoke when using this product.
 P264 - Wash thoroughly after handling.

Response : P391 - Collect spillage.
 P314 - Get medical advice/attention if you feel unwell.
 P362 + P364 - Take off contaminated clothing and wash it before reuse.
 P302 + P352 - IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Glass Indicating O2 Trap

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Causes digestive tract burns.

SECTION 3: Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

3.1 Substances : Mixture (encapsulated in article)

Product/ingredient name	Identifiers	%	Classification	Type
Silicon dioxide	EC: 231-545-4 CAS: 7631-86-9	≥25 - ≤50	Not classified.	[2]
manganese dioxide	EC: 215-202-6 CAS: 1313-13-9 Index: 025-001-00-3	≥10 - ≤24	Acute Tox. 4, H302 Acute Tox. 4, H332	[1] [2]
dicopper oxide	EC: 215-270-7 CAS: 1317-39-1 Index: 029-002-00-X	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	[1] [2]
aluminium oxide	EC: 215-691-6 CAS: 1344-28-1	≥10 - ≤25	Not classified.	[2]
Talc , not containing asbestiform fibres	EC: 238-877-9 CAS: 14807-96-6	≤10	Not classified.	[2]
Calcium oxide	EC: 215-138-9 CAS: 1305-78-8	<3	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
Disodium oxide	EC: 215-208-9 CAS: 1313-59-3	≤3	Skin Corr. 1B, H314 Eye Dam. 1, H318 EUH014	[1]
crystalline silica, respirable powder	EC: 238-878-4 CAS: 14808-60-7	≤3	STOT RE 1, H372 (lungs) (inhalation)	[1] [2]
barium salts	EC: 215-127-9 CAS: 1304-28-5 Index: 056-002-00-7	≤1	Acute Tox. 4, H302 Acute Tox. 4, H332	[1] [2]
zinc oxide	EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤1	Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Additional information : May catch fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : Specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Glass Indicating O2 Trap

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
1	100 tonne	200 tonne

7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Silicon dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). [silica, amorphous] TWA: 2.4 mg/m ³ 8 hours. Form: respirable dust TWA: 6 mg/m ³ 8 hours. Form: inhalable dust
manganese dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). [manganese and its inorganic compounds] TWA: 0.2 mg/m ³ , (as Mn) 8 hours. Form: Inhalable fraction TWA: 0.05 mg/m ³ , (as Mn) 8 hours. Form: Respirable fraction
dicopper oxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). [Copper and compounds] STEL: 2 mg/m ³ , (as Cu) 15 minutes. Form: Dusts and Mists TWA: 1 mg/m ³ , (as Cu) 8 hours. Form: Dusts and Mists
aluminium oxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). [aluminium oxides] TWA: 4 mg/m ³ 8 hours. Form: respirable dust TWA: 10 mg/m ³ 8 hours. Form: inhalable dust
Talc , not containing asbestiform fibres	

Glass Indicating O2 Trap

SECTION 8: Exposure controls/personal protection

Calcium oxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 1 mg/m ³ 8 hours. Form: respirable dust
crystalline silica, respirable powder	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 1 mg/m ³ 8 hours. Form: Respirable fraction STEL: 4 mg/m ³ 15 minutes. Form: Respirable fraction TWA: 2 mg/m ³ 8 hours.
barium salts	EH40/2005 WELs (United Kingdom (UK), 1/2020). [silica, respirable crystalline] TWA: 0.1 mg/m ³ 8 hours. Form: Respirable fraction EH40/2005 WELs (United Kingdom (UK), 1/2020). [barium compounds, soluble] TWA: 0.5 mg/m ³ , (as Ba) 8 hours.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
manganese dioxide	DNEL	Long term Dermal	0.0021 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.00414 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.043 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.2 mg/m ³	Workers	Systemic
dicopper oxide	DNEL	Long term Oral	0.041 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.082 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Systemic
aluminium oxide	DNEL	Long term Dermal	137 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.75 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.75 mg/m ³	General population	Systemic
	DNEL	Long term Oral	1.32 mg/kg bw/day	General population	Systemic
Talc , not containing asbestiform fibres	DNEL	Long term Inhalation	3 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	3 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	1.08 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	1.08 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1.8 mg/m ³	General population	Local
	DNEL	Long term Inhalation	1.8 mg/m ³	General population	Local
	DNEL	Short term Inhalation	2.16 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	2.16 mg/m ³	Workers	Systemic

Glass Indicating O2 Trap

SECTION 8: Exposure controls/personal protection

Calcium oxide	DNEL	Long term Dermal	2.27 mg/cm ²	General population	Local	
	DNEL	Short term Inhalation	3.6 mg/m ³	Workers	Local	
	DNEL	Long term Inhalation	3.6 mg/m ³	Workers	Local	
	DNEL	Long term Dermal	4.54 mg/cm ²	Workers	Local	
	DNEL	Long term Dermal	21.6 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	43.2 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Oral	160 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Oral	160 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	1 mg/m ³	General population	Local	
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	4 mg/m ³	General population	Local	
	DNEL	Short term Inhalation	4 mg/m ³	Workers	Local	
	barium salts	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Systemic
	zinc oxide	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic	

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Glass Indicating O2 Trap

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Solid.
- Colour** : Not available.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flammability** : May catch fire.
- Upper/lower flammability or explosive limits** : Not applicable.
- Flash point** : Not applicable.
- Auto-ignition temperature** : 370°C
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Kinematic: Not applicable.

Solubility(ies)	Media	Result
	<input checked="" type="checkbox"/> water	Not soluble

- Partition coefficient: n-octanol/water** : Not applicable.
- Vapour pressure** : Not applicable.
- Evaporation rate** : Not available.
- Relative density** : 0.8
- Density** : 0.8 g/cm³ [20°C]
- Vapour density** : Not applicable.

Glass Indicating O2 Trap

SECTION 9: Physical and chemical properties

Explosive properties : Not available.
Oxidising properties : Not available.
Particle characteristics
Median particle size : Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : No specific data.
10.5 Incompatible materials : May react or be incompatible with oxidising materials.
10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<input checked="" type="checkbox"/> Silicon dioxide	LC50 Inhalation Dusts and mists	Rat - Male, Female	>58.8 mg/l	4 hours
manganese dioxide	LD50 Oral	Rat	3478 mg/kg	-
dicopper oxide	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
aluminium oxide	LD50 Oral	Rat	470 mg/kg	-
Calcium oxide	LD50 Oral	Rat	>10000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat - Male, Female	>6.04 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
<input checked="" type="checkbox"/> Glass Indicating O2 Trap	1322.9	N/A	N/A	89.6	5.3
manganese dioxide	500	N/A	N/A	N/A	1.5
dicopper oxide	470	N/A	N/A	11	N/A
barium salts	500	N/A	N/A	N/A	1.5

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<input checked="" type="checkbox"/> Zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

Glass Indicating O2 Trap

SECTION 11: Toxicological information

Sensitiser

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
☑ Calcium oxide	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
☑ crystalline silica, respirable powder	Category 1	inhalation	lungs

Aspiration hazard

Not available.

Information on likely routes of exposure : ☑ Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

- Inhalation** : ☑ No known significant effects or critical hazards.
- Ingestion** : ☑ Harmful if swallowed. Corrosive to the digestive tract. Causes burns.
- Skin contact** : ☑ Causes skin irritation.
- Eye contact** : ☑ Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : ☑ No specific data.
- Ingestion** : ☑ Adverse symptoms may include the following:
stomach pains
- Skin contact** : ☑ Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Eye contact** : ☑ Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.

Glass Indicating O2 Trap

SECTION 11: Toxicological information

Potential delayed effects : Not available.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Silicon dioxide	Acute EC50 2.2 g/L Fresh water	Daphnia - Water flea - Daphnia magna - Neonate	48 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - Water flea - Daphnia magna - Neonate	21 days
manganese dioxide	Acute EC50 >100 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Acute EC50 >100 mg/l Fresh water Acute LC50 >100 mg/l Fresh water Acute NOEC >100 mg/l Fresh water	Daphnia - Daphnia magna Fish - Oncorhynchus mykiss Fish - Oncorhynchus mykiss	48 hours 96 hours 96 hours
dicopper oxide	Chronic NOEC 10 mg/l Fresh water Acute EC50 0.042 mg/l Fresh water	Daphnia - Ceriodaphnia dubia Daphnia - Water flea - Daphnia similis	8 days 48 hours
	Acute LC50 350 µg/l Marine water	Crustaceans - Barnacle - Balanus improvisus - Nauplii	48 hours
aluminium oxide	Acute LC50 0.075 mg/l Fresh water Acute EC50 114.357 mg/l Fresh water	Fish - Zebra danio - Danio rerio Daphnia - Water flea - Daphnia magna - Neonate	96 hours 48 hours
	Calcium oxide	Chronic NOEC 100 mg/l Fresh water	Fish - Nile tilapia - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)
zinc oxide	Acute IC50 1.85 mg/l Marine water	Algae - Diatom - Skeletonema costatum	96 hours
	Acute LC50 98 µg/l Fresh water	Daphnia - Water flea - Daphnia magna - Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.04 mg/l Fresh water	Daphnia - Daphnia magna	21 days

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Silicon dioxide	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Calcium oxide	-	2.34	low
zinc oxide	-	28960	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Glass Indicating O2 Trap

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.







Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

	ADR/RID	IMDG	IATA
14.1 UN number	<input checked="" type="checkbox"/> UN3077	<input checked="" type="checkbox"/> UN3077	<input checked="" type="checkbox"/> UN3077
14.2 UN proper shipping name	<input checked="" type="checkbox"/> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dicopper oxide)	<input checked="" type="checkbox"/> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dicopper oxide)	<input checked="" type="checkbox"/> Environmentally hazardous substance, solid, n.o.s. (Dicopper oxide)
14.3 Transport hazard class(es)	<input checked="" type="checkbox"/>  	<input checked="" type="checkbox"/>  	<input checked="" type="checkbox"/>  
14.4 Packing group	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
14.5 Environmental hazards	Yes.	Yes.	<input checked="" type="checkbox"/> Yes.

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Hazard identification number 90

Limited quantity 5 kg

Special provisions 274, 335, 601, 375

Tunnel code (-)

Glass Indicating O2 Trap

SECTION 14: Transport information

- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Emergency schedules F-A, S-F
Special provisions 274, 335, 966, 967, 969
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Quantity limitation Passenger and Cargo Aircraft: 400 kg. Packaging instructions: 956. Cargo Aircraft Only: 400 kg. Packaging instructions: 956. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y956.
Special provisions A97, A158, A179, A197, A215
- 14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Transport in bulk according to IMO instruments** : Not available.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH**
 - Annex XIV - List of substances subject to authorisation**
 - Annex XIV**
None of the components are listed.
 - Substances of very high concern**
None of the components are listed.
 - Ozone depleting substances**
Not listed.
 - Prior Informed Consent (PIC)**
Not listed.
 - Persistent Organic Pollutants**
Not listed.
 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**
Not listed.

Label : Not applicable.

Seveso Directive
This product is controlled under the Seveso Directive.

Danger criteria

Category
1

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
crystalline silica, respirable powder	UK Occupational Exposure Limits EH40 - WEL	silica, respirable crystalline respirable fraction	Carc.	-

Glass Indicating O2 Trap

SECTION 15: Regulatory information

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments might still be required.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory : All components are listed or exempted.
Japan	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: <input checked="" type="checkbox"/> All components are listed or exempted.
Turkey	: Not determined.
United States	: <input checked="" type="checkbox"/> All components are active or exempted.
Viet Nam	: <input checked="" type="checkbox"/> All components are listed or exempted.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
-----------------------------------	---

Glass Indicating O2 Trap

SECTION 16: Other information

Procedure used to derive the classification

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH014	Reacts violently with water.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 13/01/2023

Date of previous issue : 24/10/2019

Version : 4

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.