

Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

1 Identification

· Product identifier

· Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

· Part number: HCM-530-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd.

Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

CHSU

· Signal word Danger

(Contd. on page 2)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 1)

· Hazard-determining components of labeling:

acetone

1,2-dibromo-3-chloropropane

carbon tetrachloride

1,2-dibromoethane

tetrachloroethylene

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	s components:	
67-64-1	acetone	95.45%
75-27-4	bromodichloromethane	0.253%
56-23-5	carbon tetrachloride	0.253%
67-66-3	trichloromethane	0.253%
3252-43-5	dibromoacetonitrile	0.253%
96-12-8	1,2-dibromo-3-chloropropane	0.253%
106-93-4	1,2-dibromoethane	0.253%
127-18-4	tetrachloroethylene	0.253%
71-55-6	1,1,1-trichloroethane	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
79-01-6	trichloroethylene	0.253%
96-18-4	1,2,3-trichloropropane	0.253%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

67-64-1 a 75-27-4 b	ocetone promodichloromethane	200 ppm
75-27-4 b	promodichloromethane	
		1.3 mg/m ³
75-25-2 b	oromoform	1.5 ppm
56-23-5 с	arbon tetrachloride	1.2 ppm
67-66-3 tr	richloromethane	2 ppm
76-06-2 tr	richloronitromethane	0.050 ppm
124-48-1 d	libromochloromethane	1.1 mg/m ³
96-12-8 1	,2-dibromo-3-chloropropane	0.003 ppm
106-93-4 1	,2-dibromoethane	17 ppm
127-18-4 to	etrachloroethylene	35 ppm
71-55-6 1	,1,1-trichloroethane	230 ppm
79-00-5 1	,1,2-trichloroethane	30 ppm
79-01-6 tr	richloroethylene	130 ppm
96-18-4 1	,2,3-trichloropropane	0.015 ppm

. . .



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

D + C 2		(Contd. of page
PAC-2:		Lagari
67-64-1		3200* ppi
	bromodichloromethane	14 mg/m ³
	bromoform	6.8 ppm
	carbon tetrachloride	13 ppm
	trichloromethane	64 ppm
	trichloronitromethane	0.15 ppm
	dibromochloromethane	12 mg/m³
	1,2-dibromo-3-chloropropane	2.2 ppm
	1,2-dibromoethane	24 ppm
	tetrachloroethylene	230 ppm
	1,1,1-trichloroethane	600 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
79-01-6	trichloroethylene	450 ppm
96-18-4	1,2,3-trichloropropane	170 ppm
PAC-3:		
67-64-1	acetone	5700* pp
75-27-4	bromodichloromethane	85 mg/m³
75-25-2	bromoform	41 ppm
56-23-5	carbon tetrachloride	340 ppm
67-66-3	trichloromethane	3,200 ppr
76-06-2	trichloronitromethane	1.4 ppm
124-48-1	dibromochloromethane	73 mg/m ³
96-12-8	1,2-dibromo-3-chloropropane	4.3 ppm
106-93-4	1,2-dibromoethane	46 ppm
127-18-4	tetrachloroethylene	1,200 ppi
71-55-6	1,1,1-trichloroethane	4,200 ppr
79-00-5	1,1,2-trichloroethane	500 ppm
79-01-6	trichloroethylene	3,800 ppi
	1,2,3-trichloropropane	1,000 ppr

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 5)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

	onents with limit values that require monitoring at the workplace: -1 acetone
-	
	Long-term value: 2400 mg/m³, 1000 ppm
	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI
56-23	-5 carbon tetrachloride
	Long-term value: 10 ppm Ceiling limit value: 25; 200* ppm *5-min peak in any 4 hrs
REL	Short-term value: 12.6* mg/m³, 2* ppm *60-min;See Pocket Guide App. A
TLV	Short-term value: 63 mg/m³, 10 ppm Long-term value: 31 mg/m³, 5 ppm Skin
67-66	-3 trichloromethane
PEL	Ceiling limit value: 240 mg/m³, 50 ppm
REL	Short-term value: 9.78* mg/m³, 2* ppm *60-min; See Pocket Guide App. A
TLV	Long-term value: 49 mg/m³, 10 ppm
3252-	43-5 dibromoacetonitrile
PEL	Long-term value: 5 mg/m³ as CN; Skin
96-12	-8 1,2-dibromo-3-chloropropane
PEL	Long-term value: 0.001 ppm see 29 CFR 1910.1044
REL	See Pocket Guide App. A
106-9	3-4 1,2-dibromoethane
PEL	Long-term value: 20 ppm Ceiling limit value: 30; 50* ppm *5-min peak per 8-hr shift
	(Contd. on p



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

ceiling limit value: 0.045 ppm 15-min; See Pocket Guide App. A kin -4 tetrachloroethylene ceiling limit value: 100 ppm ceiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm cong-term value: 170 mg/m³, 25 ppm
15-min; See Pocket Guide App. A kin -4 tetrachloroethylene cong-term value: 100 ppm Geiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm cong-term value: 170 mg/m³, 25 ppm
kin -4 tetrachloroethylene ong-term value: 100 ppm Seiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
-4 tetrachloroethylene ong-term value: 100 ppm ceiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
ong-term value: 100 ppm Seiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
ceiling limit value: 200; 300* ppm 5-min peak in any 3 hrs Ainimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
5-min peak in any 3 hrs Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
Minimize workplace exp. concs.;Pocket Guide App. A hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
hort-term value: 685 mg/m³, 100 ppm ong-term value: 170 mg/m³, 25 ppm
ong-term value: 170 mg/m³, 25 ppm
ong-term value: 170 mg/m³, 25 ppm
BEI
5 1,1,1-trichloroethane
ong-term value: 1900 mg/m³, 350 ppm
Ceiling limit value: 1900* mg/m³, 350* ppm
15-min; See Pocket Guide App. C
•
hort-term value: 2460 mg/m³, 450 ppm ong-term value: 1910 mg/m³, 350 ppm
SEI
5 1,1,2-trichloroethane
ong-term value: 45 mg/m³, 10 ppm
kin
ong-term value: 45 mg/m³, 10 ppm
kin; See Pocket Guide Apps.A and C
ong-term value: 55 mg/m ³ , 10 ppm
kin
ó trichloroethylene
ong-term value: 100 ppm
Ceiling limit value: 200; 300* ppm
5-min peak in any 2 hrs
ee Pocket Guide Apps. A and C
hort-term value: 135 mg/m ³ , 25 ppm
ong-term value: 54 mg/m³, 10 ppm
BEI
1,2,3-trichloropropane
ong-term value: 300 mg/m³, 50 ppm
ong-term value: 60 mg/m³, 10 ppm
kin, See Pocket Guide App. A
ong-term value: 0.03 mg/m³, 0.005 ppm
<u> </u>
ients with biological limit values:
acetone
) mg/L
edium: urine
me: end of shift
arameter: Acetone (nonspecific)
hoose iee



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 7)

127-18-4 tetrachloroethylene

BEI 3 ppm

Medium: end-exhaled air Time: prior to shift

Parameter: Tetrachloroethylene

0.5 mg/L Medium: blood Time: prior to shift

Parameter: Tetrachloroethylene

71-55-6 1,1,1-trichloroethane

BEI 40 ppm

Medium: end-exhaled air

Time: prior to last shift of workweek Parameter: Methyl chloroform

10 mg/L Medium: urine

Time: end of workweek

Parameter: Trichloroacetic acid (nonspecific, semi-quantitative)

30 mg/L Medium: urine

Time: end of shift at end of workweek

Parameter: Total trichloroethanol (nonspecific, semi-quantitative)

1 mg/L Medium: blood

Time: end of shift at end of workweek Parameter: Total trichloroethanol (nonspecific)

79-01-6 trichloroethylene

BEI 15 mg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)

0.5 mg/L Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethanol without hydrolysis (nonspecific)

-

Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

Medium: end-exhaled air

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

(Contd. on page 9)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 8)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Color: Colorless
Odor: Characteristic
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: -94.7 °C (-138.5 °F)

Boiling point/Boiling range: 55.8-56.6 °C (132.4-133.9 °F)

• Flash point: $-17 \,^{\circ}\text{C} \, (1.4 \,^{\circ}\text{F})$

(Contd. on page 10)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

	(Contd. of page
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	465 °C (869 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13 Vol %
Vapor pressure at 20 °C (68 °F):	245.3 hPa (184 mm Hg)
Density at 20 °C (68 °F):	0.791 g/cm³ (6.6009 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	32 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	97.0 %
VOC content:	1.01 %
	10.1 g/l / 0.08 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

JS -



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 10)

	<mark>ogical inf</mark> ion on toxi	cological effects
Acute tox		cological effects
	•	at are relevant for classification:
ATE (Ac	ute Toxicit	y Estimate)
Oral	LD50	9,853 mg/kg
Dermal	LD50	8,900 mg/kg
Inhalative	LC50/4 h	108 mg/L
67-64-1 a	cetone	
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
75-27-4 b	romodichl	oromethane
Oral	LD50	450 mg/kg (mouse)
56-23-5 c	arbon tetra	
Oral	LD50	2,350 mg/kg (rat)
Dermal	LD50	5,070 mg/kg (rat)
67-66-3 t	richlorome	ethane
Oral	LD50	908 mg/kg (rat)
Dermal	LD50	75 mg/kg (rat)
		>20,000 mg/kg (rabbit)
76-06-2 t	richloronit	romethane
Oral	LD50	250 mg/kg (rat)
3252-43-5	5 dibromoa	ncetonitrile
Oral	LD50	245 mg/kg (rat)
96-12-8 1	,2-dibrom	o-3-chloropropane
Oral	LD50	170 mg/kg (rat)
Dermal	LD50	1,420 mg/kg (rat)
		1,400 mg/kg (rabbit)
106-93-4	1,2-dibron	noethane
Oral	LD50	108 mg/kg (rat)
		55 mg/kg (rabbit)
Dermal	LD50	300 mg/kg (rabbit)
127-18-4	tetrachlor	·
Oral	LD50	2,629 mg/kg (rat)
		4,000 mg/L (rat)
	,1,1-trichlo	
Oral	LD50	10,300 mg/kg (rat)
79-00-5 1	,1,2-trichle	proethane



Oral

Dermal

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

2,402 mg/kg (mouse) 4,290 mg/kg (rat)

8,450 mg/kg (mouse)

(Contd. of page 11)

96-18-4 1,2,3-trichloropropane

LD50

79-01-6 trichloroethylene LD50

Oral	LD50	152 mg/kg (rat)
Dermal	LD50	523 mg/kg (rabbit)
Inhalative	LC50/4 h	4,800 mg/L (rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (In	ternational Agency for Research on Cancer)	
75-27-4	bromodichloromethane	2B
75-25-2	bromoform	3
56-23-5	carbon tetrachloride	2B
67-66-3	trichloromethane	2B
3252-43-5	dibromoacetonitrile	2B
124-48-1	dibromochloromethane	3
96-12-8	1,2-dibromo-3-chloropropane	2B
106-93-4	1,2-dibromoethane	2A
3018-12-0	dichloromethyl cyanide	3
545-06-2	trichloroacetonitrile	3
	tetrachloroethylene	2A
	1,1,1-trichloroethane	3
79-00-5	1,1,2-trichloroethane	3
79-01-6	trichloroethylene	1
96-18-4	1,2,3-trichloropropane	2A
•	ional Toxicology Program)	
75-27-4	bromodichloromethane	R
56-23-5	carbon tetrachloride	R
67-66-3	trichloromethane	R
96-12-8	1,2-dibromo-3-chloropropane	R
106-93-4	1,2-dibromoethane	R
127-18-4	tetrachloroethylene	R
79-01-6	trichloroethylene	K
96-18-4	1,2,3-trichloropropane	R
		(Contd. on page 13)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 12)

· OSHA-Ca (Occupational Safety & Health Administration)

96-12-8 1,2-dibromo-3-chloropropane

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Not Regulated, De minimus Quantities
- · UN-Number
- · **DOT, IMDG, IATA** UN1090
- · UN proper shipping name
- · DOT Acetone
 · IMDG, IATA ACETONE
- · Transport hazard class(es)
- · DOT, IMDG, IATA



Class 3 Flammable liquids

(Contd. on page 14)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

	(Contd. of page
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	E
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
(- €)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1090 ACETONE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara	
	55 (extremely hazardous substances):
67-66-3	richloromethane
· Section 3	13 (Specific toxic chemical listings):
75-27-4	bromodichloromethane
75-25-2	bromoform
56-23-5	carbon tetrachloride
67-66-3	trichloromethane
76-06-2	trichloronitromethane
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
127-18-4	tetrachloroethylene
71-55-6	1,1,1-trichloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane
	(Contd. on page 15)



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

	(Contd. of page
	oxic Substances Control Act):
	acetone
75-27-4	bromodichloromethane
	bromoform
	carbon tetrachloride
67-66-3	trichloromethane
76-06-2	trichloronitromethane
	dibromoacetonitrile
124-48-1	dibromochloromethane
	1,2-dibromo-3-chloropropane
	1,2-dibromoethane
545-06-2	trichloroacetonitrile
127-18-4	tetrachloroethylene
71-55-6	1,1,1-trichloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane
TSCA ne	w (21st Century Act): (Substances not listed)
	bromodichloromethane
3252-43-5	dibromoacetonitrile
96-12-8	1,2-dibromo-3-chloropropane
Proposition	
Chemical	s known to cause cancer:
75-27-4	bromodichloromethane
75-25-2	bromoform
56-23-5	carbon tetrachloride
67-66-3	trichloromethane
3252-43-5	dibromoacetonitrile
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
127-18-4	tetrachloroethylene
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
	1,2,3-trichloropropane
Chemical	s known to cause reproductive toxicity for females:
	ne ingredients is listed.
Chemical	s known to cause reproductive toxicity for males:
	1,2-dibromo-3-chloropropane
	1,2-dibromoethane
	trichloroethylene



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

		(Contd. of page
	ls known to cause developmental toxicity:	
	trichloromethane	
	1,2-dibromoethane	
79-01-6	trichloroethylene	
	genic categories	
	vironmental Protection Agency)	
	acetone	I
	bromodichloromethane	B2
	bromoform	B2
56-23-5	carbon tetrachloride	L
	trichloromethane	B2, L, N
124-48-1	dibromochloromethane	C
106-93-4	1,2-dibromoethane	L
127-18-4	tetrachloroethylene	L
71-55-6	1,1,1-trichloroethane	II
79-00-5	1,1,2-trichloroethane	C
79-01-6	trichloroethylene	СаН
96-18-4	1,2,3-trichloropropane	L
,	reshold Limit Value established by ACGIH)	
67-64-1	acetone	1
75-25-2	bromoform	I
56-23-5	carbon tetrachloride	I
67-66-3	trichloromethane	I
76-06-2	trichloronitromethane	1
106-93-4	1,2-dibromoethane	1
127-18-4	tetrachloroethylene	I
71-55-6	1,1,1-trichloroethane	
79-00-5	1,1,2-trichloroethane	
79-01-6	trichloroethylene	1
96-18-4	1,2,3-trichloropropane	1
	Ca (National Institute for Occupational Safety and Health)	
	carbon tetrachloride	
	trichloromethane	
	1,2-dibromo-3-chloropropane	
106-93-4	1,2-dibromoethane	
127-18-4	tetrachloroethylene	
79-00-5	1,1,2-trichloroethane	
79-01-6	trichloroethylene	
	1,2,3-trichloropropane	



Printing date 03/28/2019 Version Number 2 Reviewed on 03/28/2019

Trade name: Disinfection Byproducts/Chlorinated Solvents Standard (1X1 mL)

(Contd. of page 16)

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 03/28/2019 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Repr. 1A: Reproductive toxicity - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 $\,$

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* * Data compared to the previous version altered.

US