

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** Graphite Furnace AA Calibration Standard (125 mL)
- **Part number:** ICM-150
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
Causes skin irritation.
Causes serious eye damage.
- **Precautionary statements**
Wash thoroughly after handling.
Wear protective gloves / eye protection / face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 1)

Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

7697-37-2	nitric acid	3.5%
-----------	-------------	------

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

7697-37-2	nitric acid	0.16 ppm
7784-27-2	aluminium nitrate	83 mg/m ³
87-69-4	(+)-tartaric acid	1.6 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	1.5 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	0.3 mg/m ³
10099-74-8	lead dinitrate	0.24 mg/m ³
3251-23-8	copper dinitrate	8.9 mg/m ³
7782-61-8	iron (III) nitrate nonahydrate	22 mg/m ³
7446-08-4	selenium dioxide	0.84 mg/m ³
1327-53-3	diarsenic trioxide	0.27 mg/m ³
10102-45-1	thallium nitrate	0.078 mg/m ³
7440-36-0	antimony	1.5 mg/m ³
10022-31-8	barium nitrate	2.9 mg/m ³
10377-66-9	manganese dinitrate	9.8 mg/m ³
7761-88-8	silver nitrate	0.047 mg/m ³
10022-68-1	Nitric acid, cadmium salt, tetrahydrate	0.27 mg/m ³

PAC-2:

7697-37-2	nitric acid	24 ppm
7784-27-2	aluminium nitrate	920 mg/m ³
87-69-4	(+)-tartaric acid	17 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	53 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	23 mg/m ³
10099-74-8	lead dinitrate	180 mg/m ³
3251-23-8	copper dinitrate	31 mg/m ³
7782-61-8	iron (III) nitrate nonahydrate	110 mg/m ³
7446-08-4	selenium dioxide	1.6 mg/m ³
1327-53-3	diarsenic trioxide	3.0 mg/m ³
10102-45-1	thallium nitrate	4.3 mg/m ³
7440-36-0	antimony	13 mg/m ³

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 3)

10022-31-8	barium nitrate	350 mg/m ³
10377-66-9	manganese dinitrate	16 mg/m ³
7761-88-8	silver nitrate	0.9 mg/m ³
10022-68-1	Nitric acid, cadmium salt, tetrahydrate	2.1 mg/m ³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7784-27-2	aluminium nitrate	5,500 mg/m ³
87-69-4	(+)-tartaric acid	100 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	320 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	140 mg/m ³
10099-74-8	lead dinitrate	1,100 mg/m ³
3251-23-8	copper dinitrate	190 mg/m ³
7782-61-8	iron (III) nitrate nonahydrate	640 mg/m ³
7446-08-4	selenium dioxide	9.5 mg/m ³
1327-53-3	diarsenic trioxide	9.1 mg/m ³
10102-45-1	thallium nitrate	26 mg/m ³
7440-36-0	antimony	80 mg/m ³
10022-31-8	barium nitrate	2,100 mg/m ³
10377-66-9	manganese dinitrate	96 mg/m ³
7761-88-8	silver nitrate	5.4 mg/m ³
10022-68-1	Nitric acid, cadmium salt, tetrahydrate	13 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:
7697-37-2 nitric acid
PEL Long-term value: 5 mg/m³, 2 ppm

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 4)

REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Colorless

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 5)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.952 mPas
Kinematic:	Not determined.
· Solvent content:	
Water:	96.1 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 6)

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	1,914 mg/L (rat)
------------	----------	------------------

7697-37-2 nitric acid

Inhalative	LC50/4 h	67 mg/L (rat)
------------	----------	---------------

Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	1
10026-22-9	cobalt (II) nitrate hexahydrate	2B
10099-74-8	lead dinitrate	2A
7446-08-4	selenium dioxide	3
1327-53-3	diarsenic trioxide	1
543-81-7	acetic acid beryllium salt	1
10022-68-1	Nitric acid, cadmium salt, tetrahydrate	1

NTP (National Toxicology Program)

13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	K
10099-74-8	lead dinitrate	R
1327-53-3	diarsenic trioxide	K
543-81-7	acetic acid beryllium salt	K
10022-68-1	Nitric acid, cadmium salt, tetrahydrate	K

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)


(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN3264
· UN proper shipping name	
· DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· Transport hazard class(es)	
· DOT, IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 8)

· Transport in bulk according to Annex II of MARPOL/73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- **Sara**

· **Section 355 (extremely hazardous substances):**

7697-37-2	nitric acid
1327-53-3	diarsenic trioxide

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7784-27-2	aluminium nitrate
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate
10026-22-9	cobalt (II) nitrate hexahydrate
7789-02-8	chromium (III) nitrate nonahydrate
10099-74-8	lead dinitrate
3251-23-8	copper dinitrate
7782-61-8	iron (III) nitrate nonahydrate
7446-08-4	selenium dioxide
1327-53-3	diarsenic trioxide
10102-45-1	thallium nitrate
7440-36-0	antimony
10022-31-8	barium nitrate
543-81-7	acetic acid beryllium salt
10377-66-9	manganese dinitrate
7761-88-8	silver nitrate
10022-68-1	Nitric acid, cadmium salt, tetrahydrate

· **TSCA (Toxic Substances Control Act):**

7697-37-2	nitric acid
-----------	-------------

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 9)

87-69-4	(+)-tartaric acid
10099-74-8	lead dinitrate
3251-23-8	copper dinitrate
7446-08-4	selenium dioxide
1327-53-3	diarsenic trioxide
10102-45-1	thallium nitrate
7440-36-0	antimony
10022-31-8	barium nitrate
10377-66-9	manganese dinitrate
7761-88-8	silver nitrate
7732-18-5	water

· Proposition 65
· Chemicals known to cause cancer:

13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate
10099-74-8	lead dinitrate
1327-53-3	diarsenic trioxide
543-81-7	acetic acid beryllium salt
10022-68-1	Nitric acid, cadmium salt, tetrahydrate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate
------------	---

· Chemicals known to cause developmental toxicity:

13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate
1327-53-3	diarsenic trioxide

· Carcinogenic categories
· EPA (Environmental Protection Agency)

10099-74-8	lead dinitrate	B2
7446-08-4	selenium dioxide	D
1327-53-3	diarsenic trioxide	A
10102-45-1	thallium nitrate	II
10022-31-8	barium nitrate	D, CBD(inh), NL(oral)
10377-66-9	manganese dinitrate	D

· TLV (Threshold Limit Value established by ACGIH)

10099-74-8	lead dinitrate	A3
1327-53-3	diarsenic trioxide	A1
10022-31-8	barium nitrate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Department issuing SDS:** Document Control / Regulatory· **Contact:** regulatory@ultrasci.com· **Date of preparation / last revision** 03/29/2019 / 2· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· *** Data compared to the previous version altered.**

US