Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

*
1 Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Graphite Furnace AA Calibration Standard (125 mL)**

· **Part number:** ICM-150
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Reagents and Standards for Analytical Chemical Laboratory Use

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Agilent Technologies LDA UK Ltd.
5500 Lakeside Cheadle Royal Business Park,
Cheadle, Cheshire, SK8 3GR
United Kingdom
Tel: +44 (0) 345 712 5292

· **Further information obtainable from:**
Telephone: 0800 603 1000
pdl-msds_author@agilent.com
· **1.4 Emergency telephone number:** CHEMTREC®: +44 20 3807 3798

*
2 Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**


GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.
Eye Dam. 1 H318 Causes serious eye damage.


GHS07

Skin Irrit. 2 H315 Causes skin irritation.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
· **Hazard pictograms**


GHS05

· **Signal word** Danger

· **Hazard-determining components of labelling:**
nitric acid
· **Hazard statements**
H290 May be corrosive to metals.
H315 Causes skin irritation.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 1)

H318 Causes serious eye damage.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P280 Wear protective gloves / eye protection / face protection.
P234 Keep only in original packaging.
P264 Wash thoroughly after handling.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of water.
P390 Absorb spillage to prevent material damage.

· **Additional information:**
Product contains: Restricted explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 5 (1) and (3).

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 7697-37-2 EINECS: 231-714-2	nitric acid	Ox. Liq. 2, H272; Skin Corr. 1A, H314	3.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

*
4 First aid measures

· **4.1 Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 2)

· **5.3 Advice for firefighters**
· **Protective equipment:** No special measures required.

6 Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep container tightly sealed.
· **7.3 Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **8.1 Control parameters**
· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**	
7697-37-2 nitric acid	
WEL	Short-term value: 2.6 mg/m³, 1 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

(Contd. on page 4)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 3)

· **Protection of hands:**
Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.
· **Material of gloves**
For normal use: nitrile rubber, 11-13 mil thickness
For direct contact with the chemical: butyl rubber, 12-15 mil thickness
· **Penetration time of glove material**
For normal use: nitrile rubber: 1 hour
For direct contact with the chemical: butyl rubber: > 4 hours
· **Eye protection:**



Tightly sealed goggles

*
9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Colour:	Colourless
· **Odour:**	Odourless
· **Odour threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/freezing point:	0 °C
Initial boiling point and boiling range:	100 °C
· **Flash point:**	Not applicable
· **Flammability**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapour pressure at 20 °C:**	23 hPa
· **Density at 20 °C:**	1 g/cm³
· **Relative density**	Not determined
· **Vapour density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.

(Contd. on page 5)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 4)

· **Partition coefficient: n-octanol/water:**	Not determined
· **Viscosity:**	
Dynamic at 20 °C:	0.952 mPas
Kinematic:	Not determined
· **Solvent content:**	
Water:	96.1 %
VOC (EC)	0.00 %
Solids content:	0.4 %
· **9.2 Other information**	No further relevant information available.

10 Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
7697-37-2 nitric acid		
Inhalative	LC50/4 h	67 mg/L (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye damage.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Additional toxicological information:**
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 6)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 5)

· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **12.6 Other adverse effects** No further relevant information available.

*
13 Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Dispose of contents/container in accordance with local/regional/national/international regulations.
Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*
14 Transport information

· **14.1 UN-Number**	
· **ADR, IMDG, IATA**	UN3264
· **14.2 UN proper shipping name**	
· **ADR**	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· **IMDG, IATA**	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· **14.3 Transport hazard class(es)**	
· **ADR, IMDG, IATA**	
· **Class**	8 Corrosive substances.
· **Label**	8
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III
· **14.5 Environmental hazards:**	Not applicable
· **14.6 Special precautions for user**	Warning: Corrosive substances.
· **Hazard identification number (Kemler code):**	80
· **EMS Number:**	F-A,S-B
· **Segregation groups**	(SGG1) Acids
· **Stowage Category**	A

(Contd. on page 7)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 6)

· **Stowage Code**	SW2 Clear of living quarters.
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **Tunnel restriction code**	E
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

*
15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**		
7697-37-2	nitric acid	3%

· **Regulated poisons**		
1327-53-3	diarsenic trioxide	Listed
10102-45-1	thallium nitrate	Listed
10022-31-8	barium nitrate	Listed

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**		
1327-53-3	diarsenic trioxide	Sunset date: 2015-05-21

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*
16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation.
No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Relevant phrases**
H272 May intensify fire; oxidiser.

(Contd. on page 8)

Safety data sheet
according to UK REACH

Printing date 09.06.2026 Revision: 09.06.2026

Trade name: Graphite Furnace AA Calibration Standard (125 mL)

(Contd. of page 7)

H314 Causes severe skin burns and eye damage.

· **Department issuing SDS:** Document Control / Regulatory
· **Contact:** pdl-acg-regulatory-cq@agilent.com
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Ox. Liq. 2: Oxidizing liquids – Category 2
Met. Corr.1: Corrosive to metals – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
· *** Data compared to the previous version altered.**