

Safety Data Sheet

acc. to OSHA HCS

Revision date: 09/24/2025

1 Identification

- **Product identifier**
- **Product Name:** EM 200.7 Calibration Standard no. 4 (125 mL)
- **Part no. :** ICM-205
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer.



GHS05 Corrosion

Corrosive to Metals 1 H290 May be corrosive to metals.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
Nitric acid, nickel(2+) salt, hexahydrate
- **Hazard statements**
H290 May be corrosive to metals.
H315 Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 1)

H318 Causes serious eye damage.

H350 May cause cancer.

Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P234 Keep only in original container.
- P264 Wash thoroughly after handling.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P302+P352 If on skin: Wash with plenty of water.
- P390 Absorb spillage to prevent material damage.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P406 Store in corrosive resistant container with a resistant inner liner.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)


Health = 3

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)


Health = *3

Fire = 0

Reactivity = 0

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

7697-37-2	nitric acid	4.95%
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	0.2478%

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

PAC-1:

7697-37-2	nitric acid	0.16 ppm
7784-27-2	aluminium nitrate	83 mg/m ³
13446-18-9	magnesium nitrate hexahydrate	16 mg/m ³
7631-99-4	sodium nitrate	3.8 mg/m ³
7757-79-1	potassium nitrate	11 mg/m ³
471-34-1	calcium carbonate	45 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	1.5 mg/m ³
10196-18-6	zinc(II) nitrate hexahydrate	27 mg/m ³
7761-88-8	silver nitrate	0.047 mg/m ³

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 3)

· PAC-2:

7697-37-2	nitric acid	24 ppm
7784-27-2	aluminium nitrate	920 mg/m ³
13446-18-9	magnesium nitrate hexahydrate	180 mg/m ³
7631-99-4	sodium nitrate	42 mg/m ³
7757-79-1	potassium nitrate	120 mg/m ³
471-34-1	calcium carbonate	210 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	53 mg/m ³
10196-18-6	zinc(II) nitrate hexahydrate	300 mg/m ³
7761-88-8	silver nitrate	39 mg/m ³

· PAC-3:

7697-37-2	nitric acid	92 ppm
7784-27-2	aluminium nitrate	5,500 mg/m ³
13446-18-9	magnesium nitrate hexahydrate	1,100 mg/m ³
7631-99-4	sodium nitrate	250 mg/m ³
7757-79-1	potassium nitrate	740 mg/m ³
471-34-1	calcium carbonate	1,300 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	320 mg/m ³
10196-18-6	zinc(II) nitrate hexahydrate	1,800 mg/m ³
7761-88-8	silver nitrate	230 mg/m ³

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters
· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 4)

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.
- **Protection of hands:**
Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.
- **Material of gloves**
For normal use: nitrile rubber, 11-13 mil thickness
For direct contact with the chemical: butyl rubber, 12-15 mil thickness
- **Penetration time of glove material**
For normal use: nitrile rubber: 1 hour
For direct contact with the chemical: butyl rubber: >4 hours
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
Form: Fluid
Color: According to product specification
Odor: Characteristic

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 5)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability:	Not applicable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density: · Relative density · Vapor density · Evaporation rate	Not determined. Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Water: VOC content:	90.7 % 0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	4.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 6)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**
7697-37-2 nitric acid

Inhalative LC50/4 h 67 mg/L (rat)

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

Oral LD50 1,620 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

1

· **NTP (National Toxicology Program)**

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Revision date: 09/24/2025



Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN3264 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) |
| · DOT | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. |
| · IMDG, IATA | (NITRIC ACID) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| · IMDG, IATA | |
|  | |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| · Packing group | III |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Corrosive substances |
| · Hazard identification number (Kemler code): | 80 |
| · EMS Number: | F-A,S-B |
| · Segregation groups | (SGG1) Acids |
| · Stowage Category | A |
| · Stowage Code | SW2 Clear of living quarters. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 8)

· Transport/Additional information:
· DOT
· Quantity limitations

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG
· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC,
N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7784-27-2 aluminium nitrate

13446-18-9 magnesium nitrate hexahydrate

7789-02-8 chromium (III) nitrate nonahydrate

7757-79-1 potassium nitrate

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

10196-18-6 zinc(II) nitrate hexahydrate

7761-88-8 silver nitrate

· TSCA (Toxic Substances Control Act):

7732-18-5 water

ACTIVE

7697-37-2 nitric acid

ACTIVE

7631-99-4 sodium nitrate

ACTIVE

7757-79-1 potassium nitrate

ACTIVE

471-34-1 calcium carbonate

ACTIVE

7761-88-8 silver nitrate

ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65
· Chemicals known to cause cancer:

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet acc. to OSHA HCS

Revision date: 09/24/2025

Product Name: EM 200.7 Calibration Standard no. 4 (125 mL)

(Contd. of page 9)

· Chemicals known to cause reproductive toxicity for males:

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

· Chemicals known to cause developmental toxicity:

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation.
No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: pdl-acg-regulatory-cq@agilent.com

· Date of preparation / last revision 09/24/2025 / 8

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Corrosive to Metals 1: Corrosive to metals – Category 1

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A

· * Data compared to the previous version altered.