

Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

### 1 Identification

· Product identifier

· Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

· Part number: ICM-232

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Agilent Technologies, Inc.

5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

### 2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water. Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



 $\frac{2}{1}$  Health = 2 Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable. · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

7697-37-2 nitric acid

1.4%

### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5 Fire-fighting measures**

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 2)

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
	*, * * * *	0.16
7697-37-2		0.16 ppm
	potassium nitrate	$9 \text{ mg/m}^3$
	sodium nitrate	4.1 mg/m <sup>3</sup>
554-13-2	lithium carbonate	3.1 mg/m <sup>2</sup>
1313-27-5	molybdenum trioxide	2.3 mg/m <sup>3</sup>
10042-76-9	strontium nitrate	5.7 mg/m <sup>3</sup>
· PAC-2:		
7697-37-2	nitric acid	24 ppm
7757-79-1	potassium nitrate	100 mg/m
7631-99-4	sodium nitrate	45 mg/m <sup>3</sup>
554-13-2	lithium carbonate	34 mg/m <sup>3</sup>
1313-27-5	molybdenum trioxide	43 mg/m <sup>3</sup>
10042-76-9	strontium nitrate	62 mg/m <sup>3</sup>
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7757-79-1	potassium nitrate	600 mg/m
7631-99-4	sodium nitrate	270 mg/m
554-13-2	lithium carbonate	210 mg/m
1313-27-5	molybdenum trioxide	260 mg/m
10042-76-9	strontium nitrate	370 mg/m

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 7697-37-2 nitric acid

P	EL	Long-term value: 5 mg/m³, 2 ppm
R	EL	Short-term value: 10 mg/m³, 4 ppm
		Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
T	LV	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm
		Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 4)

Physical and chemical properties				
· Information on basic physical and c	chemical properties			
General Information				
· Appearance:	T1 '1			
Form:	Fluid			
Color: · Odor:	Colorless Odorless			
· Odor: · Odor threshold:	Not determined.			
· pH-value:	Not determined.			
•	110t determined.			
· Change in condition	TT 14 ' 1			
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	100 °C (212 °F)			
· Flash point:	Not applicable.			
Flammability (solid, gaseous):	Not applicable.			
Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)			
· Density at 20 °C (68 °F):	1.00642 g/cm <sup>3</sup> (8.39857 lbs/gal)			
· Relative density	Not determined.			
Vapor density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
Water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/wate	er): Not determined.			
· Viscosity:				
Dynamic at 20 °C (68 °F):	0.952 mPas			
Kinematic:	Not determined.			
· Solvent content:				
Water:	98.5 %			
VOC content:	0.00 %			
	0.0 g/l / 0.00 lb/gal			
Solids content:	0.1 %			
· Other information	No further relevant information available.			

### 10 Stability and reactivity

· Reactivity No further relevant information available.



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 5)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### **ATE (Acute Toxicity Estimate)**

Inhalative LC50/4 h 4,786 mg/L (rat)

#### 7697-37-2 nitric acid

Inhalative LC50/4 h 67 mg/L (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

### · NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 6)

· Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	
DOT, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI
-,	ACID)
Transport hazard class(es)	
DOT, IMDG, IATA	
\$	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F-A,S-B
Segregation groups	Acids
<b>Stowage Category</b>	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
- v	On cargo aircraft only: 60 L



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 7)

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID), 8, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7757-79-1 potassium nitrate

554-13-2 lithium carbonate

1313-27-5 molybdenum trioxide

10042-76-9 strontium nitrate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

554-13-2 lithium carbonate

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US



Printing date 03/29/2019 Version Number 3 Reviewed on 03/29/2019

Trade name: EM 200.7 Mixed Calibration Standard III (125 mL)

(Contd. of page 8)

### 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- $\cdot$  Date of preparation / last revision 03/29/2019 / 2
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

\* Data compared to the previous version altered.

US ·