

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**1 Identification**

- **Product identifier**
- **Trade name:** CLP ICP Graphite Furnace Standard (50 mL)
- **Part number:** ICM-464
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA
- **Information department:**  
Telephone: 800-227-9770  
e-mail: [pdl-msds\\_author@agilent.com](mailto:pdl-msds_author@agilent.com)
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
nitric acid
- **Hazard statements**  
Causes skin irritation.  
Causes serious eye damage.
- **Precautionary statements**  
Wash thoroughly after handling.  
Wear protective gloves / eye protection / face protection.  
If on skin: Wash with plenty of water.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Immediately call a poison center/doctor.  
Specific treatment (see on this label).

(Contd. on page 2)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 1)

Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice/attention.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

|            |   |                |
|------------|---|----------------|
| HEALTH     | 3 | Health = 3     |
| FIRE       | 0 | Fire = 0       |
| REACTIVITY | 0 | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

|           |             |       |
|-----------|-------------|-------|
| 7697-37-2 | nitric acid | 4.95% |
|-----------|-------------|-------|

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

(Contd. on page 3)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 2)

## 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### · Protective Action Criteria for Chemicals

#### · PAC-1:

|            |                                         |                         |
|------------|-----------------------------------------|-------------------------|
| 7697-37-2  | nitric acid                             | 0.16 ppm                |
| 87-69-4    | (+)-tartaric acid                       | 1.6 mg/m <sup>3</sup>   |
| 7440-36-0  | antimony                                | 1.5 mg/m <sup>3</sup>   |
| 10099-74-8 | lead dinitrate                          | 0.24 mg/m <sup>3</sup>  |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate | 0.27 mg/m <sup>3</sup>  |
| 1327-53-3  | diarsenic trioxide                      | 0.27 mg/m <sup>3</sup>  |
| 10102-45-1 | thallium nitrate                        | 0.078 mg/m <sup>3</sup> |
| 7446-08-4  | selenium dioxide                        | 0.84 mg/m <sup>3</sup>  |

#### · PAC-2:

|            |                                         |                       |
|------------|-----------------------------------------|-----------------------|
| 7697-37-2  | nitric acid                             | 24 ppm                |
| 87-69-4    | (+)-tartaric acid                       | 17 mg/m <sup>3</sup>  |
| 7440-36-0  | antimony                                | 13 mg/m <sup>3</sup>  |
| 10099-74-8 | lead dinitrate                          | 180 mg/m <sup>3</sup> |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate | 2.1 mg/m <sup>3</sup> |
| 1327-53-3  | diarsenic trioxide                      | 3.0 mg/m <sup>3</sup> |
| 10102-45-1 | thallium nitrate                        | 4.3 mg/m <sup>3</sup> |
| 7446-08-4  | selenium dioxide                        | 1.6 mg/m <sup>3</sup> |

#### · PAC-3:

|            |                                         |                         |
|------------|-----------------------------------------|-------------------------|
| 7697-37-2  | nitric acid                             | 92 ppm                  |
| 87-69-4    | (+)-tartaric acid                       | 100 mg/m <sup>3</sup>   |
| 7440-36-0  | antimony                                | 80 mg/m <sup>3</sup>    |
| 10099-74-8 | lead dinitrate                          | 1,100 mg/m <sup>3</sup> |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate | 13 mg/m <sup>3</sup>    |
| 1327-53-3  | diarsenic trioxide                      | 9.1 mg/m <sup>3</sup>   |
| 10102-45-1 | thallium nitrate                        | 26 mg/m <sup>3</sup>    |
| 7446-08-4  | selenium dioxide                        | 9.5 mg/m <sup>3</sup>   |

US

(Contd. on page 4)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

Trade name: CLP ICP Graphite Furnace Standard (50 mL)

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

### 7697-37-2 nitric acid

|     |                                                |
|-----|------------------------------------------------|
| PEL | Long-term value: 5 mg/m <sup>3</sup> , 2 ppm   |
| REL | Short-term value: 10 mg/m <sup>3</sup> , 4 ppm |
|     | Long-term value: 5 mg/m <sup>3</sup> , 2 ppm   |
| TLV | Short-term value: 10 mg/m <sup>3</sup> , 4 ppm |
|     | Long-term value: 5.2 mg/m <sup>3</sup> , 2 ppm |

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing.
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- **Breathing equipment:**
  - When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
  - Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.
- **Protection of hands:**
  - Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.
- **Material of gloves**
  - For normal use: nitrile rubber, 11-13 mil thickness
  - For direct contact with the chemical: butyl rubber, 12-15 mil thickness

(Contd. on page 5)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 4)

- **Penetration time of glove material**  
For normal use: nitrile rubber: 1 hour  
For direct contact with the chemical: butyl rubber: >4 hours
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

|                 |                 |
|-----------------|-----------------|
| Form:           | Fluid           |
| Color:          | Colorless       |
| Odor:           | Odorless        |
| Odor threshold: | Not determined. |

· pH-value: Not determined.

#### · Change in condition

|                              |                 |
|------------------------------|-----------------|
| Melting point/Melting range: | Undetermined.   |
| Boiling point/Boiling range: | 100 °C (212 °F) |

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

#### · Explosion limits:

|        |                 |
|--------|-----------------|
| Lower: | Not determined. |
| Upper: | Not determined. |

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density: Not determined.

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

#### · Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

#### · Viscosity:

|            |                 |
|------------|-----------------|
| Dynamic:   | Not determined. |
| Kinematic: | Not determined. |

(Contd. on page 6)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 5)

|                            |                                            |
|----------------------------|--------------------------------------------|
| · <b>Solvent content:</b>  |                                            |
| <b>Water:</b>              | 94.8 %                                     |
| <b>VOC content:</b>        | 0.00 %                                     |
|                            | 0.0 g/l / 0.00 lb/gal                      |
| · <b>Solids content:</b>   | 0.2 %                                      |
| · <b>Other information</b> | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### ATE (Acute Toxicity Estimate)

|            |          |                  |
|------------|----------|------------------|
| Inhalative | LC50/4 h | 1,354 mg/L (rat) |
|------------|----------|------------------|

### 7697-37-2 nitric acid

|            |          |               |
|------------|----------|---------------|
| Inhalative | LC50/4 h | 67 mg/L (rat) |
|------------|----------|---------------|

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|            |                                         |    |
|------------|-----------------------------------------|----|
| 10099-74-8 | lead dinitrate                          | 2A |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate | 1  |
| 1327-53-3  | diarsenic trioxide                      | 1  |
| 7446-08-4  | selenium dioxide                        | 3  |

- **NTP (National Toxicology Program)**

|            |                                         |   |
|------------|-----------------------------------------|---|
| 10099-74-8 | lead dinitrate                          | R |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate | K |
| 1327-53-3  | diarsenic trioxide                      | K |

(Contd. on page 7)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN3264
- **UN proper shipping name**
- **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
- **IMDG, IATA** CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
- **Transport hazard class(es)**
- **DOT, IMDG, IATA**
- 
- **Class** 8 Corrosive substances
- **Label** 8

(Contd. on page 8)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 7)

|                                                                                                                                                                                      |                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| · <b>Packing group</b><br>· <b>DOT, IMDG, IATA</b>                                                                                                                                   | III                                                                                                                    |
| · <b>Environmental hazards:</b>                                                                                                                                                      | Not applicable.                                                                                                        |
| · <b>Special precautions for user</b><br>· <b>Danger code (Kemler):</b><br>· <b>EMS Number:</b><br>· <b>Segregation groups</b><br>· <b>Stowage Category</b><br>· <b>Stowage Code</b> | Warning: Corrosive substances<br>80<br>F-A,S-B<br>Acids<br>A<br>SW2 Clear of living quarters.                          |
| · <b>Transport in bulk according to Annex II of MARPOL/73/78 and the IBC Code</b>                                                                                                    | Not applicable.                                                                                                        |
| · <b>Transport/Additional information:</b><br>· <b>DOT</b><br>· <b>Quantity limitations</b>                                                                                          | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L                                                        |
| · <b>IMDG</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>                                                                                               | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>                                                                                                                                                      | UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III                                              |

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

|           |                    |
|-----------|--------------------|
| 7697-37-2 | nitric acid        |
| 1327-53-3 | diarsenic trioxide |

### · Section 313 (Specific toxic chemical listings):

|            |                                         |
|------------|-----------------------------------------|
| 7697-37-2  | nitric acid                             |
| 7440-36-0  | antimony                                |
| 10099-74-8 | lead dinitrate                          |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate |
| 1327-53-3  | diarsenic trioxide                      |
| 10102-45-1 | thallium nitrate                        |
| 7446-08-4  | selenium dioxide                        |

### · TSCA (Toxic Substances Control Act):

|           |                   |
|-----------|-------------------|
| 7697-37-2 | nitric acid       |
| 87-69-4   | (+)-tartaric acid |
| 7440-36-0 | antimony          |

(Contd. on page 9)



# Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 8)

|            |                    |
|------------|--------------------|
| 10099-74-8 | lead dinitrate     |
| 1327-53-3  | diarsenic trioxide |
| 10102-45-1 | thallium nitrate   |
| 7446-08-4  | selenium dioxide   |
| 7732-18-5  | water              |

## Proposition 65

### Chemicals known to cause cancer:

|            |                                         |
|------------|-----------------------------------------|
| 10099-74-8 | lead dinitrate                          |
| 10022-68-1 | Nitric acid, cadmium salt, tetrahydrate |
| 1327-53-3  | diarsenic trioxide                      |

### Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

### Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

### Chemicals known to cause developmental toxicity:

|           |                    |
|-----------|--------------------|
| 1327-53-3 | diarsenic trioxide |
|-----------|--------------------|

## Carcinogenic categories

### EPA (Environmental Protection Agency)

|            |                    |    |
|------------|--------------------|----|
| 10099-74-8 | lead dinitrate     | B2 |
| 1327-53-3  | diarsenic trioxide | A  |
| 10102-45-1 | thallium nitrate   | II |
| 7446-08-4  | selenium dioxide   | D  |

### TLV (Threshold Limit Value established by ACGIH)

|            |                    |    |
|------------|--------------------|----|
| 10099-74-8 | lead dinitrate     | A3 |
| 1327-53-3  | diarsenic trioxide | A1 |

### NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

**Department issuing SDS:** Document Control / Regulatory

**Contact:** regulatory@ultrasci.com

**Date of preparation / last revision** 03/29/2019 / 2

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/29/2019

Version Number 3

Reviewed on 03/29/2019

**Trade name: CLP ICP Graphite Furnace Standard (50 mL)**

(Contd. of page 9)

NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· **\* Data compared to the previous version altered.**

US