US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Agilent

Version Number 4

Reviewed on 09/10/2018

1 Identification

· Product identifier

- · Trade name: Thulium Standard
- · Part number: ICP-069, ICP-069-25, ICP-069-L
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation.

· Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning · Hazard statements Causes skin irritation. Causes serious eye irritation. · Precautionary statements Wash thoroughly after handling. Wear protective gloves / eye protection / face protection. If on skin: Wash with plenty of water. Specific treatment (see on this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention. (Contd. on page 2)

Reviewed on 09/10/2018

Trade name: Thulium Standard

(Contd. of page 1) · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH $\frac{2}{2}$ Health = 2 FIRE 0 Fire = 0**REACTIVITY** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

7697-37-2 nitric acid

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

US



Printing date 03/29/2019

Version Number 4

1.98%

Reviewed on 09/10/2018

Trade name: Thulium Standard

(Contd. of page 2)

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Not required.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
7697-37-2	nitric acid	0.16 ppm
12036-44-1	thulium oxide	30 mg/m ³
· PAC-2:		
7697-37-2		24 ppm
12036-44-1	thulium oxide	330 mg/m ³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
12036-44-1	thulium oxide	2,000 mg/m ³

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace	:

7697-37-2 nitric acid

- PEL Long-term value: 5 mg/m³, 2 ppm
- REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

(Contd. on page 4)

US

Agilent

Printing date 03/29/2019



Version Number 4

Reviewed on 09/10/2018

Agilent

Trade name: Thulium Standard

Printing date 03/29/2019

· A	dditional information: The lists that were valid during the creation were used as basis.
	xposure controls
	ersonal protective equipment:
	eneral protective and hygienic measures:
	eep away from foodstuffs, beverages and feed.
	nmediately remove all soiled and contaminated clothing.
	Vash hands before breaks and at the end of work.
	void contact with the eyes and skin.
	reathing equipment:
W W	/hen used as intended with Agilent instruments, the use of the product under normal laboratory conditions and ith standard practices does not result in significant airborne exposures and therefore respiratory protection is needed.
	nder an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved evice/equipment with appropriate organic or acid gas cartridge.
	rotection of hands:
th di	Ithough not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil ickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is irect contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time acceeding 4 hrs. Supplier recommendations should be followed.
	Iaterial of gloves
	or normal use: nitrile rubber, 11-13 mil thickness
	or direct contact with the chemical: butyl rubber, 12-15 mil thickness
·Pe	enetration time of glove material
Fo	or normal use: nitrile rubber: 1 hour
Fo	or direct contact with the chemical: butyl rubber: >4 hours
·E	ye protection:
	Tightly sealed goggles

9 Physical and chemical properties	
------------------------------------	--

 Information on basic physical and one of the second second	chemical properties	
· Appearance:		
Form:	Fluid	
Color:	Colorless	
· Odor:	Odorless	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	

Reviewed on 09/10/2018

Trade name: Thulium Standard

	(Contd. of pag
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
• Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	0.952 mPas
Kinematic:	Not determined.
Solvent content:	
Water:	97.9 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.1 %
• Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:


· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4 h 3,384 mg/L (rat)

(Contd. on page 6)





US

Reviewed on 09/10/2018

(Contd. of page 5)

Trade name: Thulium Standard

Printing date 03/29/2019

7697-37-2 nitric acid

Inhalative LC50/4 h 67 mg/L (rat)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)



Reviewed on 09/10/2018

(Contd. of page 6)

Trade name: Thulium Standard

· UN-Number	
· DOT, IMDG, IATA	UN3264
· UN proper shipping name	
·DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITR
	ACID)
· Transport hazard class(es)	
· DOT, IMDG, IATA	
8	
· Class	8 Corrosive substances
· Label	8
 Packing group DOT, IMDG, IATA 	III
• Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Transport in bulk according to Annex 1	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5L
-	On cargo aircraft only: 60L
·IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

(Contd. on page 8)

US

Printing date 03/29/2019

Agilent

Reviewed on 09/10/2018

(Contd. of page 7)

Printing date 03/29/2019

Version Number 4

Trade name: Thulium Standard

• Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

• Date of preparation / last revision 03/29/2019 / 3

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation
- IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

US



Reviewed on 09/10/2018

Printing date 03/29/2019

Trade name: Thulium Standard

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

• * Data compared to the previous version altered.



Version Number 4

(Contd. of page 8)

US