

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

1 Identification

- **Product identifier**
- **Trade name:** Beryllium Blank Custom Standard (100 mL)
- **Part number:** ICUS-5200-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
ammonium bifluoride
- **Hazard statements**
Causes severe skin burns and eye damage.
- **Precautionary statements**
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Store locked up.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 3

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = 3

Fire = 0

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

1341-49-7	ammonium bifluoride	1.0%
-----------	---------------------	------

4 First-aid measures

· Description of first aid measures
· General information: Immediately remove any clothing soiled by the product.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:
· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media
· Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters
· Protective equipment: Mouth respiratory protective device.

US

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** No special measures required.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1341-49-7	ammonium bifluoride	11 mg/m ³
7697-37-2	nitric acid	0.16 ppm

- **PAC-2:**

1341-49-7	ammonium bifluoride	130 mg/m ³
7697-37-2	nitric acid	24 ppm

- **PAC-3:**

1341-49-7	ammonium bifluoride	750 mg/m ³
7697-37-2	nitric acid	92 ppm

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:** Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s):** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 3)

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.
- **Protection of hands:**
Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.
- **Material of gloves**
For normal use: nitrile rubber, 11-13 mil thickness
For direct contact with the chemical: butyl rubber, 12-15 mil thickness
- **Penetration time of glove material**
For normal use: nitrile rubber: 1 hour
For direct contact with the chemical: butyl rubber: >4 hours
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Color:	Colorless
- **Odor:** Odorless
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
-------------------------------------	---------------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 4)

Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.00563 g/cm ³ (8.39198 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.952 mPas
Kinematic:	Not determined.
· Solvent content:	
Water:	98.8 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	1.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	13,000 mg/kg (rat)
------	------	--------------------

1341-49-7 ammonium bifluoride

Oral	LD50	130 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**

- **on the skin:** Caustic effect on skin and mucous membranes.

- **on the eye:**

- Strong caustic effect.

- Strong irritant with the danger of severe eye injury.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

1341-49-7	ammonium bifluoride	3
-----------	---------------------	---

· NTP (National Toxicology Program)
--

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)
--

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

- Not hazardous for water.

- Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)


· **Other adverse effects** No further relevant information available.

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN3264 |
| · UN proper shipping name | Corrosive liquid, acidic, inorganic, n.o.s. (Ammonium hydrogendifluoride, Nitric acid)
CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(AMMONIUM HYDROGENDIFLUORIDE, NITRIC ACID) |
| · DOT | |
| · IMDG, IATA | |
| · Transport hazard class(es) |  |
| · DOT, IMDG, IATA | |
| · Class | |
| · Label | 8 |
| · Packing group | III |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Corrosive substances |
| · Danger code (Kemler): | 80 |
| · EMS Number: | F-A,S-B |
| · Segregation groups | Acids |
| · Stowage Category | A |
| · Stowage Code | SW2 Clear of living quarters. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |
| · Quantity limitations | |

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 7)

- | | |
|--|--|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (AMMONIUM HYDROGENDIFLUORIDE, NITRIC ACID), 8, III |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):
--

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):
--

7697-37-2 nitric acid

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)
--

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1341-49-7 ammonium bifluoride

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- **Date of preparation / last revision** 04/10/2019 / 1

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/10/2019

Version Number 2

Reviewed on 04/10/2019

Trade name: Beryllium Blank Custom Standard (100 mL)

(Contd. of page 8)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· * Data compared to the previous version altered.

US