

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** Calibration Standard (1X1 mL)
- **Part number:** NAIM-529A-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

ethyl acetate

- **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 1)

Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

141-78-6	ethyl acetate	99.845%
----------	---------------	---------

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

141-78-6	ethyl acetate	1,200 ppm
99-65-0	1,3-dinitrobenzene	3 mg/m ³
121-14-2	2,4-dinitrotoluene	0.6 mg/m ³
606-20-2	2,6-dinitrotoluene	0.6 mg/m ³
98-95-3	nitrobenzene	3 ppm
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine	3 mg/m ³
99-35-4	1,3,5-trinitrobenzene	1.5 mg/m ³
479-45-8	N-methyl-N,2,4,6-tetranitroaniline	4.5 mg/m ³
99-08-1	3-nitrotoluene	6 ppm
99-99-0	4-nitrotoluene	6 ppm
118-96-7	2,4,6-trinitrotoluene	0.3 mg/m ³
35572-78-2	2-amino-4,6-dinitrotoluene	4.2 mg/m ³
88-72-2	2-nitrotoluene	6 ppm

- **PAC-2:**

141-78-6	ethyl acetate	1,700 ppm
----------	---------------	-----------

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 3)

99-65-0	1,3-dinitrobenzene	33 mg/m ³
121-14-2	2,4-dinitrotoluene	12 mg/m ³
606-20-2	2,6-dinitrotoluene	47 mg/m ³
98-95-3	nitrobenzene	20 ppm
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine	26 mg/m ³
99-35-4	1,3,5-trinitrobenzene	16 mg/m ³
479-45-8	N-methyl-N,2,4,6-tetranitroaniline	14 mg/m ³
99-08-1	3-nitrotoluene	14 ppm
99-99-0	4-nitrotoluene	33 ppm
118-96-7	2,4,6-trinitrotoluene	17 mg/m ³
35572-78-2	2-amino-4,6-dinitrotoluene	46 mg/m ³
88-72-2	2-nitrotoluene	33 ppm

· PAC-3:

141-78-6	ethyl acetate	10000** ppm
99-65-0	1,3-dinitrobenzene	200 mg/m ³
121-14-2	2,4-dinitrotoluene	200 mg/m ³
606-20-2	2,6-dinitrotoluene	200 mg/m ³
98-95-3	nitrobenzene	200 ppm
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine	160 mg/m ³
99-35-4	1,3,5-trinitrobenzene	54 mg/m ³
479-45-8	N-methyl-N,2,4,6-tetranitroaniline	1,300 mg/m ³
99-08-1	3-nitrotoluene	200 ppm
99-99-0	4-nitrotoluene	200 ppm
118-96-7	2,4,6-trinitrotoluene	1,000 mg/m ³
35572-78-2	2-amino-4,6-dinitrotoluene	280 mg/m ³
88-72-2	2-nitrotoluene	200 ppm

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities
· Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

 · **Specific end use(s)** No further relevant information available.

(Contd. of page 4)

8 Exposure controls/personal protection

 · **Additional information about design of technical systems:** No further data; see item 7.

 · **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**
141-78-6 ethyl acetate

 PEL Long-term value: 1400 mg/m³, 400 ppm

 REL Long-term value: 1400 mg/m³, 400 ppm

 TLV Long-term value: 1440 mg/m³, 400 ppm

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

 · **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

 · **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

 · **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

 · **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

 · **Eye protection:**


Tightly sealed goggles

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Fruit-like
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	-83.57 °C (-118.4 °F)
Boiling point/Boiling range:	77 °C (170.6 °F)

· **Flash point:** -4 °C (24.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 460 °C (860 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	2.1 Vol %
Upper:	11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 75 hPa (56.3 mm Hg)

· **Density at 20 °C (68 °F):** 0.9 g/cm³ (7.5105 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water at 20 °C (68 °F): 79 g/l

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	99.8 %
VOC content:	99.84 %
	998.4 g/l / 8.33 lb/gal

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 6)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	1,602 mg/L (rat)
------------	----------	------------------

141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rabbit)
------	------	----------------------

Inhalative	LC50/4 h	1,600 mg/L (rat)
------------	----------	------------------

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

121-14-2	2,4-dinitrotoluene	2B
606-20-2	2,6-dinitrotoluene	2B
98-95-3	nitrobenzene	2B
99-08-1	3-nitrotoluene	3
99-99-0	4-nitrotoluene	3
118-96-7	2,4,6-trinitrotoluene	3
88-72-2	2-nitrotoluene	2A

- **NTP (National Toxicology Program)**

98-95-3	nitrobenzene	R
88-72-2	2-nitrotoluene	R

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)


(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Not Regulated, De minimus Quantities	-
· UN-Number	
· DOT, IMDG, IATA	UN1173
· UN proper shipping name	
· DOT	Ethyl acetate
· IMDG, IATA	ETHYL ACETATE
· Transport hazard class(es)	
· DOT, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	B

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 8)

- | | |
|--|---|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1173 ETHYL ACETATE, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

98-95-3	nitrobenzene
---------	--------------

· Section 313 (Specific toxic chemical listings):

99-65-0	1,3-dinitrobenzene
121-14-2	2,4-dinitrotoluene
606-20-2	2,6-dinitrotoluene
98-95-3	nitrobenzene
88-72-2	2-nitrotoluene

· TSCA (Toxic Substances Control Act):

141-78-6	ethyl acetate
99-65-0	1,3-dinitrobenzene
121-14-2	2,4-dinitrotoluene
606-20-2	2,6-dinitrotoluene
98-95-3	nitrobenzene
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine
99-35-4	1,3,5-trinitrobenzene
479-45-8	N-methyl-N,2,4,6-tetranitroaniline
99-08-1	3-nitrotoluene
99-99-0	4-nitrotoluene
118-96-7	2,4,6-trinitrotoluene
88-72-2	2-nitrotoluene

· Proposition 65
· Chemicals known to cause cancer:

121-14-2	2,4-dinitrotoluene
----------	--------------------

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 9)

606-20-2	2,6-dinitrotoluene
98-95-3	nitrobenzene
118-96-7	2,4,6-trinitrotoluene
88-72-2	2-nitrotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

99-65-0	1,3-dinitrobenzene
121-14-2	2,4-dinitrotoluene
606-20-2	2,6-dinitrotoluene
98-95-3	nitrobenzene

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

99-65-0	1,3-dinitrobenzene	D
98-95-3	nitrobenzene	L
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine	C
118-96-7	2,4,6-trinitrotoluene	C

· TLV (Threshold Limit Value established by ACGIH)

98-95-3	nitrobenzene	A3
121-82-4	perhydro-1,3,5-trinitro-1,3,5-triazine	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

121-14-2	2,4-dinitrotoluene
----------	--------------------

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

· Date of preparation / last revision 03/29/2019 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 10)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * **Data compared to the previous version altered.**

US