31.03.2019 Kit components		
Product code Description		
PANAL0216	ASTM D5453 Total Sulfur by UV Fluorescence Kit (High)	
Components:		
PANAL0216-1	Isooctane Solvent Blank	
PANAL0216-2	Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)	
PANAL0216-3	Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)	
PANAL0216-4	Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)	
PANAL0216-5	Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)	
PANAL0216-6	Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)	

Printing date 31.03.2019

Agilent

Version number 3

Revision: 23.03.2019

Identification		
· Product identifier · Trade name: Isooctane Solvent	4 Dlank	
• Part number: PANAL0216-1		
• CAS Number:		
540-84-1 • EC number:		
208-759-1		
Index number: 601-009-00-8		
	substance or mixture and uses advised against	
Reagents and Standards for Anal		
• Details of the supplier of the sa	afety data sheet	
• Manufacturer/Supplier: Agilent Technologies Australia F	Pty Ltd	
679 Springvale Road		
Mulgrave Victoria 3170, Australia		
· Further information obtainabl	e from:	
Telephone: 1800 802 402		
e-mail: pdl-msds author@agiler	nt.com ; CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds author@agiler	nt.com : CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds_author@agiler Emergency telephone number:	nt.com : CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification	: CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification	: CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification	: CHEMTREC®: +(61) - 290372994	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance	: CHEMTREC®: +(61) - 290372994 or mixture	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance	: CHEMTREC®: +(61) - 290372994 or mixture	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flamm	: CHEMTREC®: +(61) - 290372994 or mixture	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance	: CHEMTREC®: +(61) - 290372994 or mixture	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flamm health hazard	: CHEMTREC®: +(61) - 290372994 or mixture	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flamm health hazard	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flamm health hazard	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flamm health hazard	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flame Flam. Liq. 2 H225 Highly flame health hazard Asp. Tox. 1 H304 May be fatal Skin Irrit. 2 H315 Causes skin	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flam health hazard Asp. Tox. 1 H304 May be fatal Skin Irrit. 2 H315 Causes skin STOT SE 3 H336 May cause d	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance flame Flam. Liq. 2 H225 Highly flam health hazard Asp. Tox. 1 H304 May be fatal Skin Irrit. 2 H315 Causes skin STOT SE 3 H336 May cause d Label elements	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	
e-mail: pdl-msds_author@agiler Emergency telephone number: Hazard(s) Identification Classification of the substance iflame Flam. Liq. 2 H225 Highly flam health hazard Asp. Tox. 1 H304 May be fatal Skin Irrit. 2 H315 Causes skin STOT SE 3 H336 May cause d Label elements GHS label elements	cHEMTREC®: +(61) - 290372994 or mixture mable liquid and vapour.	stem (GHS).

Revision: 23.03.2019

Printing date 31.03.2019

Agilent

Version number 3

Trade name: Isooctane Solvent Blank

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: 2,2,4-trimethylpentane · Hazard statements Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Substances
- · CAS No. Description

540-84-1 2,2,4-trimethylpentane

(Contd. on page 3)

AU

Version number 3

Revision: 23.03.2019

Trade name: Isooctane Solvent Blank

(Contd. of page 2)

· Identification number(s)

Printing date 31.03.2019

- EC number: 208-759-1
- · Index number: 601-009-00-8

4 First Aid Measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
 - Reference to other sections
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.





Version number 3

Revision: 23.03.2019

Trade name: Isooctane Solvent Blank

(Contd. of page 3)

7 Handling and Storage

· Handling:

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)

AU



Printing date 31.03.2019



Revision: 23.03.2019

Trade name: Isooctane Solvent Blank

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours · Eye protection:

Tightly sealed goggles

Physical and Chemical Propertie	28			
· Information on basic physical and chemical properties				
· General Information				
· Appearance:				
Form:	Fluid			
Colour:	Colourless			
Odour:	Nearly odourless			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point/freezing point:	-107 °C			
Initial boiling point and boiling range				
· Flash point:	-12 °C			
· Flammability (solid, gas):	Not applicable.			
· Ignition temperature:	410 °C			
· Decomposition temperature:	Not determined.			
· Auto-ignition temperature:	Not determined.			
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.			
· Explosion limits:				
Lower:	1.1 Vol %			
Upper:	6 Vol %			
· Vapour pressure at 20 °C:	41.25 hPa			
· Density at 20 °C:	0.692 g/cm ³			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not determined.			
Solubility in / Miscibility with water: Not miscible or difficult to mix.				
			· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:				
Dynamic at 20 °C:	0.51 mPas			

Printing date 31.03.2019

Version number 3



(Contd. of page 4)

AU

Version number 3

Revision: 23.03.2019

Trade name: Isooctane Solvent Blank

Printing date 31.03.2019

	(Contd. of	page 5)
Kinematic:	Not determined.	
[•] Solvent content: Organic solvents: VOC (EC)	100.0 % 100.00 %	
Solids content: • Other information	0.0 % No further relevant information available.	

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.5 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>33.52 mg/L (rat)

· Primary irritant effect:

• Skin corrosion/irritation Irritant to skin and mucous membranes.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

12 Ecological Information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- \cdot Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

(Contd. on page 7)



AU

Revision: 23.03.2019

(Contd. of page 6)

Trade name: Isooctane Solvent Blank

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADG, IMDG, IATA	UN1262
UN proper shipping name	
ADG	1262 OCTANES, ENVIRONMENTALLY
	HAZARDOUS
IMDG, IATA	OCTANES
Transport hazard class(es)	
ADG	
Class	3 Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADG, IMDG, IATA	II
Environmental hazards:	
Special marking (ADG):	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33



Printing date 31.03.2019

according to WHS Regulations

Revision: 23.03.2019

Printing date 31.03.2019

Version number 3

Trade name: Isooctane Solvent Blank

	(Contd. of page
· EMS Number:	3-07
· Stowage Category	В
· Transport in bulk according to Annex	II of Marpol
and the IBC Code	Not applicable.
Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1262 OCTANES, 3, II, ENVIRONMENTALLY
	HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory	of Chemical Substances
------------------------	------------------------

Substance is listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

Substance is not listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I Substance is not listed.

· Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $100\ t$
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)



⁻ AU

Revision: 23.03.2019

Printing date 31.03.2019

Version number 3

Trade name: Isooctane Solvent Blank

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 (Contd. of page 8)

AU -



Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

1 Identification · Product identifier • Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL) · Part number: PANAL0216-2 · Relevant identified uses of the substance or mixture and uses advised against Reagents and Standards for Analytical Chemical Laboratory Use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies Australia Pty Ltd 679 Springvale Road Mulgrave Victoria 3170, Australia · Further information obtainable from: Telephone: 1800 802 402 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: +(61) - 290372994 2 Hazard(s) Identification · Classification of the substance or mixture flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. health hazard Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. _____ · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: 2,2,4-trimethylpentane · Hazard statements Highly flammable liquid and vapour.



Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 1) Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

540-84-1 2,2,4-trimethylpentane

🕐 Flam. Liq. 2, H225; 🚯 Asp. Tox. 1, H304; 🗘 Skin Irrit. 2, H315; STOT SE 3, H336

99.934%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



Printing date 31.03.2019

AU

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 2)

 \cdot After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

Printing date 31.03.2019

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

- For direct contact with the chemical: butyl rubber: >4 hours
- Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: **Colour:**

Fluid Colourless

(Contd. on page 5)



according to WHS Regulations

Agilent

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

	(Contd. of page 4		
· Odour:	Nearly odourless		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	-107 °C e: 99 °C		
· Flash point:	-12 °C		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	410 °C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
Lower:	1.1 Vol %		
Upper:	6 Vol %		
· Vapour pressure at 20 °C:	41.25 hPa		
· Density at 20 °C:	0.6921 g/cm ³		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not determined.		
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/water:	Not determined.		
· Viscosity:			
Dynamic at 20 °C:	0.51 mPas		
Kinematic:	Not determined.		
· Solvent content:			
Organic solvents:	99.9 %		
VOC (EC)	99.93 %		
Solids content:	0.0 %		
• Other information	No further relevant information available.		

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

AU

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

Printing date 31.03.2019

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

>2,001 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h >33.5 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

LD50 >5,000 mg/kg (rat) Oral Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.52 mg/L (rat)

· Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

AU



according to WHS Regulations

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 6)

AU

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, IMDG, IATA	UN1262
· UN proper shipping name · ADG · IMDG · IATA	1262 OCTANES solution, ENVIRONMENTALLY HAZARDOUS OCTANES solution, MARINE POLLUTANT OCTANES solution
Transport hazard class(es)	
ADG, IMDG	
Class Label	3 Flammable liquids. 3
·IATA	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADG, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances:
Marine pollutant: Special marking (ADG):	2,2,4-trimethylpentane Symbol (fish and tree) Symbol (fish and tree)
	Warning: Flammable liquids.
• Special precautions for user • Danger code (Kemler): • EMS Number: • Stowage Category	33 F-E,S-E B
Danger code (Kemler): EMS Number:	33 F-E,S-E B
• Danger code (Kemler): • EMS Number: • Stowage Category • Transport in bulk according to Annex II of	33 F-E,S-E B f Marpol



Printing date 31.03.2019

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

	(Contd. of page
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1262 OCTANES SOLUTION, 3, II,
2	ENVIRONMENTALLY HAZARDOUS
	ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

•	Australian	Inventory	of	Chemical	Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



AU

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 100 mg/L (1X2 mL)

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
* *** Data compared to the previous version altered.**



Printing date 31.03.2019

Printing date 31.03.2019

1 Identification

Agilent

Version number 3

Revision: 30.03.2019

· Product identifier • Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL) · Part number: PANAL0216-3 · Relevant identified uses of the substance or mixture and uses advised against Reagents and Standards for Analytical Chemical Laboratory Use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies Australia Pty Ltd 679 Springvale Road Mulgrave Victoria 3170, Australia · Further information obtainable from: Telephone: 1800 802 402 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: +(61) - 290372994 2 Hazard(s) Identification · Classification of the substance or mixture flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. health hazard Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. _____ · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: 2,2,4-trimethylpentane · Hazard statements Highly flammable liquid and vapour. (Contd. on page 2)

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 1) Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

540-84-1 2,2,4-trimethylpentane

🛞 Flam. Liq. 2, H225; 🚸 Asp. Tox. 1, H304; 🚸 Skin Irrit. 2, H315; STOT SE 3, H336

99.835%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



Printing date 31.03.2019

AU

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 2)

 \cdot After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- 1

7 Handling and Storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

Printing date 31.03.2019

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

- For direct contact with the chemical: butyl rubber: >4 hours
- · Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: Colour:

Fluid Colourless

(Contd. on page 5)



(0, 1) (

according to WHS Regulations

Agilent

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

	(Contd. of page 4		
· Odour:	Nearly odourless		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	-107 °C e: 99 °C		
· Flash point:	-12 °C		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	410 °C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
Lower:	1.1 Vol % 6 Vol %		
Upper:			
· Vapour pressure at 20 °C:	41.25 hPa		
· Density at 20 °C:	0.69224 g/cm ³		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not determined.		
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/water:	ent: n-octanol/water: Not determined.		
· Viscosity:			
Dynamic at 20 °C:	0.51 mPas		
Kinematic:	Not determined.		
· Solvent content:			
Organic solvents:	99.8 %		
VOC (EC)	99.84 %		
Solids content:	0.0 %		
• Other information	No further relevant information available.		

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

AU

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

Printing date 31.03.2019

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

>2,003 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h >33.6 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

LD50 >5,000 mg/kg (rat) Oral Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.52 mg/L (rat)

· Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

AU



according to WHS Regulations

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 6)

AU

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, IMDG, IATA	UN1262
UN proper shipping name ADG IMDG IATA	1262 OCTANES solution, ENVIRONMENTALLY HAZARDOUS OCTANES solution, MARINE POLLUTANT OCTANES solution
Transport hazard class(es)	
ADG, IMDG	
Class	3 Flammable liquids.
Label	3
Class Label	3 Flammable liquids. 3
Packing group ADG, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: 2,2,4-trimethylpentane
Marine pollutant: Special marking (ADG):	Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-E B
Transport in bulk according to Annex II of and the IBC Code	of Marpol Not applicable.
Transport/Additional information:	



Printing date 31.03.2019

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

	(Contd. of page	
· Excepted quantities (EQ)	Code: E2	
• • • • •	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
· Transport category	2	
· Tunnel restriction code	D/E	
· IMDG		
[·] Limited quantities (LQ)	1L	
· Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
· UN "Model Regulation":	UN 1262 OCTANES SOLUTION, 3, II,	
0	ENVIRONMENTALLY HAZARDOUS	
	ENVIRONMENTALET HALARDOUS	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



AU

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 250 mg/L (1X2 mL)

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 ** Data compared to the previous version altered.



Printing date 31.03.2019

Printing date 31.03.2019

1 Identification

Agilent

Version number 3

Revision: 30.03.2019

· Product identifier • Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL) · Part number: PANAL0216-4 · Relevant identified uses of the substance or mixture and uses advised against Reagents and Standards for Analytical Chemical Laboratory Use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies Australia Pty Ltd 679 Springvale Road Mulgrave Victoria 3170, Australia · Further information obtainable from: Telephone: 1800 802 402 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: +(61) - 290372994 2 Hazard(s) Identification · Classification of the substance or mixture flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. health hazard Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. _____ · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: 2,2,4-trimethylpentane · Hazard statements Highly flammable liquid and vapour. (Contd. on page 2)

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 1) Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

```
540-84-1 2,2,4-trimethylpentane
```

Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336

99.67%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



Printing date 31.03.2019

AU

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 2)

 \cdot After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

Printing date 31.03.2019

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- · Material of gloves
- For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- · Penetration time of glove material
- For normal use: nitrile rubber: 1 hour
- For direct contact with the chemical: butyl rubber: >4 hours
- Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: **Colour:**

Fluid Colourless



according to WHS Regulations

Agilent

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

	(Contd. of page 4)		
· Odour:	Nearly odourless		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
Change in condition Melting point/freezing point: -107 °C Initial boiling point and boiling range: 99 °C			
· Flash point:	-12 °C		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	410 °C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
[·] Explosion limits: Lower: Upper:	1.1 Vol % 6 Vol %		
· Vapour pressure at 20 °C:	41.25 hPa		
Density at 20 °C:0.69248 g/cm³Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.			
· Solubility in / Miscibility with water:			
· Partition coefficient: n-octanol/water:	r: Not determined.		
· Viscosity: Dynamic at 20 °C: Kinematic:			
 Solvent content: Organic solvents: VOC (EC) 	99.7 % 99.67 %		
Solids content: • Other information	0.0 % No further relevant information available.		

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

AU

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

Printing date 31.03.2019

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

>2,007 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h >33.6 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

LD50 >5,000 mg/kg (rat) Oral Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.52 mg/L (rat)

· Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

AU



according to WHS Regulations

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 6)

AU

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

Transport information				
· UN-Number · ADG, IMDG, IATA	UN1262			
· UN proper shipping name · ADG · IMDG	1262 OCTANES solution, ENVIRONMENTALLY HAZARDOUS OCTANES solution, MARINE POLLUTANT			
· IMDG · IATA	OCTANES solution, MARINE POLLOTANT OCTANES solution			
· Transport hazard class(es)				
ADG, IMDG				
· Class · Label	3 Flammable liquids.			
· Class · Label	3 Flammable liquids. 3			
· Packing group · ADG, IMDG, IATA	II			
Environmental hazards:	Product contains environmentally hazardous substances: 2,2,4-trimethylpentane			
· Marine pollutant: · Special marking (ADG):	Symbol (fish and tree) Symbol (fish and tree)			
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E,S-E B			
Transport in bulk according to Annex II and the IBC Code	of Marpol Not applicable.			
Transport/Additional information:				
· ADG · Limited quantities (LQ)	lL			
	(Contd. on page			



Printing date 31.03.2019

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

	(Contd. of page	
· Excepted quantities (EQ)	Code: E2	
• • • • •	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
· Transport category	2	
· Tunnel restriction code	D/E	
· IMDG		
[·] Limited quantities (LQ)	1L	
· Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
· UN "Model Regulation":	UN 1262 OCTANES SOLUTION, 3, II,	
0	ENVIRONMENTALLY HAZARDOUS	
	ENVIRONMENTALET HALARDOUS	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	•	Australian	Inventory	of	Chemical	Substances
--	---	------------	-----------	----	----------	------------

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



Revision: 30.03.2019


Trade name: Di-n-butyl Sulfide (as S), 500 mg/L (1X2 mL)

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 ** Data compared to the previous version altered.

Agilent

Printing date 31.03.2019



Printing date 31.03.2019

1 Identification

Agilent

Version number 3

Revision: 30.03.2019

· Product identifier • Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL) · Part number: PANAL0216-5 · Relevant identified uses of the substance or mixture and uses advised against Reagents and Standards for Analytical Chemical Laboratory Use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies Australia Pty Ltd 679 Springvale Road Mulgrave Victoria 3170, Australia · Further information obtainable from: Telephone: 1800 802 402 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: +(61) - 290372994 **2 Hazard(s) Identification** · Classification of the substance or mixture flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. health hazard Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. _____ · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: 2,2,4-trimethylpentane · Hazard statements Highly flammable liquid and vapour.

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 1) Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

540-84-1 2,2,4-trimethylpentane

🛞 Flam. Liq. 2, H225; 🚸 Asp. Tox. 1, H304; 🚸 Skin Irrit. 2, H315; STOT SE 3, H336

99.506%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



Printing date 31.03.2019

AU

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 2)

 \cdot After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- · Material of gloves
- For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- · Penetration time of glove material
- For normal use: nitrile rubber: 1 hour
- For direct contact with the chemical: butyl rubber: >4 hours
- · Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: Colour:

Fluid Colourless



Printing date 31.03.2019

according to WHS Regulations

Agilent

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

	(Contd. of page 4
· Odour:	Nearly odourless
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	-107 °C e: 99 °C
· Flash point:	-12 °C
· Flammability (solid, gas):	Not applicable.
Ignition temperature:	410 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
• Explosion limits:	
Lower:	1.1 Vol %
Upper:	6 Vol %
· Vapour pressure at 20 °C:	41.25 hPa
Density at 20 °C:	0.69272 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	0.51 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.5 %
VOC (EC)	99.51 %
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

AU

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

>2,010 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h >33.7 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

LD50 >5,000 mg/kg (rat) Oral Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.52 mg/L (rat)

· Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

AU



Printing date 31.03.2019

according to WHS Regulations

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 6)

AU

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · ADG, IMDG, IATA	UN1262
· UN proper shipping name · ADG · IMDG · IATA	1262 OCTANES solution, ENVIRONMENTALLY HAZARDOUS OCTANES solution, MARINE POLLUTANT OCTANES solution
· Transport hazard class(es)	
· ADG, IMDG	
· Class	3 Flammable liquids.
· Label	3
· Class · Label	3 Flammable liquids. 3
· Packing group · ADG, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: 2,2,4-trimethylpentane
• Marine pollutant: • Special marking (ADG):	Symbol (fish and tree) Symbol (fish and tree)
 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids. 33 F-E,S-E B
• Transport in bulk according to Annex II a and the IBC Code	of Marpol Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ)	1L
	(Contd. on page



Printing date 31.03.2019

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

	(Contd. of page
· Excepted quantities (EQ)	Code: E2
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
[·] Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1262 OCTANES SOLUTION, 3, II,
0	ENVIRONMENTALLY HAZARDOUS
	ENVIRONMENTALET HALARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

AU

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 750 mg/L (1X2 mL)

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 ** Data compared to the previous version altered.



Printing date 31.03.2019




Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019



Highly flammable liquid and vapour.

(Contd. on page 2)

- AU

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 1) Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

540-84-1 2,2,4-trimethylpentane

🕐 Flam. Liq. 2, H225; 🚯 Asp. Tox. 1, H304; 🛟 Skin Irrit. 2, H315; STOT SE 3, H336

99.341%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



AU –

Printing date 31.03.2019

Agilent

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 2)

- \cdot After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- · Material of gloves
- For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- · Penetration time of glove material
- For normal use: nitrile rubber: 1 hour
- For direct contact with the chemical: butyl rubber: >4 hours
- · Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: Colour:

Fluid Colourless



Printing date 31.03.2019

according to WHS Regulations

Agilent

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

	(Contd. of page 4
· Odour:	Nearly odourless
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	-107 °C :: 99 °C
· Flash point:	-12 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	410 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	6 Vol %
· Vapour pressure at 20 °C:	41.25 hPa
· Density at 20 °C:	0.69296 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	0.51 mPas Not determined.
· Solvent content: Organic solvents: VOC (EC)	99.3 % 99.34 %
Solids content: • Other information	0.0 % No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

AU

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

Printing date 31.03.2019

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

>2,013 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h >33.7 mg/L (rat)

540-84-1 2,2,4-trimethylpentane

LD50 >5,000 mg/kg (rat) Oral Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50/4 h >33.52 mg/L (rat)

· Primary irritant effect:

· Skin corrosion/irritation Irritant to skin and mucous membranes.

- Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

AU





according to WHS Regulations

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 6)

AU

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number	
· ON-Number · ADG, IMDG, IATA	UN1262
· UN proper shipping name	
· ADG	1262 OCTANES mixture, ENVIRONMENTALLY
	HAZARDOUS
· IMDG · IATA	OCTANES mixture, MARINE POLLUTANT OCTANES mixture
	OCTANES mixture
· Transport hazard class(es)	
· ADG, IMDG	
· Class	3 Flammable liquids.
· Label	3
· Class	3 Flammable liquids.
· Label	3
· Packing group · ADG, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances:
. Marina nallutanti	2,2,4-trimethylpentane Symbol (fish and tree)
 Marine pollutant: Special marking (ADG): 	Symbol (fish and tree)
• Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
EMS Number:	F-E,S-E
· Stowage Category	В
• Transport in bulk according to Annex II and the IBC Code	of Marpol Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ)	1L



Printing date 31.03.2019

Printing date 31.03.2019

Version number 3

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
2
D/E
1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
UN 1262 OCTANES MIXTURE, 3, II,
ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



AU

Revision: 30.03.2019

Trade name: Di-n-butyl Sulfide (as S), 1000 mg/L (1X2 mL)

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 ** Data compared to the previous version altered.



Printing date 31.03.2019

