

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

1 Identification

- **Product identifier**
- **Trade name:** Haloacetic Acid Standard (1X1 mL)
- **Part number:** PHM-5523A-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

tert-butyl methyl ether

- **Hazard statements**

Highly flammable liquid and vapor.

Harmful in contact with skin.

Causes skin irritation.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 1)

Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1634-04-4	tert-butyl methyl ether	99.05%
-----------	-------------------------	--------

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1634-04-4	tert-butyl methyl ether	50 ppm
79-43-6	dichloroacetic acid	1.5 ppm
79-11-8	chloroacetic acid	1.5 ppm
79-08-3	bromoacetic acid	0.023 mg/m ³
76-03-9	trichloroacetic acid	1.5 ppm

- **PAC-2:**

1634-04-4	tert-butyl methyl ether	570 ppm
79-43-6	dichloroacetic acid	8.9 ppm
79-11-8	chloroacetic acid	6.6 ppm
79-08-3	bromoacetic acid	0.26 mg/m ³
76-03-9	trichloroacetic acid	16 ppm

- **PAC-3:**

1634-04-4	tert-butyl methyl ether	5300* ppm
79-43-6	dichloroacetic acid	140 ppm
79-11-8	chloroacetic acid	15 ppm
79-08-3	bromoacetic acid	1.5 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)
--

(Contd. of page 3)

76-03-9	trichloroacetic acid
---------	----------------------

99 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

1634-04-4 tert-butyl methyl ether
--

TLV	Long-term value: 180 mg/m ³ , 50 ppm
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.
Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.
- **Protection of hands:**
Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 4)

- **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid

Color: Colorless

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55.2 °C (131.4 °F)

· **Flash point:** 0 °C (32 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 374 °C (705.2 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower: 1.6 Vol %

Upper: 8.4 Vol %

· **Vapor pressure at 20 °C (68 °F):** 279 hPa (209.3 mm Hg)

· **Density at 20 °C (68 °F):** 0.74 g/cm³ (6.1753 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water at 25 °C (77 °F): 51 g/l

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 5)

· Viscosity:	
Dynamic at 20 °C (68 °F):	0.27 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.1 %
VOC content:	99.05 %
	990.5 g/l / 8.27 lb/gal
Solids content:	0.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:
ATE (Acute Toxicity Estimate)

Oral	LD50	4,038 mg/kg (rat)
Dermal	LD50	1,010 mg/kg (rabbit)

1634-04-4 tert-butyl methyl ether

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23,576 mg/L (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

IARC (International Agency for Research on Cancer)

1634-04-4	tert-butyl methyl ether	3
-----------	-------------------------	---

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 6)

79-43-6	dichloroacetic acid	2B
5589-96-8	bromochloroacetic acid	2B
631-64-1	dibromoacetic acid	2B
76-03-9	trichloroacetic acid	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Not Regulated, De minimus Quantities** -
- **UN-Number**
- **DOT, IMDG, IATA** UN2350
- **UN proper shipping name**
- **DOT** Butyl methyl ether solution
- **IMDG, IATA** BUTYL METHYL ETHER solution

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 7)

· **Transport hazard class(es)**· **DOT, IMDG, IATA**

· Class	3 Flammable liquids
· Label	3

· Packing group	II
· DOT, IMDG, IATA	

· Environmental hazards:	Not applicable.
---------------------------------	-----------------

· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	B

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
--	-----------------

· **Transport/Additional information:**· **DOT**

· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
-------------------------------	---

· **IMDG**

· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2

Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":	UN 2350 BUTYL METHYL ETHER SOLUTION, 3, II
---------------------------------	--

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· **Section 355 (extremely hazardous substances):**

79-11-8	chloroacetic acid
---------	-------------------

· **Section 313 (Specific toxic chemical listings):**

1634-04-4	tert-butyl methyl ether
-----------	-------------------------

79-11-8	chloroacetic acid
---------	-------------------

· **TSCA (Toxic Substances Control Act):**

1634-04-4	tert-butyl methyl ether
-----------	-------------------------

75-96-7	tribromoacetic acid
---------	---------------------

600-05-5	2,3-dibromopropionic acid
----------	---------------------------

79-43-6	dichloroacetic acid
---------	---------------------

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 8)

79-11-8	chloroacetic acid
75-99-0	2,2-dichloropropionic acid
79-08-3	bromoacetic acid
631-64-1	dibromoacetic acid
76-03-9	trichloroacetic acid

· Proposition 65
· Chemicals known to cause cancer:

79-43-6	dichloroacetic acid
71133-14-7	bromodichloroacetic acid
5589-96-8	bromochloroacetic acid
631-64-1	dibromoacetic acid
76-03-9	trichloroacetic acid

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

79-43-6	dichloroacetic acid
---------	---------------------

· Chemicals known to cause developmental toxicity:

79-43-6	dichloroacetic acid
---------	---------------------

· Carcinogenic categories
· EPA (Environmental Protection Agency)

79-43-6	dichloroacetic acid	L
76-03-9	trichloroacetic acid	SC

· TLV (Threshold Limit Value established by ACGIH)

1634-04-4	tert-butyl methyl ether	A3
79-43-6	dichloroacetic acid	A3
79-11-8	chloroacetic acid	A4
75-99-0	2,2-dichloropropionic acid	A4
76-03-9	trichloroacetic acid	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

· Date of preparation / last revision 03/30/2019 / 2

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Haloacetic Acid Standard (1X1 mL)

(Contd. of page 9)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

· *** Data compared to the previous version altered.**

US