

Safety Data Sheet

acc. to OSHA HCS

Revision date 07/07/2024

1 Identification

- **Product identifier**
- **Product Name:** MCPP (Mecoprop) Standard (1X1 mL)
- **Part number:** PST-1190K1000
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTRAC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 1)

P240 Ground/bond container and receiving equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a poison center/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-64-1	acetone	99.9874%
---------	---------	----------

4 First-aid measures

· Description of first aid measures
· General information: Immediately remove any clothing soiled by the product.
· After inhalation: Supply fresh air; consult doctor in case of complaints.
· After skin contact: Immediately rinse with water.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 2)

- After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:** If symptoms persist consult doctor.
- Information for doctor:**
- Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**
- Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents:** Water with full jet
- Special hazards arising from the substance or mixture** No further relevant information available.
- Advice for firefighters**
- Protective equipment:** No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals**

PAC-1:	
67-64-1 acetone	200 ppm
PAC-2:	
67-64-1 acetone	3200* ppm
PAC-3:	
67-64-1 acetone	5700* ppm

7 Handling and storage

- Handling:**
- Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 3)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

- **Ingredients with biological limit values:**

67-64-1 acetone

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

- **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 4)

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

*

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Color: Colorless

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: -94.7 °C (-138.5 °F)

Boiling point/Boiling range: 55.8-56.6 °C (132.4-133.9 °F)

· Flash point: -17 °C (1.4 °F)

· Flammability (solid, gaseous): Highly flammable.

· Auto igniting: 465 °C (869 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 2.6 Vol %

Upper: 13 Vol %

· Vapor pressure at 20 °C (68 °F): 245.3 hPa (184 mm Hg)

· Density at 20 °C (68 °F): 0.791 g/cm³ (6.0009 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 5)

Viscosity:	
Dynamic at 20 °C (68 °F):	32 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity** No further relevant information available.
- Chemical stability**
- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- Possibility of hazardous reactions** No dangerous reactions known.
- Conditions to avoid** No further relevant information available.
- Incompatible materials:** No further relevant information available.
- Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects**
- Acute toxicity:**

- LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- Primary irritant effect:**

- on the skin:** No irritant effect.

- on the eye:** Irritating effect.

- Sensitization:** No sensitizing effects known.

- Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories**

- IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 7)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information**· Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.**· Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.**13 Disposal considerations****· Waste treatment methods****· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:· **Recommendation:** Disposal must be made according to official regulations.**14 Transport information****· Not Regulated, De minimis Quantities**

-

· UN-Number**· DOT, IMDG, IATA**

UN1090

· UN proper shipping name

Acetone solution

· IMDG, IATA

ACETONE solution

· Transport hazard class(es)**· DOT****· Class**

3 Flammable liquids

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)
--

<p>(Contd. of page 7)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">· Label</td> <td style="width: 90%;">3</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· IMDG, IATA</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">  </td> </tr> <tr> <td>· Class</td> <td>3 Flammable liquids</td> </tr> <tr> <td>· Label</td> <td>3</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Packing group</td> <td></td> </tr> <tr> <td>· DOT, IMDG, IATA</td> <td>II</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Environmental hazards:</td> <td>Not applicable.</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Special precautions for user</td> <td>Warning: Flammable liquids</td> </tr> <tr> <td>· Hazard identification number (Kemler code):</td> <td>33</td> </tr> <tr> <td>· EMS Number:</td> <td>F-E,S-D</td> </tr> <tr> <td>· Stowage Category</td> <td>B</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</td> <td>Not applicable.</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Transport/Additional information:</td> <td></td> </tr> <tr> <td>· DOT</td> <td></td> </tr> <tr> <td>· Quantity limitations</td> <td>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· IMDG</td> <td></td> </tr> <tr> <td>· Limited quantities (LQ)</td> <td>1L</td> </tr> <tr> <td>· Excepted quantities (EQ)</td> <td>Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· UN "Model Regulation":</td> <td>UN 1090 ACETONE SOLUTION, 3, II</td> </tr> </table>	· Label	3	<hr style="border-top: 1px dashed #000;"/>		· IMDG, IATA				· Class	3 Flammable liquids	· Label	3	<hr style="border-top: 1px dashed #000;"/>		· Packing group		· DOT, IMDG, IATA	II	<hr style="border-top: 1px dashed #000;"/>		· Environmental hazards:	Not applicable.	<hr style="border-top: 1px dashed #000;"/>		· Special precautions for user	Warning: Flammable liquids	· Hazard identification number (Kemler code):	33	· EMS Number:	F-E,S-D	· Stowage Category	B	<hr style="border-top: 1px dashed #000;"/>		· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	<hr style="border-top: 1px dashed #000;"/>		· Transport/Additional information:		· DOT		· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L	<hr style="border-top: 1px dashed #000;"/>		· IMDG		· Limited quantities (LQ)	1L	· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	<hr style="border-top: 1px dashed #000;"/>		· UN "Model Regulation":	UN 1090 ACETONE SOLUTION, 3, II
· Label	3																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· IMDG, IATA																																																								
																																																								
· Class	3 Flammable liquids																																																							
· Label	3																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Packing group																																																								
· DOT, IMDG, IATA	II																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Environmental hazards:	Not applicable.																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Special precautions for user	Warning: Flammable liquids																																																							
· Hazard identification number (Kemler code):	33																																																							
· EMS Number:	F-E,S-D																																																							
· Stowage Category	B																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Transport/Additional information:																																																								
· DOT																																																								
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· IMDG																																																								
· Limited quantities (LQ)	1L																																																							
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· UN "Model Regulation":	UN 1090 ACETONE SOLUTION, 3, II																																																							

<p>(Contd. of page 7)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">· Label</td> <td style="width: 90%;">3</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· IMDG, IATA</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">  </td> </tr> <tr> <td>· Class</td> <td>3 Flammable liquids</td> </tr> <tr> <td>· Label</td> <td>3</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Packing group</td> <td></td> </tr> <tr> <td>· DOT, IMDG, IATA</td> <td>II</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Environmental hazards:</td> <td>Not applicable.</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Special precautions for user</td> <td>Warning: Flammable liquids</td> </tr> <tr> <td>· Hazard identification number (Kemler code):</td> <td>33</td> </tr> <tr> <td>· EMS Number:</td> <td>F-E,S-D</td> </tr> <tr> <td>· Stowage Category</td> <td>B</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</td> <td>Not applicable.</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· Transport/Additional information:</td> <td></td> </tr> <tr> <td>· DOT</td> <td></td> </tr> <tr> <td>· Quantity limitations</td> <td>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· IMDG</td> <td></td> </tr> <tr> <td>· Limited quantities (LQ)</td> <td>1L</td> </tr> <tr> <td>· Excepted quantities (EQ)</td> <td>Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</td> </tr> <tr> <td colspan="2"><hr style="border-top: 1px dashed #000;"/></td> </tr> <tr> <td>· UN "Model Regulation":</td> <td>UN 1090 ACETONE SOLUTION, 3, II</td> </tr> </table>	· Label	3	<hr style="border-top: 1px dashed #000;"/>		· IMDG, IATA				· Class	3 Flammable liquids	· Label	3	<hr style="border-top: 1px dashed #000;"/>		· Packing group		· DOT, IMDG, IATA	II	<hr style="border-top: 1px dashed #000;"/>		· Environmental hazards:	Not applicable.	<hr style="border-top: 1px dashed #000;"/>		· Special precautions for user	Warning: Flammable liquids	· Hazard identification number (Kemler code):	33	· EMS Number:	F-E,S-D	· Stowage Category	B	<hr style="border-top: 1px dashed #000;"/>		· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	<hr style="border-top: 1px dashed #000;"/>		· Transport/Additional information:		· DOT		· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L	<hr style="border-top: 1px dashed #000;"/>		· IMDG		· Limited quantities (LQ)	1L	· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	<hr style="border-top: 1px dashed #000;"/>		· UN "Model Regulation":	UN 1090 ACETONE SOLUTION, 3, II
· Label	3																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· IMDG, IATA																																																								
																																																								
· Class	3 Flammable liquids																																																							
· Label	3																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Packing group																																																								
· DOT, IMDG, IATA	II																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Environmental hazards:	Not applicable.																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Special precautions for user	Warning: Flammable liquids																																																							
· Hazard identification number (Kemler code):	33																																																							
· EMS Number:	F-E,S-D																																																							
· Stowage Category	B																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· Transport/Additional information:																																																								
· DOT																																																								
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· IMDG																																																								
· Limited quantities (LQ)	1L																																																							
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml																																																							
<hr style="border-top: 1px dashed #000;"/>																																																								
· UN "Model Regulation":	UN 1090 ACETONE SOLUTION, 3, II																																																							

*

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

93-65-2 2-(4-chloro-2-methylphenoxy)propionic acid

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

None of the ingredients is listed.

<p>(Contd. on page 9)</p>

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2024

Revision date 07/07/2024

Product Name: MCPP (Mecoprop) Standard (1X1 mL)

(Contd. of page 8)

· Proposition 65**· Chemicals known to cause cancer:**

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

67-64-1 acetone

I

· TLV (Threshold Limit Value)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory**· Contact:** pdl-acg-regulatory-cq@agilent.com**· Date of preparation / last revision** 08/23/2024 / 4**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.